

N72-21991

NASA SP-7037 (15)



CASE FILE
COPY

AERONAUTICAL ENGINEERING

A SPECIAL BIBLIOGRAPHY
WITH INDEXES
Supplement 15

FEBRUARY 1972

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

PREVIOUS BIBLIOGRAPHIES IN THIS SERIES

<i>Document</i>	<i>Date</i>	<i>Coverage</i>
NASA SP-7037	September 1970	Jan.-Aug. 1970
NASA SP-7037 (01)	January 1971	Sept.-Dec. 1970
NASA SP-7037 (02)	February 1971	January 1971
NASA SP-7037 (03)	March 1971	February 1971
NASA SP-7037 (04)	April 1971	March 1971
NASA SP-7037 (05)	May 1971	April 1971
NASA SP-7037 (06)	June 1971	May 1971
NASA SP-7037 (07)	July 1971	June 1971
NASA SP-7037 (08)	August 1971	July 1971
NASA SP-7037 (09)	September 1971	August 1971
NASA SP-7037 (10)	October 1971	September 1971
NASA SP-7037 (11)	November 1971	October 1971
NASA SP-7037 (12)	December 1971	November 1971
NASA SP-7037 (13)	January 1972	December 1971

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by Informatics Tisco, Inc.

Use of funds for printing this publication approved by the Director of the Office of Management and Budget June 23, 1971.

AERONAUTICAL ENGINEERING

A Special Bibliography

Supplement 15

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in January 1972 in

- *Scientific and Technical Aerospace Reports (STAR)*
- *International Aerospace Abstracts (IAA).*



Scientific and Technical Information Office
OFFICE OF INDUSTRY AFFAIRS AND TECHNOLOGY UTILIZATION 1972
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C.

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering.

This supplement to *Aeronautical Engineering—A Special Bibliography* (NASA SP-7037) lists 363 reports, journal articles, and other documents originally announced in January 1972 in *Scientific and Technical Aerospace Reports (STAR)* or in *International Aerospace Abstracts (IAA)*. For previous bibliographies in this series, see inside of front cover.

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied by an abstract. The listing of the entries is arranged in two major sections, *IAA Entries* and *STAR Entries* in that order. The citations and abstracts are reproduced exactly as they appeared originally in *IAA* or *STAR*, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances.

Three indexes—subject, personal author, and contract number—are included.

An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A72-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc., (AIAA), as follows: Paper copies are available at \$5.00 per document up to a maximum of 20 pages. The charge for each additional page is 25 cents. Microfiche⁽¹⁾ are available at the rate of \$1.00 per microfiche for documents identified by the # symbol following the accession number. A number of publications, because of their special characteristics, are available only for reference in the AIAA Technical Information Service Library. Minimum airmail postage to foreign countries is \$1.00. Please refer to the accession number, e.g., A72-10969, when requesting publications.

STAR ENTRIES (N72-10000 Series)

A source from which a publication abstracted in this Section is available to the public is ordinarily given on the last line of the citation, e.g., Avail: NTIS. The following are the most commonly indicated sources (full addresses of these organizations are listed at the end of this introduction):

Avail: NTIS. Sold by the National Technical Information Service at a standard price of \$3.00 for hard copy (printed, facsimile, or reproduced from microcopy) of 300 pages or less. Documents in the 301 to 600 page range are sold for \$6.00 in hard copy, and those in the 601 to 900 page range are sold at \$9.00. Documents exceeding 900 pages are priced by NTIS on an individual basis. These prices apply retroactively to all documents in the NTIS collection, but in addition, documents of 300 pages or less that are over two years old (from date of announcement in *Government Reports Announcements*, or *STAR* for those items announced only in *STAR*) will have a surcharge of \$3.00 added for a total price of \$6.00. No additional surcharge will be added for documents over 300 pages.

Microfiche is available from NTIS at a standard price of 95 cents (regardless of age) for those documents identified by the # sign following the accession number (e.g., N72-11045#) and having an NTIS availability shown in the citation.

Avail: SOD (or GPO). Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The price is given following the availability line. (An order received by NTIS for one of these documents will be filled at the SOD price if hard copy is requested. NTIS will also fill microfiche requests, at the standard 95 cent price, for those documents identified by a # Ssymbol.)

Avail: NASA Scientific and Technical Information Office. Documents with this availability are usually news releases or informational brochures available without charge in paper copy.

Avail: AEC Depository Libraries. Organizations in U.S. cities and abroad that maintain collections of U.S. Atomic Energy Commission reports, usually in microfiche form, are listed in *Nuclear Science Abstracts*. Services available from the USAEC and its depositories are described in a booklet, *Science Information Available from the Atomic Energy Commission* (TID-4550), which may be obtained without charge from the USAEC Division of Technical Information.

Avail: Univ. Microfilms. Documents so indicated are dissertations selected from *Dissertation Abstracts*, and are sold by University Microfilms as xerographic copy (HC) at \$10.00 each and microfilm at \$4.00 each, regardless of the length of the manuscript. Handling and shipping charges are additional. All requests should cite the author and the Order Number as they appear in the citation.

(1) A microfiche is a transparent sheet of film, 105 x 148 mm in size, containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 24:1 reduction)

- Avail: HMSO. Publications of Her Majesty's Stationery Office are sold in the U.S. by **Pendragon House, Inc., (PHI), Redwood City, California. The U.S. price (including a service charge) is given, or a conversion table may be obtained from PHI.**
- Avail: National Lending Library, Boston Spa, England. Sold by this organization at the price shown. (If none is given, an inquiry should be addressed to NLL.)
- Avail: ZLDI. Sold by the Zentralstelle für Luftfahrtokumentation und -Information, Munich, Federal Republic of Germany, at the price shown in deutschmarks (DM).
- Avail: Issuing Activity, or Corporate Author, or no indication of availability: Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.
- Avail: U.S. Patent Office. Sold by Commissioner of Patents, U.S. Patent Office, at the standard price of \$.50 each, postage free.
- Other availabilities: If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line.

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA. A listing of public collections of NASA documents is included on the inside back cover.

SUBSCRIPTION AVAILABILITY

This publication is available on subscription from the National Technical Information Service (NTIS). The annual subscription rate for the monthly supplements, excluding the annual cumulative index, is \$18.00. All questions relating to subscriptions should be referred to the NTIS.

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics
and Astronautics
Technical Information Service
750 Third Ave.
New York, N.Y. 10017

National Technical Information Service
Springfield, Virginia 22151

Pendragon House, Inc.
899 Broadway Avenue
Redwood City, California 94063

Commissioner of Patents
U.S. Patent Office
Washington, D.C. 20231

Superintendent of Documents
U.S. Government Printing Office
Washington, D.C. 20402

ESRO/ELDO Space Documentation Service
European Space Research Organization
114, av. de Neuilly
92-Neuilly-sur-Seine, France

University Microfilms, Inc.
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

Her Majesty's Stationery Office
P.O. Box 569, S.E. 1
London, England

University Microfilms, Inc.
Tylers Green
London, England

NASA Scientific and Technical Information
Facility
P.O. Box 33
College Park, Maryland 20740

U.S. Atomic Energy Commission
Division of Technical Information
P.O. Box 62
Oak Ridge, Tennessee 37830

National Aeronautics and Space
Administration
Scientific and Technical Information
Office (KSI)
Washington, D.C. 20546


Zentralstelle für Luftfahrt-doku-
mentation und-Information
8 München 86
Postfach 880
Federal Republic of Germany

National Lending Library for Science
and Technology
Boston Spa, Yorkshire, England


TABLE OF CONTENTS

	Page
IAA Entries	1
STAR Entries	27
Subject Index	A-1
Personal Author Index	B-1
Contract Number Index	C-1

TYPICAL CITATION AND ABSTRACT FROM STAR



TYPICAL CITATION AND ABSTRACT FROM IAA





AERONAUTICAL ENGINEERING

A Special Bibliography (Suppl. 15) FEBRUARY 1972

IAA ENTRIES

A72-10070 # Problems of the use of inertial navigation systems in aviation (Problemele utilizării sistemelor inerțiale de navigație în aviație). I. Aron. *Transporturi Auto, Navale și Aeriene*, vol. I (18), July 1971, p. 367-372, 390. 10 refs. In Rumanian.

Analysis of the limits of the classical navigation systems, the progress achieved in the field of automated inertial navigation devices, and the advantages and urgency of using the latter on board passenger aircraft. Attention is paid to accelerometer and gyroscope design and construction as major devices in inertial systems. By computing the aircraft's coordinates continuously and automatically, inertial systems lighten and simplify the crew's work. M.M.

A72-10149 Recording antenna radiation patterns by semi-automation. M. A. Ziller (United Aircraft Corp., Sikorsky Aircraft Div., Stratford, Conn.). *VertiFlite*, vol. 17, Sept.-Oct. 1971, p. 6, 7, 10.

Use of models to permit three-dimensional recording of radiation patterns under relative free-space conditions, thus facilitating trial antenna relocations. The aircraft and antenna are scaled down, requiring an upward scaling of test frequencies to maintain aircraft size-to-wavelength ratio. A polar recorder, synchronized via a synchro-servo drive with the model rotator, plots the pattern semiautomatically. A saving of more than 90% in flight costs has been realized. In addition, resolution is improved with almost continuous data in contrast to 24 discrete data points. F.R.L.

A72-10150 Elastomeric bearings for rotor system applications. C. H. Fagan (Bell Helicopter Co., Fort Worth, Tex.). *VertiFlite*, vol. 17, Sept.-Oct. 1971, p. 12, 13, 16-19.

Discussion of all-elastomeric-bearing rotors developed by the U.S. Army and Bell Helicopter Co., which should virtually eliminate the need for replacing bearings and related parts, thus greatly reducing the down time and cost of unscheduled helicopter maintenance. Another advantage of elastomeric bearings is that the appearance of the elastomer can be used as an indicator of the severity of previous rotor oscillatory loads and motions. Endurance tests conducted on flapping bearings for both main and tail rotors have shown that their service life can be expected to be in excess of 2000 hr. F.R.L.

A72-10157 Field measurement of infrasonic noise. R. A. Hood and H. G. Leventhall (Chelsea College, London, England). *Acustica*, vol. 25, July 1971, p. 10-13. 10 refs. Research supported by the Medical Research Council.

Portable equipment for the detection and recording of noise in the frequency range from 2 to 500 Hz is described, together with typical results obtained in an automobile, blast furnace, railroad car, engine room, and helicopters. Factors responsible for peaks appearing at various frequencies are identified, and research on the subjective effects of infrasonic noise is indicated. T.M.

A72-10160 * # Jet-noise reduction through liquid-base foam injection. L. Manson and H. L. Burge (TRW Systems Group, Redondo Beach, Calif.). *Acoustical Society of America, Journal*, vol. 50, Oct. 1971, pt. 1, p. 1067-1074. 11 refs. Contract No. NAS 1-9425.

An experimental investigation has been made of the sound-absorbing properties of liquid-base foams and of their ability to reduce jet noise. Protein, detergent, and polymer foaming agents were used in water solutions. A method of foam generation was developed to permit systematic variation of the foam density. The investigation included measurements of sound-absorption coefficients for both plane normal incidence waves and diffuse sound fields. The intrinsic acoustic properties of foam, e.g., the characteristic impedance and the propagation constant, were also determined. The sound emitted by a 1-in.-diam cold nitrogen jet was measured for subsonic (300 m/sec) and supersonic (422 m/sec) jets, with and without foam injection. Noise reductions up to 10 PNdB were measured. (Author)

A72-10177 # Air traffic control separation minima and navigational capability. A. White (National Air Traffic Control Services, London, England). *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 443-456.

Examination of the manner in which navigation capability, ATC systems and the general ATC environment have been interlinked in the development of adequate separation values. Only safe separation standards are considered, and not spacing criteria, although inevitably the two are interrelated. Errors in navigation in a typical long-range oceanic environment are discussed, together with errors in navigation during flight on airways and other continental controlled airspace, and ATC intervention capability as related to the development of separation minima. Positive measures that are being taken to explore the means by which separation values can be derived from the direct measurement of navigational and ATC performance during current operations are indicated. M.M.

A72-10178 Mathematical studies on separation standards. D. E. Lloyd (Royal Aircraft Establishment, Farnborough, Hants.,

A72-10179

England). *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 456-458.

Brief description of the mathematical theory of navigational collision risk for parallel tracks. The results of calculations made in 1967 on the required spacing between the center lines of opposite-direction twin airways carrying, mainly, climbing and descending traffic leaving and entering a terminal area are tabulated. For the radar monitored cases, the spacing was assumed to be determined by controller workload, represented by the 'intervention rate' which was defined as the ratio between the number of interventions and the number of flights along the sector. M.M.

A72-10179 # A preliminary analysis of navigational performance observed at Strumble 1969-70. C. M. Britland (Royal Aircraft Establishment, Farnborough, Hants., England). *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 458-462; Discussion, p. 462-468.

Discussion of some of the features of a statistical analysis of data on track-keeping recently collected along Green 1 Airway near the Strumble VOR. All values quoted are illustrative only and have no firm validity at this time but illustrate the numbers involved in determining acceptable separation standards for the lateral navigation case in a typical 'continental' environment. The statistical data suggest that a spacing of 6 nm would increase the risk about 30 times without surveillance; hence the surveillance system must prevent all but 1 in 30 of the potential collisions - namely, be 97% effective - for the same safety level. M.M.

A72-10180 The potential of existing avionics technology. S. Ratcliffe (Royal Radar Establishment, Malvern, Worcs., England). *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 469-483. 21 refs.

Discussion of the areas in which improved avionics could, in the relatively near future, contribute to overcoming the limitations described by Reich (1966) and Dickie. The constraints under which the airspace planners must operate are considered, together with the contribution which good electronic design might make to breaking the decision-taking bottleneck. The important areas in which improved avionics techniques may be expected to ease the problems resulting from rising traffic are listed as: (1) navigational and control techniques which better exploit the potentialities of airborne computers; (2) the evolution of a compatible SSR (secondary surveillance radar) with discrete addressing; (3) correlation protected ILS; and (4) problem-solving computers for ATC. M.M.

A72-10181 # Polar navigation - A new Transverse Mercator technique. G. C. Dyer. *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 484-495.

The secant-expansion of the grid overprint on the Global Navigation Chart GNC 1N Transverse Mercator allows a new look at polar navigation. A navigator can operate his latitude/longitude GPI (ground position indicator) up to 90 deg earth latitude and plot accurately on the GNC 1N. Operation in a FALSE LAT./LONG. mode with a FALSE equator established through the pole means that the gyro transport correction term is small. The 'meridian difference' angle (MERDIFF) involved in this technique is analogous to, and no more difficult to handle than, the convergence angle which applies to more traditional 'grid' techniques. Adoption of the method could mean that many aircraft will be able to conduct their polar flight on one chart; the need to change 'grids' can be avoided. The technique does as well as traditional grid methods in reducing the effect of longitude error being reflected as astro heading error. M.M.

A72-10183 # Terrain clearance during descent and approach. J. D. Proctor. *Institute of Navigation, Journal*, vol. 24, Oct. 1971, p. 565-568.

The effect of ATC is often to bring the aircraft below the optimum profile; the controller likes to get the aircraft down too early rather than too late because too late may entail descent in holding patterns which takes up extra airspace and disrupts sequencing. It is pointed out that information on areas and safe heights where aircraft descend under radar control should be provided to pilots and navigators. The areas should be defined by lines easily discerned by the aircrew, for instance VOR radials or DME distances. While following radar instructions they could then easily check terrain clearance. M.M.

A72-10192 # Rigid pavement stresses under aircraft loading. M. Sargious, G. A. Ross (Calgary, University, Calgary, Alberta, Canada), and G. A. LeMoal. *ASCE, Transportation Engineering Journal*, vol. 97, Nov. 1971, p. 579-590. 9 refs.

Surface strain measurements were made under field loading conditions on an airport apron rigid pavement. Theoretical calculations for the same loading conditions were carried out using finite element method and pavement structure properties as determined by laboratory tests on materials sampled from the test site. It was found that theoretical predictions considering static loads are in fair agreement with field pavement strain measurements under parking aircraft. Dynamic effects in field measurements due to aircraft vibration and load shifts were found to be insignificant in the cases studied. It was found that careful consideration must be given to gauge size and placement when using strain rosettes to predict stresses at a point near a wheel load. O.H.

A72-10193 # Density altitude variations and runway lengths. T. B. Davinroy (Pennsylvania State University, University Park, Pa.). (American Society of Civil Engineers, National Transportation Engineering Meeting, Boston, Mass., July 13-17, 1970, Preprint 1242.) *ASCE, Transportation Engineering Journal*, vol. 97, Nov. 1971, p. 591-607. 19 refs.

The effect of variations in density altitude - i.e., altitude in the standard atmosphere to which the actual density corresponds - on required airport runway lengths and takeoff weights is investigated. It is shown that the necessity of accurate knowledge of changing meteorological conditions, particularly air temperature and pressure altitude, at departure airports was recognized prior to the introduction of jumbo-jet aircraft into service. Previous studies on the effect of variations in these two variables were made and, because the effects of pressure altitude variations were smaller than those of temperature variations, pressure accountability was not made a part of the U.S. regulations. A different form of presentation of computed runway lengths, with and without pressure accountability utilizing a probability plot, results in a much broader picture of the effects and permits an analysis both from the point of view of the aircraft operator and the airport designer. The results of the study indicate that payloads can be effected from 1.5 to 13%, or the required runway length can vary from 1 to 4%, or both. O.H.

A72-10216 Interior noise radiated by an airplane fuselage subjected to turbulent boundary layer excitation and evaluation of noise reduction treatments. W. V. Bhat and J. F. Wilby (Boeing Co., Acoustic Research Group, Seattle, Wash.). *Journal of Sound and Vibration*, vol. 18, Oct. 22, 1971, p. 449-464. 11 refs.

Measurement of the acoustic power radiated by an aircraft fuselage structure exposed to a turbulent boundary layer pressure field at two flight Mach numbers. For a single fuselage panel the radiated power is approximately 90 and 70 dB relative to 10 the minus 13th W at Mach 0.85 and 0.55, respectively. Damping tape and rubber wedge treatments applied to the structure reduce the acoustic radiation, but they are more effective at Mach 0.85 than at

Mach 0.55. The flight test data are in poor agreement with available wind tunnel measurements, indicating the need for improvements in scaling laws. (Author)

A72-10217 Turbulent boundary layers and surface pressure fluctuations on two-dimensional aerofoils. B. D. Mugridge (Southampton, University, Southampton, England). *Journal of Sound and Vibration*, vol. 18, Oct. 22, 1971, p. 475-486. 11 refs.

The unsteady flow about two-dimensional aerofoils has been examined experimentally to determine the surface pressure fluctuations induced by turbulent boundary layers. The measured pressures are described in terms of the boundary layer steady state flow parameters and on this basis the magnitude of the fluctuations are approximately 15 dB greater than the pressures beneath an equivalent wall boundary layer. The difference is attributed to greater flow intermittency in the aerofoil boundary layers and cross-correlations between the surface pressures and the turbulent velocities are examined to test the validity of this conclusion. (Author)

A72-10219 * The vibration of a box-type structure. II - Response to a travelling pressure wave. N. Popplewell (Southampton, University, Southampton, England). *Journal of Sound and Vibration*, vol. 18, Oct. 22, 1971, p. 521-531. 11 refs. Grant No. NGR-52-025-003.

A finite element method is formulated for determining the transient response of a box-type structure to a traveling, arbitrarily shaped pressure wave. The method is illustrated by considering an example of practical concern - the sonic boom. The acceleration-time histories of a closed box are compared with those obtained experimentally from a simulated boom. Satisfactory agreement is obtained with only four rectangular elements per individual face and a simplified loading of the box. (Author)

A72-10220 Tone radiation from axial flow fans running in turbulent flow. N. Chandrasekhara (Southampton, University, Southampton, England). *Journal of Sound and Vibration*, vol. 18, Oct. 22, 1971, p. 533-543. 9 refs.

The theory of sound radiation from helicopter rotors is extended to axial flow fans running in turbulent flow. The inlet turbulence is treated as gusts superposed on the mean flow. The fluctuating lift on the rotor blades due to the incident gusts is evaluated from the two-dimensional analysis. Then the expression for the sound radiated is evaluated. The analysis is compared with the experimental results. (Author)

A72-10223 The reduction of aircraft engine fan-compressor noise using acoustic linings. R. A. Mangiarotti (Department of Trade and Industry /Civil Aviation/, London, England). (*British Acoustical Society, Spring Meeting, University of Birmingham, Birmingham, England, Apr. 5-7, 1971, Paper 71 SA6.*) *Journal of Sound and Vibration*, vol. 18, Oct. 22, 1971, p. 565-576. 19 refs.

The development of a method is described for reducing the approach-landing noise of commercial jet transports by means of acoustic linings for attenuating the noise generated by the fan-compressor in turbofan engines and radiated from the intake and fan-exit ducts. The method is applied in particular to the Pratt & Whitney JT3D engine powering the Boeing 707 and the Douglas DC-8 aircraft. A brief discussion is given on the general characteristics of aircraft subjective noise spectra, engine noise reduction techniques, results of research and development on acoustic linings,

lining technology and full scale engine testing. Finally, a summary of areas of lining research and technology requiring further investigation is given. (Author)

A72-10245 Producibility considerations in production planning for new aircraft. S. J. Torget (Boeing Co., Commercial Airplane Group, Renton, Wash.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710746*. 9 p. Members, \$1.00; nonmembers, \$1.50.

This paper describes some aspects of aircraft producibility at The Boeing Company, and discusses the functions of Design Engineering and Manufacturing organizations in achieving a producible airplane. The makeup and function of the product team prior to Corporate go-ahead, as well as their objectives and timing, are defined. Producibility aspects in both preliminary design and production phases of the aircraft program are identified and described. Specifically, producibility considerations during the preliminary design phase in the provisioning of facilities, subcontracting, and scheduling, as well as production-phase design verification, production planning, subcontractor coordination, materials handling, and plant layout and equipment, are discussed. The effects of design changes on producibility are noted. A discussion of motivation as a factor in producibility is included. (Author)

A72-10247 Producibility in design. G. Petronio (Grumman Aerospace Corp., Bethpage, N.Y.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710748*. 8 p. Members, \$1.00; nonmembers, \$1.50.

Discussion of aspects of producibility, a concept defined as an input to aircraft design techniques which is aimed at the reduction of production cost and the enhancement of product profitability. Under this concept, a joint engineering and manufacturing team continuously analyzes fabrication methods and materials to minimize production cost and optimize product performance. This analysis is concurrent with all stages of design and can have strong influence on aircraft design. Applications of this concept to cast canopy frames, wing carry-through members, split cockpit sections, forgings, and castings are considered. V.Z.

A72-10248 Future trends in aircraft design. M. L. Olason and K. W. Hoefs (Boeing Co., Commercial Airplane Group, Renton, Wash.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710749*. 12 p. Members, \$1.00; nonmembers, \$1.50.

This paper identifies some future aircraft design trends by reviewing the projected traffic forecast, current transports and their potential derivatives, new technology, and some possible new programs. New airplanes examined include two versions (0.84M and 0.98M) for transcontinental and international use and a STOL version for short-haul operation. In addition, a special-purpose resource air carrier is discussed to indicate the degree to which an aircraft designer is able to accommodate unique requirements. For each new aircraft, the purpose of the design and the associated technology challenges are discussed. (Author)

A72-10249 The crystal ball focuses on the next generation of transport aircraft. R. E. Black, D. G. Murphy, and J. A. Stern (Douglas Aircraft Co., Long Beach, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufac-*

turing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710750. 20 p. Members, \$1.00; nonmembers, \$1.50.

Commercial aircraft market requirements are reviewed and all-cargo, STOL, SST and CTOL aircraft types currently being studied are discussed. It is concluded that after the derivative versions of the present generation of wide-body transports have been introduced into service, the next all-new commercial transport will probably be an advanced technology CTOL. This transport must be quieter than present aircraft. An assessment is made of what technological advances are most likely to be incorporated in this aircraft. Supercritical airfoil technology represents the most promising of the several expected technological advances. It can be applied to either economically increase cruise speeds or to significantly reduce operating costs. There are, in addition, a number of interesting possibilities in structures, propulsion and systems design. The characteristics of medium range aircraft, having cruise Mach numbers of 0.85, 0.92, 0.95, and 0.98, are presented. (Author)

A72-10250 **Advanced technology for STOL transports.** J. J. Cornish, III (Lockheed Georgia Co., Marietta, Ga.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710751.* 11 p. Members, \$1.00; nonmembers, \$1.50.

From an analysis of a typical large airport and its growth problems, it is concluded that STOL aircraft systems are needed now - with or without high-speed ground transportation systems. It is also shown that the needed first-generation STOL aircraft can be in operation in 1975. These contemporary STOL aircraft will, however, be only a step in the evolution to improved aircraft of the future. The needs for technological improvements are discussed, and some new prospects in STOL technology are described. (Author)

A72-10251 **FAA certification and the growth model 747B airplane.** E. Pfafman (Boeing Co., Seattle, Wash.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710753.* 6 p. Members, \$1.00; nonmembers, \$1.50.

Major differences in the 747-200B compared with the 747-100 include provisions for the higher thrust JT9D-7 engines, increased fuel capacity, increased maximum taxi weight and maximum flight weights, and a nacelle modification to meet the noise rule. Areas which could be improved by revised rules are considered together with certain problems encountered in connection with the overall 747 program. G.R.

A72-10252 **Development status of the L-1011 TriStar.** J. E. Hawkes (Lockheed-California Co., Burbank, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710755.* 21 p. Members, \$1.00; nonmembers, \$1.50.

A new commercial jet transport capable of expanding the current limits of operating efficiency, reliability and safety was the goal of the TriStar program in its design phase. Now, all indications are that the flight test phase of the program will result in the timely certification of such a plane and a prompt start of deliveries to airline customers. Flight time in the test program is ahead of schedule, and test results to date indicate that the TriStar will meet or exceed guarantees to the airlines. The latter case holds true particularly in respect to performance of certain advanced systems, such as the Autoland. G.R.

A72-10253 **The airworthiness certification of Concorde.** N. Harpur (British Aircraft Corp., Ltd., London, England). *Society of Automotive Engineers, National Aeronautic and Space Engineer-*

ing and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710756. 10 p. Members, \$1.00; nonmembers, \$1.50.

The certification authorities organization is discussed together with airworthiness requirements, maintenance procedures, and the certification program. Problems were encountered in connection with airworthiness objectives, the airworthiness performance code, the flying qualities, and the fatigue evaluation of structures. With the ground and flight test programs for development and for certification well under way, the task of establishing conformance with the requirements is progressing well. With increasing confidence that the ground and flight tests yet to be completed will proceed without any major setback, it is considered that British, French and U.S. Type Certification of Concorde will be achieved during the first half of 1974. G.R.

A72-10254 * **A progress report on the development of an augmentor wing jet STOL research aircraft.** H. C. Quigley, S. R. M. Sinclair (NASA, Ames Research Center, Moffett Field, Calif.), T. C. Nark, Jr., and J. V. O'Keefe (Boeing Co., Seattle, Wash.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710757.* 13 p. 14 refs. Members, \$1.00; nonmembers, \$1.50.

The development of the aircraft has progressed to the point where the design of the modifications to the de Havilland C-8A Buffalo is complete and the engines are being tested. The predicted performance shows that the aircraft will be able to take off and land in less than 1500 ft. Simulation studies indicate that the handling qualities of the aircraft, with stability augmentation, will be acceptable for STOL research missions. Special techniques were required, however, for flight path control and transition from cruise to landing configuration. G.R.

A72-10255 **Air Force STOL tactical transport technology program.** R. B. Lowry and G. S. Oates, Jr. (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710758.* 8 p. Members, \$1.00; nonmembers, \$1.50.

An industry-assisted, state-of-the-art assessment of STOL tactical transport technology has been conducted by the Air Force. The assessment indicated that three turbofan concepts possessed the highest potential for satisfying the Air Force medium STOL transport mission. These concepts are the externally blown jet flap, internally blown jet flap, and mechanical flap with vectored cruise thrust. The Air Force has constructed a program to identify and fill the gaps in the technology, thereby reducing future system development risk. The program will also identify areas requiring future research. The program is in three phases, with the first phase primarily small-scale wind tunnel tests, analyses, and ground-based simulation. Phase II consists of larger-scale wind tunnel testing, critical component testing, and further simulation. Phase III is scheduled to be development of a technology demonstrator vehicle. Inasmuch as approval has only been granted for phase I, detailed task descriptions for only that phase are given in this paper. (Author)

A72-10256 **Design comparison of quiet M = 0.80 STOL transports.** R. Scherrer and R. Olson (Lockheed-California Co., Burbank, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710759.* 14 p. 27 refs. Members, \$1.00; nonmembers, \$1.50.

This paper deals with a comparison, on a common basis, between quiet, point-design, turbofan, prop-fan, and turboprop intercity STOL transports as a means of possibly accelerating convergence toward a preferred system. Results indicate the high

speed turboprop aircraft is superior in terms of minimum gross weight, and therefore superior in direct operating cost and ticket cost. It is probably also the safest of the three aircraft because of the greatest thrust margin and least thrust asymmetry during wave-off.

(Author)

A72-10257 **Propulsion system optimization for the ATT.**
G. L. Brines (United Aircraft Corp., Pratt and Whitney Aircraft Div., East Hartford, Conn.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710760.* 6 p. Members, \$1.00; nonmembers, \$1.50.

Supercritical airfoil technology offers the potential of efficient commercial flight at or near the speed of sound. This paper reviews a recent internal study by Pratt and Whitney to define the optimum propulsion system characteristics for a commercial transport designed to fly at Mach 0.95. The impact on aircraft gross weight of propulsion cycle characteristics such as bypass ratio, overall pressure ratio, turbine temperature, nacelle weight and drag as well as the important criteria of noise is reviewed. In addition, the implications of flying at very high initial cruise altitudes above the majority of current traffic is discussed.

(Author)

A72-10258 **Propulsion system requirements for advanced technology air transports.** M. B. Schwartz (United Air Lines, Inc., Chicago, Ill.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710761.* 6 p. 5 refs. Members, \$1.00; nonmembers, \$1.50.

This paper endeavors to identify some of the requirements for the propulsion system of the advanced technology transport. These requirements lie in the areas of design, material selections, accessibility and maintainability of the system, and noise and emission control. The design should provide for adequate stall margins for the compressor, maximum reliability, mechanical and operational simplicity whenever possible, and a modular type of assembly to facilitate on-line and on-wing maintenance. The airframe manufacturer must engineer the powerplant installation to provide maximum accessibility to the engine gas path hardware and the engine accessories. The engine designers must strive for noise levels within the state-of-the-art and preferably below the FAR 36 compliance requirements. The engine should be optimized to produce the minimum possible amount of noxious gases, particulates, and unburned hydrocarbons.

(Author)

A72-10259 * **Installation and integration of transonic transport propulsion systems.** L. T. Goodmanson and W. H. Schultz (Boeing Co., Commercial Airplane Group, Renton, Wash.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710762.* 14 p. Members, \$1.00; nonmembers, \$1.50. Contract No. NAS 1-10703.

Initial work indicates that a viable aircraft family can be designed for higher subsonic cruise speeds. Studies to date suggest that the propulsion system/nacelle design and the incorporation of noise attenuation into this design will have more influence on the choice of an optimum engine than engine weight and fuel consumption. These studies also suggest the payoff resulting from the incorporation of new technology items such as the internal engine generator and new structural cowl concepts because of the greater sensitivity to drag. These factors, plus the greater interdependency of the transonic aircraft and its propulsion system, point up the importance of a total system approach to propulsion system optimization and design.

G.R.

A72-10265 **Graphite fan blade development.** B. L. Koff (General Electric Co., Aircraft Engine Group, West Lynn, Mass.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710771.* 17 p. Members, \$1.00; nonmembers, \$1.50.

A status summary is given for the development at General Electric's engine test facility at Peebles, Ohio, of a graphite fiber composite fan blade design suitable for flight application. Used in subsonic turbofan engines, the fan blade design provides substantial potential reductions in weight for both the fan rotor and the containment structure as well as reduces sensitivity to fatigue failure from foreign object damage. A composite system containing 60% Modmor Type 2 fibers and 40% E293 epoxy resin was selected as the material for the blade design. The various phases of processing and testing the composite fans are described. At the present development stage the graphite composite fan can take the impact of twelve 1 and 2-in. iceballs fired at 400 knots without damage.

V.Z.

A72-10266 * **The NASA Quiet Engine.** J. J. Kramer (NASA, Lewis Research Center, Cleveland, Ohio). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710774.* 8 p. 13 refs. Members, \$1.00; nonmembers, \$1.50. NASA-supported research.

The NASA Quiet Engine Program will incorporate all available noise-reduction technology into a propulsion system suitable for subsonic civil transport aircraft. Full-scale experimental hardware is being built and tested primarily for noise performance. The program is in process, and component tests to date indicate that it is possible to achieve or exceed noise reduction objectives of 15-20 PNdB below the levels of 707/DC-8 long-range transport aircraft.

(Author)

A72-10267 **Olympus 593 powerplant in Concorde.** P. H. Calder (Rolls-Royce, Ltd., Bristol Engine Div., Bristol, England). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710775.* 18 p. Members, \$1.00; nonmembers, \$1.50.

Most of the important technical aspects of the two prototype Concorde and of their Olympus 593 powerplants have been explored and the aeroplanes are flying regularly at Mach 2.0 over long distances. The current status of the powerplant performance, further performance development, the engine and intake control systems, the reheat and exhaust systems, engine/intake compatibility, bench and flight engine development program, the environment and service experience, are reviewed. Convincing performance demonstrations have been made and active discussions with airlines are in hand regarding production versions of the aeroplane.

(Author)

A72-10268 **Design features of the Garrett ATF3 turbofan engine.** R. R. Van Nimwegen (AiResearch Manufacturing Co., Los Angeles, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710776.* 14 p. Members, \$1.00; nonmembers, \$1.50.

A new approach in the design of small turbofan aircraft propulsion engines is directed toward providing executive type aircraft with coast-to-coast capability. The Garrett ATF3 turbofan engine employs a unique three-spool design concept using advanced component technology, provides an efficiency comparable to the largest turbofan engines, has low emissions, and is easily maintained.

(Author)

A72-10269 Influence of powerplant design on airplane operational effectiveness - The operator's point of view. J. R. Wilcox (American Airlines, Inc., New York, N.Y.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710777*. 3 p. Members, \$1.00; nonmembers, \$1.50.

Discussion of a single-team approach to the development of the jumbo tri-jet and its power-plant installation. According to it, the manufacturers and operators of the airframe and the engine are organized into a single team to produce a power-plant installation with an operational efficiency in keeping with the jumbo tri-jet mission requirements. V.Z.

A72-10270 Team approach to power plant design for maximum operational effectiveness. L. A. Wright (Douglas Aircraft Co., Long Beach, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710778*. 8 p. Members, \$1.00; nonmembers, \$1.50.

A new concept of intimate customer participation evolved during the design, development, and test phases of the DC-10 propulsion system. This concept was resolved into the Airline Propulsion Team approach which took full advantage of the unique contributions to design available from the customer. The design of the DC-10 propulsion system incorporates customer contributions based on his experience and expertise in such areas as operation, maintenance, and overhaul. This paper discusses the methods and operation of the Airline Propulsion Team as well as the immediate and projected benefits resulting from customer participation.

(Author)

A72-10271 The CF6 engine - Designed to improve operational effectiveness. R. W. Hevener (General Electric Co., New York, N.Y.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710779*. 15 p. Members, \$1.00; nonmembers, \$1.50.

Description of improved design concepts incorporated in the CF6 engine to meet new requirements in performance, operational characteristics, environmental considerations, dispatch reliability and utilization, and heavy maintenance. Improvements described involve fuel consumption, thrust-weight ratio, starter air requirements, noise levels, smoke emission, maintenance schedules, monitoring capabilities, and accessory replacement procedures. T.M.

A72-10280 Control of warpage during machining. C. L. Bennett (General Dynamics Corp., Convair Aerospace Div., San Diego, Calif.). *Society of Automotive Engineers, National Aeronautic and Space Engineering and Manufacturing Meeting, Los Angeles, Calif., Sept. 28-30, 1971, Paper 710801*. 7 p. Members, \$1.00; nonmembers, \$1.50.

The increased use of large aluminum-alloy forgings for structural components of the jumbo jet air transport brought attention to bear on the costly distortion problem associated with machining these forgings. This paper discusses one warpage problem - the floor beam - and its solution. Investigation showed that distortion is due primarily to the relief of residual quenching stresses by machining, and that the amount of distortion depends upon the magnitude, distribution, and locations of these stresses within the part. Control of this condition and improved packing and storage methods resulted in a greatly reduced distortion incidence. (Author)

A72-10301 Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. Symposium sponsored by the Royal Aeronautical Society. London, Royal Aeronautical Society, 1971. 239 p.

Following a review of parachute applications and some associated research problems, the symposium deals with escape from aircraft, paratrooping, supply dropping, braking of aircraft, and the stabilization and retardation of weapons and other armament stores. Three-component measurements for rigid parachute models, parachute research and development, testing, observations on breathing and related phenomena, high and low speed parachute research, aerodynamic inflation of parachutes, supersonic and transonic deployment of ribbon parachutes, materials, and mechanics of failure are among the subjects treated.

F.R.L.

A72-10302 A review of parachute applications and some associated current research problems. G. W. H. Stevens (Royal Aircraft Establishment, Farnborough, Hants., England). In: *Two-Day Symposium on Parachutes and Related Technologies*, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 19 p. 45 refs.

Review of the major designs of parachutes that have been used and why they are used in certain particular roles. Emphasis is on the basic scientific and technical aspects. The fields of application discussed are escape systems, weapons systems, paratrooping, supply dropping, upper atmosphere recovery systems, braking and energy absorption, aids to aircraft testing, and sport. An attempt is made to discuss problems rather than techniques. F.R.L.

A72-10303 # Three component measurements for rigid parachute models. K.-F. Doherr and D. Schmerwitz (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Braunschweig, West Germany). In: *Two-Day Symposium on Parachutes and Related Technologies*, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 13 p. 5 refs.

The results of three component measurements for two sets of nonporous rigid models are presented. Both sets consisted in a hemispherical canopy with conical skirts of different length and with suspension lines made of thin wires. The second model set differed from the first one by a small ring of brass sheet which was placed at the position of the largest projected diameter of the hemisphere. This ring predetermined the region of flow separation. (Author)

A72-10304 # Parachute R & D in industry. D. Gladstone (Irvin Great Britain, Ltd., Letchworth, Herts., England). In: *Two-Day Symposium on Parachutes and Related Technologies*, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 8 p.

Examination of the industrial approach to parachute research and development in the U.K., with particular reference to the management aspects. The task of the research and development department is to generate production work; its activity is divided into the areas of materials and the parachutes themselves. Technical staff requirements are outlined, and the need for close liaison between government and industry is emphasized. F.R.L.

A72-10305 # The testing of parachutes at supersonic speeds. A. R. Turley and J. A. I. Reid (Hunting Engineering, Ltd.). In: *Two-Day Symposium on Parachutes and Related Technologies*,

London, England, September 15, 16, 1971, Proceedings.

London, Royal Aeronautical Society, 1971. 16 p.

Results of experience in obtaining information on the performance of small ribbon parachutes at speeds up to Mach 1.5. Trial work was carried out in a 9 x 8 ft transonic wind tunnel, a rocket sled track, and a water channel simulator. The rocket-propelled test vehicle overcomes the problems in wind tunnel trials of the small size of the specimen and the low density of the air. Initial water-channel simulator trials determined that the largest practical model size was a parachute with a flying diameter of 3 in.

F.R.L.

A72-10306 **The influence of axial cords on parachute performance.** K. James (Royal Aircraft Establishment, Farnborough, Hants., England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 17 p.

The paper describes some trials that have recently been made in a wind tunnel at RAE to ascertain some of the characteristics of parachutes fitted with axial cords. The properties examined were the effect of the length of the axial cord on the drag of the parachute, on the diameter and projected area, shape, drag coefficient and stability. The drag was separated into its two components, carried respectively by the axial cord and by the main rigging lines. The opening characteristics of the parachutes were not investigated in these trials, but a number of parachutes of different shape were examined. These trials were supplemented by full-scale tests on 124 parachutes fitted with axial cords, by dropping block rubber dummies with them from a balloon at Cardington, and the time of opening was measured in these trials. The results of all these trials are given in the paper and discussed.

(Author)

A72-10307 # **Observations on breathing and related phenomena in some paratroop type parachutes when freely descending.** R. G. Hume and G. W. H. Stevens (Royal Aircraft Establishment, Farnborough, Hants., England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 14 p. 6 refs.

Results of a series of parachute trials arranged to perform a dual function: to study the performance of several paratroop-type parachute assemblies under various store loadings, and to observe breathing oscillations, if any, in these parachutes. High speed motion picture cameras and kinetheodolites tracked the parachutes for about 15 sec during the steady part of each descent. It appears that breathing does not appear to be a priority consideration; rather, there seems to be a need to concentrate on canopy stability.

F.R.L.

A72-10308 # **High speed parachute research in the U.K.** B. Tansley and D. Northey (Irvin Great Britain, Ltd., Letchworth, Herts., England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 12 p. 9 refs.

Review of the results obtained in the aerodynamic and structural sections of a program designed to investigate problems of supersonic parachutes for release at speeds up to Mach 1.5 at low altitude. The work dealt with flat, conical and hemispherical ribbon parachutes, and was carried out in a wind tunnel and on a rocket sled. In addition to aspects of aerodynamic drag, structure, and loads in individual elements, ribbon flutter and inflation time are discussed.

F.R.L.

A72-10309 # **The performance of parachutes at low speeds.** J. R. Mitchell (RFD-GO, Ltd., Woking, Surrey, England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 6 p.

Study of the flow characteristics of parachutes in free descent at low airspeed, which requires taking account of the variation in drag, glide angle, and oscillation angle. Wind tunnel tests showed that the effect of the gliding angle was to make the total drag of the parachute about twice what would be expected for the same parachute following a path parallel to its axis. Flow patterns were studied in a water channel, from which it appears reasonable to assume that the section of the parachute canopy can be represented by the arc of a circle.

F.R.L.

A72-10310 **Theory and experiment on parachute opening shock and filling time.** H. G. Heinrich (Minnesota, University, Minneapolis, Minn.). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 14 p. 18 refs.

Outline of a method of parachute opening force and filling time calculation which is based on the time functions of aerodynamic drag, included air mass, apparent mass, and effective porosity. Using the momentum and continuity equations, an idealized canopy shape development, and a linear drag area-time relationship, expressions are obtained for the canopy volume and velocity. The calculated peak forces agree well with least mean square averages of field test results of 28-ft solid flat parachutes. It was found that forces and times change very little when figures were used which are within the presently accepted range of values.

F.R.L.

A72-10311 # **The aerodynamic inflation of shell type structures with particular reference to parachutes.** B. W. Roberts (Sydney, University, Sydney, Australia). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 19 p. 15 refs.

Development of a new method for calculating the inflation loads and inflation times on a variety of subsonic parachute assemblies. The method is intended to serve as an alternative to the 'filling time' method proposed by Heinrich et al. The unsteady pressure distribution on a decelerating, inflating parabolic shell of revolution in the presence of an unsteady starting vortex flow is derived. If this resulting pressure distribution is used in conjunction with the structural constraints on the parachute system, then it is possible to find explicitly the opening loads and opening times. In essence, the method is a numerical solution to a nonlinear, second-order continuous system beginning with an appropriate set of initial conditions. A series of numerical examples is given to illustrate the versatility of the method.

F.R.L.

A72-10312 # **Supersonic and transonic deployment of ribbon parachutes at low altitudes.** R. C. Maydew and D. W. Johnson (Sandia Laboratories, Albuquerque, N. Mex.). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 17 p. 8 refs. AEC-supported research.

Results are presented for twenty-five flight tests of a 22.2-ft (6.8-m) diameter ribbon parachute (reefed for 0.5 sec) with a nominal 2000-lb (907 kg) store. The design, fabrication, and packing of the parachute system are discussed. Low altitude drop tests were made with F-4 and A-4 aircraft at Mach numbers from 0.57 to 1.22, and rocket-booster tests were made at Mach numbers from 1.62 to

1.70, the latter corresponding to a maximum dynamic pressure of 2720 psf (130 kN/sq m). The maximum measured snatch load, reefed stage opening shock, and second stage opening shock were approximately 65 klb (289 kN), 165 klb (734 kN) and 150 klb (667 kN), respectively. The measured load data and sequence of parachute function times are relatively consistent and repeatable. There is no discernible effect of Mach number on the steady state drag area of the reefed parachute at Mach numbers from 0.7 to 1.50. (Author)

A72-10314 # Materials for use in parachutes. S. A. Birch (Irvin Great Britain, Ltd., Letchworth, Herts., England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 17 p.

Outline of the properties required for canopy fabrics and rigging line cordages, with review of materials in use and suggestions as to future trends. Nylon 66 is considered to be the most suitable material, and will continue to be used extensively. Nonwoven scrim-reinforced fabrics are likely to be used as canopy fabrics for 'once-off' use. Polypropylene fabrics and cordages have the advantage of cheapness. F.R.L.

A72-10315 # The strain of stitched joins. J. R. Mitchell (RFD-GQ, Ltd., Woking, Surrey, England). In: Two-Day Symposium on Parachutes and Related Technologies, London, England, September 15, 16, 1971, Proceedings. London, Royal Aeronautical Society, 1971. 4 p.

Consideration of one type of nylon webbing and two main types of thread, flax, and nylon. Flax extends about 3% at failure, which means that when a webbing join is stitched with flax, the first row of stitching is unable to stretch sufficiently to pass on much of the strain to the second row of stitching. The use of a nylon thread enables the strain to be transmitted differentially along the stitched join, but if the thread is more than twice as strong as the weft yarn it is possible for the weft yarn to be broken instead of the stitching so that the main webbing becomes shredded. A thicker webbing is more efficient to stitch than a thinner one because the extension of thread is greater in comparison with the actual extension of the warp yarns. F.R.L.

A72-10384 Aerospace wire and cables methods of testing. *SAE Aerospace Standard*, AS 1198, July 15, 1971. 43 p.

Recommended physical, electrical, and chemical methods of testing aerospace wires and cables for conformance to the requirements of their controlling detail specifications and other related documents. The intent of this instruction is to promote standardization and to eliminate unnecessary or undesirable variation in testing procedures. Conductor, insulation, wire, and cable test procedures are detailed for evaluating mechanical properties, coating thicknesses, continuity flaws, resistance, flammability, dimensions, dielectric properties, geometrical symmetry, abrasion characteristics, durability of identification, power factors, thermal effects, smoke characteristics, and other requirements. T.M.

A72-10385 High pressure oxygen system filler valve. *SAE Aerospace Standard*, AS 1225, July 30, 1971. 4 p.

Optimum standards of design, construction, and performance are defined for an oxygen filler valve used in aircraft to ensure safe servicing of high-pressure oxygen system cylinders. The intent is that the valve shall automatically control the rate of fill such that the temperature rise in the oxygen system caused by compression

heating of the gas will be within acceptable limits. In addition, the valve is to have a pressure sensitive closing valve to automatically control the final pressure for a correct amount of oxygen in the system cylinder. The pressure closing level may be manually selected by means of adjustment dials on the valve. T.M.

A72-10386 Pressure altimeter system minimum safe performance standard. *SAE Aerospace Standard*, AS 942, June 15, 1971. 15 p.

Specification of the requirements for minimum safe performance of an altimeter system in its normal mode of operation on subsonic aircraft. Compliance is a means of assuring that the altimeter system will satisfactorily perform its intended function when exposed to conditions encountered in routine operations. The instrument system specified shall accept an input of static pressure, and in some equipment other inputs, that contribute altitude information to provide a visual indication of pressure altitude. Test procedures are described which apply specifically to analog type instruments. F.R.L.

A72-10388 Hose assemblies - Aircraft and missiles, lightweight plastic hose, low pressure. *SAE Aerospace Recommended Practice*, ARP 1180, July 15, 1971. 12 p.

Physical requirements and quality assurance provisions for lightweight plastic hose assemblies to be used in aircraft and missile petroleum-base-fuel and petroleum-base and synthetic lubricating oil systems operating in a temperature range of -65 to +275 F at pressures to 200 psi. Performance tests, oil resistance tests, fuel resistance tests, flexibility and vacuum tests, qualification testing, and preparation for delivery of the product are detailed. T.M.

A72-10389 Flight test procedures for static pressure systems installed in subsonic transport aircraft. *SAE Aerospace Recommended Practice*, ARP 921, July 15, 1971. 11 p. 24 refs.

Definition of the test procedures and equipment for performing flight testing on pitot-static systems installed in subsonic transport aircraft, the regulator documents being those of the FAA and the SAE. Prior to flight testing of any pitot-static system, the system should have been tested in accordance with the recommendations of ARP 975. In the interest of standardization only the trailing cone method of flight calibration is recommended; it exhibits very little or no static pressure errors. In principle, the idea is to suspend a static reference far enough behind an aircraft so that the ports are not affected by the aerodynamic disturbances of the airframe. F.R.L.

A72-10390 Turbine nozzle area measurement by airflow method. *SAE Aerospace Recommended Practice*, ARP 1195, July 15, 1971. 21 p.

Description of a recommended practice which provides a standard basis for airflow measurement of the relative aerodynamic throat area of gas turbine nozzles. Methods, conditions of measurement, and acceptable standards of accuracy are covered, and equipment known to meet the general requirements is described. Standard reference nozzles and mounting flanges are specified. F.R.L.

A72-10506 # Compensation of cross-couplings in aircraft motion (Kompensatsiia perekrestnykh svyazei v dvizhenii samoleta). V. S. Mechetnyi. In: Complex control systems.

Kiev, Naukova Dumka, 1971, p. 132-142. 11 refs. In Russian.

Investigation of the problem of aeroinertial interaction between the longitudinal and lateral motions (pitching and yawing) of a high-speed aircraft. The presence of cross-couplings between these motions leads to a deterioration of the dynamic properties of the aircraft and a complication of the control process. It is noted that known means of combating this phenomenon are frequently accompanied by undesirable consequences involving a disturbance of controllability, a reduction of maneuverability, and a limitation of the possibilities of a modern high-speed aircraft. A method of compensating aerodynamic cross-couplings is proposed. The laws of operation of a special cross-coupling compensation device performing this task are determined. It is shown that if the time constant of the compensation device is taken into account the aircraft/compensator system will be stable if the isolated pitching and yawing motions were stable. A.B.K.

A72-10723 # Strength and stiffness of sandwich panels under transverse loading. M. Langley. *Aircraft Engineering*, vol. 43, Oct. 1971, p. 11-15. 8 refs.

Description of work performed to translate Allen's (1969) theory of structural sandwich panel design into a form suitable for rapid estimation in a design office. The properties of end grain balsa were evaluated from the viewpoint of using it as the core material between metal and reinforced plastic facings. The consistency of balsa at any given density was examined as an essential property of the shear modulus; the latter quantity was evaluated and checked through a large number of beam tests. The results were used in panel testing for establishing a simple design office method of calculating the stresses and corresponding deflections in panels. T.M.

A72-10724 # A300B European Airbus - Hydraulics and landing gear. *Aircraft Engineering*, vol. 43, Oct. 1971, p. 16, 17.

Description of the hydraulics and landing gear of the European Airbus, demonstrating that generally known solutions are used. The landing gear was designed to have long fatigue life (32,000 flights); safety - e.g., free fall lowering and downlocking; reliability; easy maintenance - e.g., all parts of the main gear are identical and interchangeable between right and left hand; and simplicity. Maximum effort was made toward keeping weight to a minimum. Altogether the gear with its retraction jacks, but without wheels, brakes, and tires, weighs 7800 lb, or 2.7% of the takeoff weight of the aircraft. F.R.L.

A72-10725 # Flap and slat systems and tailplane actuator. *Aircraft Engineering*, vol. 43, Oct. 1971, p. 20-23.

Description of the flap and slat systems and the tailplane actuator of the A300B which were designed to the highest standard of reliability combined with minimum weight. Complexity is reduced to a minimum, and maximum use is made of proven principles in an attempt to reduce development costs. The slat operating system comprises a control unit, a transmission system, and twelve ball screw jacks, and it is required to operate three slat sections in each wing. The flap operating system is basically similar. The tailplane actuator, sited in the unpressurized rear section of the fuselage, forward of the tailplane pivot center, controls the longitudinal pitch trim by setting the position of the variable incidence tailplane according to commands initiated by the pilot or autopilot. F.R.L.

A72-10749 Tensile behavior of high-strength alloys during rapid heating. D. Hauser (Battelle Columbus Laboratories, Columbus,

Ohio) and J. W. Wright, Jr. (U.S. Army, Research and Engineering Directorate, Redstone Arsenal, Ala.). In: Space shuttle materials; Proceedings of the National Technical Conference, Huntsville, Ala., October 5-7, 1971. Azusa, Calif., Society of Aerospace Material and Process Engineers, 1971, p. 287-295. 7 refs. Contract No. N 60921-68-C-0220.

Studies of tensile behavior were conducted on two grades of maraging steel, Ti-6Al-4V titanium alloy, and 7075-T6 aluminum alloy by applying a high tensile stress at room temperature that was maintained during subsequent rapid heating to failure. The results were compared to properties obtained from standard room- and elevated-temperature tensile tests. Significant differences in tensile behavior between these types of evaluations were found that demonstrate the need for developing design properties under conditions that closely simulate launch and reentry service conditions. (Author)

A72-10783 Experimental evaluation of lightning protective coatings for boron/epoxy composites. E. H. Schulte and D. W. Clifford (McDonnell Aircraft Co., St. Louis, Mo.). In: Space shuttle materials; Proceedings of the National Technical Conference, Huntsville, Ala., October 5-7, 1971. Azusa, Calif., Society of Aerospace Material and Process Engineers, 1971, p. 737-745. 12 refs.

A number of candidate lightning protective coatings for composite structural materials have been evaluated in the McDonnell Aircraft Company (MCAIR) Lightning Simulation Laboratory. Emphasis has been placed on coating parameter optimization and elucidation of damage mechanisms. Coated and uncoated aluminum foils, plasma sprayed aluminum, aluminum meshes, and bronze meshes, on dielectric substrates were tested by exposure to simulated high current lightning strikes. (Author)

A72-10813 # Radioactive gas penetrant system - A report on initial product application. W. C. Eddy, Jr. (Industrial Nucleonics Corp., Columbus, Ohio). In: Symposium on Nondestructive Evaluation in Aerospace, Weapons Systems, and Nuclear Applications, 8th, San Antonio, Tex., April 21-23, 1971, Proceedings. North Hollywood, Calif., Western Periodicals Co., 1971, p. 265-271.

Review of the application of radioactive gas penetrants to jet engine manufacturing nondestructive evaluation problems and maintenance or service problems. The process is superior for the detection of porosity in complex investment castings and shows promise for measuring and evaluating low-cycle fatigue damage. Although the gas penetrant system would appear to serve only as a technique where defects are open to the surface, microstructure anomalies in most engineering materials have given a surprising degree of depth measurement capability. F.R.L.

A72-10814 # Development of ultrasonic field inspection equipment for T53 gas turbine compressor discs. B. E. Leonard (School of the Ozarks, Point Lookout, Mo.), S. R. McFarland (Southwest Research Institute, San Antonio, Tex.), and J. M. Thorp (U.S. Army, Aviation Systems Command, St. Louis, Mo.). In: Symposium on Nondestructive Evaluation in Aerospace, Weapons Systems, and Nuclear Applications, 8th, San Antonio, Tex., April 21-23, 1971, Proceedings. North Hollywood, Calif., Western Periodicals Co., 1971, p. 272-277. Grant No. DA-AJ-01-68-C-1981(31).

Study of the cracking mechanism and development of a nondestructive means of early crack detection, undertaken because of the occurrence of service-induced cracking in the tenons of T53

gas turbine compressor disks. An ultrasonic device to locate cracks in affected components without removing the engine from the aircraft is described. The unit is completely portable and self-contained.

F.R.L.

A72-10816 # A metallurgical analysis of cracking in compressor discs of the T53-L13 gas turbine engine. H. C. Burghard, Jr. (Southwest Research Institute, San Antonio, Tex.). In: Symposium on Nondestructive Evaluation in Aerospace, Weapons Systems, and Nuclear Applications, 8th, San Antonio, Tex., April 21-23, 1971, Proceedings. North Hollywood, Calif., Western Periodicals Co., 1971, p. 299-310. 6 refs. Army-sponsored research.

Results of a comprehensive metallographic and fractographic examination of selected cracked tenons from second-stage compressor disks. The macroscopic features of the crack surfaces indicated crack initiation at points along the groove surface but did not provide any definite evidence of the fracture mechanism involved. Electron fractographic examination revealed that the crack surfaces were characterized by a predominance of a unique 'step-type' topography and only limited regions of well-defined fatigue striations. The combined observations of the metallographic and fractographic investigation established that the predominant fracture mechanism involved in the cracking of second-stage disks was high-cycle fatigue crack propagation.

F.R.L.

A72-10864 An assessment scheme for aerodrome forecasts. P. B. Wright. *Meteorological Magazine*, vol. 100, Oct. 1971, p. 285-293.

A method is described which enables an assessment to be made, in a broad sense, of the usefulness of a set of terminal aerodrome forecasts. The test is confined to the elements of visibility, surface wind and low cloud, and the scoring system is such that an error in the neighborhood of values critical for the landing and takeoff of aircraft is marked more harshly than an error in another part of the range. The scheme also takes into account the use of PROB, TEMPO and INTER in a way which simulates the loss of value to the customer of a reduction in the preciseness of the forecast. (Author)

A72-10946 MSDS - An experimental 24-channel multi-spectral scanner system. E. M. Zaitzeff (Bendix Corp., Aerospace Systems Div., Ann Arbor, Mich.). In: Astronautical research 1970; International Astronautical Federation, Congress, 21st, Konstanz, West Germany, October 4-10, 1970, Proceedings. Amsterdam, North-Holland Publishing Co., 1971, p. 702-711.

Description of the electromechanical scanner, encoding and recording electronics, ground processing operations, and aircraft mounting details of a multispectral scanning system to be flown in a NASA C-130 earth resources aircraft. Scanner operation covers 24 channels assigned to bands between 0.34 and 13 microns. The energy reflected or radiated from underlying terrain is reflected from a 45-deg rotating mirror and introduced into a spectrometer followed by appropriate detectors for the different channels. Calibration sources are explained, together with the electronics equipment. T.M.

A72-10960 Automated air traffic control. W. G. Laliberte, J. C. Nelson (Sperry Rand Corp., Univac Div., Washington, D.C.), R. J. Rolfe, J. C. Sater, J. D. Erickson, and G. L. Humfelt (Sperry Rand Corp., Univac Div., St. Paul, Minn.). *Sperry Rand Engineering Review*, vol. 24, no. 2, 1971, p. 2-23.

Description of the automated radar terminal system, ARTS III,

whose installation is either planned or underway in 62 major U.S. air terminals. It is a modularly expandable, radar-controlled, beacon-tracking system which satisfies its essential design goal: it monitors - and has the potential capability of tracking - all aircraft flying within its radar range. In essence, ARTS 'sees' all aircraft within a 55-mile radius of the terminal, and displays the tracks of all beacon-equipped aircraft. The information displayed for the controller includes identification, altitude, and ground speed. By 1980, it is expected that 200 of the most advanced terminal automation systems will be in operation, thereby enabling the traffic controller to keep pace with the increase in global air traffic.

M.V.E.

A72-10961 Automated landing system. M. J. Popik (Sperry Rand Corp., Sperry Flight Systems Div., Phoenix, Ariz.). *Sperry Rand Engineering Review*, vol. 24, no. 2, 1971, p. 24-31.

The role of automatic flight control in the over-all air traffic monitoring scheme is to provide precision, consistency, and automaticity, while giving flight crews more time for situation assessment and managerial duties. This role is especially crucial in the terminal area, where traffic density compounds crew workload and where the need for craft guidance during poor weather conditions presents the greatest challenge. Over the past five years, automatic flight control capability has been expanded to include not only landing, but also a variety of cruise modes of operation as required under specific, federally designated weather categories. The most recent automatic landing system to go into scheduled service is the 'fail-operational' system in the Boeing 747, which includes Sperry Rand's SPZ-1 autopilot-flight director system. This system has the capability of sustaining a failure while automatically guiding an aircraft to touchdown. As a result, it is the first autoland system for which a reduction in operational weather minimums has been allowed by either the United States or United Kingdom regulatory agencies. Early versions of the SPZ-1 and other automated Sperry Rand equipment have been controlling scheduled commercial aircraft to touchdown since February 1967, when one of Pan American's Boeing 727 jetliners made a fully automatic landing at JFK International Airport in New York. Since that time, other commercial aircraft have gained certification for automatic landing; in the future, all major aircraft are expected to be certified with autoland capability as a result of the safety it has added to poor-weather landings.

(Author)

A72-10962 Electronic scanning array for ATC. J. J. Stangel and R. J. Timms (Sperry Rand Corp., Sperry Div., Great Neck, N.Y.). *Sperry Rand Engineering Review*, vol. 24, no. 2, 1971, p. 32-36.

Phased array systems overcome many of the critical restraints on air traffic control. They can be used for air traffic control radar beacon systems, airport or air route surveillance radars, and ground landing systems. A microwave data link between aircraft and ground control can be incorporated in the beacon system on a time share basis, significantly alleviating the burden on voice communications. The flexibility of electronic scanning will contribute to further automation of the air traffic control system.

(Author)

A72-10963 Aircraft power steering. J. Camp and M. J. Campbell (Sperry Rand Corp., Vickers Div., Troy, Mich.). *Sperry Rand Engineering Review*, vol. 24, no. 2, 1971, p. 37-40.

The increasing demand for short-haul air travel, once in the exclusive service of big business but now compounded by a more general public need, has contributed to a rapid sales growth of intermediate-sized aircraft. The intermediate-sized plane must be able to utilize small fields (many of which do not have elaborate service

and maintenance facilities); at the same time, it must be capable of restarting with a self-contained energy source after standing unattended for long periods of time. All aircraft subsystems, designed with this same self-sufficiency potential, must be simple enough for easy maintenance and repair, yet sufficiently rugged for long life. An electromechanical nose wheel steering system developed by Sperry Rand's Vickers Division now supplies general aviation aircraft with the needed maneuverability and durability, and meets each aircraft's unique design parameters. (Author)

A72-10964 **A simple three-dimensional missile trajectory model.** G. B. Henton (Hughes Aircraft Co., Culver City, Calif.). *Simulation*, vol. 17, Aug. 1971, p. 83-87.

A three-dimensional trajectory model for missiles roll-controlled to an extent precluding any appreciable degree of roll is presented. It makes possible quite simple time-sharing digital or analog three-dimensional simulations. Motivation for the development of this missile trajectory model came from the need to overcome the limitations of single-plane simulation which restricts consideration to incoming and outgoing targets, even though crossing targets are of equal - if not greater - interest. In developing the presented trajectory model, advantage was taken of the existence of an easily computed direct transformation from wind-axis coordinates to inertial-axis coordinates for the case of a perfectly roll-controlled missile. M.V.E.

A72-10968 **Manufacturing experiences with graphite filament reinforced composites.** F. J. Fechek (USAF, Materials Laboratory, Wright-Patterson AFB, Ohio). *Society of Manufacturing Engineers, International Engineering Conference and Tool Exposition, Philadelphia, Pa., Apr. 26-30, 1971, Paper EM 71-205*. 16 p.

Graphite filament reinforced composites possessing significant strength and modulus to density ratios have been developed to the point where feasibility and performance potential has been definitely established. The fiber/resin combinations available provide the designer with many alternatives to mechanical performance vs cost and manufacturing technique. This multiplicity of materials systems has tended to limit the obtaining of a large amount of statistical data on any single system to date, however. A description of the various constituent materials properties is presented along with a listing of components which have been designed, fabricated and tested using graphite fiber reinforced composites as the major structural material. Selected examples of structural hardware demonstration items are used to describe the fabrication processes and the tooling concepts which were employed. (Author)

A72-10969 **Integrity control procedures for machining 300M steel and titanium aircraft components.** C. M. Fleming and P. Arzt (McDonnell Aircraft Co., St. Louis, Mo.). *Society of Manufacturing Engineers, International Engineering Conference and Tool Exposition, Philadelphia, Pa., Apr. 26-30, 1971, Paper IQ 71-238*. 18 p.

This paper describes engineering programs and methods used at McDonnell Aircraft Company (MCAIR) to develop surface integrity data for establishing process requirements for conventional machining, drilling, and grinding 300M steel and Ti-6Al-4V annealed titanium. Procedures, specimen types and test data obtained during drilling, reaming, and grinding of these materials are given. Also included is a discussion of the temper etch inspection method for steel surfaces and various methods used to improve the sensitivity of this nondestructive inspection method. Finally, methods used to control surface integrity during the fabrication of both commercial and fighter aircraft parts are described. (Author)

A72-11021 **Ultrasonic inspection of helicopter rotor blades.** I. Glover (Westland Aircraft, Ltd., Yeovil, Somerset, England). In: *Ultrasonics 1971; Proceedings of a Conference, London, England, September 28, 29, 1971*. Guildford, England, IPC Science and Technology Press, Ltd., 1971, p. 76-78.

Description of an automatic ultrasonic testing facility for use in inspecting a new type of blade construction on the Lynx helicopter. The basic NDT problems involved in inspecting the new type of blade are outlined, and the methods employed in solving them are described. Finally, the complete test installation is discussed, including the arrangements for ultrasonic inspection, complex scanning, and facsimile recording. A.B.K.

A72-11067 **Influence of electric power quality on avionic design and weapon system effectiveness.** J. S. Frichtel (General Electric Co., Aircraft Equipment Div., Utica, N.Y.). In: *PCSC '71; Power Conditioning Specialists Conference, California Institute of Technology, Pasadena, Calif., April 19, 20, 1971, Record*. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 152-161.

Design of all avionic systems on future aircraft is tied to the past by MIL-STD-704. Despite dramatic advances in performance and reliability of the avionic equipments, the power conditioning section of each subsystem must still tolerate wide frequency swings on a transient basis, long power interruptions, large voltage transients, and unbalanced phase voltages. During the past decade, General Electric has developed the variable speed constant frequency (VSCF) generation equipment under sponsorship by the U.S. Navy and Air Force. The power quality available through VSCF systems represents a significant improvement over that required by MIL-STD-704. The weapon system improvements achievable through the use of this improved power were reviewed and assessed on existing production avionic subsystems. Proposed next generation avionic systems were also assessed to determine relative benefits achievable for new designs. Parameters considered were power dissipation, weight, volume, reliability, performance and cost. Data from this study on specific equipments was extrapolated to the avionic systems of future aircraft and cost and weight projections were made for both avionics and airframes. (Author)

A72-11068 * **A hybrid electrical power system for aircraft application.** C. H. Lee and C. Y. Chin (AiResearch Manufacturing Co., Torrance, Calif.). In: *PCSC '71; Power Conditioning Specialists Conference, California Institute of Technology, Pasadena, Calif., April 19, 20, 1971, Record*. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 162-174. Contract No. NAS 12-659.

Possible improvements to present aircraft electrical power systems for use in future advanced types of aircraft have been investigated. The conventional power system is examined, the characteristics of electric loads are reviewed, and various methods of power generation and distribution are appraised. It is shown that a hybrid system, with variable-frequency generation and high-voltage dc distribution, could overcome some of the limitations of the conventional system. O.H.

A72-11107 **On the concept of air law (Zum Begriff des Luftrechts).** W. Schwenk. *Zeitschrift für Luftrecht und Weltraumrechtsfragen*, vol. 20, Oct. 1, 1971, p. 260-263. 10 refs. In German.

Air law comprises the totality of legal regulations related to the use of the earth atmosphere by devices which maintain themselves in

the atmosphere through the utilization of the air properties. The relation of air law to concepts considered by Sand (1971) in connection with questions of international environmental protection and the use of the atmosphere is discussed. It is argued that an extension of the customary concept of air law as proposed by Sand would lead to an interlacing of various formerly strictly limited legal areas. Such an extension is objected to on the basis that it would be very difficult to define the boundaries of the new field. G.R.

A72-11109 Development of the DC-10 Nondestructive Testing Manual. D. J. Hagemeyer and H. J. McFaul (Douglas Aircraft Co., Long Beach, Calif.). *Materials Evaluation*, vol. 29, Nov. 1971, p. 249-255.

The completion status and format of the NDT Manual being developed by a team of specialists are discussed. A detailed explanation of the section/subject format and a summary of NDT methods used are given. Planned accessibility to specific areas monitored by nondestructive test methods is the key to successful maintenance inspections based on the Manual. V.Z.

A72-11117 Aviation system design for safety and efficiency. N. Braverman (FAA, National Aviation Facilities Experimental Center, Atlantic City, N.J.). (*Institute of Navigation, Annual Meeting, 27th, Pasadena, Calif., June 29-July 1, 1971.*) *Navigation*, vol. 18, Fall 1971, p. 308-319. 28 refs.

Acceptable levels of risks and methods for determining appropriate safety limits are discussed. The basic principles of proper and improper use of such design characteristics as accuracy, blunder rate, reliability, redundancy, Kalman filtering, independence, integration, and flexibility are reviewed with particular reference to their effects upon safety as distinguished from efficiency of air traffic control systems. Mutually consistent definitions of these various loosely used terms are presented. The nature and role of blunders and the basic principles usable for their prevention through employment of navigation facilities and independent surveillance systems are examined. M.V.E.

A72-11118 The role of inertial navigation in future air traffic control systems. D. Mackinnon and J. W. Hursh (MIT, Cambridge, Mass.). (*Institute of Navigation, Annual Meeting, 27th, Pasadena, Calif., June 29-July 1, 1971.*) *Navigation*, vol. 18, Fall 1971, p. 320-330. 8 refs.

Review of some of the trends in automatic flight control system development which will have a significant effect on the performance of the future air traffic control system. The higher path-control accuracies achievable with the aid of inertial measurement data will permit fully automatic flight operations under environmental conditions (wind, wind gust, and wind shear) which would be prohibitive with current technology. In addition, higher path accuracies and improved versatility will permit complex curved approach and departure paths leading to reductions in noise and air pollution while achieving maximum terminal capacity with a mix of CTOL, STOL, and VTOL aircraft. M.V.E.

A72-11132 # The configuration of a cable towed in a circular path. R. A. Skop (U.S. Navy, Naval Research Laboratory, Washington, D.C.) and Y.-I. Choo (Catholic University of America, Washington, D.C.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 856-862. 7 refs.

The problem of determining the equilibrium configuration of a cable towed in a circular path has both mathematical and practical interest. Mathematically, this interest is generated because of the multivalued nature of the boundary value problem. Practically, this interest arises because the towed drogue, for certain ranges of the governing parameters, obtains an equilibrium position very near the axis of rotation thus enabling pinpoint deliveries of payloads from fixed-wing aircraft. In this paper, the circular towing problem for a flexible, inextensible cable is examined. The equations of equilibrium and the boundary conditions which govern the cable configuration are derived and nondimensionalized to isolate the important parameters. The significance of these parameters for modeling the towing system is discussed. Finally, extensive numerical results are obtained for a particular airborne system. This example shows that an intimate relation exists between the mathematically interesting multivalued regions of solution and the practically interesting regions for which large towline verticality and small drogue radius are simultaneously present. (Author)

A72-11133 # An approximate true damping solution of the flutter equation by determinant iteration. H. J. Hassig (Lockheed-California Co., Burbank, Calif.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 885-889. 17 refs.

Description of the difference between a true damping, or rate-of-decay, solution of the flutter equation and the structural-damping-type of solution. True damping solutions are possible if unsteady aerodynamics can be expressed in terms of the complex variable p . If the aerodynamics are given at discrete values of the reduced frequency k , an approximate determination of the true damping is possible by assuming that the aerodynamic forces for harmonic motion are a good approximation for the cases of slowly increasing or decreasing amplitude. A determinant iteration method for obtaining the solution is presented. Results obtained by different methods of solving the flutter equation are compared. M.M.

A72-11134 * # Analysis of pilot warning indicator performance in terminal area traffic. J. R. Ruetenik, W. R. Lange, and J. H. Thompson (Kaman Sciences Corp., Burlington, Mass.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 905-911. 11 refs. Contract No. NAS 12-698.

Three pilot warning indicator concepts for collision hazard avoidance are analyzed using computer fast-time simulation. A hazard measure is defined based on a 1/2-g maximum horizontal acceleration, a maximum climb or dive angle of 10 deg for each aircraft, and a 20-sec warning time, through escape completion. The traffic model is based on flight tracks recorded in the Atlanta terminal area over an 11 hr period during August 1967. The basic PWI concept studied alarms on range to flashing beacons mounted on intruder aircraft as a function of relative azimuth and elevation. The alarm-hazard epoch ratio is about 17/1 to maintain the missed-alarm rate below 10%. Beacon vignetting or range-rate discrimination are shown to reduce the false-alarm rate by about 75%. (Author)

A72-11135 # Vortex velocity distributions at large downstream distances. A. H. Logan (United Aircraft Corp., Sikorsky Aircraft Div., Stratford, Conn.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 930-932. 5 refs. Contract No. DA-31-124-ARO(D)-149.

Extension of the available data on the velocity structure within a trailing line vortex to large distances downstream of the generating wing. Data are presented to show the variation of both axial and tangential velocity with tunnel speed and trailing vortex strength. Specifically, data are presented at downstream distances of 10 and

26 chord lengths behind a semispan wing set at 4 and 12 deg angle of attack for tunnel speeds of 50 and 70 mph. It is pointed out that, for both speeds considered, the vortex generated at 4 deg angle of attack dissipated more rapidly than the vortex generated at 12 deg angle of attack. M.M.

A72-11136 # Determining aircraft stability coefficients from dynamic motions. S. M. Batill and C. W. Ingram (Notre Dame, University, Notre Dame, Ind.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 932-934, 5 refs.

Description of analytical and experimental work indicating that the aerodynamic stability coefficients can be extracted from the angular motion of aircraft configurations. Using a numerical integration fitting technique applied to the differential equations of motion, it is possible to determine values for the stability coefficients without imposing limiting assumptions on the configuration or its motion. The fitting technique demonstrated a high degree of accuracy as well as establishing the nonlinearity of the stability coefficients. This technique is currently being applied to the complete pitch, yaw and roll of an aircraft configuration with primary interest in extracting the cross-coupling stability coefficients. M.M.

A72-11137 # Acoustics - A new approach for monitoring the environment near airports. D. W. Beran (NOAA, Wave Propagation Laboratory, Boulder, Colo.). *Journal of Aircraft*, vol. 8, Nov. 1971, p. 934-936, 11 refs.

Description of a relatively new device, an acoustic echo sounder, which has the potential of not only indicating the presence or absence of wake vortices, but of acting as a continuous monitor of other important meteorological parameters of airport environments. The device consists of a fixed, vertically pointing antenna, in conjunction with two orthogonally positioned scanning antennas, which could provide a continual real time record of the inversion height, turbulent intensity, as well as an indication of the presence of wing tip vortices, and the vertical profile of the total wind vector. M.M.

A72-11150 Production applications of EDM and ECM. *Manufacturing Engineering and Management*, vol. 67, Nov. 1971, p. 19-22.

The applications of EDM and ECM machines in continuous and repetitive production of aircraft jet engine components at General Electric in Evendale are discussed. The machines are used for drilling and cutting when conventional machining of the thin-cross-section machine parts made of high temperature superalloys is costlier or difficult and impractical. Production of contoured slots, cutting of small holes, feeding of parts into electrodes, multiple-lead EDM, power supply units, and scalloped compressor retainers are covered as particular types of EDM and ECM tooling applications. The Shaped Tube Electrolytic Machining (STEM) method, an ECM variation for drilling small holes, is also described briefly. V.Z.

A72-11151 Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Annual Report 1970 (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Jahresbericht 1970). Porz-Wahn, Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, 1971. 422 p. In German.

A summary is presented of the organizational structure and areas of activity of the Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt (DFVLR) during the year 1970. The distribution of activity at the various facilities operated by the DFVLR is illustrated. Research being performed and findings obtained in the

fields of flow mechanics, flight mechanics and piloting, strength of materials and structures, power plants and power conversion, and electronics are summarized, as well as research in the field of physics of the atmosphere, space simulation, and flight medicine. The operations of various computer centers maintained by the DFVLR are described, and the organization of the various institutions and working groups of the DFVLR which deal with problems of aircraft and spacecraft design and propulsion is discussed. The work of a study group dealing with extraterrestrial research is cited. A.B.K.

A72-11153 STOL aircraft in future transport systems. E. E. Marshall (British Aircraft Corp., Ltd., London, England). *Aeronautical Journal*, vol. 75, Oct. 1971, p. 695-704.

Travel characteristics and habits are examined in order to show how short takeoff and landing (STOL) aircraft can dramatically reduce the noise and land use problems. In particular, the following topics are discussed: airport congestion; community noise; airport location and layout; and traffic growth and airport capacity. An airport system for the United Kingdom and the London area is suggested together with a proposed STOL airliner design to meet these requirements. O.H.

A72-11154 A note on subsonic linearised theory for symmetrical cranked wings at zero incidence. R. C. Lock (Ministry of Technology, National Physical Laboratory, Teddington, Middx., England). *Aeronautical Journal*, vol. 75, Oct. 1971, p. 735-739.

Corrected formulas are presented for the basic streamwise and spanwise components of perturbation velocity due to the thickness, at and near the crank, in a simplified example consisting of two semiinfinite wing panels of different sweep angles joined together. Possible singularities in the flowfield in the neighborhood of the crank are examined. Finally, the implications of these formulas on the magnitude of the 'crank effect,' including the influence of freestream Mach number, are qualitatively discussed. O.H.

A72-11158 Time dependence of variances of sonic boom waveform. G. Kamali and A. D. Pierce (MIT, Cambridge, Mass.). *Nature*, vol. 234, Nov. 5, 1971, p. 30, 31.

Sonic boom pressure signatures during level overflights of F-104 aircraft (flight Mach number of 1.3 at 30,000 ft altitude) were recorded by forty-two ground-level microphones spaced equally in an 8,000-ft linear array. The variations in the signatures recorded by different microphones during the same overflight are believed to be caused primarily by atmospheric turbulence. The variations in these data were analyzed, and the results are used to partially substantiate Crow's (1969) theoretical model. T.M.

A72-11178 Numerical calculation of a sonic flow about an aircraft wing profile, by an inverse method (Calcul numérique d'un écoulement sonique autour d'un profil d'aile d'avion par une méthode inverse). D. Euvrard, J. Hubert, F. Rigaut, and G. Tournemine (Rennes, Université, Rennes, France). *Académie des Sciences (Paris), Comptes Rendus, Série A - Sciences Mathématiques*, vol. 273, no. 16, Oct. 18, 1971, p. 739-742. 6 refs. In French. Research supported by the Direction des Recherches et Moyens d'Essais.

The first three terms are considered in the asymptotic development of a long-distance velocity field of an arbitrary plane symmetrical obstacle. The trail of this development on a large circle

is used in initiating the study. A mixed Cauchy problem is then solved by combining the pseudoviscosity-introducing Lax finite difference scheme with an extrapolation to the limit. The results obtained show qualitative agreement with experimental data. M.V.E.

A72-11258 # From the propeller to the jet engine (Dall'elica al reattore). G. Rotondi. *Alata Internazionale*, vol. 27, Oct. 1971, p. 17, 18, 21 (2 ff.). In Italian.

Discussion of problems connected with increasing the efficiency of modern air transport. It is pointed out that the large-capacity helicopter is best suited to operate from extremely small spaces and to reach adequate speeds over short hauls. The conventional aircraft is logically the most economical transportation over distances of 500-600 km, while STOL's supremacy from 150 to 500 km appears to be unchallenged. The VTOL aircraft also offers remarkable possibilities, particularly in the most radical solutions which are less penalized by the necessity of achieving a delicate compromise of a technical and operational nature. The features of various versions of STOL and VTOL aircraft are examined from the standpoint of performance and efficiency, together with various approaches to the problem of reducing landing and takeoff distances. M.M.

A72-11373 # Thermal strength testing methods for aircraft gas turbine engine nozzle apparatuses (Metodika termoprochnostnykh ispytaniy soplovykh apparatov turbin aviatsionnykh GTD). P. F. Grigor'ev and M. P. Meshcheriakov. *Prochnost' i Dinamika Aviatsionnykh Dvigateli*, no. 6, 1971, p. 182-185. In Russian.

A special gasdynamic test stand is used for thermal shock tests on aircraft gas turbine engine nozzles to determine the causes of damage produced in nozzle blades under thermal load cycles. It is found that cracks and edge wobbling, depending on blade material, can be produced by cycled thermal loads in nozzle blades. The damage is linked to stability loss due to creep under pressure. It is also shown that the thermal fatigue damage can be controlled by varying the thermal cycle parameters and temperature maxima. V.Z.

A72-11374 # Determination of radial stresses in ring-to-drum transition areas of disks (K opredeleniiu napriazhenii v radiusakh perekhoda oboda diska v baraban). A. A. Kovalev, A. A. Simakov, and I. I. Kurtseva. *Prochnost' i Dinamika Aviatsionnykh Dvigateli*, no. 6, 1971, p. 185-190. In Russian.

Analysis of thermal stresses which develop in the disk-to-drum transition areas of the axial compressor of an operating AM-3 aircraft engine. The thermal stresses vary in magnitude and sign, produce tension during takeoff and compression during landing, and may lead to radial cracks in these areas. Experiments are carried out to measure the temperature and stress distributions in rigidly connected compressor disks and drums. The occurrence of alternating static loads in the rigid-junction areas is demonstrated by both calculations and experiments. V.Z.

A72-11395 The three-dimensional turbulent boundary layer on an infinite yawed wing. J. F. Nash and R. R. Tseng (Lockheed-Georgia Research Laboratory, Marietta, Ga.). *Aeronautical Quarterly*, vol. 22, Nov. 1971, p. 346-362. 10 refs.

Description of the results of calculations of the incompressible turbulent boundary layer on an infinite yawed wing. The effects of increasing lift coefficient, and increasing Reynolds number, on the displacement thickness, and on the magnitude and direction of the skin friction, are discussed. The effects of the state of the boundary layer along the attachment line are also considered. A study is made

to determine whether the behavior of the boundary layer can adequately be predicted by a two-dimensional calculation. It is concluded that there is no simple way to accomplish this. However, with some modification, a two-dimensional calculation can be made to give an acceptable numerical representation of the chordwise components of the flow. M.M.

A72-11441 Experimental manufacture of Inconel Alloy 718 compressor rotor blades from metal powder preforms. B. Triffleman, F. C. Wagner, and K. K. Irani (Curtiss-Wright Corp., Buffalo, N.Y.). In: Modern developments in powder metallurgy, Volume 5; Proceedings of the International Powder Metallurgy Conference, New York, N.Y., July 12-16, 1970. New York, Plenum Press, 1971, p. 37-46. 6 refs.

Development of methods for making aircraft quality parts from forged Inconel Alloy 718 metal powder preforms. Wherever possible, standard production type equipment was used for the consolidation of the metal powders, and metal powder preforms were designed which would fit into present shop forging practices. It was found possible to produce fully dense aircraft engine compressor blades meeting specification properties, including improved fatigue properties as compared with conventional wrought blades. F.R.L.

A72-11511 # Buckling of an elastic column containing a fatigue crack. A. Berkovits and A. Golod (Technion - Israel Institute of Technology, Haifa, Israel). *Society for Experimental Stress Analysis, Fall Meeting, Milwaukee, Wis., Oct. 19-22, 1971, Paper 1914A*. 17 p. 10 refs.

Results of an experimental program conducted in order to study the residual buckling strength of an elastic column containing a fatigue crack, are presented in this paper. Tests were performed on bars of rectangular cross-section, made from 2024-T351 aluminum-alloy plate and containing a fatigue crack at the midsection. Results obtained show a reduction of buckling strength of 8% under hinged-hinged end conditions, in apparent tentative accord with data obtained from columns containing machined notches. Although it is small, the reduction in buckling strength is thought to be significant for design and requires further investigation. (Author)

A72-11584 # One-dimensional unsteady flow in a rotating vane cascade (Odnomernoe nestatsionarnoe techenie vo vrashchayushcheisia reshetke). V. T. Mitrokhin. *Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza*, Sept.-Oct. 1971, p. 77-83. 6 refs. In Russian.

Theoretical analysis of the dynamic behavior of one-dimensional fluid flows in the rotating and static vane cascades of turbine engines. The propagation of vibrations in a fluid flow having an unsteady average velocity during rotation is discussed. It is assumed that a cascade vane is a linear system with distributed parameters and that mechanical energy is fed into and removed from the system by vibrations. V.Z.

A72-11637 # Experimental investigation of the strength of rotating disks in aircraft gas turbines operating under variable thermal conditions (Eksperimental'noe issledovanie prochnosti vrashchayushchikhsia diskov aviatsionnykh gazovyykh turbin, rabotaiushchikh v usloviakh teplosmen). V. I. Formichev, I. A. Kozlov, V. A. Sekistov, and V. M. Leshchenko. In: Strength and plasticity. Moscow, Izdatel'stvo Nauka, 1971, p. 380-382. In Russian.

Description of a test assembly for strength analysis of gas turbine disks at rotation rates up to 75,000 rpm with temperature

gradients between the periphery and center of the disk reaching 500 C in alternation. Thermal and mechanical loads close to real operational loads can be obtained when this assembly is used in testing gas turbine disks. V.Z.

A72-11654 * The handling qualities simulation program for the augmentor wing jet STOL research aircraft. W. B. Cleveland (NASA, Ames Research Center, Moffett Field, Calif.). In: *Fall Joint Computer Conference*, Las Vegas, Nev., November 16-18, 1971, Proceedings. Montvale, N.J., AFIPS Press, 1971, p. 213-223.

Description of a program in which a complete STOL research aircraft (modified de Havilland C8-A Buffalo) was simulated to determine final design values for control systems and devices which augment aircraft control. Program objectives, computer requirements, and the simulation software and hardware are outlined together with the organization of the digital operations. The simulation program in combination with simulator hardware provided test pilots a realistic representation of the aircraft, with the result that various control and stability augmentation systems were evaluated using pilot handling qualities ratings. Final design parameters were then found for the aircraft which is scheduled for flight test in early 1972. T.M.

A72-11669 # A note of the configuration of jet sheet on a thin, jet-flapped airfoil. T. Kida and Y. Miyai (Osaka Prefecture, University, Sakai, Japan). *Osaka Prefecture, University, Bulletin, Series A - Engineering and Natural Sciences*, vol. 19, no. 2, 1970, p. 187-196. 5 refs.

Derivation of a solution to an integrodifferential equation describing the aerodynamic behavior of this airfoil within the framework of the linear theory. Convergence of the solution is examined and the solution is extended in the form of a power series to be applicable to the airfoil configuration at the trailing edge, at infinity and at an intermediate point. Calculations are made to compare this solution with the one given by Spence (1956), showing that the latter is less effective. V.Z.

A72-11699 # The development of small gas turbine engines at UACL /Lecture/. J. P. Beauregard (United Aircraft of Canada, Ltd., Longueuil, Quebec, Canada). *Canadian Aeronautics and Space Institute, Annual General Meeting, Montreal, Canada, May 6, 7, 1971.* *Canadian Aeronautics and Space Journal*, vol. 17, Oct. 1971, p. 308-322. 10 refs.

Two types of successful small gas turbine aircraft engines - i.e., PT6 and JT15D - are discussed in detail. A review is presented of the PT6 and JT15D stories covering the factors which led to their overall configuration, some representative development problems, and the experience with the engines in service. O.H.

A72-11700 # On the possibility of roll control for the externally-blown jet flap. R. H. Wickens (National Research Council, Low Speed Aerodynamics Section, Ottawa, Canada). *Canadian Aeronautics and Space Journal*, vol. 17, Oct. 1971, p. 329, 330.

Correction of rolling moments, induced by an asymmetric loss of lift due to an engine failure, has been investigated for the case of the externally blown flap. A relatively simple technique is proposed which may be used to aid conventional controls and which yields encouraging results. The results indicate a significant measure of roll control in the event of an engine failure, provided sufficient lateral adjustment of the additional lift distribution is available. O.H.

A72-11716 Air transportation in our changing society. J. P. Loomis and J. K. Wetherbee (Battelle Columbus Laboratories, Columbus, Ohio). *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 2-6.

Description of the present situation in the air transport industry, with discussion of what is needed and of what might be done to achieve the kinds of service that air transport can furnish. Attention is given to general and commercial aviation, and the roles of the FAA and CAB. Various possible policies are considered, leading to the conclusion that the Federal government must provide the leadership in making them work. F.R.L.

A72-11717 Improving the efficiency of airports. R. H. Byers, C. B. Shields, and R. E. Thompson. *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 7-12.

Outline of the steps being taken to develop more efficient airports in order to shorten total trip time. Airports must be enlarged, boarding gates must be spread out, and the parking space must be expanded. These changes involve longer travel distances within the terminal area. Basic transport systems considered are the continuous type (private cars or taxis), and the batching type (buses and guided systems). Baggage handling, fire protection, security, monitoring of dispersed equipment, and central control are discussed. F.R.L.

A72-11718 Air traffic control - A problem in decision-making. A. C. Robinson and J. D. Hill (Battelle Columbus Laboratories, Columbus, Ohio). *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 13-17.

Exposition of the tasks of air traffic control, which must keep thousands of crisscrossing flights untangled. Some 16,000 air traffic controllers man the system, and are distributed between the Air Traffic Control Centers, which control traffic en route, and the terminal areas which control takeoffs, approaches, landings, and terminal-area holding patterns. The way the system works is outlined, various problems are discussed, and future improvements are described. Technological and administrative delays in correcting deficiencies are reviewed. F.R.L.

A72-11719 For a better, short-haul flight. J. W. Chadwick, R. F. Porter, and E. F. Hitt (Battelle Columbus Laboratories, Columbus, Ohio). *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 18-21.

Characterization of the needs of the short-haul air transport system, with suggestions of how future short takeoff and landing aircraft will help satisfy them. To achieve the goal aircraft, airways, and airports must be developed jointly, within the constraints of economic reality. A cruising speed of about 400 kt is desirable, as well as the ability to fly safely at low airspeed. Aircraft should be able to operate from runways less than 2000 ft long, and to climb steeply. Attention is given to navigation and landing aids, as well as to the interrelationship between short-haul airports and the community. F.R.L.

A72-11720 Smoother travel in rough air. J. H. Brown, Jr. (Battelle Columbus Laboratories, Columbus, Ohio) and L. J. Reynolds. *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 22-25.

Discussion of aircraft ride comfort, a subject of considerable importance, since about 85% of all flights take place at moderate or low altitudes, where turbulence is greatest. The main problem is due to unscheduled rising or sinking; rotational oscillation and structural

vibration are of relatively minor importance. One route to comfort criteria is to correlate personal discomfort stemming from the severity of in-flight turbulence with measured aircraft responses. Free-wing and fixed-wing aircraft are compared, and it is considered that the former are of considerable promise. Such wings are free, either partially or completely, to rotate about a lateral axis that extends through the fuselage. F.R.L.

A72-11721 **Air transportation in the American economy.** N. Simons, Jr. and R. L. Craig (Battelle Columbus Laboratories, Columbus, Ohio). *Battelle Research Outlook*, vol. 3, no. 2, 1971, p. 26-29.

Attempt, beginning with 1960, to find reliable figures for dissecting civil aviation into its major contributing factors to the American economy, and estimating their worth. The overall contribution is the sum of the sales of aviation services by air carriers, plus the costs of operating business and personal aircraft. In the 1970's, civil aviation can expect benefits from population changes, particularly in age distribution. Three factors in future growth are real disposable income, airline fares, and the time-trend variable. It is suggested that the demand for air transportation will be able to support an annual increase in growth of about 15%. It is pointed out that almost as many people now travel by general aviation as by scheduled airlines. F.R.L.

A72-11756 **Electronic displays for attack aircraft (Elektronische Displays für Kampfflugzeuge).** R. Beyer (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Institut für Flugführung, Braunschweig, West Germany). *Wehrtechnik*, no. 6, 1971, p. 235-239. 5 refs. In German. (DFVLR-SONDDR-140)

The characteristics of modern attack aircraft, their subsystems, and the role of the pilot are described. Features of electronic displays employed in these aircraft are reviewed, and the development of suitable displays using a mission model for testing individual flight maneuvers is discussed. Basic principles of the simulation technique are outlined, and display design criteria are examined. Recent advances in the display techniques, such as head-up and head-down displays, multisensor displays (MSD), and eyeglass displays, are reviewed. Future prospects in this field are outlined. O.H.

A72-11968 # **Ways of improving the antiwear properties of fuels for jet engines (Puti uluchsheniia protivoiznosnykh svoystv topliv dlia reaktivnykh dvigatelei).** I. E. Bespolov, B. F. Korobov, M. D. Khaikin, V. V. Sashevskii, and M. V. Khokhlacheva (Vsesoiuznyi Nauchno-Issledovatel'skii Institut Neftianoi Promyshlennosti, Moscow, USSR). *Khimiia i Tekhnologiya Topliv i Masel*, vol. 16, no. 10, 1971, p. 56-58. 9 refs. In Russian.

Study of the effect of fuel viscosity on the antiwear properties of a number of fuels differing in their naphthene hydrocarbon and sulfur contents. It is found that the antiwear properties of jet fuels noticeably improve with an increase in fuel viscosity only if the samples being compared do not differ in chemical composition and are obtained by similar processes. An increase in the naphthene hydrocarbon content in the fuel leads to an improvement in its antiwear properties. With an increase in the mercaptan sulfur content the antiwear properties of the fuel deteriorate. The use of an additive effectively improves antiwear properties. A.B.K.

A72-11972 **Real-gas effects in very weak shock waves in the atmosphere and the structure of sonic bangs.** J. P. Hodgson and

N. H. Johannesen (Manchester, Victoria University, Manchester, England). *Journal of Fluid Mechanics*, vol. 50, Nov. 15, 1971, p. 17-20. 8 refs.

An approximate expression is given for the thickness of weak fully dispersed shock waves. Using available data on the thermodynamic properties of air, it is shown that shocks of the strength expected in sonic bangs are fully dispersed. Estimated relaxation times for dry and humid air lead to wide variations in possible thickness, varying from millimeters to meters. (Author)

A72-11973 **On the noise sources of the unsuppressed high-speed jet.** K. A. Bishop, W. Smith (Rolls-Royce, Ltd., Bristol, England), and J. E. Ffowcs Williams (Rolls-Royce, Ltd., Bristol; Imperial College of Science and Technology, London, England). *Journal of Fluid Mechanics*, vol. 50, Nov. 15, 1971, p. 21-31. 16 refs.

The paper describes an interpretation of jet-noise theory and scale-model experiments to highlight physical properties of jet-noise sources at very high speed. The study is prompted by current efforts to suppress the noise of supersonic transport aircraft. The principal noise sources are shown to be very large-scale wave-like undulations of the jet flow that travel downstream at supersonic speed for a distance of several jet diameters. These motions are relatively well ordered and are probably more akin to recognizable instabilities of a laminar flow than the confused small-scale turbulence. Because of this we postulate a model of the noise generating motions as the instability products of a jet flow of low equivalent Reynolds number. This Reynolds number is based on an eddy viscosity and can be further reduced by artificially increasing the small-scale turbulence level. This step would tend to stabilize the flow and inhibit the formation of large-scale noise producing eddies. (Author)

A72-12002 # **Vibration - A review of interesting cases.** J. P. Den Hartog (MIT, Cambridge, Mass.). In: *CANCAM 71; Proceedings of the Third Canadian Congress of Applied Mechanics*, University of Calgary, Calgary, Alberta, Canada, May 17-21, 1971. Calgary, Canada, University of Calgary, 1971, p. 17-27. 5 refs.

Review of a number of cases of vibration which was not predicted during the design stage or even during the experimental development stage. The cases discussed are those of the Comet and Electra aircraft and the Graf Zeppelin dirigible, Pogo vibration in large rockets, solar flutter of missile antennas, and density wave oscillations in a boiling water atomic power reactor. Factors complicating the construction of an alternating velocity precipitator designed to remove extremely small solid particles (flyash) from smokestack gas are considered. A.B.K.

A72-12022 **Future aircraft noise in the vicinity of airports.** G. Zimmermann (Max-Planck-Institut für Strömungsforschung, Göttingen, West Germany). *Airport Forum*, no. 3, 1971, p. 38, 39, 42-46. In English and German.

Consideration of the effects of aircraft engine noise on the environs of airports and of the possibility of reducing the level of this noise. Noise measurement scales currently in use are reviewed, and the sources of engine noise are investigated, tracing a large portion of this noise to the use of turbofan engines with a low bypass ratio. It is foreseen that the problem of fan noise will be greatly mitigated by the trend toward turbofan engines with high bypass ratios which are used in jumbo jets. An estimate is made of future air traffic and of the noise level to be expected in the vicinity of some typical airports by 1975. The provisions of an Aircraft Noise Act recently enacted by the Federal Republic of Germany are reviewed. A.B.K.

A72-12023 **New paving concept for New York airports.** N. C. Yang (Port of New York Authority, New York, N.Y.). *Airport Forum*, no. 3, 1971, p. 53-57, 59-65. In English and German.

Description of the design and testing of a new type of airport pavement (called pozzolanic) consisting of lime, cement, and fly ash that combine with sand (and stone where needed) to form a semirigid base. The material is distinguished by the fact that it spreads like dirt, hardens like concrete, but has many of the advantages of asphalt. Also, the new material is considerably cheaper than conventional pavement materials. The new material is not as rigid as concrete and will therefore conform more readily to long-term settling of the subgrade with a minimum of stress induced in the pavement structure. At the same time, it is able to withstand more loadings without cracking or rutting than a conventional asphaltic base. Its strength increases significantly for at least five years, automatically compensating for the almost certain increase in aircraft size and weight. A.B.K.

A72-12030 # **Supersonic and hypersonic flow with attached shock waves over delta wings.** W. H. Hui (Southampton, University, Southampton, England). *Royal Society (London), Proceedings, Series A*, vol. 325, no. 1561, Nov. 9, 1971, p. 251-268. 17 refs.

A unified theory is developed for supersonic and hypersonic flow with attached shock waves over the lower surface of a delta wing at an angle of attack. The flow field on the lower surface of a delta wing consists of uniform flow regions near the leading edges, where the crossflow is supersonic and a nonuniform flow region near the central part, where the crossflow is subsonic. In the nonuniform flow region, the theory is based on the assumption that the flow differs slightly from the corresponding two-dimensional flow over a flat plate. Thus a linearized perturbation on a nonlinear flow field is first calculated and then strained and corrected so that the flow is matched continuously to the uniform flow which is obtained exactly. When compared with available exact numerical solutions the theory gives, in all cases, almost identical results, except near the crossflow sonic line where existing numerical methods fail to produce a discontinuous slope in the pressure curve, whereas the present theory predicts such a discontinuity and shows that the slope has a square root singularity at the crossflow sonic line similar to that in the supersonic linear theory. (Author)

A72-12033 **Conflict detection at Knoxville.** H. Wachsman (FAA, Systems Research and Development Service, Washington, D.C.). *Journal of Air Traffic Control*, vol. 14, Nov. 1971, p. 8-11.

Discussion of the STARAN (Stellar Attitude Reference and Navigation) Associative Processor which has been installed in the Knoxville TRACON (Terminal Radar Approach Control). An associative processor attains magnitudes of computational speed through the use of arithmetic and logic associated with each word in its memory array. Its strength lies in its ability to perform great numbers of calculations in parallel. STARAN performs a conflict detection function which will relieve the air traffic controllers of the responsibility for any conflict, near-miss, or collision of aircraft in flight. F.R.L.

A72-12042 **Avoid - A short-range high-definition radar.** K. L. Fuller (Mullard, Ltd., Redhill, Surrey, England). *Philips Technical Review*, vol. 32, no. 1, 1971, p. 13-19.

A system is described in which established principles of radar technology are combined in an original way to produce a radar with a range from 3 to 160 m, a 2 m resolution, and a 50 Hz picture-frequency display. Range measurements are made with a CW FM signal. Electronic angular scan is obtained with the aid of an antenna consisting of a length of waveguide with about 80 radiating

holes. Undesirable side lobes in the radiation pattern are avoided by filling the waveguide with a dielectric. Mounted on a vehicle, the system allows the latter to be driven on an airfield under very poor visibility conditions. V.P.

A72-12050 # **Two examples of application of Kalman filters to integrated navigation systems (Due esempi di applicazioni del filtro di Kalman ad equipaggiamenti integrati di navigazione).** A. Ferraro and A. Lucifredi (Genova, Università, Genoa, Italy). *Tecnica Italiana*, vol. 36, May 1971, p. 163-168. 11 refs. In Italian.

Discussion of the application of optimal stochastic filters to navigation systems by means of two examples. The first example considers an air navigation system consisting of an inertial device (INS) and a LORAN (plus an altimeter); the measurement errors are modeled as colored noises. The second example shows the application to a system of submarine navigation; the instruments are an inertial device (SINS) and an OMEGA (plus a depth sensor). The measurement errors are modeled as the sum of a bias and a colored noise. M.M.

A72-12077 **Preliminary results of measurements of heavy primaries in the region of supersonic transport using plastic stacks.** O. C. Ailkofer, W. Enge, W. Heinrich, and H. Röhrs (Institut für reine und angewandte Kernphysik, Kiel, West Germany). In: International Congress on Protection Against Accelerator and Space Radiation, Geneva, Switzerland, April 26-30, 1971, Proceedings. Volume 1. Geneva, Organisation Européenne pour la Recherche Nucléaire, 1971, p. 512-521; Discussion, p. 522, 523. Discussion in English and French.

Study of so-called thin-down hits, i.e., stopping heavy primaries, which can deposit a radiation dose of some thousand rads near the end of their trajectory, using balloon-borne stacks of cellulose nitrate, cellulose acetate, and a polycarbonate as detectors. The aim of the experiment is to determine the intensities of thin-down hits with charges Z equal to or greater than 6 for different deep layers in the plastic stack. The thin-down intensities which are measured in the deeper layers of the plastic stack can be directly compared with the intensities in the interior of the body of an SST traveler, since the fragmentation probabilities and the interaction mean free paths for heavy ions can be assumed to be equal in plastic and in human tissue. F.R.L.

A72-12078 **Radiological protection in SST aircraft.** E. W. Fuller and B. Day (Atomic Weapons Research Establishment, Aldermaston, Berks., England). In: International Congress on Protection Against Accelerator and Space Radiation, Geneva, Switzerland, April 26-30, 1971, Proceedings. Volume 1. Geneva, Organisation Européenne pour la Recherche Nucléaire, 1971, p. 524-554; Discussion, p. 555, 556. 34 refs. Research supported by the Ministry of Aviation Supply.

The work done so far in the United Kingdom in the field of radiological environment studies of supersonic transport aircraft (SSTs), such as the Franco-British Concorde, and the development of such instrumentation as might be required for monitoring it, is reviewed. It is shown that, as the first step, the extent was considered to which the stratospheric situation is covered by recommendations initially proposed to control exposure to ground based sources of radiation. Then a study was made of the dose and dose equivalent rates produced in the altitude band of interest by the galactic and solar cosmic radiation. To measure the dose equivalent rate from solar cosmic radiation at the Concorde cruising altitude, an instrument, referred to as the In-Flight Radiation Warning Meter (IFRWM), was developed and evaluated using the galactic cosmic radiation at altitudes up to 30 km (balloon flights) and the radiation from GeV accelerators. O.H.

A72-12106 Pictorial navigation systems. B. H. L. Blake (Marconi-Elliott Avionic Systems, Ltd., Basildon, Essex, England). *Shell Aviation News*, no. 400, 1971, p. 18-20.

General evaluation of visual position display, used in addition to the more usual digital readout for navigation. Such a display enables the latter to be monitored at a glance, and prevents gross blunders in insertion or readout of alphanumeric position information. A display system normally consists of a computer which accepts the sensor information and converts it into values to drive the map display; a control unit; and the display head itself. The system should be able to work with any type of airborne navigation sensor and with combinations of these sensors. A typical pictorial navigation system, the Marconi AD670, is described, with details of the map display unit, the electronics unit, and the controller. F.R.L.

A72-12226 B-1 design keyed to future growth. R. R. Ropelewski. *Aviation Week and Space Technology*, vol. 95, Nov. 29, 1971, p. 34-37.

Consideration of the B-1 strategic bomber design, which is expected to exert some influence on future aircraft. The B-1 is intended to serve for the remainder of this century as the primary manned strategic bomber of the U.S. The variable-sweep wing and its pivot is the single most complex structural aspect of the B-1. Projected operating speeds up to Mach 2.2 have dictated the requirement for variable-geometry inlets on the engine nacelles to maintain high inlet efficiency at all speeds. Attention is given to the landing gear, control system, and instrumentation. F.R.L.

A72-12228 # Boundary-layer development on a wing-body combination. Z. Jaňour. *Zpráva VZLÚ*, Sept. 1971, p. 1-13. 5 refs.

Results of measurements of aerodynamic forces and pressure distribution on a model simulating a wing-body combination. The effect of the fuselage on the flow past the wing is analyzed. The boundary layer on the upper surface of the wing, as developed under the conditions given by the outer flow, is investigated by means of a hot-wire technique and flow visualization. The results show the changes of the outer potential flow and of the boundary layer (mainly its transition to turbulence) which occur in the neighborhood of the fuselage. A.B.K.

A72-12270 # A new area rule for hypersonic wing-bodies. N. Malmuth (North American Rockwell Science Center, Thousand Oaks, Calif.). *AIAA Journal*, vol. 9, Dec. 1971, p. 2460-2462. 6 refs. Contract No. F44620-71-C-0021.

An area rule is obtained for the change in the lift-drag ratio of a hypersonic delta wing due to the addition on its compressive side of a conical body of arbitrary cross section. The area rule states that the change in aerodynamic efficiency of such a wing is directly proportional to the body volume and independent of its cross-sectional shape. O.H.

A72-12275 # Skin-friction measurement in flow with pressure gradient. R. G. Bradley and A. R. Mann (General Dynamics Corp., Convair Aerospace Div., Fort Worth, Tex.). *AIAA Journal*, vol. 9, Dec. 1971, p. 2470, 2471. 5 refs. Research supported by the General Dynamics Independent Research and Development Funds.

Description of data comparing two different surface-impact-probe measurements for nonisobaric flow over an airfoil section in high subsonic flow. The two impact-probe devices were a Preston tube (a surface-mounted circular tube) and a Stanton tube (a segment of razor blade mounted over a static pressure orifice). The performances of these two devices are compared with each other and with theoretical calculations of the skin-friction coefficient. M.M.

A72-12295 # High-altitude equipment of civil aircraft (*Vysotnoe oborudovanie samoletov grazhdanskoi aviatsii*). N. G. Grishanov. Moscow, Izdatel'stvo Transport, 1971. 264 p. 16 refs. In Russian.

The principles of design and operation of the air-conditioning systems in pressurized cabins of transport aircraft and the oxygen equipment of such aircraft are outlined. Air-pressure, air-temperature, and air-moisture control systems are described, as well as aircraft oxygen supply systems and equipment for monitoring aircraft life-support systems. The maintenance of pressurized cabins and their high-altitude equipment is discussed, as well as the maintenance and operation of the oxygen equipment. A.B.K.

A72-12298 # Course-indicating systems and automatic navigation aids for civil aviation aircraft (*Kursovye sistemy i navigatsionnye avtomaty samoletov grazhdanskoi aviatsii*). N. M. Bogdanchenko, G. Iu. Voloshin, and V. S. Belykh. Moscow, Izdatel'stvo Transport, 1971. 268 p. 13 refs. In Russian.

The general design and operational principles of course-indicating systems, astronomical compasses, and navigation aids are outlined. Errors and their causes are examined along with means of improving the precision of these systems. Particular attention is given to the design and elements of the GIK-1 gyro flux gate telecompass, and the KS-6 and GMK-1 course-indicating systems. Technical servicing, maintenance, and maintenance schedules are discussed. A general method of determining the basic reliability features of aids and systems is proposed, and general principles of error analysis are studied. The book is equally well suited as a textbook and as a reference for engineers and technicians. V.P.

A72-12323 C-SCAN - Pilot's window to the deck. H. Hechtman (Cutler-Hammer Co., Airborne Instruments Laboratory Div., Deer Park, N.Y.). *Signal*, vol. 26, Dec. 1971, p. 32-34, 36.

Discussion of the Carrier System for Controlled Approach of Naval aircraft (C-SCAN) which provides a clear guidance for a poor-visibility landing of tactical jets on the flight deck of an aircraft carrier. The system transmits, receives, and decodes landing information with the aid of microwave scanning beams which give the pilot of an approaching jet a window to the carrier deck. The C-SCAN equipment, the shore-based installations and the reliability of the system are discussed. The fail-safe features of C-SCAN, such as SPN-41, TRN-28 monitors, ARA-63 fault detectors, and BIT circuits, are noted. V.Z.

A72-12345 A comparison of the lift of flat delta wings and waveriders at high angles of incidence and high Mach number. L. C. Squire (Cambridge University, Cambridge, England). *Ingenieur-Archiv*, vol. 40, no. 5, 1971, p. 339-352. 16 refs.

It has been suggested that in the conditions of lifting reentry caret wings are likely to have higher lift coefficients than flat-bottomed wings with the same ratio of lift to drag. Thus, for given speed and wing loading, they can reenter at higher altitudes with a consequent reduction in stagnation point heating rate. In this paper thin-shock-layer theory is used to study the lifting properties of caret and flat-bottomed wings and of wings with concave lower surfaces. It is found that significant gains in lift coefficient can be achieved with moderately recessed lower surfaces. These results hold for both perfect and real gas flows. (Author)

A72-12376 EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. Convention sponsored by the Institute of Electrical and Electronics Engineers. New York, Institute of Electrical and Electronics Engineers, Inc. (IEEE Publication 71 C 34 - AES), 1971. 272 p. Members,

\$12.50; nonmembers, \$14.50.

Digital matched filters using fast Fourier transforms, splash-detection radar digital signal processing, detection of targets in non-Rayleigh sea clutter, and radar measurement accuracy in log-normal clutter are among the topics covered in contributions concerned with results in radar signal processing. Other contributions include industrial and biomedical transducers, air traffic control, oceanographic and atmospheric technology, technical requirements and resource allocation in aerospace-borne earth resources exploration, and current problems in radar technology.

M.V.E.

A72-12377 The microwave landing system development program. J. W. Edwards (FAA, Washington, D.C.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 17-21.

A summary is presented of the activities required over a five year time period for the development of a microwave landing system. The broad range of user operational requirements this system must satisfy has been tentatively established by Special Committee 117 of the Radio Technical Commission for Aeronautics.

M.V.E.

A72-12378 A discrete address ATC beacon system. M. T. Pozesky (FAA, Washington, D.C.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 22-26.

A discussion of the concept, operation, and various design options for the development of an upgraded Air Traffic Control surveillance and data acquisition/communication system is presented in this paper. A review of the development, evolution, and functions of the present Air Traffic Control Radar Beacon System is presented together with a discussion of the need and concept for an upgraded Discrete Address Beacon System. The operation, functions, and critical design issues of the proposed Discrete Address Beacon System are presented and various design considerations and alternatives are developed and identified.

(Author)

A72-12379 FAA CAS/PWI program - Past, present, future. J. L. Brennan (FAA, Washington, D.C.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 27-32.

This paper traces the history of Federal Aviation Administration (FAA) activity in the Collision Avoidance System (CAS) and Pilot Warning Instrument (PWI) areas, examines the results of these efforts to the extent they have influenced our present program, discusses some remaining problem areas, and presents FAA's plans to solve these problems.

(Author)

A72-12380 The FAA air traffic control automation program. J. W. Rabb (FAA, National Airspace System Program Office, Washington, D.C.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 33-40.

Review of the air traffic control automation program currently implemented in order to meet the challenge of rapid growth of air transportation. When completed in 1974, each of the 20 domestic air route traffic control centers and the busiest terminal facilities will be interconnected to form the world's largest real time computer command and control network.

M.V.E.

A72-12383 FAA plans for AEROSAT. G. E. Lundquist (FAA, Washington, D.C.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 108-112.

Review of the present program requirements, technical features, and implementation plans for the UHF preoperational and operational Aeronautical Satellite Systems (AEROSAT) over the Pacific and Atlantic airspaces. Following a brief glimpse at the history, present state, and future trends of oceanic air traffic and air traffic control (ATC), the international aspects and special problems of ATC are discussed. ATC problems reviewed include: limited flight levels available, long-haul track conflicts, air speed differences in aircraft operations, differences in estimated and actual fix times, adverse weather conditions, and communication delays. Satellite national policy and present aeronautical satellite programs are considered.

M.V.E.

A72-12393 A limited scan antenna. L. Melancon (Raytheon Co., Equipment Div., Waltham, Mass.). In: EASCON '71; Electronics and Aerospace Systems Convention, Washington, D.C., October 6-8, 1971, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 190-192.

An antenna system is described that is capable of electronically scanning a pencil beam more than ten beamwidths from boresight with a comparatively small number of active elements. This is accomplished by using a large inexpensive reflector to obtain aperture gain and a small phased array to provide electronic scanning. The antenna is part of a tactical aircraft landing system which must be transportable by aircraft, helicopter and ground vehicles. One of the most challenging aspects of the design was to achieve the proper balance between antenna characteristics, as they affect system performance, and tight weight and volume constraints.

(Author)

A72-12403 * Telemetry and the integrated avionics approach. W. O. Frost (NASA, Marshall Space Flight Center, Instrumentation and Communications Div., Huntsville, Ala.) and D. H. Ellis (SCI Electronics, Inc., Huntsville, Ala.). In: Telemetry applications in the aerospace industry; Proceedings of the Seventeenth International Aerospace Instrumentation Symposium, Las Vegas, Nev., May 10-12, 1971. Pittsburgh, Instrument Society of America, 1971, p. 1-7.

The unique problems encountered in the integrated approach to aircraft and spacecraft avionics system designs are discussed with the emphasis on recent advances in telemetry as a factor facilitating the integration. A listing of subsystems planned for integration on the Space Shuttle vehicle is given, covering auxiliary pumping and propellant, crew controls and displays, computation, communications and radar, electric power, guidance, navigation and control, air-bearing engines, main engines, reaction control, and structural/mechanical elements. Considerations are given for the multiplexed data bus design applicable to integrated avionics.

V.Z.

A72-12408 Data analysis system for Army flight testing. A. L. Kelley and R. J. Haase (EMR-Telemetry, Sarasota, Fla.). In: Telemetry applications in the aerospace industry; Proceedings of the Seventeenth International Aerospace Instrumentation Symposium, Las Vegas, Nev., May 10-12, 1971. Pittsburgh, Instrument Society of America, 1971, p. 40-47.

Discussion of the EMR-designed system used presently by the Army Aviation Systems Activity (ASTA) for improvement of fixed and rotary wing aircraft tests. Covered are components of the Advanced Instrumentation and Data Analysis System (AIDAS), including the Airborne System, the computer-controlled Central

A72-12420

Ground Station, and two computer-controlled mobile Remote Ground Stations (RGS). Details are given on the PCM and FM data acquisition packages of the Airborne System, RGS subsystems, computer subsystems, and software. The improvement of data reduction achieved with the AIDAS system is noted. V.Z.

A72-12420 Interactive graphic displays for air traffic control. J. T. McNamara, Jr. (Raytheon Digital Systems and Displays Laboratory, Sudbury, Mass.). *Electronic Progress*, vol. 13, Fall 1971, p. 11-18.

Review of the current computer-aided air traffic control displays, covering the Computer Display Channel (CDC), the Computer Update Equipment (CUE) subsystem, the Central Computer Complex (CCC), Plan View Displays (PVD), and the Digital Control and Vector Generator (DCVG). The operational capabilities of these systems are discussed and block diagrams of CUE/CDC display subsystems, CDC data processing flow and PVD are given. Also described are the vector and character generation process and depletion systems. V.Z.

A72-12421 Tactical displays. G. B. Levine (Raytheon Digital Systems and Displays Laboratory, Sudbury, Mass.). *Electronic Progress*, vol. 13, Fall 1971, p. 19-24.

Discussion of a new tactical air traffic control system, the AN/TPN-19 Landing Control Central, being developed by Raytheon Company for the Air Force. The system provides airport surveillance, precision approach and landing, and operator/aircraft/machine operations by using a terminal Area Surveillance Radar (ASR), a Precision Approach Radar (PAR) and an Operations Center (OPS). Besides the basic radar information, the display provides the following operator aids to ease the operator work load: Range Marks giving the operator a range reference, Runway Cursor, which is an extension of the runway centerline to facilitate aircraft vectoring, Azimuth Cursor, which is a line which can be suitably positioned, and a display capable of being off-centered one radius to provide sector coverage. V.Z.

A72-12422 # Nonequilibrium boundary layer flow on highly-swept hypersonic wings. G. R. Inger (Virginia Polytechnic Institute and State University, Blacksburg, Va.). *International Astronautical Federation, International Astronautical Congress, 22nd, Brussels, Belgium, Sept. 20-25, 1971, Paper. 26* p. 10 refs. (VPI-E-71-23)

Analysis of the nonequilibrium effects in a laminar three-dimensional flow at the leading edge of a swept hypersonic infinite span wing with an intensively cooled surface. A significant effect of a sweep-induced crossflow on the nonequilibrium behavior of the three-dimensional flow is demonstrated. This effect is caused by a change in the flow inviscid characteristics changing the boundary layer pattern, by an alteration of the Dahmköhler parameters which control the nonequilibrium level in the gas phase and in the catalytic surface reactions, and by the development of dissipative viscous heating which can change the nonequilibrium boundary flow condition from one with prevailing recombination to one with prevailing dissociation. Two approximate closed solutions are given for estimating the nonequilibrium characteristics of the boundary layer in terms of gasdynamics. V.Z.

A72-12440 # Matrix method of calculating the strength of hinged main-rotor blades for a helicopter in steady forward flight (Macierzowa metoda obliczeń wytrzymałościowych przegubowych łopat wirników nośnych śmigłowców w ustalonym locie skośnym).

L. Żerek. *Instytut Lotnictwa, Prace*, no. 46, 1971, p. 69-103. 5 refs. In Polish.

Description of a matrix method of calculating the aerodynamic loads (lift), transverse forces, bending moments, torques, flexural deflections, and the twist of hinged main-rotor blades in a helicopter during steady forward flight. The proposed method accounts for the influence of flexural and torsional deflections on the distribution of aerodynamic loads along the blade span as a function of time. The actual blade, representing a continuous system with a given distribution of mass and torsional and flexural rigidity, is replaced by an elastic axis with piecewise constant rigidity and a discrete distribution of mass and moments of inertia. The displacement of the centers of mass of individual blade segments along the chord is taken into account together with both internal blade damping and aerodynamic damping. T.M.

A72-12498 Fatigue damage detection. J. R. Barton and F. N. Kusenberger (Southwest Research Institute, San Antonio, Tex.). In: *Metal fatigue damage - Mechanism, detection, avoidance, and repair*. Philadelphia, American Society for Testing and Materials, 1971, p. 123-227. 89 refs.

Relationships between the characterization and the non-destructive detection of fatigue damage are discussed and illustrated. Inspection methods presently used at overhaul facilities are reviewed, and examples of the equipment used and the results obtained are given. The advantages and limitations of currently used non-destructive methods are summarized. A perspective review of recent research efforts in nondestructive fatigue damage detection including descriptions of methods and typical experimental results is presented. Finally, nondestructive evaluation technology is appraised critically in relation to the desired results and practices, and this appraisal is used as a basis for a look into the future. (Author)

A72-12499 Field practices in the repair of fatigue damaged jet engine components. H. G. Popp, L. G. Wilbers (GE Material and Process Technology Laboratories, Evendale, Ohio), and V. J. Erdeman (Eastern Air Lines, Inc., Miami, Fla.). In: *Metal fatigue damage - Mechanism, detection, avoidance, and repair*. Philadelphia, American Society for Testing and Materials, 1971, p. 228-253. 5 refs.

Review of jet engine overhaul procedures for hardware fatigue damage repair. Details are given on techniques for removal of distressed metal, replacement of distressed area, and repair welding for restoring components to original condition. Lack of knowledge on fatigue damage buildup and lack of confidence to restoration processing are noted as major obstacles for progress in this field. V.Z.

A72-12501 # A synopsis on Q/STOL engines. *Aircraft Engineering*, vol. 43, Nov. 1971, p. 12, 13.

Discussion of powerplants for Q/STOL aircraft, which must be capable of landing and taking off from a runway not more than 2000 ft in length, with a noise level not greater than 95 PNdB at a distance of 500 ft from the runway. A Q/STOL aircraft has more installed thrust at takeoff than a CTOL aircraft, and it can therefore have engines with a higher bypass ratio for the same cruise speed. A rapidly increasing number of turbine stages are required. Some details of the Rolls-Royce/SNECMA M45S(RB 410) engine project are given. F.R.L.

A72-12502 # Externally blown flaps, aerodynamic feasibility study of a STOL-transporter. P. Kuehl and D. Welte (Dornier

AG, Friedrichshafen, West Germany). *Aircraft Engineering*, vol. 43, Nov. 1971, p. 16-18.

Use of externally blown flaps to achieve typical STOL characteristics for medium and heavy jet transport aircraft. As part of a project study conducted by Dornier AG concerning a 40-ton transport aircraft, the aerodynamic and flight mechanical feasibility is demonstrated. The basic data were supplied by wind tunnel tests on a model of the aircraft. With a view to V/STOL capability, the engine jet deflection was optimized by means of a novel slot flap design on a simple rectangular wing. Short takeoff and short landing distances are calculated, and aspects of tailplane design are discussed.

F.R.L.

A72-12503 # V/STOL R & D in France. *Aircraft Engineering*, vol. 43, Nov. 1971, p. 20-23.

Discussion of various configurations for the Aladin II noiseless STOL aircraft project. The solution envisaged consists in combining a wing equipped with adapted flaps with a convenient number of noiseless propelling units of a design similar to those imagined for the Bertin Aerotraine. Rudders relatively larger than those provided for a conventional aircraft should be used. The proposed turbojet unit is described, as well as two versions of the aircraft, one of 90 to 100 passenger capacity, the other of 45 to 50 passengers. Economical aspects and commercial activities and tasks of STOL aircraft are considered.

F.R.L.

A72-12504 # The load on the brake parachute of a jet aeroplane under the influence of the engine wake. R. Sandstrom. *Aircraft Engineering*, vol. 43, Nov. 1971, p. 26, 27, 30. 9 refs.

Consideration of the effect of jet engine efflux which, in certain cases, can give a considerable contribution to the load caused by the aircraft velocity on a deployed brake parachute. When engine disturbances appear incidentally during landing it can happen that the engine speed is considerably higher than the speed corresponding to ground idle power when the brake parachute is released. The load on the parachute can thus in certain cases hazard the strength of the installation. To evaluate the load contribution from the engine efflux implies information about certain engine characteristics, aircraft velocity, and the drag coefficient of the brake parachute.

F.R.L.

A72-12542 # In-flight studies of aircraft stability and controllability (Issledovaniia v polete ustoiichivosti i upravliaemosti samoleta). Iu. I. Sneshko. Moscow, Izdatel'stvo Mashinostroenie, 1971. 328 p. 41 refs. In Russian.

The theoretical principles and current methods of in-flight study of the stability and controllability of aircraft in both steady and unsteady regimes are outlined. Aircraft tests in limiting regimes (limiting speed, acceleration, and angle of attack) and in special flight situations (engine failure, failure of the automatic stabilization system, and failure of the control system hydraulic amplifiers) are considered. The equations of motion and the characteristics of an aircraft as a dynamic system are presented, as well as criteria for estimating and characterizing stability and controllability. Methods and techniques for in-flight determination of aircraft stability and controllability are described, together with methods of determining balancing curves from acceleration and speed, methods of determining aerodynamic force moments and their derivatives, methods of determining frequency characteristics and impulse and transition functions, and methods of evaluating the behavior of aircraft in limiting regimes and in special flight situations.

A.B.K.

A72-12561 # Ductility improvements in superalloys. R. G. Dunn and D. I. Sponseller (Climax Molybdenum Company of Europe, Ltd., London, England). In: *Toward improved ductility and*

toughness; Proceedings of the Symposium, Kyoto, Japan, October 25, 26, 1971. Tokyo, Climax Molybdenum Development Co. (Japan), Ltd., 1971, p. 321-343. 22 refs.

Some recent developments concerning ductility improvements in superalloys are discussed. Particular emphasis is placed upon ductility or workability improvements that are achieved without sacrificing elevated-temperature strength properties. Because of the economic and technological impact that the aircraft gas turbine exerts on the superalloy industry, the ductility improvements are specifically directed toward aircraft engine applications. Two of the developments involve hafnium alloying and directional-solidification effects on cast-superalloy ductility properties. The two remaining developments relate to ductility and workability improvements in wrought superalloys and involve a discussion of thermomechanically processed and powder-metallurgy components.

(Author)

A72-12621 # Air traffic regulations (Luftverkehrs-Verordnungen). M. Hofmann and E. Grabherr (Bayerische Staatsministerium für Wirtschaft und Verkehr, Munich, West Germany). Munich, C. H. Beck'sche Verlagsbuchhandlung, 1971. 554 p. 56 refs. In German. \$28.40.

The regulations considered are valid in the territory of the Federal German Republic. The obligations of the participants in the air traffic are covered together with general rules, rules for the flight with and without instruments, and fines to be imposed in case of violations of the regulations. Other regulations discussed are concerned with questions of granting licenses. Also covered are rules for the examination of personnel and equipment, the operation of aircraft, flight security, and administrative costs.

G.R.

A72-12622 # Air traffic law (Luftverkehrsgesetz). M. Hofmann and E. Grabherr (Bayerische Staatsministerium für Wirtschaft und Verkehr, Munich, West Germany). Munich, C. H. Beck'sche Verlagsbuchhandlung, 1971. 622 p. 53 refs. In German. \$28.40.

The air traffic law discussed covers according to German law the totality of special legal norms concerned with air traffic, the vehicles used in air traffic, and the air space with regard to its properties as an element of air traffic. The subjects covered include German air law, the organization of air traffic administration, international air law, and other important legal regulations concerning the air traffic. Private organizations related to air traffic are also considered, giving attentions to international and national organizations.

G.R.

A72-12640 Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings (Simposio su Radioaiuti alla Navigazione Marittima e Aerea, Trieste, Italy, June 24-26, 1971, Proceedings). Symposium sponsored by the Associazione Elettrotecnica ed Elettronica Italiana. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 124 p. In Italian.

Papers on radio aids to navigation covering radar cross section of real targets, problems and technical aspects connected with the use of the L band in an aerial navigation aid system via satellite, use of sequential analysis in communications and radar systems, improvement of visibility in scattering media, aircraft radio navigation systems by means of polar coordinates and their development, and contribution to the radar resolution problem.

M.M.

A72-12642 # Problems and technical aspects connected with the use of the L band in an aerial navigation aid system via satellite

(Problemi ed aspetti tecnici connessi con l'uso della banda L in un sistema via satellite per l'assistenza alla navigazione aerea). G. Quaglion and E. Vitali. In: Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 24 p. 9 refs. In Italian.

Description of the advantages of using the L band (1540 to 1660 MHz) in a satellite system employed in solving the various problems connected with assistance to aerial navigation. The accuracy of determination of a vehicle's position made possible by the L band is discussed, together with the use of data transmission at a rate of 600 to 1200 bit/sec to provide the ground station with information on vehicle status and position. Voice communications and modulation methods are examined, including the factors which determine the margin to be assigned to the L band system. A technical and financial evaluation of the system is made. M.M.

A72-12645 # ILS system for landing aircraft and its future developments (Sistema ILS per l'atterraggio dei velivoli e suoi sviluppi futuri). D. Graziani. In: Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 4 p. In Italian.

Description of the currently used ILS aircraft landing system, following a brief historical outline. The refinements recently undergone by this system in order to make landing possible under particularly adverse weather conditions are discussed. New future systems destined to replace the ILS system are briefly mentioned. M.M.

A72-12646 # Aircraft radio navigation systems by means of polar coordinates and their development (Sistemi di radionavigazione a coordinate polari per velivoli e loro sviluppo). D. Graziani. In: Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 10 p. In Italian.

Following a brief historical outline, the principles of operation of radio navigation systems by means of polar coordinates (VOR, TACAN, DME) currently in use are discussed. Recently introduced improvements are briefly mentioned, together with further developments and conversions that such systems will undergo in the future in order to ensure ever greater flight safety and accuracy. M.M.

A72-12647 # Investigation of an associative memory for use in digital computers employed as aids to air and naval traffic (Studio di una memoria associativa per l'utilizzazione in calcolatori digitali impiegati in aiuto al traffico aereo/navale). G. De Stasio and C. Maggi (Selenia S.p.A., Rome, Italy). In: Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 7 p. In Italian.

Analysis of problems connected with the real time processing of data on air and naval traffic by means of conventional computers. A new system of associative memory for carrying out the most interesting logic functions for such problems is proposed. The times that can be obtained by means of the new memory are compared with those of the conventional systems. A computer architecture for the optimum use of such a memory and suitable treatment of the related problems is proposed. M.M.

A72-12649 # Automation of air traffic - The ATCAS system (Automazione del traffico aereo - Sistema ATCAS). A. Venditti and F. La Rovere (Selenia S.p.A., Rome, Italy). In: Symposium on Radio

Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 7 p. In Italian.

Brief but complete description of the ATCAS system. An overview of the principal problems presented by air traffic control is given, with emphasis on the Italian situation, and a description of the solutions adopted in ATCAS. M.M.

A72-12650 # Techniques for the extraction of radar data (Tecniche di estrazione dei dati radar). G. Grasso (Selenia S.p.A., Rome, Italy). In: Symposium on Radio Aids to Maritime and Aerial Navigation, Trieste, Italy, June 24-26, 1971, Proceedings. Trieste, Associazione Elettrotecnica ed Elettronica Italiana, 1971. 10 p. 5 refs. In Italian.

Discussion of the requirements and characteristics of methods used in the automatic extraction of data detected by radar. The setup and functions of a data extractor are treated, together with methods for quantifying the azimuth, moving window detection, and coordinate measurement. The ATCAS data extractor is described and analyzed, and the results obtained are examined. M.M.

A72-12705 # Angle of attack and thrust control for steeply approaching aircraft (Anstellwinkel- und Schubregelung für steil anfliegende Flugzeuge). G. Schänzer (Bodenseewerk Gerätetechnik GmbH, Überlingen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-063.* 32 p. In German.

Description of an integrated STOL flight control system which refers the angle of attack, the altitude deviation, and all other essential state variables in a highly coupled form to the altitude controller and the gas throttle. With the aid of quadratic integral criteria the proposed system was optimized in such a way that it completely satisfies all requirements with reference to piloting accuracy, gust suppression, and passenger comfort. The results of a test of this system in a twin-engine propeller-driven tailwheel aircraft are cited. A.B.K.

A72-12707 # Force and pressure distribution measurements on a wing-body combination with wing of low aspect ratio in compressible flow (Kraft- und Druckverteilungsmessungen an einer Flügel-Rumpf-Kombination mit Flügel kleiner Streckung in kompressibler Strömung). W. Stahl, K. Hartmann, and W. Schneider (Aerodynamische Versuchsanstalt, Göttingen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-118.* 39 p. 9 refs. In German.

The combination investigated consisted of a delta wing and a body in the form of a circular cylinder with an ogival nose. Mach numbers were in the range from 0.5 to 2.2. Normal forces and pitching moments were measured as well as spanwise pressure distributions in several sections on the pressure and suction sides. Oil-flow and smoke pictures provided some insight into the flow field. The influence of the Reynolds number was investigated at Mach numbers 0.5, 1.0, and 1.8. Angles of incidence varied from 0 deg to 30 deg. G.R.

A72-12709 # Investigation of unsteady interference effects on a harmonically oscillating wing-tailplane model with a variable sweep wing in the low subsonic region (Untersuchung instationärer Interferenzeffekte an einem harmonisch schwingenden Flügel-Höhenleitwerks-Modell mit variabler Flügelpeilung im niedrigen Unterschallbereich). H. Triebstein (Aerodynamische Versuchsanstalt, Göttingen, West Germany) and J. Becker (Messerschmitt-Bölkow-

Blohm GmbH, Munich, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-081*. 48 p. 17 refs. In German.

Special emphasis in the investigation is given to the unsteady aerodynamic interfering effects at various wing-tailplane configurations. In particular, the effects of the wing sweep-back, the wing angle of attack and the V-position of the tailplane stabilizer are investigated in detail for several reduced frequencies and longitudinal positions of the wing and tailplane. G.R.

A72-12712 # Experimental investigation of the drag and lift of wings with a blunt trailing edge in compressible flow (Experimentelle Untersuchung des Widerstandes und Auftriebes von Flügeln mit stumpfer Hinterkante bei kompressibler Strömung). M. Tanner (Aerodynamische Versuchsanstalt, Göttingen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-114*. 33 p. 12 refs. In German.

Drag and lift measurements were performed on two rectangular wings with an aspect ratio equal to 2 and with various trailing edges, in the freestream Mach number range from 0.5 to 2.2. In addition to straight trailing edges - i.e., sharp and blunt - various serrated blunt trailing edges were also examined. Some of these were found to reduce the drag remarkably. By splitting up the total drag in its components, it was possible to predict the relative magnitude of the components and the optimum trailing edge thickness. O.H.

A72-12714 # Adaptation of the nonlinear characteristic of an attitude control system developed for a V/STOL aircraft to a helicopter (Anpassung eines Lagereglers nichtlinearer Charakteristik, entwickelt für ein VSTOL-Flugzeug, an einen Hubschrauber). H. Schmidlein (Vereinigte Flugtechnische Werke-Fokker GmbH, Bremen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-060*. 72 p. In German.

Free-flight simulation tests are described whose aim was to determine the adaptability of a nonlinear attitude control system developed by VFW-Fokker for the VAK 191 B aircraft to the roll and pitch control of a helicopter. The modifications which arise from this adaptation and some associated problems are examined. The Bell 47-G free-flight simulator was employed in the tests. V.P.

A72-12718 Spin control by means of the 'superstall' characteristic (Trudelbeeinflussung durch die 'Superstall'-Charakteristik). H. Neppert (Hamburger Flugzeugbau GmbH, Hamburg, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-057*. 24 p. 10 refs. In German.

Three cases of spinning have been investigated and compared. These include conventional steep and flat spins which depend on damping in yaw, and flat spins with a 'superstall' characteristic. This latter is not determined by damping in yaw, and is mostly distinguished from conventional flat spins by a lower rate of rotation. These relationships are explained by some examples. O.H.

A72-12722 Methods of construction of aeroelastic models for a rational flutter analysis of modern aircraft designs (Bauweisen aeroelastischer Modelle für eine rationelle Flatteruntersuchung moderner Flugzeugkonzeptionen). H. Hönlinger (Messerschmitt-Bölkow-Blohm GmbH, Munich, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-082*. 27 p. 8 refs. In German.

Description of a combined computational-experimental method of flutter analysis involving the study of specially constructed aeroelastic models. The proposed method is characterized by a considerable reduction of the risk of error and also by a reduction of the labor involved. In the proposed method appropriately constructed flutter models are investigated in a wind tunnel concurrently with the calculations in an early stage of the design process. These models are not intended to simulate the real state of the aircraft by accurate imitation of the original structure so as to make the computation superfluous, but to constitute a complementary concurrent analysis in analog form in contrast to the digitally performed calculation. A.B.K.

A72-12723 # Experimental studies of aerodynamic coefficients of a wing-fuselage combination and comparison with the results of linear and nonlinear theories at subsonic speeds (Experimentelle Untersuchungen aerodynamischer Beiwerte einer Flügel-Rumpf-Kombination und Vergleich mit den Resultaten linearer und nichtlinearer Theorien bei Unterschallgeschwindigkeiten). E. Herpfer and J. T. Heynatz (Dornier System GmbH, Friedrichshafen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-115*. 66 p. 25 refs. In German.

Comparison of various methods of calculating the most important aerodynamic coefficients of the longitudinal, lateral, and roll motion of a wing-fuselage combination in the range of large angles of attack and small sideslip angles. The ranges of applicability and the reliabilities of the various methods are established on the basis of comparisons with the results of experimental studies of a wing-fuselage configuration in incompressible and compressible flow regions. It is found that while linear theories are useful only for angles of attack up to 5 deg, the nonlinear methods considered yield good or satisfactory results for angles of attack up to 12 deg. At larger angles of attack all the theories discussed become increasingly inapplicable. A.B.K.

A72-12725 Methods of flight vibration testing of modern high-performance aircraft (Methoden des Flugschwingungsversuches an modernen Hochleistungsflugzeugen). G. Haidl and F.-J. Rudolph (Messerschmitt-Bölkow-Blohm GmbH, Munich, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-083*. 25 p. 8 refs. In German.

Review of the existing methods of ascertaining the flutter stability of high-speed aircraft. Methods of producing in-flight vibrations of aircraft are discussed, including pulsed excitation by solid-fuel rockets, pulsed excitation by electrically controlled rudder impacts, harmonic excitation, and sliding frequency excitation. Methods of evaluating the responses to these various types of excitation are considered, including filtering, the root-locus method, spectral decomposition, and methods based on the use of correlation functions. A.B.K.

A72-12730 # Calculation of the unsteady pressure distribution on harmonically oscillating slender wing-fuselage configurations (Berechnung der instationären Druckverteilungen an harmonisch schwingenden schlanken Flügel-Rumpf-Konfigurationen). K. Chao (Aerodynamische Versuchsanstalt, Göttingen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-080*. 34 p. 13 refs. In German.

Based upon the slender body theory the pressure distribution is calculated numerically. The configurations investigated consist of a circular cylindrical fuselage body with a conical nose and a delta

wing with straight, cubic or sinusoidal leading edges. In particular, the influence of the fuselage and the effects of wing geometry and reduced frequency are investigated in detail. For three delta wings with straight leading edges the results were compared with the corresponding data obtained on the basis of three-dimensional lifting surface theory.

G.R.

A72-12733 # Application of interactive computer graphics in wing unit designs (Die Anwendung von interaktiver Computer-Graphik bei der Berechnung von Tragwerken). J. H. Argyris and I. Grieger (Stuttgart, Universität, Stuttgart, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-107.* 36 p. 20 refs. In German.

Discussion of a man-machine dialog technique which uses graph screen displays to facilitate the input of human decisions into a computer in response to information provided by the computer. Some aspects of the application of this technique to aircraft wing unit designs are analyzed. Graph transformation, interactive computer data graph analysis and system structure representation by this technique are considered. Details are given on the application of this computer data input and display technique to a two-cell fuselage, an aircraft tail unit and truss.

V.Z.

A72-12745 # Unsolved problems of airplane aerodynamics (Offene Probleme der Flugzeug-Aerodynamik). J. Barche (Vereinigte Flugtechnische Werke-Fokker GmbH, Bremen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971, Paper 71-105.* 32 p. 32 refs. In German.

Problems inherent in current and future aircraft design which still lack a solution as a result of gaps in the theoretical and experimental description of flow patterns are discussed. Both civil and military aircraft in the subsonic and transonic range are considered. Problems arising in different phases of aerodynamic design are examined first. Next, special flow problems encountered during different flight phases, such as takeoff and landing, during transonic flight, and during flight maneuvers, are characterized and explained.

O.H.

A72-12748 # Current situation of radio aids for aerial navigation in Italy and prospects for the near future (Situazione attuale dei radioaiuti alla navigazione aerea in Italia e prospettive per il prossimo futuro). A. Pepe (Aeronautica Militare, Ispettorato Telecomunicazioni ed Assistenza al Volo, Rome, Italy). *Associazione Elettrotecnica ed Elettronica Italiana, Simposio su Radioaiuti alla Navigazione Marittima e Aerea, Trieste, Italy, June 24-26, 1971, Paper.* 11 p. In Italian.

Emphasis is placed on problems connected with the efficiency, updating and technical development of facilities as well as their quantitative and qualitative suitability to the growing requirements of air traffic. The contribution that automation of ATC will make to air navigation is briefly discussed.

M.M.

A72-12749 # Doppler - A modern aid for air navigation (Doppler - Moderno ausilio per la navigazione aerea). G. Puddu and J. Glagg (Marconi Italiana S.p.A., Genoa, Italy). *Associazione Elettrotecnica ed Elettronica Italiana, Simposio su Radioaiuti alla Navigazione Marittima e Aerea, Trieste, Italy, June 24-26, 1971, Paper.* 4 p. In Italian.

Description of a typical Doppler system consisting of a sensor (navigation radar device), a computer unit, and a data transmitter. The navigation radar operates on the basis of the Doppler effect and provides a precise value of the aircraft's horizontal speed, obtained through the course data and velocity relative to the ground. Such data are sent continuously to the navigation computer unit. This equipment, completely transistorized, arranges for the continuous recording of the aircraft's position. The device can operate by means of a storage system, thus ensuring continuous performance during periods when the Doppler data may not be temporarily available.

M.M.

A72-12800 # Influence of the hydrocarbon composition of jet fuels on their thermal stability (Vliianie uglevodorodnogo sostava reaktivnykh topliv na ikh termicheskuiu stabil'nost'). E. M. Bushueva and I. E. Bespolov (Vsesoiuznyi Nauchno-Issledovatel'skii Institut Neftianoi Promyshlennosti, Moscow, USSR). *Khimiia i Tekhnologiya Topliv i Masel*, vol. 16, no. 9, 1971, p. 46-49. 6 refs. In Russian.

It is shown that aromatic hydrocarbons, particularly naphthalene derivatives and polycyclic naphtheno-aromatic hydrocarbons, comprise another (in addition to heteroorganic compounds) source of deposit formation during oxidation of jet fuels. The structure of the nonaromatic component exerts a strong influence on the degree of coagulation of the oxidation products of aromatic hydrocarbons. The maximum amount of the solid phase is observed during oxidation of a mixture of aromatic hydrocarbons with isoparaffin hydrocarbons. The minimum quantity of the solid phase is produced during oxidation of aromatic hydrocarbons mixed with bicyclic naphthenic hydrocarbons.

T.M.

A72-12825 # On the characteristics of wing with tip clearance. III - The force acting on a rectangular wing of low aspect ratio. Y. Sugiyama (Nagoya University, Nagoya, Japan). *JSME, Bulletin*, vol. 14, Oct. 1971, p. 1077-1087. 13 refs.

Theoretical study of the effect of tip clearance on the aerodynamic force of an inviscid incompressible uniform flow about a wing. It is assumed that the vortex strength is constant across the wing span and that the downwash along the wing span is equal to its level at the center of the wing span. Expressions are derived to determine the force acting on a low aspect ratio wing with a tip clearance under the conditions studied. The expressions are based on an extension of Bollay's results.

V.Z.

A72-12882 The rostrum. R. Prouty (Lockheed-California Co., Burbank, Calif.). *American Helicopter Society, Journal*, vol. 16, Oct. 1971, p. 61, 62.

Simple exploration of tip relief, with suggestion of an empirical means of predicting its magnitude. A blade tip may be thought of as a combination of a two-dimensional airfoil and a three-dimensional body. Because of the geometric relationships, tips with thick airfoil sections have more tip relief than do tips with thin airfoil sections. For quick estimates of the tip relief, the apparent drag divergence Mach number can be computed from the two-dimensional drag divergence, Mach number, the airfoil parameters, and flight conditions.

F.R.L.

A72-12898 Measuring, data-acquisition, and data-processing systems for the large wind tunnels of the Aerodynamische Versuchsanstalt Göttingen (Messtechnik, Datenerfassung und Datenverarbeitung an den grossen Windkanälen der Aerodynamischen Versuchsanstalt Göttingen). H. Fütterer, D. Mehmél, and F. W.

Riegels (Aerodynamische Versuchsanstalt, Göttingen, West Germany). In: Deutsche Gesellschaft für Luft- und Raumfahrt, Yearbook 1970. Cologne, Deutsche Gesellschaft für Luft- und Raumfahrt, 1971, p. 166-185. 14 refs. In German.

The measuring equipment and procedures, and the electronics of the data acquisition and processing systems employed at the 3-m wind tunnel and the transonic wind tunnel at Göttingen are examined. Improvements in the measuring equipment made during the last decade, and an improved compressor system suitable for engine simulation are discussed. A computerized real-time data processing system is described. V.P.

A72-12900 Conception and flight behavior of a jet-powered recoverable lift engine (Zur Konzeption und zum Flugverhalten eines strahlgetragenen Abwurftriebwerks). D. Rist (München, Technische Universität, Munich, West Germany). In: Deutsche Gesellschaft für Luft- und Raumfahrt, Yearbook 1970. Cologne, Deutsche Gesellschaft für Luft- und Raumfahrt, 1971, p. 196-249. 13 refs. In German.

The concept of a disk-shaped lift engine intended to provide additional thrust during the takeoff and transition phases of V/STOL aircraft. After fulfilling this task, the engine returns to the ground, using its jet for a soft landing. The design of the engine, characterized by an unconventional arrangement of compressor, turbine, and combustion chamber is described. The recovery process is controlled solely by the strong gyroscopic properties of the engine rotor. V.P.

Page intentionally left blank

STAR ENTRIES

N72-10003# Naval Weapons Lab., Dahlgren, Va. Warfare Analysis Dept.

EFFECT OF FIN SLOTS ON THE STATIC AND DYNAMIC STABILITY CHARACTERISTICS OF FINNED BODIES

Thomas A. Clare and Peter Daniels Jun. 1971 31 p refs (AD-728016; NWL-TR-2582) Avail: NTIS CSCL 19/1

Static and dynamic stability characteristics of a cruciform, slotted fin configuration are presented. Aerodynamic coefficients are extracted from single degree of freedom, free oscillation wind tunnel tests employing nonlinear least squares procedures. The linear and nonlinear variations with angle of attack of the restoring and damping moment coefficients are presented for various fin slot sizes at subsonic speeds. Results indicate that, as slot size increases, the nonlinear contributions decrease in magnitude to a greater extent than the linear terms. Based on the signs of the various moment contributions, it was found that, while stability is reduced at small angles of attack due to increased slot size, greater stability is affected at moderate angles of attack. Author (GRA)

N72-10004# Deutsche Gesellschaft fuer Luft- und Raumfahrt, Porz (West Germany).

AERODYNAMIC INTERFERENCE BETWEEN AIRCRAFT AND ENGINE JET [AERODYNAMISCHE INTERFERENZ ZWISCHEN FLUGZEUG UND TRIEBWERKSSTRAHL]

Apr. 1971 312 p refs Partly in ENGLISH and partly in GERMAN Proc. of the DGLR Symp., Duesseldorf, 3 Dec. 1970 (DLR-MITT-70-28) Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

CONTENTS:

1. POSSIBILITIES FOR JET SIMULATION IN THE 3m-WIND TUNNEL OF THE DFVLR-AVA GOETTINGEN E. Melzer and R. Wulf (DFVLR, Goettingen, West Ger.) 28 p refs

2. INTERFERENCE EFFECTS FROM JETS ON AIRCRAFT STATIC STABILITY. WIND TUNNEL METHODS USED IN SWEDEN G. Bennich (SAAB Aircraft Co.) 16 p

3. TECHNIQUE OF PROPULSION SYSTEM SIMULATION WITH HIGH PRESSURE EJECTORS FOR SUBSONIC WIND TUNNEL MEASUREMENTS ON A FIGHTER AIRCRAFT MODEL WITH VERTICAL TAKEOFF CHARACTERISTICS W. Heinzerling (Messerschmitt-Boelkow-Blohm, Munich) 22 p

4. TURBULENT AND LAMINAR JET PROPAGATION IN ROTATING SYSTEMS AND ITS APPLICATION TO JET MIXING IN THE WAKE OF REACTION DRIVEN ROTORS R. Schmidt and J. T. Heynatz (Dornier-Werke, Friedrichshafen, West Ger.) 37 p refs

5. SOME EXPERIMENTS ON AN ENGINE INSTALLATION ABOVE THE WING OF A SWEEP-WINGED AIRCRAFT J. A. Bagley (RAE, Farnborough, Engl.) 20 p refs

6. INFLUENCE OF A JET ON THE AERODYNAMIC

PROPERTIES OF WINGS POSITIONED ABOVE THE JET NOZZLE W. Baumert and L. Harms (DFVLR, Goettingen, West Ger.) 20 p refs

7. THE INFLUENCE OF AN INCLINED JET ON THE AERODYNAMIC CHARACTERISTICS OF A CONTROL SURFACE M. Seidel (DFVLR, Brunswick) 28 p refs

8. FORCE AND DOWNWASH MEASUREMENTS WITH JET SIMULATION ON MODELS OF THE EUROPEAN AIRBUS IN A LOW SPEED WIND TUNNEL, W. Geissler (DFVLR, Goettingen, West Ger.) 22 p refs

9. INVESTIGATIONS OF EXHAUST JETS OF TL-ENGINE MODELS E. Schwantes (DFVLR, Brunswick) 33 p refs

10. CALCULATION OF THE PRESSURE DISTRIBUTION ON AN AIRCRAFT FUSELAGE WITH EMERGING LIFTING JETS USING SINGULARITIES G. Schulz (DFVLR, Porz, West Ger.) 36 p refs

11. AERODYNAMIC CALCULATIONS FOR THE INTERFERENCE OF SEVERAL PROPELLER-JETS WITH AN AEROFOIL G. Loeber (Ver. Flugtech. Werke Fokker, Munich) 43 p refs

N72-10005# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Goettingen (West Germany), Abteilung Aerodynamik.

POSSIBILITIES FOR JET SIMULATION IN THE 3m-WIND TUNNEL OF THE DFVLR-AVA GOETTINGEN [MOEGLICHKEITEN ZUR STRAHLSIMULATION IM 3M-WINDKANAL DER DFVLR-AVA GOETTINGEN]

E. Melzer and R. Wulf In DGLR Aerodyn. Interference Between Aircraft and Engine Jet Apr. 1971 28 p refs In GERMAN; ENGLISH summary

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

Experiments were carried out in a low speed wind tunnel to determine jet aircraft/engine interference with several aircraft models. After a discussion of the similarity parameters of engine intake and exhaust models, some possibilities of jet generation are explained, including compressed air, motor-driven fans or propellers, and the use of compressed air for ejectors of turbines. The power plants involved are described, and their possibilities and limitations are discussed. ESRO

N72-10006# Saab Aircraft Co., Linkoping (Sweden). INTERFERENCE EFFECTS FROM JETS ON AIRCRAFT STATIC STABILITY. WIND TUNNEL METHODS USED IN SWEDEN

G. Bennich In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 16 p

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

The development of equipment for measuring jet interference in aircraft models is described. The main object of these tests was the determination of jet interference effects on the static stability of the twin engined SAAB 105 aircraft and the single engined SAAB-37 Viggen which has an ejector type of afterbody. Special supports enabled the measurement of yaw stability for the twin-engined aircraft; the single engined model support permitted variation in angle of attack and yaw. The supply of compressed air was regulated to simulate all engine settings. ESRO

N72-10007# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany). Unternehmensbereich Flugzeuge-Entwicklung. TECHNIQUE OF PROPULSION SYSTEM SIMULATION

WITH HIGH PRESSURE EJECTORS FOR SUBSONIC WIND TUNNEL MEASUREMENTS ON A FIGHTER AIRCRAFT MODEL WITH VERTICAL TAKEOFF CHARACTERISTICS [TECHNIK DER TRIEBWERKSSIMULATION MIT HOCH-DRUCKEJEKTOREN BEI UNTERSCHALLWINDKANALMESSUNGEN AM MODELL EINES SENKRECHTSTARTFAEHIGEN KAMPFFLUGZEUGES]

W. Heinzerling /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 22 p In GERMAN (See

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

A wind tunnel model of a vertical takeoff fighter aircraft was designed to cater for the normal 6 component measurements in addition to jet interference measurements. The model's engines were high pressure ejectors, driven by compressed air. A survey is given of the measurements performed to determine aerodynamic characteristics with and without interference drag.

ESRO

N72-10008# Dornier-Werke G.m.b.H., Friedrichshafen (West Germany).

TURBULENT AND LAMINAR JET PROPAGATION IN ROTATING SYSTEMS AND ITS APPLICATION TO JET MIXING IN THE WAKE OF REACTION DRIVEN ROTORS [TURBULENTE UND LAMINARE STRAHLAUSBREITUNG IN ROTIERENDEN SYSTEMEN UND IHRE ANWENDUNG AUF DIE STRAHLMISCHUNG IM ABWINDFELD VON ROTOREN MIT REAKTIONSANTRIEBEN]

R. Schmidt and J. T. Heynatz /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 37 p refs In GERMAN

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

The kinematics and dynamic laws governing the propagation of a jet emerging from a rotating arm tip are derived for a fixed coordinate system. Using typical mixing laws for rectilinear jet propagation as an approximation, the cases of plane and round laminar and turbulent jets are compared. The spatial deviation of a jet in a rotor wake results from a further approximation. The transferability of the theoretical statements on jet propagation from one reference system to another is discussed. The principles of jet propagation in rotating systems are treated in a system of correlated coordinates. The theoretical derivations are clarified with examples of jets with temperature equal to or higher than their environment. In addition, the characteristic properties of jet propagation are experimentally investigated using smoke photographs.

ESRO

N72-10009# Royal Aircraft Establishment, Farnborough (England).

SOME EXPERIMENTS ON AN ENGINE INSTALLATION ABOVE THE WING OF A SWEEP-WINGED AIRCRAFT

J. A. Bagley /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 20 p refs

(RAE-TM-AERO-1271) Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

Experiments are described for a possible large diameter turbofan engine nacelle installation above the wing of a transport aircraft. The current generation of turbofan engines for transport aircraft have nacelle diameters of about 3m, and as engine bypass ratio increases, the nacelles will become even larger. To fit such engines in the conventional position below the wings will be increasingly difficult. Tests were first made on a partial model of the wing and nacelle with the jet represented by blowing from an external supply. Interference between the jet and wing was investigated by measuring pressures on the wing, by surveys of the total-head distribution in the jet, and by schlieren and oil-flow photography. These tests were followed by force measurements in a low-speed wind tunnel on a model of a swept wing and fuselage, fitted with a pair of free-flow nacelles.

The results suggest that the lift-dependent drag of such an installation may be significantly larger than that of a conventional installation below the wing.

Author (ESRO)

N72-10010# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Goettingen (West Germany). Abteilung Aerodynamik.

INFLUENCE OF A JET ON THE AERODYNAMIC PROPERTIES OF WINGS POSITIONED ABOVE THE JET NOZZLE [EINFLUSS EINES DUESENSTRAHLS AUF DIE AERODYNAMISCHEN BEIWERTE VON UEBER DER STRAHLDUESE ANGEORDNETEN FLUEGELN]

W. Baumert and L. Harms /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 20 p refs In GERMAN; ENGLISH summary

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

Rectangular and swept wings were investigated; position, inclination and velocity of the jet were varied. Wing and nacelle were mounted separately so that the wind tunnel balance did not measure jet thrust. A simple determination of jet interference was possible with this arrangement. The jet decreased wing lift, for the ratio of jet velocity and free stream velocity from 2 to 17 the lift loss increased linearly with the velocity ratio. The lift loss also increased with jet angle. The induced pitching moment is dependent on velocity ratio and varies with position of the jet.

ESRO

N72-10011# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany). Inst. Aerodynamik.

THE INFLUENCE OF AN INCLINED JET ON THE AERODYNAMIC CHARACTERISTICS OF A CONTROL SURFACE [DER EINFLUSS EINES GENEIGTEN STRAHLS AUF DIE AERODYNAMISCHEN EIGENSCHAFTEN EINES LEITWERKS]

M. Seidel /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 28 p refs In GERMAN

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

The variations in lift of a freestanding control surface due to a round, cold, engine jet were investigated. The most important parameter in VTOL longitudinal stability is the inclination of the jet engine to the flow direction. The measurements show that inclined incident jets result in lift losses of the control surface and thus are generally unfavorable to longitudinal stability. An empirical formula is derived for the estimation of lift loss due to jet impingement.

ESRO

N72-10012# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Goettingen (West Germany). Abteilung Aerodynamik.

FORCE AND DOWNWASH MEASUREMENTS WITH JET SIMULATION ON MODELS OF THE EUROPEAN AIRBUS IN A LOW SPEED WIND TUNNEL [KRAFT- UND ABWINDMESSUNGEN MIT TRIEBWERKSSIMULATION AN MODELLEN DES EUROPAEISCHEN AIRBUS IM NIEDERGESCHWINDIGKEITSBEREICH]

c02 W. Geissler /In DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 22 p refs In GERMAN; ENGLISH summary

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

Extensive wind tunnel measurements of the European airbus, including jet simulation, are reported. The jet interference influence on longitudinal stability led to repositioning of the nacelles. Simulation with the improved engine position did not indicate any reduction in jet interference, whilst bypass jet simulation showed further stability deterioration. Near ground, on the other hand, a clear improvement of longitudinal stability was observed. Further investigation at higher Reynolds numbers is necessary. ESRO

N72-10013# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany). Inst. fuer Luftsaugende Antriebe.

INVESTIGATIONS OF EXHAUST JETS OF TL-ENGINE MODELS [UNTERSUCHUNGEN AN ABGASSTRAHLEN VON TL-TRIEBWERKSMODELLEN] c28

E. Schwantes /n DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 33 p refs In GERMAN

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

A systematic investigation of hot gas free jets, with an excess temperature of 550C, with critical nozzle pressure, and five differently shaped convergent nozzles is described. Large differences were noted with free jet measurements at lower nozzle Mach number. The exhaust jet emerged from the convergent nozzle with very high static overpressure, and accelerated to hypersonic speed within a core of approximately five nozzle diameters. The jet disintegration and the spatial jet propagation were less for the high speed jet than for a free jet with lower nozzle exhaust velocity due to weather turbulence. The jet propagation angle is almost the same for hot and cold jets, but thermal lifting forces resulted in a deformation of the circular cross section for horizontal hot gas jets. ESRO

N72-10014# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Porz (West Germany). Inst. fuer Angewandte Gasdynamik.

CALCULATION OF THE PRESSURE DISTRIBUTION ON AN AIRCRAFT FUSELAGE WITH EMERGING LIFTING JETS USING SINGULARITIES [BERECHNUNG DER DRUCKVERTEILUNG AUF EINEM FLUGZEUGRUMPF MIT AUSTRETENDEN HUBSTRAHLEN MITTELS SINGULARITAETEN]

G. Schulz /n DGLR Aerodyn. Interference between Aircraft and Engine Jet Apr. 1971 36 p refs In GERMAN

Avail: NTIS HC \$3.00/MF \$0.96; ZLDI Munich: 54 DM

The influence of a lifting jet perpendicular to a cylindrical aircraft fuselage is theoretically calculated. The secondary action of the jet is twofold: ambient air is drawn in as an injector, whilst the external airflow around the jet is considered as that around a solid body. The injector action is determined by a half empirical relation. The injector is represented as a line sink in potential theory. The displacing action of the jet is represented by dipole distribution on the jet axis. Both sink and dipoles cause undue disturbances near the fuselage surface by velocity components normal to the contour. These disturbances can be corrected by additional singularities. The determination of these singularities is the essential problem of the investigation. ESRO

N72-10015# Vereinigte Flugtechnische Werke-Fokker G.m.b.H., Munich (West Germany).

AERODYNAMIC CALCULATIONS FOR THE INTERFERENCE OF SEVERAL PROPELLER-JETS WITH AN AEROFOIL [BERECHNUNG DER AERODYNAMIK DES VON MEHREREN STRAHLEN BEAUFSCHLAGTEN TRAGFLUEGELS]

G. Loebert /n DGLR Aerodyn. Interference between Aircraft

and Engine Jet Apr. 1971 43 p refs In GERMAN; ENGLISH summary

Avail: NTIS HC \$6.00/MF \$0.95; ZLDI Munich: 54 DM

The suitability of the lifting surface theory for V/STOL aircraft for the calculation of the aerodynamics of a wing immersed in one or more propeller slipstreams was investigated by comparison with experimental results. The comparison was conducted on the basis of lift, drag, pitching moment, normal-force distribution, and wake characteristics. The impact pressure distribution and field of direction in the airfoil wake are discussed. The influence of the main propeller-wing interference characteristics on the descent capability of propeller driven V/STOL aircraft is investigated. ESRO

N72-10018# National Physical Lab., Teddington (England). Aerodynamics Div.

A PROGRAMME OF RESEARCH INTO VISCOUS ASPECTS OF FLOW ON SWEEP WINGS

B. G. Thompson, G. A. Carr-Hill, and B. J. Powell (Kingston Polytech.) Sep. 1970 89 p refs
(NPL-AERO-NOTE-1100; ARC-32402; FM-4175; PERF-2947)
Avail: NTIS

Current research to produce forward and inverse design programs for swept wings is described briefly. Calculations of linearized velocities, boundary layer development, and of external streamlines from surface pressures are presented. Problems affecting airfoil design and testing in viscous, nominally two-dimensional flow are also considered. Author (ESRO)

N72-10021# National Physical Lab., Teddington (England). Aerodynamics Div.

A NOTE ON SUBSONIC LINEARISED THEORY FOR SYMMETRICAL CRANKED WINGS AT ZERO-INCIDENCE

R. C. Lock Jul. 1970 17 p refs
(NPL-AERO-NOTE-1090; ARC-32225; FM-4167; PERF-2921)
Avail: NTIS

Formulae are given for the streamwise and spanwise components of perturbation velocity due to thickness, as predicted by subsonic linearized theory, in the neighborhood of the crank formed by the junction of two semi-infinite swept wings of different sweep angles. The implications of these formulae for the magnitude of the crank effect are discussed qualitatively, including the influence of free stream Mach number. Author (ESRO)

N72-10022# National Physical Lab., Teddington (England). Aerodynamics Div.

SEPARATION MEASUREMENTS ON A DELTA WING IN A SHOCK TUNNEL AT M=8.6 USING MONOCHROME AND COLOUR-SCHLIEREN PHOTOGRAPHY

R. F. Cash and A. M. Catley Sep. 1970 14 p refs Original contains color illustrations
(NPL-AERO-NOTE-1097; ARC-32399) Avail: NTIS

The measurements were made on a 78 deg swept delta wing in a 400 mm (16 in) shock tunnel and the free stream Reynolds number was 49,000 cm (125,000 in) for stagnation conditions of 150 atmospheres and 2000 K. A series of schlieren photographs of the established separated flow, induced by spanwise steps and wedges fixed at the rear of the model, were taken in monochrome and color. The technique, equipment, and the relative merits of the two systems are discussed in detail. Author (ESRO)

N72-10023# National Physical Lab., Teddington (England). Aerodynamics Div.

THE MECHANICAL DESIGN OF AN ADJUSTABLE NOZZLE FOR THE NPL 26 IN BY 20 IN (635 mm BY 508 mm) TRANSONIC WIND TUNNEL

N. G. Marcus Sep. 1970 28 p refs
(NPL-AERO-NOTE-1098; ARC-32400) Avail: NTIS

A description is given of the mechanical engineering design of a pair of steel flexible liners. These are positioned by simple motorized jack systems which easily adjust the flexible nozzle to control the tunnel Mach number. The aerodynamic loading, calculations, and design features are discussed. Author (ESRO)

N72-10025*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

EFFECT OF CASING TREATMENT ON OVERALL AND BLADE ELEMENT PERFORMANCE OF A COMPRESSOR ROTOR

Royce D. Moore, George Kovich, and Robert J. Blade Washington Nov. 1971 65 p refs

(NASA-TN-D-6538; E-6119) Avail: NTIS CSCL 20D

An axial flow compressor rotor was tested at design speed with six different casing treatments across the rotor tip. Radial surveys of pressure, temperature, and flow angle were taken at the rotor inlet and outlet. Surveys were taken at several weight flows for each treatment. All the casings treatments decreased the weight flow at stall over that for the solid casing. Radial surveys indicate that the performance over the entire radial span of the blade is affected by the treatment across the rotor tip.

Author

N72-10031*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

FULL-SCALE WIND-TUNNEL TESTS OF A SMALL UNPOWERED JET AIRCRAFT WITH A T-TAIL

Paul T. Soderman and Thomas N. Aiken Washington Nov. 1971 99 p refs Prepared in cooperation with Army Air Mobility Res. and Develop. Lab.

(NASA-TN-D-6573; A-3135) Avail: NTIS CSCL 01A

The aerodynamic characteristics of a full scale executive type jet transport aircraft with a T-tail were investigated in a 40 x 80 ft (12.2 by 24.4 meter) wind tunnel (subsonic). Static, longitudinal, and lateral stability, and control characteristics were determined at angles of attack from -2 deg to +42 deg. The aircraft wing had 13 deg of sweep and an aspect ratio of 5.02. The aircraft was tested power off with various wing leading- and trailing-edge high lift devices. The basic configuration was tested with and without such components as engine nacelles, wing tip tanks, and empannage. Hinge-moment data were obtained and downwash angles in the horizontal-tail plane location were calculated. The data were obtained at Reynolds numbers of 4.1 million and 8.7 million based on mean aerodynamic chord. The model had static longitudinal stability through initial stall. Severe tail buffet occurred near the angle of attack for maximum lift. Above initial stall the aircraft had pronounced pitch-up, characteristic of T-tail configurations. A stable trim point was possible at angles of attack between 30 deg and 40 deg (depending on c.g. location and flap setting). Hinge-moment data showed no regions with adverse effects on stick force. Comparisons of wind-tunnel data and flight-test are presented.

Author

N72-10033*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

MULTIPLE FAN INTEGRATED PROPULSION WING SYSTEM Patent Application

Roger W. Luidens, inventor (to NASA) Filed 21 Jun. 1971 14 p

(NASA-Case-LEW-11224-1; US-Patent-Appl-SN-154934) Avail:

NTIS CSCL 01B

A system for directing air against the wing flaps of STOL aircraft to produce both lift and forward thrust is described. Airpumps provide high pressure air to small tip turbine fans disposed spanwise under the wings and forward of the flaps; the fans then direct the air against the flaps to produce the lift and thrust.

J.G.M.

N72-10034# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany). Unternehmensbereich Flugzeuge.

PRELIMINARY TESTS AND PERFORMANCE OF ROLLING VERTICAL TAKEOFF AND LANDING OF THE VJ 101 C-X2 WITH IGNITED AFTERBURNERS [VORUNTERSUCHUNGEN UND DURCHFUEHRUNG VON ROLLENDEN SENKRECHTSTARTS UND -LANDUNGEN MIT DER VJ 101 C-X2 MIT GEZUENDETEN NACHBRENNERN]

O. Richarz, H. Heidrich, and V. Zeidler Bonn Bundeswehramt 1971 38 p In GERMAN; ENGLISH summary Sponsored by Bundesmin. der Verteidigung

(BMVg-FBWT-71-13) Avail: NTIS; Bundeswehramt, Bonn: 25 DM

A special takeoff and landing procedure, termed RVTOL (rolling vertical takeoff and landing), was developed for the VTOL aircraft VJ 101 C-X2. The RVTOL technique is believed to be an answer with this type of aircraft to the problems of recirculation, ground erosion, airframe thermal stress, and controllability. Almost complete independence from conventional ground equipment is claimed, due to the reliable operation of the three-channel flight control system.

ESRO

N72-10035# National Physical Lab., Teddington (England). Environmental Unit.

A NEW BASIS FOR AIRCRAFT NOISE RATING

D. W. Robinson Mar. 1971 23 p refs

(NPL-Aero-Ac-49) Avail: NTIS

Starting with the definition of noise pollution level, it is shown that the incremental value of this quantity due to the occurrence of an aircraft noise provides a logical basis for rating the noise. This measure has simple additive properties which permit the same definition to be extended to an arbitrary series of events, including the background noise and its fluctuations. By specifying reference values of certain parameters, a formula is evolved which is suitable for aircraft noise certification purposes; the relation of this measure to effective perceived noise level is discussed.

Author (ESRO)

N72-10036# Defense Documentation Center, Alexandria, Va. NOISE POLLUTION - AIRPLANE NOISE, VOLUME 1

Bibliography, Aug. 1947 - Dec. 1970

Jun. 1971 147 p refs 2 Vol.

(AD-724850; DDC-TAS-71-26-1) Avail: NTIS CSCL 20/1

The annotated bibliography is an unclassified compilation of references on airplane noise pollution in a series of bibliographies on environmental pollution. References deal primarily with effects of noise exposure on hearing, speech, communications and community/airport noise. Computer-generated indexes for corporate author-monitoring agency, subject, and title are included. requesting AD-722 910.

Author (GRA)

N72-10037# Naval Ship Research and Development Center, Washington, D.C. Aviation and Surface Effects Ratios.

THEORETICAL PERFORMANCE OF A PURE JET FLAP ROTOR AT HIGH ADVANCE RATIOS

Robert M. Williams and Charles L. Bernitt Dec. 1970 49 p refs

(Proj. WF32.421.202)

(AD-726706; TN-AL-189) Avail: NTIS CSCL 01/3

The theoretical performance of a jet flap rotor at advance ratios greater than 1.0 is examined. The rotor is four bladed with purely elliptical airfoils of fifteen percent thickness ratio. Each airfoil has two plenum chambers which supply air to slots located beneath the leading and trailing edges, respectively. The rotor operates in cruise at advance ratios greater than unity so that the retreating blade is immersed in reverse flow. The lift and moments are controlled by ejecting a jet sheet out of the trailing edge on the advancing side of the azimuth and both the leading and trailing edge on the retreating side of the azimuth. Standard blade element theory is used to calculate jet flap rotor performance thrust coefficients representative of actual full-scale rotor operation. It is shown that good performance can be obtained using the jet flap and that substantially better performance can be achieved using a circulation control airfoil.

Author (GRA)

N72-10038# National Transportation Safety Board, Washington, D.C. Bureau of Aviation Safety.

BRIEFS OF ACCIDENTS INVOLVING AMATEUR/HOME BUILT AIRCRAFT: US GENERAL AVIATION

Jun. 1971 44 p

(PB-201438; NTSB-AMM-71-2) Avail: NTIS CSCL 01B

The publication contains statistical, cause/factor and injury tables, accident rates and the briefs of accidents involving amateur built aircraft.

Author (GRA)

N72-10039# National Transportation Safety Board, Washington, D.C. Bureau of Aviation Safety.

BRIEFS OF ACCIDENTS INVOLVING WEATHER AS A CAUSE RELATED FACTOR: US GENERAL AVIATION, 1968

Jun. 1971 196 p

(PB-201437; NTSB-AMM-71-1) Avail: NTIS CSCL 01B

The publication contains statistical, cause/factor and injury tables, accident rates and the briefs of accidents involving weather.

Author (GRA)

N72-10040# Quality Assurance Directorate (Materials), London (England).

THE INFRA-RED ANALYSIS OF AIRCRAFT CABIN-GAS ATMOSPHERES

D. J. Bishop and J. K. Corbett Oct. 1970 31 p refs

(QAD-MATS-174) Avail: NTIS

The analysis of the air-bleed cabin gas produced by Olympus and Pegasus engines has been carried out by infra-red spectrometry. The method utilizes a conventional double beam recording infra-red spectrophotometer equipped with a pair of multireflection long path cells. The lower limits of detection of the various contaminants listed in the specification have been determined both individually and in conjunction with large amounts of other impurities. This method has also been extended to cover air-bleed cabin gas samples which have been taken from development engines in which malfunctions of the engine components have been simulated.

Author (ESRO)

N72-10041# National Transportation Safety Board, Washington, D.C. Bureau of Aviation Safety.

BRIEFS OF AIRCRAFT ACCIDENTS INVOLVING MISSING AIRCRAFT: US GENERAL AVIATION, 1968

Jun. 1971 92 p

(NTSB-AMM-71-4; PB-201440) Avail: NTIS CSCL 01B

The publication contains statistical cause/factor and injury tables, accident rates and the briefs of accidents involving missing aircraft.

Author (GRA)

N72-10042# Louisiana State Univ., Baton Rouge. Dept. of Chemical Engineering.

OPTIMIZATION STUDIES OF AIRCRAFT CONTROL

VARIABLES

Mario Calude, G. D. Whitehouse, and A. J. McPhate May 1971 144 p refs

(Contract F44620-68-C-0021; AF Proj. 7921; Proj. THEMIS)

(AD-725069; THEMIS-LSU-T-TR-45; AFOSR-71-1798TR) Avail: NTIS CSCL 01/3

The feasibility of using an adaptive linear mathematical model to represent a human operator subjected to the task of controlling an attacking fighter aircraft was investigated. The ability of the model to perform pursuit tracking tasks subject to random evader tactics was analyzed by the implementation of the model into a six-degree-of-freedom digital fire control simulation. For the model to approach reality in every flight regime, an adaptive procedure was incorporated into the simulation in every flight regime, and an adaptive procedure was incorporated into the simulation to adjust the variable gain and lead time parameters of the human model. The adaptive procedure which uses a six parameter optimization scheme similar to that developed by M. J. D. Powell achieves the desired pursuit tracking results in the most direct way. As a means of evaluating the simulated performance of the human operator when performing this task, the performance data of the attacking aircraft was subjected to a number of spectral analysis operations. These spectral operations compared the frequency content of the data obtained from the simulation to actual data obtained from combat flight maneuvers. For both sets of data the evaders performed the same identical tactics. Author (GRA)

N72-10043*# Boeing Co., Wichita, Kans.

STUDY AND DEVELOPMENT OF ACOUSTIC TREATMENT FOR JET ENGINE TAILPIPES

M. D. Nelson, L. L. Linscheid, B. A. Dinwiddie, III, and O. J. Hall, Jr. Washington NASA Nov. 1971 66 p refs

(Contract NAS1-9622)

(NASA-CR-1853; D3-8535) Avail: NTIS CSCL 01B

A study and development program was accomplished to attenuate turbine noise generated in the JT3D turbofan engine. Analytical studies were used to design an acoustic liner for the tailpipe. Engine ground tests defined the tailpipe environmental factors and laboratory tests were used to support the analytical studies. Furnace-brazed, stainless steel, perforated sheet acoustic liners were designed, fabricated, installed, and ground tested in the tailpipe of a JT3D engine. Test results showed the turbine tones were suppressed below the level of the jet exhaust for most far field polar angles.

Author

N72-10044# Honeywell, Inc., Minneapolis, Minn. Systems and Research Center.

INVESTIGATION OF DISPLAY REQUIREMENTS FOR HELICOPTER IFR MANUAL FORMATION FLIGHT UNDER VARIOUS OPERATIONAL AND ENVIRONMENTAL CONDITIONS Final Report, Aug. 1969 - Jun. 1970

Myrna L. Toivanen, Paul A. Anderson, and S. R. Hollingsworth Apr. 1971 199 p refs

(Contract N00014-66-C-0362; NR Proj. 213-054)

(AD-725209; JANAIR-700911; Rept-12543-FR6) Avail: NTIS CSCL 01/4

Systematic man-in-the-loop simulations were conducted to evaluate pilot/system performance in the manually controlled IFR SK/FF task for the UH-1 helicopter under various operational and environmental conditions. Interpreted within the constraints imposed upon and by the simulations, the empirical results indicated that leader heading, even when perturbed by lateral gusts, was an adequate system reference; 250-2000 feet were acceptable separation distances for fixed-formation maneuvers; there were no significant performance differences between the leader or follower frame of reference; the pursuit guidance technique was applicable to the rendezvous phase; display augmentation was not required during the rendezvous, but it reduced the difficulty of the control task and improved performance; the formation grouping concept was feasible from the standpoint of display/control considerations; and the trajectory-following and pursuit guidance control techniques were both suitable for providing control commands to the pilot for

formation grouping, although trajectory-following yielded better performance and pursuit guidance was easier to mechanize.

Author (GRA)

N72-10045*# National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.

AERODYNAMIC CHARACTERISTICS OF AN ALL-BODY HYPERSONIC AIRCRAFT CONFIGURATION AT MACH NUMBERS FROM 0.65 TO 10.6

Walter P. Nelms, Jr. and Charles L. Thomas Washington Nov. 1971 100 p refs

(NASA-TN-D-6577; A-4017) Avail: NTIS CSCL 01B

Aerodynamic characteristics of a model designed to represent an all body, hypersonic cruise aircraft are presented for Mach numbers from 0.65 to 10.6. The configuration had a delta planform with an elliptic cone forebody and an afterbody of elliptic cross section. Detailed effects of varying angle of attack (-2 to +15 deg), angle of sideslip (-2 to +8 deg), Mach number, and configuration buildup were considered. In addition, the effectiveness of horizontal tail, vertical tail, and canard stabilizing and control surfaces was investigated. The results indicate that all configurations were longitudinally stable near maximum lift drag ratio. The configurations with vertical tails were directionally stable at all angles of attack. Trim penalties were small at hypersonic speeds for a center of gravity location representative of the airplane, but because of the large rearward travel of the aerodynamic center, trim penalties were severe at transonic Mach numbers.

Author

N72-10046# Army Foreign Science and Technology Center, Charlottesville, Va.

HELICOPTER AERODYNAMICS

D. I. Bazov 14 May 1971 224 p refs Transl. into ENGLISH of the book "Aerodinamika Vertoletov" Moscow, Transport Publishing House, 1969 p 1-196 (Proj. T702301-2301)

(AD-726841; FSTC-HT-23-549-71; ACSI-J-9360) Avail: NTIS CSCL 01/1

The principles of helicopter flight, special characteristics of the main rotor and its function in autorotation axial and oblique flow, regimes of vertical and horizontal flight, climb and descent, takeoff and landing, balance, stability and control of the helicopter and their acting aerodynamic forces are presented.

Author (GRA)

N72-10047# Grumman Aerospace Corp., Bethpage, N.Y.

AN AUTOMATED PROCEDURE FOR THE OPTIMIZATION OF PRACTICAL AEROSPACE STRUCTURES. VOLUME 2: TECHNICAL PROGRAMMER'S MANUAL Final Report, 15 Jan. 1969 - 15 Aug. 1970

Walter J. Dwyer, Robert K. Emerton, and Irving V. Ojalvo Wright-Patterson AFB, Ohio AFFDL Apr. 1971 107 p (Contract F33615-69-C-1278)

(AD-725744; ADR-02-01-71-Vol-2; AFFDL-TR-70-118-vol-2) Avail: NTIS CSCL 01/3

The report documents the computer programs described in Volume I of this report entitled 'An Automated Procedure for the Optimization of Practical Aerospace Structures' (AD-726112). Both the main structural optimization program and the shell dynamics program are written in Fortran 4 language. This manual contains a description of the overlay structure, data set arrangement, and subroutines of both programs.

Author (GRA)

N72-10048# Cornell Aeronautical Lab., Inc., Buffalo, N.Y.

THE GENERATION OF A MILITARY SPECIFICATION FOR FLYING QUALITIES OF PILOTED V/STOL AIRCRAFT MIL-F-83300 Final Report, Apr. 1966 - Mar. 1971

David L. Key Wright-Patterson AFB, Ohio AFFDL Apr. 1971 41 p refs

(Contracts AF 33(615)-3736; F33615-70-C-1322; AF Proj. 6980C)

(AD-726746; CAL-BB-2925-F-1; AFFDL-TR-21-23) Avail: NTIS

CSCL 01/3

The document describes a four year effort which led to the adoption of a new military specification MIL-F-83300, 'Flying Qualities of Piloted V/STOL Aircraft', and the publication of a supporting document, 'Background Information and User Guide for MIL-F-83300, Military Specification - Flying Qualities of Piloted V/STOL Aircraft' (AFFDL-TR-70-88). Included in the report is an assessment of the status of V/STOL flying qualities research and recommendations for future work.

Author (GRA)

N72-10049# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT: SOUTHERN AIRWAYS, INCORPORATED, DOUGLAS DC-9-15, N92A, GULFPORT, MISSISSIPPI, 17 FEBRUARY 1971

1 Sep. 1971 22 p

(NTSB-AAR-71-14) Avail: NTIS

On February 17, 1971, DC-9-15 aircraft struck an electric transmission line static cable during a VOR approach to Runway 31 at the Gulfport, Mississippi, Municipal Airport. A successful missed approach was accomplished, and the aircraft landed at Gulfport. Of the seven passengers and four crew aboard the aircraft, the only reported injury was a passenger's scratched hand. The aircraft received substantial damage to the left main landing gear, left wing, left fuselage, and the left engine. There was no fire. The weather was a partial obscuration with visibility 3/4 mile in fog. The probable cause of this accident was inadequate monitoring of the approach. The captain was preoccupied with the prelanding checklist during the final approach, and the first officer, who was flying the aircraft, was devoting his attention to an attempt to establish visual contact with the runway in low visibility. These activities resulted in an improperly executed VOR/DME approach during which the aircraft descended below the minimum descent altitude before the crew acquired visual contact with the runway environment.

Author

N72-10050# East Central Florida Regional Planning Council, Winter Park.

METROPOLITAN AIRCRAFT NOISE ABATEMENT POLICY STUDY: CAPE KENNEDY REGIONAL AIRPORT, MELBOURNE, FLORIDA

Jun. 1971 134 p refs

(PB-201195; ECFRPC-71-2) Avail: NTIS CSCL 13B

The report is an analysis of the relationship between noise generated by aircraft operations and the use of affected land surrounding the airport in Melbourne, Florida. It includes a presentation of current land use information and the prospects for change. Proposals were developed to encourage and enable the local governments involved to achieve compatible development through cooperative intergovernmental measures: comprehensive planning, capital improvement programming, mapping, zoning, annexation, land acquisition. The ecological impact is considered in a separate section.

Author (GRA)

N72-10122# Army Aeromedical Research Lab., Fort Rucker, Ala. Aviation Center Team Study Group.

ENVIRONMENTAL EFFECTS ON ATTACK HELICOPTER CREW TASK PERFORMANCE IN THE NATO THEATER

Stanley C. Knapp, ed. May 1971 43 p ref

(AD-726949; USAARL-71-21) Avail: NTIS CSCL 06/19

The unique tasks, requirements and demands upon attack helicopter crews, and the effects of the environment upon the performance of these tasks are analyzed. Night operations under low ceilings, reduced visibility, high or low speeds, nap-of-the-earth flight profiles and a threat of sophisticated anti-aircraft weaponry is defined as the 'worst-credible-environment' for the NATO theater. In this environment, the attack helicopter and its crew will be expected to fly a large percentage of its missions and deliver its ordnance with a high degree of accuracy. Task performance is outlined in a detailed matrix. Collective tasks are grouped into functional task clusters. The effects of climatic conditions, the hostile threat, social and civil factors upon performance of these task clusters are discussed. The effects of

the machine/mission created environment are presented and include hypoxia, toxic products, temperature extremes, visual and optical problems, acoustics, vibration, and human factors.

Author (GRA)

N72-10127# Aerospace Medical Research Labs., Wright-Patterson AFB, Ohio.

CREW COMPARTMENT VIBRATION ENVIRONMENT IN THE B-52 AIRCRAFT DURING LOW-ALTITUDE, HIGH-SPEED FLIGHT Final Report, Aug. 1966 - Dec. 1970

Jerry D. Speakman and Justis F. Rose, Jr. Mar. 1971 208 p refs

(AF PROJ. 7231)

(AD-727023; AMRL-TR-71-12) Avail: NTIS CSCL 08/19

Measurements were made of the pilot station vibration environment experienced in the B-52 aircraft during low-altitude, high-speed flight. Data were obtained of the longitudinal, lateral and vertical linear accelerations and the roll axis angular velocities and accelerations. The terrain contour following flights at 500-900 feet above the flat to semi-mountainous regions of Louisiana and Arkansas were made at 350 knots true airspeed. Data analyses included probability density and distribution and the auto-power spectral density functions in addition to tests for stationarity, randomness and normality. The individual degree-of-freedom results are presented in graphical and tabular form and in general indicate that the pilot station vibration environment produced by the combination of gust response and maneuvering: (1) is stationary for up to 590 seconds; (2) is a random phenomena that does not satisfy the chi-square goodness-of-fit test for Gaussian distribution; (3) cannot be adequately simulated in the laboratory for human biomedical tolerance and/or psycho-physiological performance studies using only vertical axis motion; (4) is remarkably in agreement with those PSD's calculated for the lateral and vertical axes using an aircraft transfer function experimentally derived on another program and the Dryden gust input spectrum. Author (GRA)

N72-10171# Federal Aviation Administration, Washington, D.C.

AERONAUTICAL TELECOMMUNICATIONS IN SOUTHEAST ASIA: INDONESIA, LAOS, MALAYSIA AND THAILAND

1970 262 p

Avail: NTIS

Descriptions of existing airway operations systems, conclusions and recommendations, equipment requirements, proposed courses of action, and economic and financial factors in aeronautical telecommunications are presented and discussed for Indonesia, Laos, Malaysia, and Thailand. The background and regional aspects of the study including objectives, scope, and methodology are summarized. J.M.

N72-10173# National Aviation Facilities Experimental Center, Atlantic City, N.J.

INVESTIGATION OF AIRBORNE MARKER BEACON Final Report, Jun. 1970 - Sep. 1971

Louis A. Dvorsky Nov. 1971 98 p

(Proj. 341-004-03X)

(FAA-NA-71-29) Avail: NTIS

Ground and air tests of a flight inspection marker beacon receiving system were made to identify and correct variations in marker pattern measurement from time to time and from aircraft to aircraft. The tests were made with both the T-29 Convair and DC-3 aircraft. Based on the flight test results, new receiver calibration and antenna system ramp calibration procedures were devised. Author

N72-10184# National Physical Lab., Teddington (England). Aerodynamics Div.

POSSIBLE DEVELOPMENTS OF A WIND TUNNEL COMPUTER SYSTEM

R. J. Young Sep. 1970 9 p

(NPL-AERO-1326; ARC-32396; Comp-FM-218) Avail: NTIS

Ways for developing the computer system with a view to

providing multiple on-line facilities are explored. The function and applicability of available operating systems and hardware are discussed. The possibilities of a system using a sophisticated real-time executive program are compared with those of a system using a second computer. Author (ESRO)

N72-10232# Metropolitan Washington Council of Governments, D.C.

MARKETING ACCESS SERVICES: BALTIMORE-WASHINGTON REPORT NO. 1: IMMEDIATE AIRPORT ACCESS STUDY ACTION IMPROVEMENTS

1970 25 p Sponsored by Metropol. Washington Council of Govt.

(PB-200686; P-010) Avail: NTIS CSCL 05E

Short term airport access improvements in the Baltimore-Washington area, are studied with the design and implementation of a suitable access services brochure. Current access services at the region's airports and at nonregion airports; functional requirements for information dissemination; brochure contents; distribution possibilities; and financial and management aspects of brochure development, maintenance, and dissemination are considered. GRA

N72-10233# National Aviation Facilities Experimental Center, Atlantic City, N.J.

TEST AND EVALUATION OF A DAYTIME COCKPIT FOG SIMULATOR Final Report, Apr. 1969 - May 1971

Morris Ritter Nov. 1971 35 p refs

(Proj. 073-323-04X)

(FAA-NA-71-44; FAA-RD-71-82) Avail: NTIS

An evaluation was conducted to determine the suitability of a daytime cockpit fog simulator to accurately and realistically simulate Category II and Category III weather conditions to the pilot during flight approaches. Thirteen pilots, using a DC-7 aircraft, participated in the program. The fog simulator was evaluated during atmospheric meteorological visibilities ranging from 1.5 to over 12 miles. Technical data, as well as completed pilot questionnaires, comprised the data analyzed. Although the simulator shows merit insofar as projecting realism, a redesign of the unit is necessary to correct deficiencies in various optical, electronic, and mechanical areas. Author

N72-10245# Von Karman Inst. for Fluid Dynamics, Rhode Saint-Genese (Belgium).

TURBULENT JET FLOWS

1971 343 p refs

(VKI-LS-36) Avail: NTIS HC \$6.00/MF \$0.95

CONTENTS:

1. A REVIEW OF THEORETICAL AND EXPERIMENTAL WORK ON THE DEVELOPMENT OF TURBULENT JETS L. J. S. Bradbury (Surrey Univ.) 38 p refs

2. TURBULENCE SIMILARITY IN A PLANE JET IN A MOVING AIRSTREAM L. J. S. Bradbury (Surrey Univ.) 21 p refs

3. REMARKS ON TURBULENT FLOWS WITH FREE STREAM BOUNDARIES J. Mathieu 89 p refs

4. WALL JETS AND THEIR APPLICATION TO BOUNDARY LAYER CONTROL I. S. Gartshore 35 p refs

5. SELF-PRESERVING FLOWS I. S. Gartshore 26 p refs

6. HOT-WIRE MEASUREMENT TECHNIQUE: SOME BASIC PROBLEMS J. D. Vagt (Technische Univ., Berlin, West Germany) 53 p refs

7. TRANSMISSION OF LOW FREQUENCY JET PIPE SOUND THROUGH A NOZZLE FLOW J. E. FfowcsWilliams (Imp. Coll. of Sci. and Technol.) 8 p

8. JET NOISE AT VERY LOW AND VERY HIGH SPEED J. E. FfowcsWilliams (Imp. Coll. of Sci. and Technol.) 9 p refs

9. ON THE NOISE SOURCES OF THE UNSUPPRESSED HIGH SPEED JET K. A. Bishop, J. E. FfowcsWilliams, and W. Smith (Rolls-Royce, Ltd., Bristol, Engl.) 16 p refs

10. NUMERICAL METHODS FOR JETS FLOWS R. Borghi (ONERA) 24 p refs

11. LASER BEAM USAGE FOR OPTO-ELECTRONIC METHODS OF INVESTIGATING GASEOUS FLOWS H. J. Pfeifer (Inst. Franco-Allemand de Recherches, St. Louis, France) 21 p refs

N72-10252# Imperial Coll. of Science and Technology, London (England).

TRANSMISSION OF LOW FREQUENCY JET PIPE SOUND THROUGH A NOZZLE FLOW

J. E. FfowcsWilliams /In von Karman Inst. for Fluid Dyn. Turbulent Jet Flows 1971 8 p (jefw/69) Avail: NTIS HC \$6.00/MF \$0.95

The basic flow model is subsonic jet of velocity $V_{sub 2}$ formed by expanding a hot jet pipe flow of mean velocity $V_{sub 1}$ and static pressure $p_{sub 1}$ in a jet pipe of cross sectional area $A_{sub 1}$ through a nozzle down to the ambient pressure $p_{sub 0}$. The jet flows in the direction $+x$. Superimposed on this basic flow is a low frequency sound wave of pressure $p(+)$ incident from x less than 0. The meaning of the low frequency in this context is that the nozzle scale is much smaller than the wavelength in both the jet stream and the environment. The problem is to determine the unsteady conditions at the nozzle exit and the sound field radiated to the static homogeneous environment exterior to the jet. It is shown that the influence of the nozzle transmission properties on the velocity depends on the velocity of the aerodynamic sound; aerodynamic sources contained within the jet but positioned many wavelengths upstream of the nozzle generate sound depending on jet velocity in precisely the same way as if the sources were in direct communication with the nozzle exterior. G.G.

N72-10253# Imperial Coll. of Science and Technology, London (England).

JET NOISE AT VERY LOW AND VERY HIGH SPEED

J. E. FfowcsWilliams /In von Karman Inst. for Fluid Dyn. Turbulent Jet Flows 1971 9 p refs Avail: NTIS HC \$6.00/MF \$0.95

A description of the possible sources of sound that can be met in low Mach number jet flows, and their strength is given in terms of flow parameters. Considered is jet noise at very low speed where nozzle exit turbulence may be a major contributor. Lighthill's theory is briefly summarized and used to estimate the sound of jets at moderate speeds. It is shown that very reasonable estimates of the field can be achieved from a crude description of the turbulent flow without recourse to the more involved aspects of the quadrupole theory. Then the question of noise produced by combustion of excess fuel in the exhaust is examined according to Lighthill's theory. The theory is applied to high Mach number situations where it is argued that the role of both Mach waves and shock waves needs further study. Finally, estimates of the sources to be expected in a moderate speed jet issuing from a multitube suppressor are made and applied to the noise from a fully developed jet flow. Author

N72-10254# Rolls-Royce, Ltd., Bristol (England). Bristol Engine Div.

ON THE NOISE SOURCES OF THE UNSUPPRESSED HIGH SPEED JET

K. A. Bishop, J. E. FfowcsWilliams (Imperial Coll. of Sci. and Technol.), and W. Smith /In von Karman Inst. for Fluid Dyn. Turbulent Jet Flows 1971 17 p refs (ARC-32723; F.M.4211; N.730) Avail: NTIS HC \$6.00/MF \$0.95

An interpretation of jet noise theory and scale model experiments to highlight physical properties of jet noise sources at very high speed are presented. The principal noise sources are shown to be very large scale wave-like undulations of the jet

flow that travels downstream at supersonic speed for a distance of several jet diameters. These motions are relatively well ordered and are probably more akin to recognizable instabilities of a laminar flow than the confused small scale turbulence. A model of the noise generating motions as the instability products of a jet flow of low equivalent Reynolds number is formulated. This Reynolds number is based on an eddy viscosity and can be further reduced by artificially increasing the small scale turbulence level. This step stabilizes the flow and inhibits the formation of large scale noise producing eddies. Author

N72-10332# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

THE KFA (DEPARTMENT OF THE ATMOSPHERIC PHYSICS) AERIAL EXPEDITIONS 1 AND 2 FOR STUDY OF THE PECULIARITIES OF CONDITIONS OF THE BOUNDARY LAYER OF THE ATMOSPHERE OVER AN OASIS AND A SEMIARID REGION

Yu. V. Petrov 19 Mar. 1971 6 p Transl. into ENGLISH from Tr. Tashkent Univ. Nauch. (USSR) no. 34q, 1969 p 119-120 (Project AF PROJ. 682(E)) (AD-727635; FTD-HT-23-84-71; UR-0000-69-000-349) Avail: NTIS CSCL 04/1

An expedition was conducted during the periods 26 June through 23 July 1966 and 16-31 May 1967 by the Department of Physics of the Atmosphere of Tashkent University. The flights were made by a Yak-12M aircraft equipped with a meteorograph and other instruments from the Sergeli airport in the neighborhood of Chardara village at an altitude of 0.9-1.0 km in the standard atmosphere. Flights were made over the semiarid region at altitudes up to 2.5-3.0 km. The spatial distribution of zones of increased aircraft turbulence was determined; the maximum was at altitudes of 0.5-1.0 km. In this layer the accelerations attained 0.45 G in spring and 0.7 G in summer. Author (GRA)

N72-10361# Bay Area Air Pollution Control District, San Francisco, Calif.

REGIONAL AIRPORT SYSTEMS STUDY. ENVIRONMENTAL STUDIES: AVIATION EFFECT ON AIR QUALITY IN THE BAY REGION

Feb. 1971 169 p refs Sponsored in part by Dept. of Housing and Urban Develop. Avail: NTIS

The results of a study of air contaminants associated with aircraft operations in the San Francisco Bay area are presented. Oxidant, carbon monoxide, sulfur dioxide, particulate matter, and nitrogen dioxide contaminants from aircraft engine emissions at public and military airports are covered as well as fuel handling, jet fuel dumping, and ground vehicle emissions. Region-wide and local climatological features are discussed including inversion climatology, airflow regimes, and temperature and precipitation distributions. The impact of aviation activities on air quality at four airports (San Francisco, Oakland, Oakland-North, and San Jose) is discussed utilizing a hybrid diffusion model. J.M.

N72-10396# Intermountain Forest and Range Experiment Station, Missoula, Mont. Northern Forest Fire Lab.

AIRBORNE INFRARED FOREST FIRE DETECTION SYSTEM Final Report, Apr. 1962 - Dec. 1967

Ralph A. Wilson, Stanley N. Hirsch, Forrest H. Madden, and John B. Losensky May 1971 114 p refs (Contract OCD-OS-72-174; ARPA Order 636) (AD-726953; FSRP-INT-83) Avail: NTIS CSCL 02/6

The report outlines the basic requirements for an airborne infrared forest fire detection system and discusses the capability of the system to detect hot fire targets in natural forest backgrounds. Author (GRA)

N72-10401# Avco Corp., Wilmington, Mass. Systems Div. FLIGHT INSTRUMENT AND TELEMETRY RESPONSE AND ITS INVERSION

M. R. Weinberger Washington NASA Sep. 1971 260 p refs
(Contract NAS1-8541)

(NASA-CR-1788; AVSD-0283-70-CR) Avail: NTIS CSCL 01D

Mathematical models of rate gyros, servo accelerometers, pressure transducers, and telemetry systems were derived and their parameters were obtained from laboratory tests. Analog computer simulations were used extensively for verification of the validity for fast and large input signals. An optimal inversion method was derived to reconstruct input signals from noisy output signals and a computer program was prepared. Author

N72-10425# General Dynamics/Fort Worth, Tex.

DEVELOPMENT OF COMPOSITE TAPE LAYING PROCESS FOR ADVANCED FIBROUS REINFORCED COMPOSITE STRUCTURES Final Technical Report, Dec. 1966 - Jan. 1971

W. O. Sunafrank, W. H. Drebing, and H. L. Eaton Mar. 1971 421 p

(Contract F33615-67-C-1271; AF Proj. 872-7)

(AD-725765; AFML-TR-71-71; FTR-15) Avail: NTIS CSCL 13/9

The objective of the research was to develop and fabricate a numerically controlled prototype tape laying machine for performing layup operations required by airframe structural components of filament reinforced resin matrix composites. Mechanical functions of the machine as related to airframe component design requirements were investigated and defined. These included machine head variables of roller type, heat and pressure application, laying rates, tape feed mechanisms, shearing methods, disposal of cutoffs and tape specifications. In addition, compound contour requirements were considered. These included tilting vertical axis, pivot rollers, self-shaping rollers, and draping of flat layups to contour. It was determined that 75 percent of the airframe surfaces could be laid while using either the self-shaping roller or drape to shape approach, thereby eliminating the complexity factor of a 5-axis tilting head and the association of high production costs. A major problem has been tolerance control of fiber placement on the carrier. The contract has provided an improved manufacturing technology through development of an NC tape laying machine that will apply fiber reinforced tape up to 3 inches wide, to a part along a preprogrammed path. Author (GRA)

N72-10489# Naval Air Development Center, Johnsville, Pa. Aero Materials Div.

DEVELOPMENT OF A STRESS CRACK RESISTANT URETHANE SEALANT FOR HEATED AREAS OF AIRCRAFT SURFACES

A. Stander Jul. 1971 15 p refs

(Project WF51.543.202)

(AD-727592; NADC-MA-7139) Avail: NTIS CSCL 11/1

A sprayable urethane sealant, AMD-P-28A was developed for protection of exterior fastener areas. This sealant in laboratory testing does not crack around fastener heads during -60F cyclic fatigue loading (1,000-11,000 lbs.) even after a heating of 20 hours at 280F plus one hour at 325F, which simulates the frictional heating of F14A aircraft during a single PAR cycle.

Author (GRA)

N72-10501# Louisiana State Univ., Baton Rouge. Coll. of Engineering.

SPECTRAL ANALYSIS OF TRANSIENT DATA WITH APPLICATION TO AUTO-PILOT PARAMETER STUDIES

Raymond Speeg, G. D. Whitehouse, and A. J. McPhate May 1971 112 p refs

(Contract F44620-68-C-0021; AF Proj. 7921; Proj. Themis)

(AD-725088; THEMIS-LSU-T-TR-46; AFOSR-71-1797TR) Avail: NTIS CSCL 12/1

The objective of this work was to determine, through a frequency analysis approach, an appropriate range of values for the parameters which could be used to provide for an effective auto-pilot coupler transfer function. The power spectral density function for random data, describing the general frequency

composition of the data in terms of the density of its mean square value was used in this analysis. Spectral plots of data generated by a digital simulation were compared to those of an actual flight test case used as a reference to determine when the appropriate range has been found. In the development a spectral analysis program was written that incorporates the Cooley-Tukey fast Fourier transfer, allowing the conversion of the data sets from the time domain to the frequency domain. This resulted in a range of values for the parameters of gain and lead in two channels of a model of the human pilot operator in an attacker-evader simulation. Author (GRA)

N72-10539*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

TARGET CONTRAST CONSIDERATIONS IN MILLIMETER WAVE RADIOMETRY FOR AIRBORNE NAVIGATION

A. Mayer Aug. 1971 73 p refs

(NASA-TM-X-62082) Avail: NTIS CSCL 17G

Target signal requirements for aircraft navigation systems that use radiometric receivers which map thermally emitted power radiated by terrain or power radiated by ground-based beacons are discussed. For selected millimeter wavelength bands, microwaves suffer relatively little degradation by absorption or scattering on passage through the atmosphere, despite extreme weather variations. Interest centers on 8-millimeter waves because of component availability, portability (small size), high image resolution, and all-weather capability at this wavelength. The idea of radiometric airborne navigation is introduced. Elements of radiometry, terrain radiation, and atmospheric transmission characteristics are reviewed. Data pertaining to these elements at 8 mm wavelength are collected. Calculation of radiometric contrasts is discussed for some simple models of terrain targets. Author

N72-10543# Lincoln Lab., Mass. Inst. of Tech., Lexington.

AIR TRAFFIC CONTROL Quarterly Technical Summary Report, 1 Feb. - 30 Apr. 1971

Herbert G. Weiss 15 May 1971 15 p refs

(Contract F19628-70-C-0230; AF Proj. 649L)

(AD-725743; ESD-TR-71-146) Avail: NTIS CSCL 17/7

The report discusses the activities under way in Division 4 that are funded mainly by the Air Force. The progress on two other ATC tasks, namely, the preparation of a Technical Development Plan for the Discrete Address Beacon System for the FAA OSEM and studies relating to Fourth Generation ATC System Concepts for the DOT transportation Systems Center, are reported separately. A highlight of this quarter was the successful conclusion of the testing phase of a laser warning system for Logan Airport. Author (GRA)

N72-10589# National Physical Lab., Teddington (England). Acoustics Section.

INDEX OF NPL ACOUSTICS PUBLICATIONS, 1960 - 1970

D. W. Robinson, comp. Mar. 1971 39 p refs

(NPL-Aero-Ac-47) Avail: NTIS

This bibliography on acoustics comprises reports, separate publications, papers in scientific journals and contributions to published symposia. The works are listed in chronological order and are referred to in the subject index and author index by means of serial numbers. Author (ESRO)

N72-10824*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

GAS TURBINE ENGINE FUEL CONTROL Patent Application Harold C. Gold, inventor (to NASA) Filed 28 May 1971 29 p

(NASA-Case-LEW-11187-1; US-Patent-Appl-SN-147922) Avail: NTIS CSCL 21E

A variable-orifice system that is responsive to compressor inlet pressure and temperature, compressor discharge pressure,

and rotational speed of a gas turbine engine is incorporated into a hydraulic circuit. The circuit includes a zero gradient pump driven at a speed proportional to the speed of the engine. The resulting system provides control of fuel rate for starting, steady running, acceleration, and deceleration under varying altitudes and flight speeds. NASA

N72-10828# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany). Unternehmungsbereich Flugzeuge.
BASIC INVESTIGATIONS OF RECIRCULATION WITH CONFIGURATIONS CONSISTING OF 1 TO 6 JETS [GRUNDSATZUNTERSUCHUNGEN ZUR REZIRKULATION AN 1- BIS 6-STRAHLANORDNUNGEN]
F. Aulehla, W. Eder, and V. Zeidler Bonn Bundeswehramt 1971 60 p In GERMAN; ENGLISH summary Sponsored by Bundesmin. fuer Verteidigung (BMVG-FBWT-71-12) Avail: NTIS; Bundeswehramt, Bonn: 25 DM

Analyses of the fundamental factors were performed and model tests were carried out to determine the mechanism of recirculation in jet powered V/STOL aircraft and to devise methods for preventing or reducing the occurrence of thrust loss, engine surge and flame-out for differing engine configurations. Preliminary studies of the correlation between model measurements and full-size operation, and flow effects from forward, aft and the sides on a lift thrust configuration, are separated. ESRO

N72-10830# Mitre Corp., McLean, Va.
A SURVEY OF PROPULSION SYSTEMS FOR LOW EMISSION URBAN VEHICLES
W. E. Fraize and R. K. Lay Sep. 1970 116 p refs Sponsored by DOT (Contract F19628-68-C-0365) (PB-200144; UMTA-TRD-52-70-2; M70-45) Avail: NTIS CSCL 13F

An overview is presented of low and negligible emission urban vehicle technology. Propulsion systems suitable for low emission urban vehicles are described. The state-of-the-art of low emission systems is surveyed by direct contact with active development efforts in industry; the more promising areas for future development are reviewed. Exhaust emissions for fossil-fueled heat engines are summarized. A computer program was developed to demonstrate the effect of the various route cycle and vehicle parameters on required power and vehicle speed; results are presented for a typical small urban bus.

Author (GRA)

N72-10957# Air Force Systems Command, Wright-Patterson AFB, Ohio. Materials Lab.
AN APPLICATION OF FRACTURE CONCEPTS TO THE PREDICTION OF CRITICAL LENGTH OF FATIGUE CRACKS. PART 2: A REVIEW OF PERTINENT ASPECTS OF FRACTURE (THEORETICAL AND ANALYTICAL ASPECTS OF FATIGUE OF METALS) M. S. Thesis - Ohio State Univ., 1970 Technical Report, Jun. 1969 - Jun. 1970 Sidney O. Davis Apr. 1971 116 p refs (AF Proj. 7351) (AD-725028; AFML-TR-70-202-PT-2) Avail: NTIS CSCL 20/11

This part of the report (Volume 2) presents a technical documentary historical review of pertinent theoretical and analytical aspects of fatigue failure and its relationship to fracture mechanics. The review covers the period 1829 to 1970. Fatigue failure, i.e., fracture without gross plastic deformation under repeated application of stress below the proportional limit, has been recognized for at least 138 years. Despite numerous investigations on the subject, there is no available theory for correlating the many variables affecting fatigue failure and for successfully predicting failure. The application of linear elastic fracture mechanics and the thermodynamics of fracture to the crack propagation facet of fatigue is proposed as an approach to the prediction of critical

lengths of stable fatigue cracking and unstable fracturing before failure. Author (GRA)

N72-10984*# Lockheed-California Co., Burbank. Science and Engineering Branch.
STUDY OF AIRCRAFT IN INTRAURBAN TRANSPORTATION SYSTEMS, VOLUME 1 Final Report, Jun. 1970 - May 1971
E. G. Stout, P. H. Kesling, H. C. Matteson, D. E. Sherwood, W. R. Tuck, Jr., and L. A. Vaughn Jun. 1971 173 p 4 Vol. (Contract NAS2-59889) (NASA-CR-114340) Avail: NTIS CSCL 05C

An analysis of an effective short range, high density computer transportation system for intraurban systems is presented. The seven county Detroit, Michigan, metropolitan area, was chosen as the scenario for the analysis. The study consisted of an analysis and forecast of the Detroit market through 1985, a parametric analysis of appropriate short haul aircraft concepts and associated ground systems, and a preliminary overall economic analysis of a simplified total system designed to evaluate the candidate vehicles and select the most promising VTOL and STOL aircraft. Data are also included on the impact of advanced technology on the system, the sensitivity of mission performance to changes in aircraft characteristics and system operations, and identification of key problem areas that may be improved by additional research. The approach, logic, and computer models used are adaptable to other intraurban or interurban areas. E.H.W.

N72-10985*# Lockheed-California Co., Burbank. Science and Engineering Branch.
STUDY OF AIRCRAFT IN INTRAURBAN TRANSPORTATION SYSTEMS, VOLUME 2 Final Report, Jun. 1970 - May 1971
E. G. Stout, P. H. Kesling, H. C. Matteson, D. E. Sherwood, W. R. Tuck, Jr., and L. A. Vaughn Jun. 1971 198 p 4 Vol. (Contract NAS2-59889) (NASA-CR-114341) Avail: NTIS CSCL 05C

A cost analysis of the major items of direct operating costs in an intraurban aircraft transportation system are presented. The results are given in the form of tables and graphs. E.H.W.

N72-10986*# Lockheed-California Co., Burbank. Science and Engineering Branch.
STUDY OF AIRCRAFT IN INTRAURBAN TRANSPORTATION SYSTEMS, VOLUME 3 Final Report, Jun. 1970 - May 1971
E. G. Stout, P. H. Kesling, D. E. Matteson, D. E. Sherwood, W. R. Tuck, Jr., and L. A. Vaughn Jun. 1971 209 p refs 4 Vol. (Contract NAS2-59889) (NASA-CR-114342) Avail: NTIS CSCL 05C

An investigation of three aircraft concepts, deflected slipstream STOL, helicopter VTOL, and fixed wing STOL, is presented. An attempt was made to determine the best concept for the intraurban transportation system. Desirability of the concept was based on ease of maintenance, development timing, reliability, operating costs, and the noise produced. Indications are that the deflected slipstream STOL is best suited for intraurban transportation. Tables and graphs are included. E.H.W.

N72-10987*# Lockheed-California Co., Burbank. Science and Engineering Div.
STUDY OF AIRCRAFT IN INTRAURBAN TRANSPORTATION SYSTEMS, VOLUME 4: APPENDIX Final Report, Jun. 1970 - May 1971
E. G. Stout, P. H. Kesling, H. C. Matteson, D. E. Sherwood, W. R. Tuck, Jr., and L. A. Vaughn Jun. 1971 273 p 4 Vol. (Contract NAS2-59889) (NASA-CR-114343) Avail: NTIS CSCL 05C

An appendix of the supporting data leading to conclusions and recommendations for an effective intraurban transportation

system from volumes 1, 2, and 3 is presented. The data are given in tables and graphs. E.H.W.

N72-10992# Institute for Defense Analyses, Arlington, Va.
COST GROWTH AND PRODUCTIVITY IN EUROPEAN AEROSPACE DEVELOPMENT PROGRAMS
 Rolf Piekarz and Susan McIntosh Dec. 1970 74 p refs
 (Contract DAHC15-67-C-0011)
 (AD-725478; RP-P-684; IDA/HQ-71-12286; T-73) Avail: NTIS CSCL 05/3

The paper reports on an exploratory study to obtain tentative estimates about two aspects of European aerospace systems development costs in comparison to the U.S. experience: the percentage cost growth occurring during the program, and the absolute costs in dollar terms of foreign projects relative to costs of comparable U.S. projects. Eight major European commercial and military aerospace programs were investigated during the 1962-1969 period, and the cost outcomes of these programs were compared to the overall U.S. experience. The tentative findings suggest that proposals to adopt foreign organization, such as nationalization, to improve U.S. military technology development performance are unlikely to solve U.S. difficulties, and that applying U.S. cost models to evaluate foreign military RDT and E efforts is not recommended for estimating the outputs and size of foreign programs. GRA

N72-10998# National Aerospace Lab., Amsterdam (Netherlands).
COMPARISON BETWEEN DISCRETE AND CONTINUOUS MODELS FOR VERTICAL GUSTS
 J. B. DeJonge Feb. 1971 68 p
 (NLR-TR-71025U) Avail: NTIS

A number of currently existing gust load models, based either on a discrete gust concept or a continuous gust concept, have been analyzed and compared. Calculations made for three different aircraft types indicated that load spectra based on either of the two model-types show relatively small differences. How flexibility effects may be accounted for in conjunction with a discrete gust model, using a technique based on the continuous gust concept, is described. Author

N72-10999# Office National d'Etudes et de Recherches Aérospatiales, Paris (France).
SOME RESULTS ON GUST ALLEVIATION
 Gabriel Coupry 1971 12 p refs Presented at the R. Ae. S. Intern. Conf. on Atmospheric Turbulence, London, 18-21 May 1971
 (ONERA-TP-925) Avail: NTIS

The mathematical search for a linear functional law which defines longitudinal response of delta wing aircraft to turbulence is discussed. Turbulence is measured in real time, aboard the aircraft with the help of information given by vanes, gyrometers, and accelerometers. The results indicate that with the help of the Wiener and Leguerre methods, gust alleviation can be provided without change to the flight mechanics of the aircraft. An analog computer analysis of the method and flight test results is also given. Author

N72-11001# Deutsche Gesellschaft fuer Luft- und Raumfahrt, Stuttgart (West Germany).
ROTOR FLOW AND FLIGHT MECHANICS OF HINGELESS ROTORS [ROTORDURCHSTROMUNG UND FLUGMECHANIK DES GELENKLOSEN ROTORS]
 Jun. 1971 284 p refs In GERMAN; ENGLISH summary Proc. of the DGLR Comm. on Helicopters and Am. Helicopter Soc. Meeting, Ottobrunn, West Ger., 9 Dec. 1970
 (DLR-MITT-71-12) Avail: NTIS; ZLDI Munich: 59.65 DM

CONTENTS:

1. SURVEY OF DIFFERENT MODELS FOR COMPUTING THE FLOW OF A LIFTING ROTOR A. Kussmann (DVL, Stuttgart) p 7-75 refs

2. INFLUENCE OF DIFFERENT PARAMETERS (LIKE JET CONTRACTION, VORTEX CORE DIAMETER) UPON ROTOR DOWNWASH CALCULATION. APPLICATION TO THE CASE OF AN AUXILIARY WING J. W. Fuhr (DFVLR, Stuttgart) p 76-107 refs

3. INFLUENCE OF THE WAKE GEOMETRY ON THE VELOCITY AND LOAD DISTRIBUTION OF VTOL PROPELLERS G. Schultzeiss (Ver. Flugtech. Werke-Fokker G.m.b.H., Munich) p 108-129 refs

4. LINEAR AERODYNAMIC ROTOR THEORY S. Wagner, K. Gehr, and W. Grädl (Messerschmitt-Boelkow-Blohm G.m.b.H., Ottobrunn, West Ger.) p 130-174 refs

5. RECOVERY ROTOR WITH VARIABLE BLADE LENGTH W. Benner and G. Engel (Dornier-Werke G.m.b.H., Friedrichshafen, West Ger.) p 175-209 refs

6. THEORETICAL CONSIDERATIONS OF A SPRING HINGED ROTOR OF VARIABLE FLAPPING STIFFNESS AND CONSTANT PHASE SHIFT W. Kugler (Dornier-Werke G.m.b.H., Friedrichshafen, West Ger.) p 210-240 refs

7. THE STABILITY- AND CONTROL BEHAVIOR OF THE HINGELESS BOELKOW ROTOR SYSTEM H. Huber (Messerschmitt-Boelkow-Blohm G.m.b.H., Ottobrunn, West Ger.) p 241-282 refs

N72-11002# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Stuttgart (West Germany).

SURVEY OF DIFFERENT MODELS FOR COMPUTING THE FLOW OF A LIFTING ROTOR [UEBERBLICK UEBER VERSCHIEDENE MODELLE ZUR BERECHNUNG DER ROTORDURCHSTROMUNG]

Alfred Kussmann In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 7-75 refs In GERMAN; ENGLISH summary

Avail: NTIS; ZLDI Munich: 59.65 DM

Several methods for computing the induced velocity field and blade loads of a lifting rotor are given, especially in the forward flight regime, with particular consideration of the different wake model configurations. Author (ESRO)

N72-11003# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Stuttgart (West Germany).

INFLUENCE OF DIFFERENT PARAMETERS (LIKE JET CONTRACTION, VORTEX CORE DIAMETER) UPON ROTOR DOWNWASH CALCULATION. APPLICATION TO THE CASE OF AN AUXILIARY WING [EINFLUSS VERSCHIEDENER PARAMETER (WIE STRAHLEKONTRAKTION, WIRBELKERN DURCHMESSER USW.) AUF DIE ROTORABWINDBERECHNUNG. ANWENDUNG AM BEISPIEL EINES ENTLASTUNGSFLUEGELS]

J. W. Fuhr In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 76-107 refs In GERMAN; ENGLISH summary

Avail: NTIS; ZLDI Munich: 59.65 DM

Some changes in the geometry of a rotor wake model with helical vortex lines were introduced in order to study the influence upon rotor downwash velocity distribution by parameter variation. The parameters varied were: diameter of near field vortices, flapping, rotor speed, and contraction of rotor radius. The velocity distribution at an infinite span wing, placed in the downwash flow, is calculated, and the interaction between wing and rotor is determined by computing the velocity distribution at the rotor. ESRO

N72-11004# Vereinigte Flugtechnische Werke-Fokker G.m.b.H., Munich (West Germany).

INFLUENCE OF THE WAKE GEOMETRY ON THE VELOCITY

**AND LOAD DISTRIBUTION OF VTOL PROPELLERS
[EINFLUSS DER NACHLAUFGEOMETRIE AUF DIE
GESCHWINDIGKEITS- UND LASTVERTEILUNG VON
VTOL-PROPELLERN]**

G. Schultheiss /In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 108-129 refs In GERMAN

Avail: NTIS; ZLDI Munich: 59.65 DM

To determine the velocity and load distribution of VTOL propellers, a method was employed with discrete slipstream vortex stress. In using this method, the assumption of the length of the wake is a difficulty, this having repercussions on the exactitude of the relationships in the propeller plane. As the length of the wake determined the computing time, two examples were taken for upright and fast flight with a known three-bladed propeller. Induced angle of incidence, circulation distribution, thrust distribution, and the distribution of the ratios of thrust and power coefficients are compared with the results obtained from the Goldstein method. ESRO

N72-11005# Messerschmitt-Boelkow-Blohm G.m.b.H., Ottobrunn (West Germany).

LINEAR AERODYNAMIC ROTOR THEORY [ZUR LINEAREN AERODYNAMISCHEN ROTORTHEORIE]

S. Wagner, K. Gehr, and W. Gradl /In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 130-174 refs In GERMAN

Avail: NTIS; ZLDI Munich: 59.65 DM

The mathematical models of a few known linear aerodynamic rotor theories and their basic physical assumptions are discussed. The principles and vortex models of an aerodynamic lifting surface and lift line theories for helicopter rotors are examined. The computing effort and obtainable accuracy for those theories which can be treated numerically are compared. Theoretical and practical thrust distribution generally correspond, and clearly show the advantages and disadvantages of the applied vortex models. It is shown that improvements in physical characteristics are easily obtained in the numerical treatment of a theory. ESRO

N72-11007# Dornier-Werke G.m.b.H., Friedrichshafen (West Germany).

THEORETICAL CONSIDERATIONS OF A SPRING, HINGED ROTOR OF VARIABLE FLAPPING STIFFNESS AND CONSTANT PHASE SHIFT [THEORETISCHE BETRACHTUNGEN UEBER EINEN FEDERGELENKSROTOR VARIABLE SCHLAGSTEIFIGKEIT UND KONSTANTER PHASENVERSCHIEBUNG]

W. Kugler /In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 210-240 refs In GERMAN

Avail: NTIS; ZLDI Munich: 59.65 DM

A rotor system with elastically attached blades in theoretically investigated for varying the flight mechanical properties while retaining constant phase shift for cyclic control. This result may be obtained if the flapping stiffness of the rotor can be reduced to relatively small values in flight when the phase shift between vibration excitation and action is changed. For good controllability of a helicopter, the obtainable moment, for a stick deviation in a certain direction, should work about the center of gravity in the same or nearly the same direction. Investigations involving the use of many parameters to obtain constant phase shift with a rotor model, and with a projected Dornier rotor system, are reported. ESRO

N72-11008# Messerschmitt-Boelkow-Blohm G.m.b.H., Ottobrunn (West Germany).

THE STABILITY- AND CONTROL BEHAVIOR OF THE

HINGELESS BOELKOW ROTOR SYSTEM [DAS STABILITÄTS- UND STEUERUNGSVERHALTEN DES GELENKLOSEN ROTORS SYSTEM BOELKOW]

H. Huber /In DGLR Rotor Flow and Flight Mech. of Hingeless Rotors Jun. 1971 p 241-282 refs In GERMAN

Avail: NTIS; ZLDI Munich: 59.65 DM

The controllability, vibration damping, and static and dynamic stability of helicopters with hingeless rotors are examined. The feedback effects resulting from the special construction of the blades are described. In addition to elastic feedback effects based on the direct flapping angle feedback, torsional coupling effects are explained, appearing when the center of gravity and the aerodynamic center of the blade profile are shifted. The results of parametric studies, showing the influence of such blade-integrated feedback systems on control and stability characteristics of the hingeless rotor, are given, and the obtainable variation in flight-mechanical properties of rotors is shown. Tests with the BO-105 helicopter verify the treatment developed. ESRO

N72-11010# Lockheed-Georgia Co., Marietta.

MATHEMATICAL MODEL FOR TWO-DIMENSIONAL MULTI-COMPONENT AIRFOILS IN VISCOUS FLOW

W. A. Stevens, S. H. Goradia, and J. A. Braden Jul. 1971 167 p Supplement to NASA-CR-1843 (Contract NAS1-9143)

(NASA-CR-1843) Avail: NTIS CSCL 20D

Appendices on customer utilization of card images and the program listing as used on a CDC 6600 computer are presented. N.E.N.

N72-11011# National Physical Lab., Teddington (England). Aerodynamics Div.

THE VORTEX DRAG OF A SWEEPED WING WITH PART-SPAN FLAPS

H. C. Garner Sep. 1970 22 p refs

(NPL-AERO-1324; ARC-32395; Perf-2945) Avail: NTIS

Two theoretical methods of calculating the vortex drag factor from a prescribed spanwise loading and a novel third method, on the reverse-flow principle without a definitive spanwise loading, are applied to an untapered swept wing with symmetrically deflected outboard flaps. Results are consistent within $\pm 1/2$. The third method is used to study the large influence of flap span and chord. Author (ESRO)

N72-11012# National Physical Lab., Teddington (England). Aerodynamics Div.

CONVERGENCE OF CURRENT ROUTINES FOR EVALUATING DOWNWASH AT A LIFTING SURFACE

Doris E. Lehrian and H. C. Garner Sep. 1970 25 p refs

(NPL-AERO-Note-1095; ARC-32397) Avail: NTIS

Subsonic lifting-surface methods are used, with increasing numbers of spanwise integration points, to calculate downwash at the center line of rectangular wings with elliptic spanwise loading; simplified formulae are derived. Each method has its pattern of convergence, expressible as a single curve for arbitrary aspect ratio and chordwise position. Given a leading-edge singularity, high aspect ratio and leading-edge proximity combine to worsen the rate of convergence. Author (ESRO)

N72-11015# Royal Aircraft Establishment, Farnborough (England). Structures Dept.

SONIC BANG MEASUREMENTS DURING EXERCISE SUMMER SKY

D. R. B. Webb, F. L. Hunt, and R. J. Pallant London Aeron. Res. Council 1971 17 p
(ARC-R/M-3659; RAE-TR-87313; ARC-30184) Avail: NTIS; HMSO: 48 p; PHI: \$2.15

During July 1967, a series of supersonic flights were made over three areas in southern England under the code name exercise summer sky. The object was to observe public reaction to sonic bangs, in order to build up some information of the consequences of overflying parts of the country with supersonic transport aircraft. The RAE was asked to participate by measuring the sonic bang pressure waveforms at selected points in each of the three areas. One of the selected points in each area was in the nominal focus area of the flight paths, and for this purpose a ship was used as a monitoring station because the flight paths were arranged so that the focus areas occurred at sea. The recorded waveforms are shown and discussed, together with details of the aircraft tracks and relevant meteorological conditions. Author (ESRO)

N72-11017# Aeronautical Research Associates of Princeton, Inc., N.J.

ON THE AERODYNAMIC FORCES OF OSCILLATING TWO DIMENSIONAL LIFTING SURFACES Final Report
John E. Yates and John C. Houbolt Dec. 1970 53 p refs
(Contract AF 49(638)-1640; AF Proj. 9782-01)
(AD-726132; ARAP-156; AFOSR-TR-71-1079) Avail: NTIS CSCL 10/1

The lift on a two-dimensional airfoil that oscillates in translation and pitch and is subject to a sinusoidal gust is calculated. The high frequency asymptotic behavior of the lift due to motion and gust is derived in the case of incompressible and compressible flow. The magnitude of the lift is asymptotically smaller in all cases when compressibility is considered.

Author (GRA)

N72-11018* National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.
VARIABLE GEOMETRY ROTOR SYSTEM Patent
John F. Ward, inventor (to NASA) Issued 13 Jul. 1971 5 p
Filed 28 Aug. 1969

(NASA-Case-LAR-10557; US-Patent-3,592,559;
US-Patent-Appl-SN-853746; US-Patent-Class-416-121;
US-Patent-Class-416-115; US-Patent-Class-416-127;
US-Patent-Class-416-130; US-Patent-Class-416-149;
US-Patent-Class-416-200) Avail: US Patent Office CSCL 01C

The rotor system described is designed to control the nonuniform wake shed from a given rotor blade impinging upon the other blades of the rotor system. The rotor system utilizes blade sets which are of a different diameter than another blade set in the system. The azimuth spacing between the blade sets can be varied while the aircraft is in flight. The vertical spacing between the blade sets can also be changed. A mechanism is provided for collective pitch control of the blade sets. The planform of blade sets, as well as the configuration of their tips, are varied. Official Gazette of the U.S. Patent Office

N72-11019# Federal Aviation Administration, Oklahoma City, Okla.

SIXTH ANNUAL INTERNATIONAL AVIATION MAINTENANCE SYMPOSIUM. THE AVIATION MAINTENANCE ENVIRONMENT IN THE 1970'S

1970 311 p refs Symp. held at Oklahoma City, Okla., 8-10 Dec. 1970
Avail: NTIS HC \$6.00/MF \$0.95

CONTENTS:

1. COMPUTER APPLICATION STRATEGY FOR CONTROL OF AIRLINE MAINTENANCE IN THE SEVENTIES J. P. Burke, J. P. DiBella, and J. B. Sabel (Eastern Air Lines, Inc., Miami, Fla.) 16 p

2. IMPROVING THE READABILITY OF MAINTENANCE MANUALS W. Jablonski (Boeing Co., Morton, Pa.) 34 p

3. HARNESSING THE DIGITAL COMPUTER FOR AIRCRAFT MAINTENANCE R. F. Cook (LTV Aerospace Corp., Dallas, Tex.) 12 p

4. FACILITIES, EQUIPMENT AND TOOLS TO SUPPORT WIDE BODIED AIRPLANE MAINTENANCE IN THE SEVENTIES M. Doyle (Boeing Co., Seattle, Wash.) 27 p

5. REMANUFACTURING OF JET ENGINE COMPONENTS EMPLOYING BRAZING TECHNIQUES R. L. Peaslee (Wall Colmonoy Corp., Detroit, Mich.) 10 p

6. NONDESTRUCTIVE INSPECTION: AN AIRCRAFT MAINTENANCE TOOL OF THE SEVENTIES E. C. Mayes (Automation Ind., Inc., Danbury, Conn.) 5 p

7. OPERATING LOGIC: NEW DATA AND TRAINING CONCEPT DEVELOPMENTS OF THE APOLLO PROGRAM J. T. Weggoner (GE Co., Houston, Tex.) 29 p ref

8. MAINTENANCE FAULT ISOLATION IN THE SEVENTIES H. W. Adams and H. Bayer (Douglas Aircraft Co., Inc., Long Beach, Calif.) 8 p

9. STREAMLINED L-1011 FAULT ISOLATION TECHNIQUES W. W. Watkins (Lockheed-Calif. Co., Burbank) 19 p

10. AN APPLICATION OF MODERN MAINTENANCE CONCEPTS AND SAFETY ANALYSIS TO THE MULTINATIONAL CERTIFICATION OF A SUPERSONIC AIRCRAFT J. Haas (Soc. Natl. Indust. Aeronautique, Paris (France)). 24 p

11. MODULAR DESIGN CONCEPT IMPROVES JET ENGINE MAINTAINABILITY G. P. Adamson (Pratt and Whitney Aircraft, East Hartford, Conn.) 32 p

12. ACCESSIBILITY: THE KEY TO GOOD POWERPLANT MAINTAINABILITY R. W. Hevener (GE Co., Cincinnati, Ohio) 16 p refs

13. MAINTAINING THE BH 125 IN THE SEVENTIES I. F. Keith (Beechcraft-Hawker Corp., London (England)) 20 p

14. THE GENERAL AVIATION MAINTENANCE OUTLOOK FOR THE SEVENTIES S. J. Green (Gen. Aviation Manufacturers Assoc., Wash., D.C.) 6 p

15. PROJECTED MAINTAINABILITY ADVANTAGES OF SOLID STATE ELECTRICAL POWER MANAGEMENT AND SOLID STATE CONTACTLESS SWITCHING SYSTEMS T. S. Miller (LTV Aerospace Corp., Dallas, Tex.) 31 p refs

16. PACIFIC AIRMOTIVE CORPORATION ACCESSORY RELIABILITY PROGRAM D. Snyder (Pacific Airmotive Corp., Burbank, Calif.) 5 p

N72-11020# Eastern Air Lines, Inc., Miami, Fla.
COMPUTER APPLICATION STRATEGY FOR CONTROL OF AIRLINE MAINTENANCE IN THE SEVENTIES

J. P. Burke, J. P. DiBella, and J. B. Sabel /in FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 16 p

Avail: NTIS HC \$6.00/MF \$0.95

The requirements and benefits of applying computer techniques to aircraft maintenance operations are discussed. It is determined that the aircraft maintenance computer applications strategy for the 1970 decade should be as follows: (1) develop and implement control, rather than information systems, (2) focus control systems at the lowest effective level where maintenance events are taking place, and (3) integrate management information systems for policy control by evolution rather than by superimposing them on the environment. Author

N72-11021# Boeing Co., Morton, Pa.
IMPROVING THE READABILITY OF MAINTENANCE MANUALS
Walter Jablonski /in FAA 6th Ann. Intern. Aviation Maintenance

Symp. 1970 34 p
 Avail: NTIS HC \$6.00/MF \$0.95

A discussion of methods for improving the readability of aircraft maintenance manuals is presented. Techniques for evaluating the understandability of written instructions are described. Requirements for and advantages of improved readability are discussed. Author

N72-11022# LTV Aerospace Corp., Dallas, Tex. Systems Effectiveness Dept.

HARNESSING THE DIGITAL COMPUTER FOR AIRCRAFT MAINTENANCE

R. F. Cook /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 12 p
 Avail: NTIS HC \$6.00/MF \$0.95

The application of digital computers to the maintenance of commercial aircraft avionics systems is discussed. The specific use of computers for detection of impending failures, fault isolation, and verification of fault correction is described. It is concluded that proper use of computer techniques will result in increased availability, lower maintenance costs, and improved flight safety. Author

N72-11023# Boeing Co., Seattle, Wash.
FACILITIES, EQUIPMENT AND TOOLS TO SUPPORT WIND BODIED AIRPLANE MAINTENANCE IN THE SEVENTIES

M. Doyle /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 27 p
 Avail: NTIS HC \$6.00/MF \$0.95

The definition and documentation of facility, equipment, and tool requirements for maintenance of large commercial aircraft are presented. The main impact of the large aircraft is the increased magnitude of the planning task. A general review of the requirements using the 747 aircraft as an example is provided. Author

N72-11024# Wall Colmonoy Corp., Detroit, Mich.
REMANUFACTURING OF JET ENGINE COMPONENTS EMPLOYING BRAZING TECHNIQUES

Robert Leon Peaslee /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 10 p
 Avail: NTIS HC \$6.00/MF \$0.95

The application of brazing techniques for the remanufacture of jet engine components is discussed. The benefits derived from brazing of jet engine parts are described. Welding of hot section components and precision braze repair procedures are presented. Author

N72-11025# Automation Industries, Inc., Danbury, Conn. Materials Evaluation Group.

NONDESTRUCTIVE INSPECTION: AN AIRCRAFT MAINTENANCE TOOL OF THE SEVENTIES

Earl C. Mayes /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 5 p
 Avail: NTIS HC \$6.00/MF \$0.95

The application of nondestructive techniques to maintenance of large commercial aircraft is discussed. Procedures described are: (1) radiography, (2) ultrasonic inspection, (3) eddy current, (4) magnetic particle, and (5) in penetrant. Present operations and future possibilities are presented. Author

N72-11026# General Electric Co., Houston, Tex.
OPERATING LOGIC: NEW DATA AND TRAINING CONCEPT DEVELOPMENTS OF THE APOLLO PROGRAM

J. T. Waggoner /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 29 p ref
 Avail: NTIS HC \$6.00/MF \$0.95

The application of Apollo Project data and training concepts to the maintenance of large commercial aircraft is discussed. Subjects presented are: (1) functional understanding of system and support equipment, (2) physical characteristics of system and support equipment, and (3) procedural directions for troubleshooting and fault isolation. Author

N72-11027# Douglas Aircraft Co., Inc., Long Beach, Calif.
MAINTENANCE FAULT ISOLATION IN THE SEVENTIES
 H. W. Adams and H. Bayer /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 8 p
 Avail: NTIS HC \$6.00/MF \$0.95

The Pattern of Cockpit Indication (PCI) system for simplified, coordinated, in-flight and on-ground fault isolation is described. Simulator tests have shown PCI to provide up to an 18 to 1 improvement over systems now in use. The principles and methods of analysis, development, simulation, and presentation are described and the benefits associated with the use of PCI by the airlines are presented. Author

N72-11028# Lockheed-California Co., Burbank.
STREAMLINED L-1011 FAULT ISOLATION TECHNIQUES
 W. W. Watkins /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 19 p
 Avail: NTIS HC \$6.00/MF \$0.95

The incorporation of built-in-test-equipment and condition monitoring capabilities for aircraft systems and components is discussed. The development of fault isolation and problem correction equipment used by the L-1011 aircraft is reported. The prime feature of the technique is the graphic presentation of functional check data through the medium of logic and schematic diagrams. Elimination of conventional test procedures facilitates the use of the maintenance data. Duplication of fault isolation tasks is avoided and appropriate maintenance procedures are followed. Author

N72-11029# Societe Nationale Industrielle Aerospatiale, Paris (France). Concorde Support Div.

AN APPLICATION OF MODERN MAINTENANCE CONCEPTS AND SAFETY ANALYSIS TO THE MULTINATIONAL CERTIFICATION OF A SUPERSONIC AIRCRAFT

J. Haas /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 24 p
 Avail: NTIS HC \$6.00/MF \$0.95

The composition and functions of an organization for multinational certification of supersonic commercial aircraft are described. The organization is primarily concerned with establishment and enforcement of design and maintenance requirements which will promote safer aircraft operation. Author

N72-11030# Pratt and Whitney Aircraft, East Hartford, Conn.
MODULAR DESIGN CONCEPT IMPROVES JET ENGINE MAINTAINABILITY

George P. Adamson /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 32 p
 Avail: NTIS HC \$6.00/MF \$0.95

Improvements in the maintenance of jet aircraft engines by incorporation of modular construction is discussed. In the JT9D engine, consideration was given to avoiding maintenance problems by simplification of structural features. Airline experience in maintaining the JT9D engines is presented and comparisons are made with previous engine maintenance operations. Author

N72-11031# General Electric Co., Cincinnati, Ohio. Aircraft Engine Group.

ACCESSIBILITY: THE KEY TO GOOD POWERPLANT MAINTAINABILITY

R. W. Hevener /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 16 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Of the several design criteria required to achieve good maintainability features, accessibility is considered the key one because of its contribution to the airline operator in reducing overall maintenance costs. This contribution is provided to the operator in three major areas: (1) increased inspection accessibility and capability permitting the airlines' maintenance personnel to monitor parts condition, trouble-shoot, and isolate problem areas, (2) easy access by attachment and arrangement features to permit rapid removal and replacement of engine and aircraft accessories, and, (3) modular construction of the basic engine components to permit replacement either on the airplane or off at line maintenance stations, resulting in significant reduction of the elapsed time that an engine is out of commission and is returned to spare inventory status. In addition to making a major contribution in reducing maintenance costs, good accessibility features aid in reducing overall operating costs through improved dispatch reliability and reduced airplane down time, thereby permitting increased utilization of the airplane. Author

N72-11032# Beechcraft-Hawker Corp., London (England).

MAINTAINING THE BH 125 IN THE SEVENTIES

Ian F. Keith /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 20 p

Avail: NTIS HC \$6.00/MF \$0.95

Maintenance procedures for the Beech Hawker 125 commercial jet aircraft are presented. Subjects discussed are: (1) maintenance schedule, (2) nondestructive testing, (3) instruction handbooks, and (4) inspection requirements. Author

N72-11033# General Aviation Manufacturers Association, Washington, D.C.

THE GENERAL AVIATION MAINTENANCE OUTLOOK FOR THE SEVENTIES

Stanley J. Green /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 6 p

Avail: NTIS HC \$6.00/MF \$0.95

Predictions of aircraft maintenance procedures and requirements for the remainder of the 1970's are presented. Emphasis is placed on the need for improvement in aircraft safety and methods for improving the safety record. The expected expansion in numbers of aircraft and changes in aircraft power plants are described. Author

N72-11034# LTV Aerospace Corp., Dallas, Tex.

PROJECTED MAINTAINABILITY ADVANTAGES OF SOLID STATE ELECTRICAL POWER MANAGEMENT AND SOLID STATE CONTACTLESS SWITCHING SYSTEMS

T. S. Miller /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 31 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Maintenance advantages of solid state electrical logic management and distribution of electrical power are described. The specific advantages discussed are those associated with the capabilities of the system to: (1) create a favorable power environment for avionics, (2) lower total systems maintenance by favorable interfacing of electrical signal and control functions, and (3) exploit the favorable failure delta of solid state switching. The discussions are predicted on a contemporary aircraft electrical power management and distribution system and a solid state contactless system. The possible variations of the two systems are infinite, therefore the discussions are limited to comparisons between aircraft systems based on the requirements of MIL-STD-704 and a solid state system specifically conceived to

operate with power sources of a MIL-STD-704 system. Military Standard 704 in this case is deemed to connote a constant frequency generator operating from a variable speed power take off with the necessary control and management required to deliver electrical power to an aircraft's AC and DC buses.

Author

N72-11035# Pacific Airmotive Corp., Burbank, Calif.

PACIFIC AIRMOTIVE CORPORATION ACCESSORY RELIABILITY PROGRAM (PACAR) c15

David Snyder /In FAA 6th Ann. Intern. Aviation Maintenance Symp. 1970 5 p

Avail: NTIS HC \$6.00/MF \$0.95

The establishment of a program for improved reliability through new maintenance procedures applied to aircraft accessories is discussed. The steps taken to insure adequate inspection and repair are described. The effects of various environmental conditions on component reliability are reported.

Author

N72-11036# Office National d'Etudes et de Recherches Aerospatiales, Paris (France).

STUDYING THE COHERENT AND INCOHERENT STRUCTURES OF AERODYNAMICALLY GENERATED NOISE [ETUDES DES STRUCTURES COHERENTES ET INCOHERENTES DE BRUIT D'ORIGINE AERODYNAMIQUE]

Jean-Francois deBelleval, Patrick Harel, Jean Lambourion, and Mariano Perulli 1971 5 p refs In FRENCH Presented at the 7th Intern. Congr. on Acoustics, Budapest, 18-26 Aug. 1971 (ONERA-TP-983) Avail: NTIS

The coherent and incoherent structures of aerodynamically generated noise is outlined using theoretical models. Space-time correlations are then used to analyze the pressure near the field of a compressor and the infrared emission of a hot jet. From this analysis the source structure is determined. Author

N72-11037# Douglas Aircraft Co., Inc., Long Beach, Calif.

A FLIGHT SIMULATOR STUDY OF STOL TRANSPORT DIRECTIONAL CONTROL CHARACTERISTICS Final Report Robert A. Berg, W. Allen Shirley, Gary L. Teper (Systems Tech., Inc., Hawthorne, Calif.), and Samuel J. Craig (Systems Tech., Inc., Hawthorne, Calif.) Jun. 1971 134 p refs Prepared in cooperation with Systems Tech., Inc., Hawthorne, Calif.

(Contract DOTFA-70-WA-2395)

(FAA-RD-71-81) Avail: NTIS

A systematic investigation was conducted of STOL transport terminal area directional control characteristics to identify the significant considerations and to establish appropriate directional control criteria. The investigation consisted of an analysis of existing data and moving-base flight simulator program using the NASA S-16 Moving Cab Transport Simulator. The simulator test program covered a broad range of lateral and directional aerodynamic characteristics representative of typical STOL transport aircraft. The study revealed the existence of an appreciable interaction between the roll and the heading control tasks which suggests that roll-mode damping requirements should be specified in terms of the heading delay characteristics. Lateral control sensitivity tests were conducted which corroborated previously obtained results. Author

N72-11038# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

THREE-TRACK RUNWAY AND TAXIWAY PROFILES MEASURED AT INTERNATIONAL AIRPORTS E AND F

Albert W. Hall Washington Nov. 1971 100 p refs

(NASA-TN-D-6567; L-7977) Avail: NTIS CSCL 01E

Three-track runway and taxiway profiles are presented for use in studies of airplane response to ground roughness. This report presents the tabulated and plotted data for two international airports (designed airports E and F). Author

N72-11039# Joint Publications Research Service, Washington, D.C.

SYSTEMS OF AIRCRAFT AUTOMATIC CONTROL

I. A. Mikhalev, B. N. Okoyemov, I. G. Pavlina, M. S. Chikulyayev, and N. M. Eydov 27 Oct. 1971 47 p Transl. into ENGLISH from the book "Sistemy Avtomaticheskogo Upravleniya Samoletom" Moscow, Mashinostroyeniye Publishing House, 1971 p 2-9, 87-128

(JPRS-54332; UDC-697.7.05.001) Avail: NTIS

Methods of analysis and calculation of the basic parameters of aircraft automatic control system components are discussed. Analysis and calculation are done with the problem stated in linear form. The materials are reduced to simple, practical calculation equations. The report contains 22 bibliographic references. Author

N72-11040# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany). Inst. fuer Flugmechanik.

NOISE-ABATEMENT FLIGHT PROFILES FOR CTOL AND V/STOL AIRCRAFT

P. Hamel 1971 49 p refs (DLR-FB-71-10; DK-658.517.2) Avail: NTIS; DFVLR, Porz, West Ger.: 12.50 DM

An overall survey of problems associated with noise abatement flight profiles for CTOL and V/STOL aircraft is presented. It is shown how aircraft design parameters and control variables, such as thrust vector control, power loading, and aerodynamic efficiency, influence the intensity of the noise source. The distance between noise source and observer, and the noise exposure duration may be influenced by steep climbout combined with moderate thrust and steep landing. Several stability and control problems due to steep noise abatement landing procedures are discussed. ESRO

N72-11042# Royal Aircraft Establishment, Farnborough (England).

CATEGORY 2: A SIMULATION STUDY OF LOW VISIBILITY APPROACHES AND LANDINGS AT NIGHT

A. D. Brown Mar. 1971 105 p refs (RAE-TR-71044; UDC-629.13.089) Avail: NTIS

The design, execution and results of a flight simulator experiment to investigate the problems of aircraft operating in Category 2 conditions. Both military and airline pilots participated and over 500 manual approaches were performed using a flight director. The effects of decision height, contact time, lateral offset, visual sequence and visual segment on the approach success (the ratio of landings to approaches) are examined and a curve relating this parameter to visual segment, the predominant factor, is determined. The influence of different visual sequences on pilot performance during the approach and landing is also considered and some observations are made about the crew techniques employed during the experiment; techniques which appeared to have certain deficiencies. Author ESRO

N72-11043# Royal Aircraft Establishment, Farnborough (England). Structures Dept.

CIVIL AIRCRAFT AIRWORTHINESS DATA RECORDING PROGRAMME, MANOEUVRE LOADS DURING TRAINING AND TEST FLYING

G. E. King London Aeron. Res. Council 1971 13 p refs Supersedes RAE-TR-70226; ARC-32850 (ARC-CP-1176; RAE-TR-70226; ARC-32850) Avail: NTIS; HMSO: 20p; PHI: \$0.80

Using continuous photographic trace records, the maneuver accelerations experienced in 35 hours of training flying were counted and measured to provide an estimate of the total

numbers and magnitude of loads for a fleet's flying training over a five year period. These data are compared with counting accelerometer data giving the estimated total number of gust plus maneuver loads for five years of revenue flying by the same fleet. Both estimates were found to be of the same order in the number and magnitude of loads although the ratio of training to revenue flying hours was one in fifty. The particular test flight analyzed, which included an unusually large number of stalls, produced approximately as many extreme negative accelerations as one year's revenue flying. Author (ESRO)

N72-11044# Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

AN HYPOTHESIS FOR THE PREDICTION OF FLIGHT PENETRATION OF WING BUFFETING FROM DYNAMIC TESTS ON WIND TUNNEL MODELS

D. G. Mabey London Aeron. Res. Council 1971 33 p refs Supersedes RAE-TR-70189; ARC-32684 (ARC-CP-1171; RAE-TR-70189; ARC-32684; UDC-533.6.013.43:533.693) Avail: NTIS; HMSO: 45p; PHI \$1.80

Buffeting coefficients appropriate to the maximum flight penetration of wing buffeting for both transport and fighter type aircraft are deduced from the comparison of flight observations and measurements of unsteady wing-root strain on stiff wind tunnel models. The necessary buffeting coefficients are derived rapidly from the unsteady wing-root strain measurements. The tunnel unsteadiness is used as a given level of aerodynamic excitation to calibrate the model response at the wing fundamental frequency. Author (ESRO)

N72-11045# Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

BRIEF FLIGHT TESTS OF CROSSWIND LANDINGS AND SIDESTEP MANOEUVRES ON THE BAC 221 AIRCRAFT

W. F. Dee, R. Rose, and O. P. Nicholas London Aeron. Res. Council 1971 32 p refs Supersedes RAE-TR-68251; ARC-30959 (ARC-CP-1168; RAE-TR-68251; ARC-30959) Avail: NTIS; HMSO: 45p; PHI: \$1.80

A brief flight study has been made of crosswind landings and sidestep maneuvers in the BAC 221 slender-wing research aircraft. Using the crabbed approach for crosswind landings, and the coordinated S-turn for sidestep maneuvers, pilots found both tasks straightforward. The time required to complete a sidestep is little longer than for unswept aircraft, despite the oscillatory roll response to aileron inputs of the BAC 221. Results of similar tests performed in a ground based simulator show good qualitative agreement. Author (ESRO)

N72-11046# Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

FLIGHT AND WIND-TUNNEL TESTS ON AN AERODYNAMICALLY COMPENSATED PITOT-STATIC HEAD FOR THE BAC 221 AIRCRAFT

C. S. Barnes and O. P. Nicholas London Aeron. Res. Council 1971 47 p refs Supersedes RAE-TR-69013; ARC-31370 (ARC-CP-1167; RAE-TR-69013; ARC-31370) Avail: NTIS; HMSO: 65p; PHI: \$2.65

The BAC 221 aircraft is fitted with a special pitot-static head, insensitive to incidence, and aerodynamically compensated on similar principles to the head fitted to the Concorde, to minimize aircraft pressure field effects. Tests have been made on the head covering the Mach number range 0.2 to 1.4 in two wind tunnels and at three altitudes in flight. The compensation significantly reduces the static pressure errors at high subsonic and transonic speeds but small errors remain at low subsonic and supersonic speeds. The sensitivity to incidence and sideslip, of the pitot and static pressures sensed, is satisfactorily low. The manufacturer's prediction of the head performance agrees

reasonably well with tunnel results but poorly with flight results. It appears that the prediction of the aircraft pressure field is inaccurate. Author (ESRO)

N72-11047# Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

SOME FULL-SCALE MEASUREMENTS OF THE FLOW IN THE WAKE OF A HANGAR

M. J. Colmer London Aeron. Res. Council 1971 30 p refs Supersedes RAE-TR-70202; ARC-32863

(ARC-CP-1186; RAE-TR-70202; ARC-32863) Avail: NTIS; HMSO: 40p; PHI: \$1.85

An experiment to measure the flow behind a full-scale building is described. The results of one set of data show that the whole wake was slowly oscillating and that the turbulence intensity in the wake was greater than upstream. An hypothesis for the wake motion is put forward and the effect of the wake behind a building on conventional and V/STOL aircraft is considered. Author (ESRO)

N72-11048# Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

PILOTED SIMULATOR INVESTIGATIONS OF FLIGHT NEAR ZERO RATE OF CLIMB SPEED

T. Wilcock London Aeron. Res. Council 1971 39 p refs Supersedes RAE-TR-70016; ARC-32171

(ARC-CP-1185; RAE-TR-70016; ARC-32171) Avail: NTIS; HMSO: 55p; PHI: \$2.45

The problems associated with flight at or below the zero rate of climb speed (V sub ZRC) have been investigated in piloted flight simulations of a supersonic transport aircraft and of the BAC 221 slender wing research aircraft. The accuracy of determining V sub ZRC by piloted tests was examined, and the height losses in recoveries from below V sub ZRC were compared with theoretical calculations. Agreement was very good for one simulation, though not quite as good for the other. Tests showed that height losses are generally minimized by a rapid recovery maneuver, but no detailed study was made of the optimum recovery technique. Author (ESRO)

N72-11049# Royal Aircraft Establishment, Bedford (England). Aero F Dept.

A THEORETICAL STUDY OF HEIGHT CONTROL IN FLIGHT CLOSE TO THE GROUND AS AFFECTED BY ELEVATOR LIFT AND COCKPIT POSITION

W. J. G. Pinsker London Aeron. Res. Council 1971 19 p refs Supersedes RAE-TR-69097; ARC-31488

(ARC-R/M-3662; RAE-TR-69097; ARC-31488) Avail: NTIS; HMSO: 50p; PHI: \$2.25

During the final landing approach pilots are often observed to attempt tight control of flight path by coarse elevator usage. It is shown by theoretical analysis that this form of control is inherently conducive to instability and that adverse elevator lift is detrimental in this situation. However, if the pilot is located in a cockpit far forward of the center of gravity of the aircraft, he perceives false motion cues which tend to reduce the possibility of this form of pilot-induced oscillation. Author (ESRO)

N72-11050# Cornell Aeronautical Lab., Inc., Buffalo, N.Y. **THE AERODYNAMIC AND AEROELASTIC CHARACTERISTICS OF A FULL SCALE ROTOR OPERATING AT VERY HIGH ADVANCE RATIOS AND DURING START/STOP OPERATION** Final Report, Feb. 1968 - May 1970

Andrew R. Trenka May 1971 183 p refs (Contract DAAJ02-68-C-0017; DA 1F1-62204-A-139) (AD-727653; CAL-BB-2595-S-1; USAVLABS-TR-70-60) Avail: NTIS CSCL 01/3

The purpose of this program was to study the aerodynamic and aeroelastic behavior of a rigid two-bladed rotor system operating at steady-state advance ratios up to approximately 15. Also to be investigated was the operation of this rotor during periods of acceleration and deceleration which were representative of the starting/stopping sequence of a stowable rotor. The objective of the program was accomplished by conducting wind tunnel tests in the NASA-Ames 40- x 80-foot wind tunnel on a full-scale rotor. Hub forces and moments, blade pressure distributions (chordwise and spanwise), and blade flatwise, chordwise and torsional moments were measured. The experimental results were used to correlate with existing theory. GRA

N72-11051# Tri-State Transportation Commission, New York. **METROPOLITAN AIRCRAFT NOISE ABATEMENT POLICY STUDY, JOHN F. KENNEDY INTERNATIONAL AIRPORT, NEW YORK, NEW YORK**

1970 21 p Sponsored in part by HUD

(PB-200164; TSTC-2053-3580-1M) Avail: NTIS CSCL 01B

Alternative measures or combinations of measures to provide relief from aircraft noise in affected communities around John F. Kennedy International Airport are considered, and methods for reducing aircraft-noise problems are recommended. A study was made of present land use, local development policies and codes, sound insulations of structures, redevelopment, future land-use alternatives, legal aspects and airport operations. Author (GRA)

N72-11052# National Transportation Safety Board, Washington, D.C.

BRIEFS OF ACCIDENTS INVOLVING CORPORATE/EXECUTIVE AIRCRAFT: US GENERAL AVIATION, 1968

Jun. 1971 58 p

(PB-201439; NTSB-AMM-71-3) Avail: NTIS CSCL 01B

The publication contains statistical, cause/factor and injury tables, accident rates, and the briefs of accidents involving corporate/executive aircraft. Author (GRA)

N72-11053# Trans-Sonics, Inc., Burlington, Mass.

HELICOPTER LIFT-MARGIN SYSTEM, VOLUME 2 Final Report

Bradford W. Edgerton and Sidney B. Williams Dec. 1970 149 p Sponsored in part by ECOM

(Contract N00014-68-C-0300; NR Proj. 213-067)

(AD-725207; JANAIR-701218-Vol-2; Rept-80001-Vol-2) Avail: NTIS CSCL 01/4

Helicopter power requirements are generally maximum when hovering out of ground effect. Thus, takeoff and landing maneuvers are the most critical, since the power requirements may not be clear to the pilot at the time he must make the corresponding decisions. Power deficiencies at takeoff or landing are very hazardous. To maximize safety of takeoff and landing operations, a system has been devised which presents to the pilot his lift margin, a figure which represents the excess weight which could be accommodated under locally-existing barometric pressure, outside-air-temperature conditions, and rotor system condition. The system includes two kinds of compensators of which the first corrects available engine torque for ambient conditions and the second makes a similar correction for the ratio of gross weight to required power. Author (GRA)

N72-11054# Air Force Flight Test Center, Edwards AFB, Calif. **THEORY OF THE MEASUREMENT AND STANDARDIZATION OF IN-FLIGHT PERFORMANCE OF AIRCRAFT** Final Technology Document

Everett W. Dunlap and Milton B. Porter Apr. 1971 281 p refs (AD-725741; AFFTC-TD-71-1) Avail: NTIS CSCL 14/2

The contents of this report were prepared to give those engaged in aircraft flight test an understanding of the analysis required to arrive at standardized flight data. Toward that end, considerable attention was given to the derivation of equations. In contrast to earlier reports, simplifying assumptions were not made; rather, efforts were made to keep the derivations of all equations as nearly exact as possible. Emphasis has been placed on climbs and level accelerations since these tests, particularly for supersonic aircraft, consume a large part of a test program and require calculations which are much more lengthy than for other tests. The information in this document was the basis for the development of uniform digital computer programs which are being constructed for use in processing flight data and correcting it to standard conditions. These programs have been given the name Uniform Flight Test Analysis System (UFTAS).

Author (GRA)

N72-11056# Dynamic Science, Irvine, Calif.
ANALYSIS OF AIRCRAFT FUEL TANK FIRE AND EXPLOSION HAZARDS Final Report, 1 Jul. 1969 - 15 Dec. 1970

Thomas C. Kosvic, Laurence B. Zung, and Melvin Gerstein Mar. 1971 88 p refs
(Contract F33615-69-C-1895; AF Proj. 3048)
(AD-725027; SN-166-F; AFAPL-TR-71-7) Avail: NTIS CSCL 13/12

Under simulated flight environments, fuel/air ratios at various locations of the ullage space were determined using in-line gas chromatograph measurement. Using the shallow tank experimental data showed that during ascent and cruise portion of the flight profile, uniform fuel/air mixtures were found to exist within the entire ullage volume. Significant fuel/air gradients existed during the descent portion of the flight profile, with mainly air near the vent inlet. Evaporation lag was observed during ascent and level flight when liquid Jet A fuel was maintained at 80 degree F. When the liquid fuel temperature was increased to 120F, evaporation rate was found to be rapid enough that the evaporative lag phenomena was no longer observed. By vibrating the fuel tank, it greatly increased the rate of off-gassing of dissolved air in the liquid fuel. This in turn significantly changed the fuel/air ratio in the ullage space. Two separate and complementary models were developed to predict fuel/air concentrations within the ullage.

Author (GRA)

N72-11057# American Nucleonics Corp., Woodland Hills, Calif.
ANALYSIS AND DESIGN STUDY OF A PILOT ASSIST SYSTEM FOR HELICOPTERS Final Report, Jan. - Dec. 1970

Arthur J. Welch and Edward L. Warren Apr. 1971 190 p refs
(Contract DAAJ02-70-C-0019)
(AD-725590; ANC-72R-14; USAAVLABS-TR-71-11; Task-1F162204A13905) Avail: NTIS CSCL 01/3

The purpose of the work performed under this contract was to conduct an analytical investigation of advanced flight control systems (AFCS) requirements for light and medium size helicopters and to design a pilot assist system based on the analytical results. The pilot assist system (PAS) design goal was to develop an AFCS that is relatively light and inexpensive and that can be readily installed in a UH-1B.

Author (GRA)

N72-11058# Serendipity Associates, Arlington, Va. Eastern Operations Div.
AIRCRAFT SYSTEM COMPUTER MODELS
BURROUGHS 5500-MOD 0, IBM 7094-MOD 1
Jun. 1971 56 p refs Sponsored by Dept. of Transportation
(PB-201432; DOT-OST-ONA-71-4) Avail: NTIS CSCL 09B

The report contains a computer listing of the airport/aircraft system computer model developed during the course of a study on transportation noise.

GRA

N72-11059# Boeing Co., Philadelphia, Pa. Vertol Div.
HELICOPTER DEVELOPMENT RELIABILITY TEST REQUIREMENTS. VOLUME 1 Final Report
Kirk G. Rummel Apr. 1971 317 p
(Contract DAAJ02-70-C-0039)
(AD-725595; D210-10207-1; USAAMRDL-TR-71-18A; Task-1F162203A14301) Avail: NTIS CSCL 01/3

The report covers a study to identify optimum reliability problem identification and demonstration test concepts for helicopter dynamic components, in order to facilitate formulation of cost-effective reliability test programs for future helicopters. Detailed failure mode test technique problem identification capability and cost data are presented from CH-47 helicopter development experience to aid in calculating specific test costs for future development programs. Sample test plans are presented for two helicopters representing size extremes. A plan is outlined for revising selected existing design and test military specifications and supplementing them with additional handbooks and specifications.

Author (GRA)

N72-11060# Oceanics, Inc., Plainview, N.Y.
MODEL STUDIES OF HELICOPTER TAIL ROTOR FLOW PATTERNS IN AND OUT OF GROUND EFFECT Final Technical Report

August F. Lehman Fort Eustis, Va. Army Air Mobility Res. and Develop. Lab. Apr. 1971 32 p refs
(Contracts DAAJ02-68-C-0089; DAAJ02-68-C-0103; DA Proj. 1-F-162204-A-14232; DA Proj. 1-F-1-62204-A-14231)
(AD-725591; Rept-70-79; USAAVLABS-TR-71-12) Avail: NTIS CSCL 01/3

Water tunnel studies of a model helicopter which entailed a visualization of the main and tail rotor wakes, the inflow patterns, and their subsequent interactions as the wind velocity and wind heading were changed resulted in a significant gain in knowledge ultimately applicable to direction control of helicopters. Of significant interest was the impingement of the main rotor wake with a ground plane, its subsequent spreading outward in a radial manner and the roll-up of the wake into a standing vortex at the outer edge of this radial expansion of the wake.

Author (GRA)

N72-11081# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.
SELECTING THE BASIC PARAMETERS OF CIVIL AIRCRAFT FOR SPECIFIED RANGES AND COMMERCIAL LOAD

G. N. Yun 3 Mar. 1971 22 p refs Transl. into ENGLISH from "Primeniye Matematicheskikh Metodov v Ekonomicheskikh Issledovaniyakh i Planirovani, Seminar" Kiev, no. 1, 1968 p 64-75
(AD-727231; FTD-MT-24-353-70) Avail: NTIS CSCL 01/3

A digital computer method of selecting the basic parameters of aircraft, using freight charges as a criterion, is described.

Author (GRA)

N72-11147 World Meteorological Organization, Geneva (Switzerland).

UTILIZATION OF METEOROLOGICAL RADAR FOR AERONAUTICS [L'UTILISATION DES RADARS METEOROLOGIQUES POUR L'AERONAUTIQUE]
H. Traussart, W. B. Beckwith, S. G. Bigler, K. Otani, V. V. Kostarev, and R. Schwarz 1971 108 p refs In FRENCH; ENGLISH summary
(OMM-264-TP-148; UDC-551.501.81; NT-110) Copyright. Avail: Issuing Activity

The detection and identification of hail and turbulence associated with thunderstorms are discussed. The question of measuring the height of echoes observed by radar is presented. Echo height is an index of storm activity. The interpretation of echoes for different types of radar is considered. The data from weather radar depend not only on meteorological phenomena

but also, to a great extent, on the characteristics of the radar. Processing and transmission of radar information is reviewed in great detail. Transmission of radar information to aircraft in flight is also considered a subject important for aviation. New techniques for radar observations are summarized. Author

N72-11289# National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.
CONTRIBUTION TO METHODS FOR CALCULATING THE FLOW ABOUT THIN LIFTING WINGS AT TRANSONIC SPEEDS: ANALYTIC EXPRESSIONS FOR THE FAR FIELD
 E. B. Klunker Washington Nov. 1971 18 p refs
 (NASA-TN-D-8530; L-7917) Avail: NTIS CSCL 20D

The problem of determining the small-disturbance flow about two-dimensional airfoils at transonic speeds has been successfully treated by the process of matching a numerical solution of the near field to analytic expressions for the far field. The three-dimensional problem, it would appear, can be treated in a similar way with the aid of algorithms adapted to high-speed and high-capacity computers. The far-field potential for both lifting and nonlifting three-dimensional wings at transonic speeds is developed herein for a subsonic free stream. This potential could be used for a three-dimensional-wing computation similar to the computation made for the two-dimensional wing. Author

N72-11291# National Physical Lab., Teddington (England). Aerodynamics Div.
EFFECTS OF REYNOLDS NUMBER AND FREQUENCY PARAMETER ON CONTROL-SURFACE BUZZ AT HIGH SUBSONIC SPEEDS
 Y. Nakamura Feb. 1970 22 p refs
 (NPL-AERO-1312; ARC-31897) Avail: NTIS

Oscillatory hinge-moment derivatives and limit cycle amplitudes were measured on an airfoil-flap combination model over the Mach number range 0.78 to 0.81 within a buzz region. Stagnation pressure was varied from 100,000 N/sq m to 200,000 N/sq m. The magnitude of both derivatives and the limit cycle amplitude tended to increase with increasing Reynolds number. The effect of increasing frequency was to produce a relatively large decrease in limit cycle amplitude and the magnitude of the derivatives. Author (ESRO)

N72-11295# National Physical Lab., Teddington (England). Aerodynamics Div.
PITOT-STEM BLOCKAGE CORRECTIONS IN UNIFORM AND NON-UNIFORM FLOW
 R. W. F. Gould London Aeron. Res. Council 1971 30 p refs
 Supersedes NPL-AERO-1322; ARC-32283
 (ARC-CP-1175; NPL-AERO-1322; ARC-32283) Avail: NTIS; HMSO: 42.5p; BIS: \$1.80

Wind tunnel measurements are described which determine the error introduced into static pressure measurements in a pipe or duct by the presence of a pitot (or other) stem downstream of the plane of measurement. The effects measured in a uniform stream are used to calculate corresponding stem-blockage corrections in nonuniform flow. The method is applied to fully developed pipe flow measurements in circular and rectangular ducts. Author (ESRO)

N72-11308# Von Karman Inst. for Fluid Dynamics, Rhode Saint-Genese (Belgium). Turbomachinery Lab.
RESEARCH ON ADVANCED AXIAL COMPRESSOR CONCEPTS Final Scientific Report, 1 Nov. 1970 - 31 Jan. 1971
 F. A. E. Breugelmans, J. Chauvin, H. Rottiers, J. Salvage, and B. Roberts 25 Feb. 1971 65 p refs
 (Contract F61052-69-C-0025; AF Proj. 7065)
 (AD-725789; ARL-71-0093) Avail: NTIS CSCL 13/7

The report covers work carried out on advanced axial compressor concepts. Cascade calculations and testing on blunt trailing edge (BTE) blades and conventional blades are described covering optimization of external and internal diffusion in BTE blade passages, low Reynolds number performance and detailed secondary flow investigations. The effort on the BTE diffusion optimization was concentrated on the experimental study of the flow from the trailing edge to infinity. Relative trailing edge thickness and trailing edge form have an influence on the Strouhal number. The latter is most prevalent. Author (GRA)

N72-11312# Air Force Systems Command, Wright-Patterson AFB, Ohio.
EXPERIMENTAL STUDY OF SHOCK IMPINGEMENT ON A BLUNT LEADING EDGE WITH APPLICATION TO HYPERSONIC INLET DESIGN Technical Report, Dec. 1967 - Mar. 1969
 Roger R. Craig and Paul J. Ortwerth Apr. 1971 44 p refs
 (AF Proj. 3012)
 (AD-726111; AFAPL-TR-71-10) Avail: NTIS CSCL 20/4

An experimental study was made of the interaction of an oblique shock with the bow shock of blunt leading edge. The interactions were classified according to the interference patterns described by Edney. Peak heating rates 5.5 times those of the blunt leading edge alone were studied. All interactions appeared to be unsteady except when the slipstream of the interaction passed above the blunt leading edge. Author (GRA)

N72-11334# California Univ., Berkeley. Lawrence Radiation Lab.
CATALYTIC REDUCTION OF STRATOSPHERIC OZONE BY NITROGEN OXIDES
 Harold Johnston Jun. 1971 117 p refs
 (Contract W-7405-eng-48)
 (UCRL-20568) Avail: NTIS

Quantitative calculations of the destruction of stratospheric ozone by nitrogen oxides omitted from SST's are presented. The calculations cover the following: (1) the rate of destruction of ozone by NO(x) relative to the ozone destruction rate by the couple, O₂, O₃, and by free radicals derived from water; and, (2) steady state calculations of the profile of ozone in the stratosphere for a wide range of uniform and nonuniform distributions of NO(x). Although special attention is given to NO(x) at 3, 7, 30, and 70 ppb, most calculations cover the complete range from zero to 100 ppb. Over the entire range of stratospheric variables, the oxides of nitrogen, NO and NO₂, have a powerful effect in reducing ozone, and a quantity (30 ppb) previously accepted as negligible would reduce the ozone column by about a factor of two, according to two different methods of computation. Author

N72-11368# Office National d'Etudes et de Recherches Aérospatiales, Paris (France).
STUDY AND CALIBRATION OF PRESSURE SENSORS IN PARTICULAR ENVIRONNEMENTS [ETUDE ET ETALONNAGE DE CAPTEURS DE PRESSIONS EN AMBIANCES PARTICULIERES]
 Bernard Baerd, Alain Julienne, and Rene Nantois 1971 5 p refs In FRENCH Presented at the 7th Intern. Congr. on Acoustics, Budapest, 18-26 Aug. 1971
 (ONERA-TP-982) Avail: NTIS

The design and calibration of unsteady pressure sensors used to measure aerodynamic noise are discussed. The sensitivity of the sensors under difficult environmental conditions such as high noise levels, surrounding flow, static overpressure, vibrations, and high temperature are determined. The sensors are also designed to measure the effects of turbomachine interior and jet interior on pipe flow. Author

N72-11370# Civil Aeromedical Inst., Oklahoma City, Okla.
CALIBRATION OF THE CONCORDE RADIATION

DETECTION INSTRUMENT AND MEASUREMENTS AT SST ALTITUDE

Wallace Friedberg and John M. Nelson Jun. 1971 21 p refs
(FAA-AM-71-26) Avail: NTIS

Performance tests were carried out on a solar cosmic radiation detection instrument developed for the Concorde SST. The instrument calibration curve was reasonably linear from 0.004 to 1 rem/hr for both gamma radiation and fast neutrons. Nonlinearity in the calibration curve was observed at dose rates below 0.003 rem/hr. The instrument responded normally after exposure to 30 rem/hr of gamma radiation. The charged particle detectors showed a directional response because of the neutron moderator. The neutron detector did not show a directional response. Measurements made with the Concorde instrument at 60,000 ft and high geomagnetic latitudes indicated a galactic cosmic radiation dose rate of 0.7-0.9 millirem/hr. Author

N72-11375# Imperial Coll. of Science and Technology, London (England). Dept. of Aeronautics.

A THREE COMPONENT GUN TUNNEL BALANCE DESIGNED FOR TESTING THIN DELTA WINGS

T. Opatowski Aeron. Res. Council 1971 36 p refs
Supersedes ARC-31278
(ARC-R/M-3664; ARC-31278) Avail: NTIS; HMSO: 95p; BIS: \$3.60

The design, development, and performance of a three component strain gage balance system designed for testing thin wings in a gun tunnel is described. The balance was machined out of high strength steel and employed miniature silicon strain gages on tension and compression links in order to meet the difficult strength/stiffness requirements. Natural frequencies were attenuated with parallel T filters. Various problems which arose in its development were successfully overcome and some excellent results were obtained. Author (ESRO)

N72-11428*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

COMPRESSIVE BEHAVIOR OF TITANIUM ALLOY SKIN-STIFFENER SPECIMENS SELECTIVELY REINFORCED WITH BORON-ALUMINUM COMPOSITE

Harvey W. Herring, Robert L. Carri, and Rosa C. Webster Washington Nov. 1971 27 p refs
(NASA-TN-D-6548; L-7938) Avail: NTIS CSCL 20K

A method of selectively reinforcing a conventional titanium airframe structure with unidirectional boron-aluminum composite attached by brazing was successfully demonstrated in compression tests of short skin-stiffener specimens. In a comparison with all-titanium specimens, improvements in structural performance recorded for the composite-reinforced specimens exceeded 25 percent on an equivalent-weight basis over the range from room temperature to 700 K (800 F) in terms of both initial buckling and maximum strengths. Performance at room temperature was not affected by prior exposure at 588 K (600 F) for 1000 hours in air or by 400 thermal cycles between 219 K and 588 K (-65 F and 600 F). The experimental results were generally predictable from existing analytical procedures. No evidence of failure was observed in the braze between the boron-aluminum composite and the titanium alloy. Author

N72-11473# Naval Ordnance Lab., White Oak, Md.
SOLVENT REMOVAL OF EC-2273 POTTING COMPOUND FROM F-4 AIRCRAFT ELECTRICAL COMPONENTS Final Report, 1 Jul. 1969 - 31 Dec. 1970

Porter W. Erickson and Joseph M. Augl 14 May 1971 32 p refs
(NOL Proj. 341/AIR-620C01)
(AD-726493) Avail: NTIS CSCL 13/8

A safe, fast, and effective solvent system was developed for the removal of EC-2273 encapsulant. This material, which is now showing signs of failing, is the potting compound used in several hundred components of a large number of Navy F-4 aircraft. The preferred solvent system consists of a mixture of N-methyl-2-pyrrolidone (M-Pyrol), benzyltrimethylammonium hydroxide and methanol. Virgin, as well as deteriorated, EC-2273 is cleanly removed from a typical electrical connector simply by immersion of the component in the solution for a period of a few hours. Author (GRA)

N72-11525# Weather Wing (1st), San Francisco, Calif. 96553
FORECASTING LOW LEVEL TURBULENCE FOR LIGHT AIRCRAFT IN HAWAII Final Report

Donald L. Best Apr. 1971 8 p
(AD-726107; Rept-1WW-TS-23) Avail: NTIS CSCL 04/2

The proposition is to forecast the intensities of turbulence below 10,000 ft MSL for aircraft weighing less than 10,000 pounds operating along the Hawaiian Island Chain during the 24 hour period beginning at 1200Z (0200 local standard time). The intensities of turbulence to be forecasted are light, moderate, and severe. Light turbulence causes slight, erratic changes in altitude, and/or attitude. Moderate turbulence is similar to light but of greater intensity while the aircraft is still in positive control. Severe turbulence causes large, abrupt changes in altitude and/or attitude and the aircraft may be momentarily out of control. Author (GRA)

N72-11527*# Massachusetts Inst. of Tech., Cambridge.

DISPLAY RESEARCH COLLISION WARNING SYSTEM Patent Application

Renwick E. Curry, Lawrence R. Young, Thomas B. Smith, III, and John R. Hatfield, inventors (to NASA) Filed 25 Jun. 1971 15 p
(Grant NGR-22-009-444)
(NASA-Case-HQN-10703; US-Patent-Appl-SN-156724) Avail: NTIS CSCL 17G

An improved head-up display for a pilot warning indicator (PWI) system is discussed. The system includes a plurality of elongated light sources which are attached about the cockpit windshield and side windows. Whenever a target in a sector, which is viewable from the cockpit, is detected by a corresponding detector at least one of the light sources is illuminated. The illuminated light source (or sources) provides an indication of the sector in which the target was detected. The length of the light source (or sources) provides a convenient indication of the sector's bearing boundaries. The novelty of the invention seems to reside in the use of elongated, rather than spot, light sources to indicate to the pilot sector bearing boundaries and thereby speed-up target detection. Author

N72-11668# Advisory Group for Aerospace Research and Development, Paris (France).

AIRCRAFT FUELS, LUBRICANTS, AND FIRE SAFETY

Aug. 1971 401 p refs Presented at 37th Meeting of the AGARD Propulsion and Energetics Panel, The Hague, 10-14 May 1971

(AGARD-CP-84-71) Avail: NTIS HC \$6.00/MF \$0.95

Papers are presented on aircraft fuels, their production, analysis, and testing. Fuel handling, fuel and fire safety, and lubricants are also discussed, using impact tests and crash simulations.

N72-11668# National Research Council of Canada, Ottawa (Ontario). Fuels and Lubricants Lab.

JET FUEL SPECIFICATIONS

L. Gardner and R. B. Whyte In AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 11 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Various military and civil jet fuel specifications are compared and their differences noted, particularly with reference to different types of additives which are used on a mandatory or optional basis. Specification test procedures and their importance in relation to limits are discussed and the increased complexity of quality control for jet fuel specifications is noted. Author

N72-11670# France. Service Technique de l'Aeronautique, Paris.

AERONAUTICAL SIGNIFICANCE OF POLYCYCLIC SATURATED HYDROCARBONS [INTERET AERONAUTIQUE DES HYDROCARBURES POLYCYCLIQUES SATURES]

G. Verdie *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs *In* FRENCH

Avail: NTIS HC \$6.00/MF \$0.95

The range of an airplane depends on the amount of energy used. When reservoir capacity is too limited, it is possible to extend the range by using a higher energy fuel. In this sense, high energy polycyclic saturated hydrocarbons are possible fuels for supersonic aeronautics in the near future, especially since their thermal stability is superior to that of present fuels. Essential fuel characteristics are presented together with the results of experimentation. Industrial fabrication problems and future perspectives are considered. Transl. by K.P.D.

N72-11671# Shell Research, Ltd., Chester (England). Thornton Research Centre.

FUELS FOR SUPERSONIC AND HYPERSONIC AIRCRAFT

A. Lewis, H. Strawson, and J. G. Kirtley *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs Sponsored in part by Min. of Aviation Supply

Avail: NTIS HC \$6.00/MF \$0.95

The first generation of supersonic aircraft is being designed to operate on existing kerosene-type fuels. The limitations of these fuels are reviewed and possibilities considered for propellants for higher-speed aircraft, serving the triple purpose of cooling the airframe, cooling engine components, and providing propulsive energy. Problems of vapor deposition in hot fuel systems are covered and the possibilities explored of increasing the cold-sink value of the fuel by precooling or by endothermic decomposition. The calorific values of different fuels and the importance of recombination of dissociated combustion products is stressed. Ways of speeding such recombination are indicated. Author

N72-11672# Shell Development Co., Emeryville, Calif.
COOLING OF ADVANCED ENGINES BY ENDOTHERMIC REACTIONS OF HYDROCARBON FUELS

L. E. Faith, G. H. Ackerman, and H. T. Henderson *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 8 p refs Sponsored by AFAPL

Avail: NTIS HC \$6.00/MF \$0.95

The fuel used in an engine is a convenient coolant, absorbing heat as sensible heat and latent heat of vaporization. Certain hydrocarbon fuels can furnish additional heat sink in the form of endothermic reactions. Possible endothermic reactions include thermal reactions such as cracking, and catalytic reactions such as dehydrogenation, dehydrocyclization, and depolymerization. Of these, the catalytic dehydrogenation of naphthenes to aromatics is the most promising type of reaction. For example, the dehydrogenation of methylcyclohexane over platinum/alumina catalyst furnishes a reaction heat sink of approximately 1000 Btu/lb fuel, which is slightly greater than the cooling capacity due solely to sensible heat and latent heat of vaporization. This reaction is very selective and proceeds rapidly to achieve high conversion of methylcyclohexane to toluene and hydrogen. The total heat sink for such a reaction system compares favorably with that of hydrogen, when these heat sinks are normalized by the heat of combustion of the fuel. Author

N72-11674# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Munich (West Germany). Inst. fuer Flugtreib- und Schmierstoffe.

THE POSSIBILITIES OF ACTUALLY TESTING THE COMBUSTION CHARACTERISTICS OF AVIATION FUELS WITH APPROPRIATE EQUIPMENT

H. Gemperlein *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 11 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Small-scale combustion chamber rigs are described, with which combustion characteristics of aviation fuels are being tested. The relationship of the chemical constitution of the fuels and their chemical-physical properties, and the processes during preparation and combustion of fuel is determined. Investigation is conducted at different air and fuel temperatures and at differently high pressures in the combustion chamber in a parallel flow. Temporally consecutive processes during fuel preparation and combustion may also be specially separated and thereby provide for a measurement with customary probes as well as spectroscopic methods. Author

N72-11675# Pisa Univ. (Italy). Lab. Prova Combustibili.

LOW EMISSION FUELS AND DEVICES FOR AVIATION ENGINES

G. Nardi *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Reduction of harmful emissions of turbine engine exhaust system is reviewed. The type of fuel used, combustion chambers, and operating conditions of combustors are also investigated. Author

N72-11676# National Research Council of Canada, Ottawa (Ontario). Fuels and Lubricants Lab.

FUEL CLEANLINESS

L. Gardner *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Dual purpose filter/separators were developed which could remove both dirt and water. Improvements in the performance of filter/separators was achieved by compliance with increasingly severe specifications. Methods of determining undissolved water and dirt in fuel and their development both for filter/separator testing and field use are discussed. Fuel contamination by microorganisms and surfactants has led to serious cases of aircraft corrosion and filter plugging. Measures to control or eliminate these two contaminants are discussed. Author

N72-11677# Lucas Gas Turbine Equipment, Ltd., Burnley (England).

FUEL RELATED PROBLEMS IN AIRCRAFT FUEL SYSTEMS

S. L. Forgham and R. G. Beckett *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 14 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Aircraft fuel problems are discussed, emphasizing problems associated with hydrogen treated fuels. Some of the problems were overcome by fuel system design modification, and other changes are reviewed which were instituted by refinery industries. Research on fuel sealing is also described. J.A.M.

N72-11678# BP Trading Ltd., London (England).

AIRCRAFT FUELLING OPERATIONS AND QUALITY CONTROL

G. R. Parker *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Aviation fuelling facilities and the fuelling operation are described. Comments on the types of aircraft are restricted to those aspects directly affecting fuelling. Author

N72-11679# Esso Development Co., Ltd., Abingdon (England). Research Centre.

AVIATION FUEL LUBRICITY

R. A. Vere *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

A laboratory test rig was developed to evaluate European jet fuels with regard to lubricity. This has shown differences in the lubricity levels of different fuels. Active lubricity agents were identified as fully saturated heterocyclic compounds and polynuclear aromatics. The addition of a surface active additive such as a corrosion inhibitor also significantly improve lubricity but can incur conductivity problems in the field due to its synergistic effects with antistatic additive. The feasibility of a fuel lubricity test by chemical, physical or mechanical techniques are being studied. Author

N72-11680# Applied Physics Lab., Johns Hopkins Univ., Silver Spring, Md.

FLAME INHIBITION CHEMISTRY

R. M. Fristrom and R. F. Sawyer *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety refs
(Grant NSF GI-12)

Avail: NTIS HC \$6.00/MF \$0.95

Techniques involving diverse mechanisms are employed in extinguishing flames and fires. Mechanisms were divided into two broad categories: (1) physical mechanisms when mechanical or thermal effects are dominant, and (2) chemical mechanisms when chemical effects are involved. Flame extinguishment viewed from the standpoint of the effects on the elementary reaction processes is reviewed. A simplified hydrogen-oxygen flame chemistry is used as an illustration. The complications introduced by chemical inhibition are pointed out. The chemical kinetic information in the area of hydrogen atom scavenging and oxygen flame radical recombination is surveyed. Author

N72-11681# Air Force Systems Command, Wright-Patterson AFB, Ohio. Aero Propulsion Lab.

FLAMMABILITY PROPERTIES OF JET FUELS AND TECHNIQUES FOR FIRE AND EXPLOSION SUPPRESSION

B. P. Botteri *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 11 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Results of investigative efforts to establish the practical flammability envelopes and associated combustion damage potential for conventional jet fuels such as JP-4, JP-8 (similar to JET A-1), and JP-5 under simulated hostile operating environment conditions are presented. Testing included liquid-space gunfire hits to assess external fire hazard and vertical (liquid to vapor) firing trajectories to determine explosion hazard associated with projectile-induced fuel sprays and mists. All tests were performed in instrumented replica target tanks varying in volume from 15 to 90 gallons. Principal test variables were fuel temperature, pressure, fuel depth, external void space, and internal and external air flow. All tests were conducted utilizing 0.50-caliber armor piercing incendiary projectiles. These tests indicate a considerable extension in the flammability range of all fuels compared to the equilibrium flammability limit values which are commonly utilized for fire safety analysis. In view of the fire and explosion potential exhibited by all conventional jet fuels, additional measures must be employed to achieve an effective

fire-protection capability. Progress in the use of reticulated polyurethane foam, halogenated hydrocarbon chemical extinguishants, and other fuel-tank inerting techniques is also reviewed. Author

N72-11683# Princeton Univ., N.J. Guggenheim Lab.

IGNITION OF FUELS BY A HOT PROJECTILE

O. P. Sharma and W. A. Sirignano *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 16 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Theoretical investigations were performed by approximating: (1) the flow at the forward end of the projectile to a stagnation flow towards a hot axisymmetric body, (2) the flow over its surface to a laminar flow over a hot plate, and (3) the flow in the wake of the projectile to a plane laminar mixing of the cold unreacted mixture with the hot combustion products. After the premixed mixture is exhausted, there is a possibility of ignition of unmixed reactants by the hot inert products which are left behind and are sandwiched between the oxidizer and the fuel. A theoretical analysis for the ignition delay time as a function of the temperature and the width of the hot gas region is also presented. Author

N72-11685# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Porz (West Germany). Inst. fuer Luftstrahlantriebe.

CONTRIBUTION TO THE SELECTION OF FIRE EXTINGUISHING SYSTEMS AND AGENTS FOR AIRCRAFT FIRES

R. Fiedl *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 10 p refs

Avail: NTIS HC \$6.00/MF \$0.95

A fire extinguishing-system in aircraft is described, which uses the exhaust gases of a solid-propellant gas generator to pressurize the extinguisher bottle. The extinguishing efficiency of this hot-bottle-system is compared with that of the current extinguishing system. The amount of agent which is necessary to extinguish a diffusion flame was measured for a number of halons, dry powders, and mixtures of dry powders and halons. The ability of agents to prevent reignition of the extinguished fuel surface by hot parts was also tested. Author

N72-11686# Shell Research, Ltd., Chester (England).

ELECTROSTATIC CHARGING IN THE HANDLING OF AVIATION FUELS

H. Strawson and A. Lewis *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 11 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Electrostatic charging of the fuel during fueling can result in the possibility of incendiary sparking in aircraft tanks; some of the more recent experimental results on the different phases of this process are presented. These results confirm that, in the absence of special precautions, discharges creating a tank explosion hazard can exist during aircraft refueling in certain circumstances. Unless the fuel conductivity is controlled, however, these hazardous circumstances cannot be precisely predicted. The use of a static dissipator additive eliminates the hazard. Methods of introducing the additive and of maintaining the correct conductivity during fuel distribution are discussed, as well as possible side effects and interactions with other fuel additives. On the basis of world-wide airline use over many years, supported by many laboratory tests, it is concluded that the additive provides a safe, simple and trouble-free solution to the problem. Author

N72-11687# National Aviation Facilities Experimental Center, Atlantic City, N.J.

CRASH SAFE TURBINE FUEL DEVELOPMENT BY THE FEDERAL AVIATION ADMINISTRATION, 1964 - 1970

R. A. Russel, Jr. *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 10 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Crash-safe fuel program, a segment of a primary mission to improve the overall crashworthiness of aircraft, is discussed. The reduction of the probability and severity of fire during aircraft ground crash situations is also examined. Author

N72-11688# Southwest Research Inst., San Antonio, Tex. Army Fuels and Lubricants Research Lab.

EMULSIFIED FUELS AND AIRCRAFT SAFETY

W. D. Weatherford, Jr. and F. W. Schaekel (Army Coating and Chem. Lab.) *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs

(Contracts DAAD05-70-C-0250; DAAJ02-69-C-0030)

Avail: NTIS HC \$6.00/MF \$0.95

Research and development program aimed at improving the post-crash fire safety of helicopter turbine-engine fuels is reviewed. Primary emphasis was placed on high-internal-phase-ratio aqueous emulsions. Interrelations among rheological and physical properties, composition, and fire safety characteristics of various fuel formulations are discussed. Implications of these results on the total safety envelope of rotary wing aircraft are examined. Author

N72-11689# Bureau of Mines, Pittsburgh, Pa. Mining and Safety Research Center.

FIRE HAZARD EVALUATION OF THICKENED AIRCRAFT FUELS

J. M. Kuchta, J. N. Murphy, A. L. Furno, and A. Bartkowiak *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 11 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Various gelled or emulsified fuels were proposed for reducing the aircraft crash-fire hazard. Results are presented from bench-scale tests for screening the fuels and from large-scale drop tests for evaluating their fire hazard under simulated crash conditions. Jet A and Jet B type thickened fuels were investigated. Their minimum autoignition temperatures and burning rates varied little, whereas their flash points, volatility rates, self-spread rates, and flame spread rates varied noticeably with either the base fuel or thickening agent composition; minimum ignition energies are also compared for liquid sprays. The performance of the thickened fuels, particularly Jet B emulsions, was not very promising under impact conditions. In fuel drops made from a 150-ft three-tower facility, the fireball size and radiation intensity varied with impact velocity, impact angle, and type of fuel container. Author

N72-11690# Royal Aircraft Establishment, Farnborough (England). Engineering Physics Dept.

FIRE AND EXPLOSION PROTECTION OF FUEL TANK ULLAGE

J. A. MacDonald and H. W. G. Wyeth *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 7 p refs

Avail: NTIS HC \$6.00/MF \$0.95

The conditions that can lead to an explosion within aircraft fuel tank ullages are examined, and the need for protection systems is reviewed. Principles employed in providing the desired degree of protection are outlined, such as oxygen reduction, vapor or mist inerting, and plastic foam fillers. Comparisons were made between the various systems, and their relative merits were also discussed. It is concluded that plastic foam is an effective system provided that the material is compatible with the environment. Liquid nitrogen is also attractive from the weight aspect but could impose logistic problems. Author

N72-11691# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Porz (West Germany). Inst. fuer Luftstrahlantriebe.

INVESTIGATION OF FIRE EXTINGUISHING POWDERS BY MEANS OF A NEW MEASURING PROCEDURE

R. Fieda and G. Winterfeld *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs

Avail: NTIS HC \$6.00/MF \$0.95

In order to optimise fire extinguishing systems it is necessary to compare the extinguishing efficiency of solid and gaseous (or liquid) extinguishing agents. A measuring procedure is described which allows this direct comparison. It makes use of the relationship between the maximum flow velocity at the burning limit of a flame-holder stabilized flame and the laminar burning velocity of the fuel-air-mixture which is given by DAMKOHLER's first number. Comparative results achieved with this procedure for several fire extinguishing agents are given. Author

N72-11692# Royal Aircraft Establishment, Farnborough (England). Materials Dept.

SIMULATED CRASH TESTS AS A MEANS OF RATING AIRCRAFT SAFETY FUELS

R. E. Miller and S. P. Wilford *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Two tests are described for assessing the fire resistance of Avtur containing polymeric additives which reduce its ability to form flammable mists. In the standard test a tank containing ten or twenty gallons of fuel is propelled on a rocket sled at speeds of 114 or 188 ft/sec and decelerated after contact with an aircraft arrester wire. Fuel is allowed to spill from a slit in the tank onto a series of ignition sources. In the run on test the tank travels at speeds up to 240 ft/sec past a series of ignition sources while spilling fuel from a slit on the leading edge. The velocities of spilled fuel relative to the surrounding air which occur in these tests are shown to be comparable to those occurring during survivable aircraft crashes. Author

N72-11693# Applied Physics Lab., Johns Hopkins Univ., Silver Spring, Md.

SURFACE ACTIVE CONSIDERATIONS IN FUEL FIRES

Richard L. Tuve *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 4 p refs

Avail: NTIS HC \$6.00/MF \$0.95

The problem of efficient extinguishment of fires in burning fuels is dealt with. The use of low density water, in the form of foam, is considered as a means of achieving some solutions to the mechanical and physical needs involved. Emphasis is placed on the utilization of fluorocarbon surfactants which combine foam requirements and fuel-water interfacial activities benefitting fire extinguishing action. Recent development and test of these materials are discussed. D.L.G.

N72-11694*# General Electric Co., Cincinnati, Ohio. Material and Process Technology Labs.

LUBRICANT AND FUEL INTERACTIONS IN ADVANCED AIRCRAFT GAS TURBINES

E. N. Bamberger, D. B. Hester, and M. W. Shaysen *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p refs Sponsored in part by NASA, AFAPL, and FAA

(NASA-CR-122842) Avail: NTIS CSCL 11H

The interactions and relationships between lubricants and fuels and their properties as related to systems in aircraft gas turbine engines are dealt with. Three areas of recent research are cited to illustrate the impact of lubricant and fuels capabilities on

modern engines: (1) a study of the influence of lubricant properties on turbine engine design characteristics, especially with regard to high speed supersonic applications, (2) the development of a precise and meaningful test procedure for measuring the thermal stability of kerosene fuels, and (3) the evaluation of advanced high temperature lubricating fluids and their effects on engine bearing performance. Author

N72-11695# Esso Development Co., Ltd., Abingdon (England). Research Centre.

STABILITY OF SYNTHETIC AVIATION GAS TURBINE LUBRICANTS AT HIGH TEMPERATURES

R. Robson *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 8 p refs

Avail: NTIS HC \$6.00/MF \$0.95

The development of ester based synthetic aviation lubricants over the last 20 years is reviewed. Methods of assessing the high temperature stability of the lubricants are described and the main factors controlling stability are discussed. The suitability of alternative synthetic fluids is considered. Author

N72-11696# Institut Francais de Petrole, Grenoble (France).

SYNTHESIS AND PROPERTIES OF ESTERS OF TETRA-METHYL-2,2-7,7 OCTANE DIOL-1,8 [LES ESTERS DU TETRA METHYL-2,2-7,7 OCTANE DIOL-1,8 SYNTHESE ET PROPRIETES]

P. Badague, B. Sillion, and G. DeGaudemaris *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 8 p refs *In* FRENCH

Avail: NTIS HC \$6.00/MF \$0.95

A diol of the neopentyl type was obtained by a series of simple reactions proceeding from cyano-4 dimethyl-2,2 butyraldehyde. Esters of linear acids and alpha alpha prime dimethylated acids were synthesized. Their physical characteristics were determined. Thermal stability and resistance to hydrolysis and oxidation in the presence of metals were examined.

Transl. by K.P.D.

N72-11697# Rolls-Royce, Ltd., Bristol (England). Engine Div. **LUBRICANT EXPERIENCE AND DUTIES IN A CIVIL SUPERSONIC GAS TURBINE ENGINE** c15

E. W. Doherty *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 12 p ref

Avail: NTIS HC \$6.00/MF \$0.95

A description is presented of the Olympus 593 Mk 602 oil system generally, and particular reference is given to the design precautions against the oil fire risk, the use of oil in engine failure warning devices, and in engine health monitoring. Current engine test and flight experience with the lubricant is covered especially with respect to oil consumption, high temperature breakdown areas, prevention of oil carbon formation, mixing of lubricants brands, erosion/corrosion effects, and policy in approval processes of lubricants. Author

N72-11698# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Munich (West Germany). Inst. fuer Flugtrieb- und Schmierstoffe.

EARLY STAGE DETECTION OF OIL CHANGES IN AIRCRAFT ENGINES c15

E. Jantzen *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Potential analytical methods for detection of changes in aircraft turbine oils in the early state are reported and their possible advantages and disadvantages as well as their informative value are discussed. In addition, the cause of premature or sudden oil changes in an aircraft engine is investigated. A test rig for simulating such oil changes and the results obtained are discussed. In conclusion, the possibilities of a simultaneous wear control of aircraft turbine oils are briefly explained. Author

N72-11699# Office National d'Etudes et de Recherches Aerospatiales, Paris (France).

THERMAL STABILITY OF A TRI-METHYL-PROPANE ESTER BASED LUBRICATING OIL [CHAMP D'APPLICATIONS D'UNE HUILE BASEE SUR UN ESTER DU TRIMETHYLOL-PROPANE]

F. Reynaud *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 22 p refs *In* FRENCH; ENGLISH summary

Avail: NTIS HC \$6.00/MF \$0.95

Following a general discussion on the increased performance requirements of lubricating oils made mandatory by increased operating temperatures, the operational possibilities of a tri-methyl-propane ester in two domains of application are described. The first area of application considered was a conventional circuit with oil temperature around 230 C. By adding appropriate additives, a formula was developed with very satisfactory characteristics, particularly in regard to oxidation corrosion. The second area of usage studied was at the 380 C level. The formula appeared not to be well adapted to the new conditions, with some additions losing their efficiency. However the ester remained valid as a base. D.L.G.

N72-11700# Air Force Systems Command, Wright-Patterson AFB, Ohio. Aero Propulsion Lab.

SOLID LUBRICATION FOR AERO PROPULSION SYSTEMS

M. R. Chasman *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 13 p refs

Avail: NTIS HC \$6.00/MF \$0.95

Self contained solid lubricated bearings were developed for application to current and future aircraft propulsion and power generation equipment. The capability for long life operation over a wide range of temperatures in an air environment was demonstrated. The approach was to use solid lubricants as a sacrificial retainer material in 20 mm and 35 mm bore bearings. In some cases stainless steel and titanium shrouds were used to provide added strength to the solid lubricant retainers. Lubricants were selected based on their strength, oxidation, friction, and wear properties. It was necessary to deviate from oil and grease lubricated bearing design to achieve acceptable life. Bearing clearance, number of balls, retainer to land clearance, and ball pocket size were optimized. Hundreds, and in some cases thousands, of hours of life were demonstrated. Author

N72-11701# BP Benzin und Petroleum AG, Munich (West Germany).

SYNTHETIC LUBRICANTS FOR SUPERSONIC AIRCRAFT

H.-D. Dorn *In* AGARD Aircraft Fuels, Lubricants, and Fire Safety Aug. 1971 6 p

Avail: NTIS HC \$6.00/MF \$0.95

Classifications and characteristics of synthetic aero turbine oils are reviewed. These oils are classified as type 1 and type 2 lubricants. The type 1 lubricants are defined as blends of a diester basestock and an additive package. Although still being used in jet engines, their use in advanced turbines is considered to be limited by marginal resistance to thermal and oxidative stress. Type 2 lubricants, developed to meet the increased requirements of more sophisticated aircraft, are defined as blends of a hindered tri- or tetraester basestock and an additive package. The burden placed on these lubricants by sustained flight at supersonic speeds is discussed, and the development of an advance complex ester lubricant with a novel additive package for Mach 2 + engines is reported. D.L.G.

N72-11706# Phillips Petroleum Co., Bartlesville, Okla. Research and Development Dept.

EFFECT OF VERY LOW SULFUR IN JP-5 FUEL ON HOT CORROSION

Robert M. Schirmer and Harold T. Quigg 20 May 1971 33 p refs Presented at the 10th Natl. Conf. on Environ. Effects on

Aircraft and Propulsion Systems, Trenton, 18-20 May 1971:
Sponsored by Naval Air Propulsion Test Center
(AD-725819) Avail: NTIS CSCL 20/4

The report discusses an investigation to determine whether the present limit of 0.4 percent by weight (4000 ppm) of sulfur in JP-5 fuel is a safe level for the protection of turbine-blade materials from hot corrosion in high-performance engines when operated in a marine environment. The present study shows that a 100-fold reduction in the sulfur limit to 40 ppm would not reduce hot corrosion significantly. Such reductions in the sulfur limit would drastically curtail fuel availability, since they approach the mean and the minimum of current production, and could cause critical problems in logistics. It was found that the use of an essentially sulfur-free fuel, containing only 4 ppm sulfur, significantly decreased both the surface scale on specimens and the weight lost by specimens of a wide variety of superalloys and superalloy-coating systems when exposed under conditions which simulate those in an aircraft-turbine engine ingesting air with 1 ppm sea salt. Thus, indications are that the sulfur in fuel must be below a 'threshold' concentration to improve the durability of turbine-blade materials. Author (GRA)

N72-11711*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

FLIGHT INVESTIGATION OF AIRFRAME INSTALLATION EFFECTS ON AN AUXILIARY INLET EJECTOR NOZZLE ON AN UNDERWING ENGINE NACELLE

Richard R. Burley Washington Nov. 1971 71 p refs
(NASA-TM-X-2396; E-6208) Avail: NTIS CSCL 21E

The local flow field approaching an installed nozzle may vary from isolated test conditions, thereby affecting exhausting nozzle performance. An installation of general interest is a podded engine mounted near the aft lower surface of the wing. The effect of this installation on the performance of an auxiliary inlet ejector nozzle was investigated over a Mach number range of 0.7 to 1.3 by using a modified F-108B aircraft. Both floating and fixed-open door configurations were examined. The ejector nozzle trailing-edge flaps were simulated in the closed position with rigid structure which provided a boattail angle of 15 deg. Primary nozzle area was varied as exhaust gas temperature was varied between 982.2 and 2003.3 K. Author

N72-11713# Pratt and Whitney Aircraft, West Palm Beach, Fla. Florida Research and Development Center.

INVESTIGATION OF FEASIBILITY OF INTEGRAL GAS TURBINE ENGINE SOLID PARTICLE INLET SEPARATORS. PHASE 2: FEASIBILITY DEMONSTRATION Final Report

William J. McAnally, III and Max T. Schilling Fort Eustis, Va. Army Air Mobility Res. and Develop. Lab. Apr. 1971 65 p refs

(Contract DAAJ02-70-C-0003; DA Proj. 1-G-162207-AA-71)
(AD-725593; PWA-FR-4197; USAAVLABS-TR-71-13) Avail: NTIS CSCL 21/5

Two different sand and dust particle separator test rigs were fabricated and tested to evaluate separation efficiency, aerodynamic performance characteristics, and operation in rain and foliage ingestion conditions. The semi-reverse-flow separator utilized fixed turning vanes on a contoured hub to induce swirl in an annular duct. At design airflow of 8 lb/sec and 40% scavenge flow, the semi-reverse-flow separator demonstrated 88.5% separation efficiency with AC coarse test dust at an average pressure drop of 2.8 in. H₂O. The powered mixed-flow separator attempted to utilize the strong centrifugal field available in a mixed-flow impeller turning at the high speeds characteristic of small gas turbine engines to achieve particle separation. At the design airflow of 8 lb/sec, it demonstrated a maximum separation efficiency of 58.7% with 8.4% scavenge flow and an average pressure rise of 6.76 psi. Both separator concepts were determined to be feasible and the semi-reverse-flow separator is considered to be superior to current engine air particle separators for the majority of aspects investigated. Author (GRA)

N72-11714# Cornell Aeronautical Lab., Inc., Buffalo, N.Y.
A STUDY OF NOISE GENERATION BY A ROTATING BLADE ROW IN AN INFINITE ANNULUS Interim Scientific Report, 7 Jul. 1969 - 31 Mar. 1971

John A. Lordi May 1971 73 p refs
(Contract F44620-69-C-0130; AF Proj. 9781)
(AD-728126; CAL-AI-2836-A-1; AFOSR-TR-71-1485) Avail: NTIS CSCL 13/1

Discrete-tone noise generation by high-speed fans and compressors has been studied by applying existing theories for the flow through a rotating blade row in an infinitely long annulus. McCune's analysis for the linearized, three-dimensional, compressible flow through a nonlifting blade row and its recent extension to lifting blades have both been used to find the acoustic disturbances produced by such flows. These analyses contain the cutoff condition for the duct acoustic modes, including the effect of through flow, and relate the amplitudes of the propagating modes to the blade thickness and loading. In the present work these relationships have been evaluated for some specific thickness and loading distributions to find the pressure and velocity fields away from the blade row. Methods have been developed to calculate the sound intensity flux upstream and downstream of the blade row and results are presented which demonstrate the influence of blade geometry and operating conditions on noise generation. Author (GRA)

N72-11803*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

ELECTRONIC STRAIN LEVEL COUNTER Patent Application Felix L. Pitts and John L. Spencer, inventors (to NASA) Filed 8 Jul. 1971 12 p
(NASA-Case-LAR-10756-1; US-Patent-Appl-SN-160859) Avail: NTIS CSCL 20K

An electronic strain-level counter for obtaining structural strain data on in-flight aircraft is described. The device counts the number of times the strain at a point on a structural member of the aircraft exceeds each of several preset levels. A dead band is provided at each level to prohibit the counting of small strain variations around a given preset level. NASA

N72-11820# Grumman Aerospace Corp., Bethpage, N.Y.
AN AUTOMATED PROCEDURE FOR THE OPTIMIZATION OF PRACTICAL AEROSPACE STRUCTURES. VOLUME 1: THEORETICAL DEVELOPMENT AND USER'S INFORMATION Final Report, 15 Jan. 1969 - 15 Aug. 1970

Walter J. Dwyer, Robert K. Emerton, and Irving U. Ojalvo Wright-Patterson AFB, Ohio AFFDL Apr. 1971 208 p refs
(Contract F33615-69-C-1278; AF Proj. 5710)
(AD-728112; ADR-02-01-71-Vol-1; AFFDL-TR-70-118-Vol-1) Avail: NTIS CSCL 01/3

The report documents the development of a new structural optimization algorithm, which is a combination of a modified fully stressed design technique and a redesign procedure based on gradients to deflection constraint surfaces. The algorithm is incorporated into a large finite element program based on the displacement method of structural analysis. Using an IBM 360/75 computer, the program is capable of obtaining near optimum distributions of material for structural idealizations consisting of up to three thousand elements and six thousand degrees of freedom, and subjected to a maximum of twenty loading conditions. Constraints may be placed on the maximum and minimum size of any of the elements, on the stresses in the elements, and on the displacements of the nodal points of the structure. Several examples of structures that were optimized are included to demonstrate the various features of the program, and to compare results with previously obtained solutions. To help make the program useful in the design of major aircraft structures, care has been taken to simplify the input and to present the program output in a form that is meaningful to the aircraft stress engineer. Results of an exploratory investigation into the optimization of dynamically loaded structures are presented, and the conversion of two existing blast-response shell codes into a unified synthesis program is documented. Author (GRA)

N72-11845

N72-11845*# Boeing Co., Seattle, Wash.
STUDY OF AIRCRAFT IN INTRAURBAN TRANSPORTATION SYSTEMS, SAN FRANCISCO BAY AREA
Sep. 1971 541 p refs
(Contract NAS2-59889)
(NASA-CR-114347) Avail: NTIS HC \$6.00/MF \$0.95
CSCL 05C

The nine-county San Francisco Bay area is examined in two time periods (1975-1980 and 1985-1990) as a scenario for analyzing the characteristics of an intraurban, commuter-oriented aircraft transportation system. Aircraft have dominated the long-haul passenger market for some time, but efforts to penetrate the very-short-haul intraurban market have met with only token success. Yet, the characteristics of an aircraft transportation system-speed and flexibility-are very much needed to solve the transportation ills of our major urban areas. This study attempts to determine if the aircraft can contribute toward solving the transportation problems of major metropolitan areas and be economically viable in such an environment. Author

N72-11849# RAND Corp., Santa Monica, Calif.
PROCEEDINGS OF A CONFERENCE ON REGIONAL TRANSPORTATION PLANNING
Joseph S. Desalvo, ed. May 1971 526 p refs Conf. held at Santa Monica, Calif., 25-27 Jan. 1971
(Contract DOT-OS-00074)
(PB-200076; R-706-DOT; DOT-OS-00074) Avail: NTIS HC \$6.00/MF \$0.95 CSCL 13B

The conference explored the idea that some form of transportation planning entity should be created between two existing levels of planning-the national level and individual states or smaller jurisdictions. The issue was to consider the advantages and disadvantages, in economic and administrative terms, of conducting transportation planning on a regional basis.

Author (GRA)

N72-11850# Center for Naval Analyses, Arlington, Va. Inst. of Naval Studies.

THE VALUE OF TIME IN AIR TRAVEL: THEORY AND EVIDENCE

Arthur S. DeVany Apr. 1971 45 p refs
(Contract N00014-68-A-0091)

(AD-725480; Contrib-162) Avail: NTIS CSCL 15/5

The roles of time and money cost in the demand for air travel are analyzed. The first step is to construct the theory of consumer demand under a time constraint and to deduce its theorems. Then these theorems are applied to air travel through use of a total price demand function. This analysis considers the effects of fare, trip time, airport delay, schedule frequency, trip distance, traveler's wage rates, and non-wage income on the demand for air travel. Many results concerning elasticities are obtained, including a necessary relationship between the time, price, and total price elasticities of demand. Tests of the theorems are performed, the various elasticities are estimates, and the relationship between the elasticities required by the theory is used to obtain an estimate of the value of time in air travel.


Author (GRA)

SUBJECT INDEX

AERONAUTICAL ENGINEERING / *A Special Bibliography (Suppl. 15)*

FEBRUARY 1972

Typical Subject Index Listing



The subject heading is a key to the subject content of the document. The Notation of Content (NOC), rather than the title of the document, is used to provide a more exact description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the Notation of Content, e.g., N72-11043. Under any one subject heading, the accession numbers are arranged in sequence with the IAA accession numbers appearing first.

A

A-300 AIRCRAFT

European A300B airbus flying control hydraulic system and landing gear design for safety and reliability, fatigue life, weight and maintenance
A72-10724

European A300B airbus flap and slat systems and tailplane actuator for longitudinal pitch trim control
A72-10725

ACCELERATION (PHYSICS)

Maneuver acceleration measured for estimating loads during civil aircraft training and test flying
[ARC-CP-1176] N72-11043

ACCELEROMETERS

Passenger aircraft onboard automated inertial navigation devices, emphasizing accelerometer and gyroscope design and construction
A72-10070

Mathematical models of rate gyros, servo accelerometers, pressure transducers, and telemetry systems and analog computer simulation programs
[NASA-CR-1768] N72-10401

ACOUSTIC ATTENUATION

Liquid-base foam sound absorbing properties for jet aircraft noise reduction
A72-10160

ACOUSTIC MEASUREMENTS

Portable detector-recorder for automobile, blast furnace, railroad car, engine room and helicopter infrasonic noise measurements, discussing peak frequencies and subjective effects
A72-10157

Acoustic echo sounder as real time monitor of airport environmental meteorological parameters
A72-11137

Aircraft engine noise effects in airport vicinities, discussing measurement scales, turbofan sources, noise reduction and future air traffic
A72-12022

Incremental value of noise pollution level as basis for aircraft noise rating
[NPL-AERO-AC-49] N72-10035

ACOUSTICS

Annotated bibliography on acoustics
[NPL-AERO-AC-47] N72-10589

ADAPTIVE CONTROL

Application of linear mathematical model to represent human operator performance in controlling attacking fighter aircraft
[AD-725069] N72-10042

ADDITIVES

Viscosity and additive effects on jet engine fuel antiwear properties improvement
A72-11968

AERIAL RECONNAISSANCE

Aerial expedition for studying conditions of atmospheric boundary layer over oasis and seniarid region
[AD-727535] N72-10332

AERODYNAMIC BRAKES

Parachute designs and applications to escape systems, paratrooping, supply dropping, aircraft braking, weapons systems stabilization, flight testing aids and sport
A72-10302

AERODYNAMIC CHARACTERISTICS

Nonporous rigid parachute models three component measurements, using low speed wind tunnel for testing skirt length effects on aerodynamic characteristics
A72-10303

Aerodynamic behavior of thin jet-flapped airfoil, investigating integrodifferential equation solution
A72-11669

Aircraft spin characteristics due to superstall, comparing three stall types with respect to recovery, yaw damping and rate of rotation
[DGLR PAPER 71-057] A72-12718

Unsolved aerodynamic problems in sub- and transonic civil and military aircraft design, considering flow problems during transonic flight, takeoff and landing
[DGLR PAPER 71-105] A72-12745

Tip clearance effect on compressor blade aerodynamic characteristics, applying Bolyay analysis to low aspect ratio rectangular wing
A72-12825

Static and dynamic stability characteristics of finned bodies with cruciform, slotted fin configuration
[AD-728016] N72-10003

Impinging inclined jet effect on aerodynamic characteristics of control surface in VTOL longitudinal stability
N72-10011

Aerodynamic characteristics of wind tunnel model of hypersonic aircraft
[NASA-TN-D-6577] N72-10045

Aerodynamic characteristics of helicopters and principles of helicopter flight
[AD-726841] N72-10046

Aerodynamic and aeroelastic characteristics of rigid two-bladed rotor system with full-scale rotor operating at very high advance ratios and during start/stop operation
[AD-727653] N72-11050

Analysis of helicopter tail rotor flow patterns in and out of ground effect
[AD-725591] N72-11060

Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions
[NASA-TN-D-6530] N72-11289

Analysis of interaction of oblique shock with bow shock of blunt leading edge and application to design of hypersonic ramjet inlets
[AD-726111] N72-11312

In-flight investigation of installation effects and aerodynamic characteristics of local flow field on auxiliary inlet ejector nozzle on underwing engine nacelle
[NASA-TN-X-2396] N72-11711

Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic

- performance
[AD-725593] N72-11713
- AERODYNAMIC COEFFICIENTS**
- Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts A72-10220
- Aircraft stability coefficient determination by numerical integration fitting to differential equations of motion A72-11136
- Area rule for change in lift/drag ratio of hypersonic delta wing due to conical body addition on compression side A72-12270
- Jet aircraft brake parachute loads under engine wake, evaluating velocity and drag coefficient influences A72-12504
- Wing-fuselage combination aerodynamic coefficients, comparing experimental data with subsonic linear and nonlinear theoretical results [DGLR PAPER 71-115] A72-12723
- Conference papers on jet and slipstream influence on aerodynamic coefficients using aircraft models [DLR-MITT-70-28] N72-10004
- Vertical takeoff aircraft wind tunnel model with high pressure ejectors to determine jet interference on aerodynamic coefficients N72-10007
- Influence of jet interference on aerodynamic coefficients of rectangular and swept wings mounted above the engine N72-10010
- AERODYNAMIC CONFIGURATIONS**
- Equilibrium configuration of cable towed in circular path, presenting multivalued boundary value problem mathematical analysis A72-11132
- Wing-fuselage combination aerodynamic coefficients, comparing experimental data with subsonic linear and nonlinear theoretical results [DGLR PAPER 71-115] A72-12723
- Static and dynamic stability characteristics of finned bodies with cruciform, slotted fin configuration [AD-728016] N72-10003
- Design programs for swept wings in subcritical, compressible, viscous flow [NPL-AERO-NOTE-1100] N72-10018
- Performance of axial flow compressor rotor with different casing treatment configuration [NASA-TN-D-6538] N72-10025
- Variable geometry rotor system for direct control over wake vortex [NASA-CASE-LAR-10557] N72-11018
- AERODYNAMIC DRAG**
- Axial cords effects on parachute drag and stability characteristics and opening time, discussing wind tunnel and balloon drop tests results A72-10306
- Parachutes flow characteristics in low speed free descent, discussing glide angle effect on total drag and water channel flow pattern studies A72-10309
- Parachute opening shock and filling time calculation based on aerodynamic drag, air mass and effective porosity time functions, using momentum and continuity equations A72-10310
- Helicopter rotor tip drag relief estimate based on two dimensional drag divergence with Mach number, airfoil parameters and flight conditions A72-12882
- Vortex drag factor of untapered swept wing with part-span flap, noting spanwise loading [NPL-AERO-1324] N72-11011
- AERODYNAMIC FORCES**
- Aerodynamic forces and pressure distribution measurement on wing-body combination model, investigating boundary layer on wing upper surface A72-12228
- European airbus wind tunnel model aerodynamic force and downwash measurements noting jet interference reduction N72-10012
- Aerodynamic lift characteristics of oscillating two dimensional airfoil subjected to sinusoidal gust [AD-726132] N72-11017
- AERODYNAMIC HEATING**
- Constant high tensile stress and rapid aerodynamic heating effect on maraging steels and Ti and Al alloys, evaluating test and simulation procedures for design data development A72-10749
- AERODYNAMIC LOADS**
- Parachute inflation loads and times, presenting calculation method based on unsteady pressure distribution on decelerating inflating parabolic shell of revolution with unsteady starting vortex A72-10311
- Matrix method calculation for aerodynamic loads, transverse forces, bending moments, torques and twist of hinged main rotor blades in helicopter during forward flight A72-12440
- AERODYNAMIC NOISE**
- Mathematical models for studying incoherent and coherent structures of aerodynamically generated noise [ONERA-TP-983] N72-11036
- Calibration of pressure sensors used to measure aerodynamic noise [ONERA-TP-982] N72-11368
- AERODYNAMIC STABILITY**
- Axial cords effects on parachute drag and stability characteristics and opening time, discussing wind tunnel and balloon drop tests results A72-10306
- Paratroop type parachutes breathing oscillations and stability characteristics, using high speed cinematography and kinetheodolites to track during steady state descent A72-10307
- AERODYNAMIC STALLING**
- Aircraft spin characteristics due to superstall, comparing three stall types with respect to recovery, yaw damping and rate of rotation [DGLR PAPER 71-057] A72-12718
- AEROELASTICITY**
- Aeroelastic models construction for flutter analysis of aircraft design, noting error risk reduction [DGLR PAPER 71-082] A72-12722
- AERONAUTICAL ENGINEERING**
- Theoretical performance of jet flap rotor at advance ratios greater than 1.0 [AD-726706] N72-10037
- AEROSPACE INDUSTRY**
- Industrial parachute R and D in UK, discussing management, technical staff requirements and government/industry liaison A72-10304
- Aerospace wire and cables testing methods standards for evaluating mechanical, electrical and chemical properties, coating thicknesses, continuity flaws, flammability, geometrical characteristics, etc [SAE-AS-1198] A72-10384
- AEROSPACE MEDICINE**
- German Research and Test Institute for Aero- and Astronautics 1970 report covering flow mechanics, power conversion, aerospace medicine, atmospheric physics, etc A72-11151
- AEROSPACE SYSTEMS**
- Electronics and aerospace systems - IEEE Conference, Washington, D.C., October 1971 A72-12376
- Cost analysis and economic models for European aerospace development compared to US experience [AD-725478] N72-10992
- AFTERBURNING**
- Recirculation mechanism in jet powered V/STOL aircraft [BMVG-PBWT-71-12] N72-10828
- AIR CONDITIONING EQUIPMENT**
- Soviet book on civil aircraft high altitude equipment covering air conditioning systems, oxygen equipment and cabin pressurization A72-12295
- AIR CURRENTS**
- Techniques for forecasting turbulent weather conditions below 10,000 feet for light aircraft operating in Hawaiian Islands [AD-726107] N72-11525
- AIR FILTERS**
- Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic performance

- [AD-725593] N72-11713
- AIR FLOW**
- Gas turbine nozzles aerodynamic throat area air flow measurement, describing accuracy, standards, reference nozzles and mounting flanges [SAE-ARP-1195] A72-10390
- Real gas effects in atmosphere to make sonic bang shock wave full dispersion and thickness wide variations A72-11972
- AIR NAVIGATION**
- ATC separation minima and navigational errors on airways in general and long range oceanic environments A72-10177
- Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques A72-10180
- Stellar attitude reference and navigation associative processor with high computational speed for radar approach control in ATC A72-12033
- Optimal stochastic /Kalman/ filters application to integrated air and submarine navigation systems, discussing measurement errors modeling as bias and colored noise A72-12050
- L band in satellite system for aerial navigation aid, discussing position accuracy, data transmission and voice communication and modulation methods A72-12642
- Radio aids for air navigation and traffic control in Italy, discussing facilities development A72-12748
- Doppler system with navigation radar device, computer unit and data transmitter for continuous recording of aircraft position and speed A72-12749
- Analysis of target signal requirements for aircraft navigation systems using millimeter wave radiometry from terrain radiation or ground-based beacons [NASA-TM-X-62082] N72-10539
- AIR POLLUTION**
- Aircraft activity effects on air pollution in San Francisco Bay area with engine emission and climatological data N72-10361
- AIR TRAFFIC**
- Future aircraft design trends for transcontinental and short haul operation, considering traffic forecasts, current transport aircraft and potential derivatives and technology [SAE PAPER 710749] A72-10248
- Pilot collision warning indicator performance in terminal area traffic, using computer fast-time simulation for traffic model A72-11134
- German Federal Republic territorial air traffic regulations covering general, VFR and IPR rules, equipment and personnel examination and certification, safety, takeoff and landing, accidents, etc A72-12621
- German book on air traffic law covering norms relative to vehicles and air space, international air law, organizations, etc A72-12622
- AIR TRAFFIC CONTROL**
- ATC separation minima and navigational errors on airways in general and long range oceanic environments A72-10177
- Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques A72-10180
- Automated radar terminal system /ARTS/ for monitoring and tracking all aircraft within radar range, displaying identification, altitude and ground speed information to air traffic controller A72-10960
- Phased scanning array for ATC radar beacon systems, airport or air route surveillance radars and ground landing systems A72-10962
- Inertial navigation role in automatic ATC systems, discussing path control accuracies, environmental conditions, noise and air pollution, etc A72-11119
- ATC system decision making problem and future technological and administrative improvements A72-11718
- Stellar attitude reference and navigation associative processor with high computational speed for radar approach control in ATC A72-12033
- Discrete address ATC radar beacon system operation and design A72-12378
- FAA air traffic control automation program, discussing en route stage, computer program, data processing and storage and terminal area navigation and display techniques A72-12380
- Uhf aeronautical satellite system, presenting ATC trends, international aspects, available flight levels, weather conditions and long haul conflicts A72-12383
- Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities A72-12420
- Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar A72-12421
- Digital computer memory system for real time processing of air and naval traffic data, discussing logic design, time comparisons and optimum use A72-12647
- ATCAS air traffic control automation system emphasizing Italian situation A72-12649
- Radio aids for air navigation and traffic control in Italy, discussing facilities development A72-12748
- Air traffic control radar beacon systems and laser warning systems [AD-725743] N72-10543
- AIR TRANSPORTATION**
- Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention A72-11117
- STOL aircraft for solving noise reduction and land use problems in future transportation systems, discussing airport location and layout for growing air traffic A72-11153
- General and commercial aircraft service needs in air transportation, considering FAA and CAB roles and policies A72-11716
- Short haul air transport system need for future short takeoff and landing aircraft, considering airports, airways, economics and navigation and landing aids A72-11719
- Civil aviation air transportation contributing factors to American economy, considering disposable income, airline fares and time-trend variable A72-11721
- Cost analysis and operational procedures of effective short range, high density computer transportation system for Metropolitan Detroit [NASA-CR-114340] N72-10984
- Graphs and tables of service cost for intraurban transportation system [NASA-CR-114341] N72-10985
- Aircraft design concepts for intraurban transportation system [NASA-CR-114342] N72-10986
- Analysis of economic and feasibility factors pertaining to commuter oriented, short haul air transportation system in San Francisco, California area [NASA-CR-114347] N72-11845
- Roles of time and money cost in demand for air travel [AD-725480] N72-11850

AIRBORNE EQUIPMENT

SUBJECT INDEX

AIRBORNE EQUIPMENT

Army data analysis system for fixed and rotary wing aircraft flight testing, including airborne and computer controlled ground stations equipment
A72-12408

Basic requirements for airborne infrared forest fire detection system
[AD-726953] N72-10396

Electronic strain-level counter for in-flight aircraft
[NASA-CASE-LAR-10756-1] N72-11803

AIRBORNE/SPACEBORNE COMPUTERS

Doppler system with navigation radar device, computer unit and data transmitter for continuous recording of aircraft position and speed
A72-12749

AIRCRAFT

Variable-orifice gas turbine system for fuel rate control in aircraft
[NASA-CASE-LEW-11187-1] N72-10824

AIRCRAFT ACCIDENT INVESTIGATION

Statistical analysis of home built aircraft accidents
[PB-201438] N72-10038

Statistical analysis of weather effects in aircraft accidents
[PB-201437] N72-10039

Briefs of US general aviation accidents involving corporate/executive aircraft in 1968
[PB-201439] N72-11052

AIRCRAFT ACCIDENTS

Statistical analysis of home built aircraft accidents
[PB-201438] N72-10038

Statistical analysis of weather effects in aircraft accidents
[PB-201437] N72-10039

Reports of accidents involving missing aircraft of US general aviation for 1968
[NTSB-AMM-71-4] N72-10041

Report of aircraft accident involving DC-9 aircraft at Gulfport, Mississippi on February 17, 1971
[NTSB-AAR-71-14] N72-10049

AIRCRAFT ANTENNAS

Helicopter antenna placement, using scale models for three dimensional radiation pattern semiautomatic recording under free space conditions
A72-10149

AIRCRAFT APPROACH SPACING

ATC separation minima and navigational errors on airways in general and long range oceanic environments
A72-10177

Mathematical analysis of separation standards and aircraft navigational collision risk for parallel tracks in radar monitored systems
A72-10178

Statistical analysis of track keeping Strumble VOR data for lateral navigation separation standards and collision risk in continental environment
A72-10179

Terrain clearance during descent and approach of aircraft under radar control, discussing optimum profile, ATC, nav aids and rules
A72-10183

AIRCRAFT CARRIERS

Carrier system for controlled approach of Naval aircraft to provide pilot window to deck for tactical jet guidance for poor visibility landing
A72-12323

AIRCRAFT CONFIGURATIONS

Industry assisted state of art assessment of high lift turbofan configurations for USAF STOL tactical transport technology program
[SAE PAPER 710758] A72-10255

AIRCRAFT CONTROL

Aircraft pitching and yawing cross couplings compensation at high speed
A72-10506

European A300B airbus flap and slat systems and tailplane actuator for longitudinal pitch trim control
A72-10725

Handling qualities simulation program for augmentor wing jet STOL research aircraft considering control devices design
A72-11654

STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure

B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation
A72-11700

Soviet book on in-flight studies of aircraft stability and controllability covering dynamic characteristics, measurements, balancing curves, aerodynamic forces and limiting and special flight regimes
A72-12226

Application of linear mathematical model to represent human operator performance in controlling attacking fighter aircraft
[AD-725069] N72-10042

Analysis and calculation of basic parameters of aircraft automatic control system components
[JPBS-54332] N72-11039

AIRCRAFT DESIGN

Aircraft producibility considerations in preliminary design and production planning phases
[SAE PAPER 710746] A72-10245

Aircraft design producibility to reduce production cost and enhance product profitability, using joint engineering and manufacturing team
[SAE PAPER 710748] A72-10247

Future aircraft design trends for transcontinental and short haul operation, considering traffic forecasts, current transport aircraft and potential derivatives and technology
[SAE PAPER 710749] A72-10248

TriStar commercial jet transport aircraft development, discussing design and flight tests for operating efficiency, reliability and safety
[SAE PAPER 710755] A72-10252

Augmentor wing jet STOL research aircraft development progress report covering design, engine tests, performance prediction, control simulation and stability augmentation
[SAE PAPER 710757] A72-10254

Propulsion system optimization for commercial transport aircraft design under Advanced Transport Technology study, considering impact on aircraft gross weight
[SAE PAPER 710760] A72-10257

Propulsion system optimization in transonic transport aircraft design, considering nacelle integration, engine choice, noise attenuation and technology utilization
[SAE PAPER 710762] A72-10259

Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness
[SAE PAPER 710778] A72-10270

Variable speed constant frequency power generation equipment influence weapon system effectiveness, considering weight and cost
A72-11067

Aircraft ride comfort problem in turbulent air, comparing free and fixed wing aircraft responses
A72-11720

B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation
A72-12226

Aircraft design interactive computer graphics technique, using human decision input response to computer output information
[DGLR PAPER 71-107] A72-12733

Unsolved aerodynamic problems in sub- and transonic civil and military aircraft design, considering flow problems during transonic flight, takeoff and landing
[DGLR PAPER 71-105] A72-12745

Aircraft design concepts for intraurban transportation system
[NASA-CR-114342] N72-10986

Effect of optimum accessibility on improved maintenance and reliability of commercial aircraft
A72-11031

AIRCRAFT ENGINES

Advanced technology air transports propulsion system requirements, considering design, engine performance and reliability, maintenance, airline problems, noise and pollution control
[SAE PAPER 710761] A72-10258

Concorde engine performance, reviewing control, reheat and exhaust systems
[SAE PAPER 710775] A72-10267

SUBJECT INDEX

AIRCRAFT LANDING

- CP6 high bypass ratio turbofan engine design improvements for fuel consumption, thrust/weight ratio, starting, noise level, smoke emission, maintenance, monitoring and accessory replacement [SAE PAPER 710779] A72-10271
- Aircraft hybrid electrical power systems, describing variable frequency generation and high voltage dc distribution A72-11068
- Thermal shock fatigue tests on aircraft gas turbine engine inlet nozzles, showing cracks as function of material A72-11373
- Thermal radial stresses in axial compressor disk-to-drum transition areas of operating AM-3 aircraft engine A72-11374
- Aircraft gas turbine rotating disks thermal and mechanical stresses under variable thermal conditions, describing test assembly A72-11637
- PT6 and JT15D gas turbine aircraft engines development and service experience A72-11699
- Q/STOL jet aircraft engines design for low noise levels, describing takeoff thrust, bypass ratio and turbine stages A72-12501
- Superalloys ductility and workability improvements without sacrificing elevated temperature strength for aircraft engine applications A72-12561
- Aircraft activity effects on air pollution in San Francisco Bay area with engine emission and climatological data N72-10361
- Application of brazing techniques for remanufacturing of jet engine components to reduce cost of commercial aircraft maintenance N72-11024
- Properties evaluation of lubricants and fuels for use in advanced aircraft gas turbine [NASA-CR-122842] N72-11694
- Assessment of high temperature stability of synthetic lubricants for aircraft gas turbines N72-11695
- Analytical methods for early-stage detection of oil deterioration in aircraft engines N72-11698
- Thermal stability of trimethyl propane ester based lubricating oil for aircraft engines N72-11699
- Feasibility analysis of solid lubricated ball bearings for aircraft propulsion systems application N72-11700
- AIRCRAFT EQUIPMENT**
- Soviet book on civil aircraft high altitude equipment covering air conditioning systems, oxygen equipment and cabin pressurization A72-12295
- Application of computers for improved maintenance of avionics equipment, fault isolation, and verification of fault correction N72-11022
- Analysis of fire and explosion hazards in aircraft fuel tanks and methods for predicting fuel/air concentrations in tanks [AD-725027] N72-11056
- Procedure for measuring performance of aircraft fire extinguishing powders N72-11691
- Electronic strain-level counter for in-flight aircraft [NASA-CASE-LAR-10756-1] N72-11803
- AIRCRAFT FUEL SYSTEMS**
- Lightweight low pressure plastic hose assemblies in aircraft and missile petroleum base fuel and synthetic lubricating oil systems at 395-710 R and up to 200 psi [SAE-ARP-1180] A72-10388
- AIRCRAFT FUELS**
- Aircraft fuels, lubricants, and fire safety - conferences [AGARD-CP-84-71] N72-11668
- Small scale combustion chamber rigs for combustion characteristics determination of aviation fuel N72-11674
- Dual purpose filter-separators for dirt and water removal from fuel N72-11676
- Fuel related problems in aircraft fuel systems, emphasizing hydrogen treated fuel N72-11677
- Theoretical analysis of fuel ignition by hot projectile and ignition delay time as function of temperature and width of hot gas region N72-11683
- Fire extinguishing system in aircraft, using exhaust gases of solid propellant gas generator to pressurize extinguisher bottle N72-11685
- Electrostatic charging in handling of aviation fuels, resulting in incendiary sparking in fuel tank N72-11686
- Crash safe turbine fuel program, using gelled fuels N72-11687
- Post-crash fire safety of helicopter turbine engine fuels N72-11688
- Simulated crash tests to assess fire resistance of aircraft fuels containing polymeric additives N72-11692
- Use of fluorocarbon surfactants to extinguish aircraft fuel fires N72-11693
- AIRCRAFT GUIDANCE**
- Carrier system for controlled approach of Naval aircraft to provide pilot window to deck for tactical jet guidance for poor visibility landing A72-12323
- AIRCRAFT HAZARDS**
- Report of aircraft accident involving DC-9 aircraft at Gulfport, Mississippi on February 17, 1971 [NTSB-AAR-71-14] N72-10049
- Extinguishing flames and fires on aircraft N72-11680
- Flammability properties of jet fuels and techniques for fire and explosion suppression under simulated hostile operating environment conditions N72-11681
- Various gelled or emulsified fuels for reducing aircraft crash-fire hazard N72-11689
- AIRCRAFT HYDRAULIC SYSTEMS**
- European A300B airbus flying control hydraulic system and landing gear design for safety and reliability, fatigue life, weight and maintenance A72-10724
- AIRCRAFT INDUSTRY**
- Commercial transport market and technology forecasting, considering all-cargo, STOL, SST and CTOL aircraft [SAE PAPER 710750] A72-10249
- AIRCRAFT INSTRUMENTS**
- Passenger aircraft onboard automated inertial navigation devices, emphasizing accelerometer and gyroscope design and construction A72-10070
- Polar navigation with transverse mercator technique for aircraft using secant geared ground position indicators A72-10181
- Pressure altimeter system minimum safe performance standards for subsonic aircraft operation, describing test procedures [SAE-AS-942] A72-10386
- Airfield Vehicle Obstacle Indication Device short range high-definition radar system for aircraft navigation aid A72-12042
- Airborne pictorial navigation systems for visual indication of aircraft position in addition to digital readout A72-12106
- Soviet book on course-indicating systems and automatic navigation aids for civil aviation aircraft covering design, operation principles, error analysis and reliability A72-12298
- AIRCRAFT LANDING**
- Short haul air transport system need for future short takeoff and landing aircraft, considering airports, airways, economics and navigation and landing aids A72-11719

- Microwave aircraft landing system development, discussing contract definition, feasibility, prototype development, management planning and program costs
 A72-12377
- Aircraft ILS, covering history, adverse weather operations and replacement systems
 A72-12645
- STOL aircraft integrated landing approach flight control system with elevator and thrust control coupling to angle of attack, altitude and other state variables
 [DGLR PAPER 71-063]
 A72-12705
- Measurement of three track runway and taxiway profiles at two international airports
 [NASA-TN-D-6567]
 N72-11038
- Flight simulator exercise for investigation of pilot performance in low visibility conditions during approach and landing
 [RAE-TR-71044]
 N72-11042
- Flight tests of BAC 221 aircraft crosswind landing and sidestep maneuvers
 [ARC-CP-1168]
 N72-11045
- Elevator lift and cockpit position effects on flight altitude control during aircraft landing approach
 [ARC-R/M-3662]
 N72-11049
- Helicopter lift margin system to aid in determining power requirements for takeoff and landing
 [AD-725207]
 N72-11053
- AIRCRAFT MAINTENANCE**
- Helicopter elastomeric bearing rotors, discussing downtime and cost reduction, maintenance, endurance and inspection
 A72-10150
- Advanced technology air transports propulsion system requirements, considering design, engine performance and reliability, maintenance, airline problems, noise and pollution control
 [SAE PAPER 710761]
 A72-10258
- Aircraft power plant design and installation influence on operational effectiveness, discussing manufacturers and operators cooperation for reliability and maintainability enhancement
 [SAE PAPER 710777]
 A72-10269
- DC-10 nondestructive testing manual, detailing section/subject format, methods, planned area accessibility and aircraft maintenance
 A72-11109
- Proceedings of conference on aviation maintenance in 1970 time period conducted at Oklahoma City, Oklahoma, December 8-10, 1970
 N72-11019
- Application of computer techniques to improvement of aircraft maintenance operations
 N72-11020
- Development of procedures for improving readability of maintenance manuals and evaluation of reading difficulty level
 N72-11021
- Application of computers for improved maintenance of avionics equipment, fault isolation, and verification of fault correction
 N72-11022
- Analysis of facilities, equipment, and tools to maintain large commercial aircraft
 N72-11023
- Application of brazing techniques for remanufacturing of jet engine components to reduce cost of commercial aircraft maintenance
 N72-11024
- Application of nondestructive testing procedures to maintenance of large commercial aircraft
 N72-11025
- Application of Apollo Project data and training concepts to maintenance of large commercial aircraft
 N72-11026
- Development and characteristics of coordinated, in-flight and on-ground fault isolation system for maintenance of large commercial aircraft
 N72-11027
- Development of technique for graphic presentation of fault isolation and problem correction for maintenance of large commercial aircraft
 N72-11028
- Development and application of modular design concept to improve jet aircraft engine maintenance
 N72-11030
- Effect of optimum accessibility on improved maintenance and reliability of commercial aircraft
 N72-11031
- Description of maintenance procedures used on Beechcraft Hawker 125 commercial jet aircraft
 N72-11032
- Predictions of aircraft maintenance procedures to be employed during 1970 to 1980 time period
 N72-11033
- Improvements in aircraft maintenance procedures based on solid state electrical power management and solid state contactless switching circuits
 N72-11034
- Description of aircraft accessory reliability program to provide improved safety of operation for commercial aircraft
 N72-11035
- AIRCRAFT MODELS**
- Low subsonic region unsteady interference effects on harmonically oscillating wing-tailplane model with variable sweep wing
 [DGLR PAPER 71-081]
 A72-12709
- Aeroelastic models construction for flutter analysis of aircraft design, noting error risk reduction
 [DGLR PAPER 71-082]
 A72-12722
- AIRCRAFT NOISE**
- STOL aircraft for solving noise reduction and land use problems in future transportation systems, discussing airport location and layout for growing air traffic
 A72-11153
- Aircraft engine noise effects in airport vicinities, discussing measurement scales, turbofan sources, noise reduction and future air traffic
 A72-12022
- Incremental value of noise pollution level as basis for aircraft noise rating
 [NPL-AERO-AC-49]
 N72-10035
- Aircraft noise effects on land use around airports
 [PB-201195]
 N72-10050
- Annotated bibliography on acoustics
 [NPL-AERO-AC-47]
 N72-10589
- Metropolitan aircraft noise abatement policy study, John F. Kennedy International Airport, New York, New York
 [PB-200164]
 N72-11051
- Airport/aircraft system computer listing for Burroughs 5500 and IBM 7094 from study on transportation noise
 [PB-201432]
 N72-11058
- AIRCRAFT PARTS**
- Integrity control procedures for machining, drilling and grinding of steel and Ti alloy aircraft parts, discussing nondestructive inspection method
 [SHE PAPER IQ 71-238]
 A72-10969
- AIRCRAFT PERFORMANCE**
- TriStar commercial jet transport aircraft development, discussing design and flight tests for operating efficiency, reliability and safety
 [SAE PAPER 710755]
 A72-10252
- STOL and VTOL aircraft performance and efficiency, discussing landing and takeoff distances reduction
 A72-11258
- AIRCRAFT PILOTS**
- Military specification adoption for flight characteristics of piloted V/STOL aircraft
 [AD-725746]
 N72-10048
- AIRCRAFT PRODUCTION**
- Aircraft producibility considerations in preliminary design and production planning phases
 [SAE PAPER 710746]
 A72-10245
- AIRCRAFT RELIABILITY**
- Boeing 747B growth model FAA certification, discussing engine thrust, fuel capacity, taxi and flight weights and aircraft noise reduction
 [SAE PAPER 710753]
 A72-10251
- Concorde airworthiness certification, discussing ground and flight test programs for performance, flying qualities and structures fatigue properties evaluation
 [SAE PAPER 710756]
 A72-10253
- Aircraft power plant design and installation influence on operational effectiveness, discussing manufacturers and operators cooperation for reliability and maintainability enhancement
 [SAE PAPER 710777]
 A72-10269
- Development and characteristics of coordinated, in-flight and on-ground fault isolation system for maintenance of large commercial aircraft

- Development of technique for graphic presentation of fault isolation and problem correction for maintenance of large commercial aircraft N72-11027
- Development and functions of organization for multinational certification of supersonic aircraft N72-11028
- Effect of optimum accessibility on improved maintenance and reliability of commercial aircraft N72-11029
- AIRCRAFT SAFETY N72-11031
- Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention A72-11117
- Proceedings of conference on aviation maintenance in 1970 time period conducted at Oklahoma City, Oklahoma, December 8-10, 1970 N72-11019
- Development and functions of organization for multinational certification of supersonic aircraft N72-11029
- Description of aircraft accessory reliability program to provide improved safety of operation for commercial aircraft N72-11035
- Techniques for forecasting turbulent weather conditions below 10,000 feet for light aircraft operating in Hawaiian Islands [AD-726107] N72-11525
- Development and operating principles of collision warning system for aircraft accident prevention [NASA-CASE-HQN-10703] N72-11527
- AIRCRAFT SPECIFICATIONS
- Military specification adoption for flight characteristics of piloted V/STOL aircraft [AD-725746] N72-10048
- AIRCRAFT STABILITY
- Aircraft stability coefficient determination by numerical integration fitting to differential equations of motion A72-11136
- Aircraft ride comfort problem in turbulent air, comparing free and fixed wing aircraft responses A72-11720
- Soviet book on in-flight studies of aircraft stability and controllability covering dynamic characteristics, measurements, balancing curves, aerodynamic forces and limiting and special flight regimes A72-12542
- Aircraft spin characteristics due to superstall, comparing three stall types with respect to recovery, yaw damping and rate of rotation [DGLR PAPER 71-057] A72-12718
- Aeroelastic models construction for flutter analysis of aircraft design, noting error risk reduction [DGLR PAPER 71-082] A72-12722
- Flight vibration testing methods for ascertaining flutter stability of high speed aircraft [DGLR PAPER 71-083] A72-12725
- Aerial expedition for studying conditions of atmospheric boundary layer over oasis and semiarid region [AD-727535] N72-10332
- AIRCRAFT STRUCTURES
- Warpage control of large Al alloy forgings machining of jumbo jet components, using packing and storage methods [SAE PAPER 710801] A72-10280
- Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core A72-10723
- AIRCRAFT WAKES
- Jet aircraft brake parachute loads under engine wake, evaluating velocity and drag coefficient influences A72-12504
- AIRFOILS
- Unsteady flow about two dimensional airfoils, determining surface pressure fluctuations induced by turbulent boundary layers A72-10217
- Aerodynamic behavior of thin jet-flapped airfoil, investigating integrodifferential equation solution A72-11669
- Skin friction measurement in nonisobaric subsonic flow with pressure gradient over airfoil section by surface impact probes A72-12275
- Customer utilization and program listing for computer program on two dimensional multicomponent airfoils in viscous flow [NASA-CR-1843] N72-11010
- Aerodynamic lift characteristics of oscillating two dimensional airfoil subjected to sinusoidal gust [AD-726132] N72-11017
- Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions [NASA-TN-D-6530] N72-11289
- AIRFRAMES
- Technical programmers manual for automated procedure of optimizing practical aerospace structures - Vol. 2 [AD-725744] N72-10047
- Design and development of numerically controlled machine for laying composite tape used in building aircraft structured from filament reinforced resin matrix composite materials [AD-725765] N72-10425
- Compression tests of short skin-stiffener specimens of conventional titanium alloys airframe structure with attached unidirectional brazen boron-aluminum composite [NASA-TN-D-6548] N72-11428
- AIRLINE OPERATIONS
- Airport efficiency improvement measures, considering boarding gates, parking space, baggage handling, fire protection, monitoring and central control A72-11717
- Civil aviation air transportation contributing factors to American economy, considering disposable income, airline fares and time-trend variable A72-11721
- AIRPORT PLANNING
- STOL transport aircraft technology assessment, analyzing airports growth problems [SAE PAPER 710751] A72-10250
- Acoustic echo sounder as real time monitor of airport environmental meteorological parameters A72-11137
- STOL aircraft for solving noise reduction and land use problems in future transportation systems, discussing airport location and layout for growing air traffic A72-11153
- Airport efficiency improvement measures, considering boarding gates, parking space, baggage handling, fire protection, monitoring and central control A72-11717
- Aircraft engine noise effects in airport vicinities, discussing measurement scales, turbofan sources, noise reduction and future air traffic A72-12022
- AIRPORTS
- Airport apron surface pavement strain measurements under field loading conditions, considering static and dynamic loads with finite element method A72-10192
- Terminal aerodrome forecasts usefulness and accuracy assessment A72-10864
- Lime, cement, fly ash and sand combination airport pavement design and testing, discussing material structural and chemical properties, compressive strength, costs, etc A72-12023
- Aircraft noise effects on land use around airports [PB-201195] N72-10050
- Evaluation of airway operations systems in Indonesia, Laos, Malaysia, and Thailand with proposed courses of action, equipment requirements, and economic factors in aeronautical telecommunications N72-10171
- Short term airport access improvements in Baltimore-Washington area with service brochure implementation [PB-200686] N72-10232
- Aircraft activity effects on air pollution in San Francisco Bay area with engine emission and

- climatological data
N72-10361
Metropolitan aircraft noise abatement policy study,
John F. Kennedy International Airport, New York,
New York
[PB-200164] N72-11051
- AIRSHIPS**
Unpredicted structural vibration in Comet and
Electra aircraft, Graf Zeppelin dirigible, missile
antennas, etc A72-12002
- ALADIN 2 AIRCRAFT**
Aladin 2 noiseless STOL jet aircraft project,
describing exhaust nozzle configuration, design
and economics A72-12503
- ALGORITHMS**
Development of structural optimization algorithm for
obtaining near optimum distributions of material
for structural idealizations
[AD-726112] N72-11820
- ALIPHATIC COMPOUNDS**
Synthesis and properties of aliphatic ester for
turbine lubrication in jet aircraft N72-11696
- ALL-WEATHER AIR NAVIGATION**
Suitability evaluation of fog simulator for weather
conditions during flight approach
[FAA-NA-71-44] N72-10233
- ALTIMETERS**
Pressure altimeter system minimum safe performance
standards for subsonic aircraft operation,
describing test procedures
[SAE-AS-942] A72-10386
- ALUMINUM ALLOYS**
Warpage control of large Al alloy forgings machining
of jumbo jet components, using packing and storage
methods
[SAE PAPER 710801] A72-10280
Constant high tensile stress and rapid aerodynamic
heating effect on maraging steels and Ti and Al
alloys, evaluating test and simulation procedures
for design data development A72-10749
Residual buckling strength of Al alloy elastic
column with fatigue crack
[SESA PAPER 1914A] A72-11511
- ALUMINUM COATINGS**
Lightning protective coatings for boron/epoxy
composite materials, discussing high current
damage mechanisms, simulation facility and test
results on aluminum foils, meshes, etc A72-10783
- ANTENNA DESIGN**
Limited scan antenna system for precision approach
radar, detailing design for reflector, aperture
gain and phased array A72-12393
- ANTENNA RADIATION PATTERNS**
Helicopter antenna placement, using scale models for
three dimensional radiation pattern semiautomatic
recording under free space conditions A72-10149
- APPROACH**
Suitability evaluation of fog simulator for weather
conditions during flight approach
[FAA-NA-71-44] N72-10233
- APPROACH CONTROL**
Stellar attitude reference and navigation
associative processor with high computational
speed for radar approach control in ATC A72-12033
Carrier system for controlled approach of Naval
aircraft to provide pilot window to deck for
tactical jet guidance for poor visibility landing
A72-12323
STOL aircraft integrated landing approach flight
control system with elevator and thrust control
coupling to angle of attack, altitude and other
state variables
[DGLR PAPER 71-063] A72-12705
Flight simulator exercise for investigation of pilot
performance in low visibility conditions during
approach and landing
[RAE-TR-71044] N72-11042
- AROMATIC COMPOUNDS**
Jet fuels hydrocarbon composition effect on thermal
stability, considering nonaromatic components
influence on aromatic hydrocarbons oxidation
- products coagulation A72-12800
- ASSEMBLIES**
Lightweight low pressure plastic hose assemblies in
aircraft and missile petroleum base fuel and
synthetic lubricating oil systems at 395-710 R and
up to 200 psi
[SAE-ARP-1180] A72-10388
- ATMOSPHERIC CIRCULATION**
Aerial expedition for studying conditions of
atmospheric boundary layer over oasis and semiarid
region
[AD-727535] N72-10332
- ATMOSPHERIC PHYSICS**
German Research and Test Institute for Aero- and
Astronautics 1970 report covering flow mechanics,
power conversion, aerospace medicine, atmospheric
physics, etc A72-11151
Real gas effects in atmosphere to make sonic bang
shock wave full dispersion and thickness wide
variations A72-11972
- ATMOSPHERIC PRESSURE**
Atmospheric temperature and pressure altitude
effects on runway lengths and aircraft takeoff
weights
[ASCE PREPRINT 1242] A72-10193
- ATMOSPHERIC TEMPERATURE**
Atmospheric temperature and pressure altitude
effects on runway lengths and aircraft takeoff
weights
[ASCE PREPRINT 1242] A72-10193
- ATMOSPHERIC TURBULENCE**
Sonic boom pressure signatures during F-104
overflights at Mach 1.3 and 30,000 ft, explaining
variations by atmospheric turbulence A72-11158
Aerial expedition for studying conditions of
atmospheric boundary layer over oasis and semiarid
region
[AD-727535] N72-10332
- ATTACK AIRCRAFT**
Electronic displays for attack aircraft, discussing
subsystems, simulation technique and pilot role
[DPVLR-SOWDDR-140] A72-11756
- ATTITUDE CONTROL**
Free flight simulation tests for V/STOL aircraft
nonlinear attitude control system adaptation to
helicopter pitch and roll control
[DGLR PAPER 71-060] A72-12714
Analysis and calculation of basic parameters of
aircraft automatic control system components
[JPRS-54332] N72-11039
- AUDIOHETRY**
Annotated bibliography on acoustics
[NPL-AERO-AC-47] N72-10589
- AUTOMATIC CONTROL**
Aircraft high pressure oxygen cylinder system filler
valve optimum standards, discussing automatic fill
rate and pressure sensitive closing control,
design, construction and performance
[SAE-AS-1225] A72-10385
ATCAS air traffic control automation system
emphasizing Italian situation A72-12649
- AUTOMATIC FLIGHT CONTROL**
Passenger aircraft onboard automated inertial
navigation devices, emphasizing accelerometer and
gyroscope design and construction A72-10070
Inertial navigation role in automatic ATC systems,
discussing path control accuracies, environmental
conditions, noise and air pollution, etc A72-11118
Soviet book on course-indicating systems and
automatic navigation aids for civil aviation
aircraft covering design, operation principles,
error analysis and reliability A72-12298
FAA air traffic control automation program,
discussing en route stage, computer program, data
processing and storage and terminal area
navigation and display techniques A72-12380
STOL aircraft integrated landing approach flight
control system with elevator and thrust control
coupling to angle of attack, altitude and other
state variables

- [DGLR PAPER 71-063] A72-12705
Analysis and calculation of basic parameters of aircraft automatic control system components [JPBS-54332] N72-11039
- AUTOMATIC LANDING CONTROL**
Automated radar terminal system /ARTS/ for monitoring and tracking all aircraft within radar range, displaying identification, altitude and ground speed information to air traffic controller A72-10960
Fail-operational automatic landing system for Boeing 747 aircraft, noting reduction in allowable minimum weather conditions in U.S. and UK A72-10961
- AUTOMATIC PILOTS**
Spectral analysis of transient data applied to auto-pilot parameter studies of coupler transfer function [AD-725068] N72-10501
- AUTOMATIC TEST EQUIPMENT**
Automatic ultrasonic testing equipment for NDT tests of helicopter rotor blades A72-11021
- AVIONICS**
Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques A72-10180
Variable speed constant frequency power generation equipment influence weapon system effectiveness, considering weight and cost A72-11067
Electronic displays for attack aircraft, discussing subsystems, simulation technique and pilot role [DFVLR-SONDDR-140] A72-11756
Aircraft and spacecraft integrated avionics systems design with emphasis on telemetry, discussing space shuttle subsystems integration A72-12403
Application of computers for improved maintenance of avionics equipment, fault isolation, and verification of fault correction N72-11022
- AXIAL FLOW**
Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts A72-10220
Cascade calculations and tests of blunt trailing edge blades used in advanced axial compressor concepts [AD-725789] N72-11308
- AXIAL FLOW TURBINES**
Noise generation by rotating blades of axial flow fan in infinite annulus [AD-726126] N72-11714
- B**
- B-52 AIRCRAFT**
Crew compartment vibration environment in B-52 aircraft during low altitude, high speed flight [AD-727023] N72-10127
- BAC AIRCRAFT**
Flight tests of BAC 221 aircraft crosswind landing and sidestep maneuvers [ARC-CP-1168] N72-11045
Performance tests on aerodynamically compensated pressure heads for BAC 221 aircraft noting pressure sensing errors [ARC-CP-1167] N72-11046
- BALL BEARINGS**
Feasibility analysis of solid lubricated ball bearings for aircraft propulsion systems application N72-11700
- BALSA**
Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core A72-10723
- BEACONS**
Analysis of target signal requirements for aircraft navigation systems using millimeter wave radiometry from terrain radiation or ground-based beacons [NASA-TM-X-62082] N72-10539
- BEARINGS**
Helicopter elastomeric bearing rotors, discussing downtime and cost reduction, maintenance, endurance and inspection A72-10150
- BENDING MOMENTS**
Matrix method calculation for aerodynamic loads, transverse forces, bending moments, torques and twist of hinged main rotor blades in helicopter during forward flight A72-12440
- BIBLIOGRAPHIES**
Annotated bibliography on aircraft noise pollution - Vol. 1 [AD-724850] N72-10036
Annotated bibliography on acoustics [NPL-AERO-AC-47] N72-10589
- BLADE TIPS**
Helicopter rotor tip drag relief estimate based on two dimensional drag divergence with Mach number, airfoil parameters and flight conditions A72-12882
- BLIND LANDING**
Carrier system for controlled approach of Naval aircraft to provide pilot window to deck for tactical jet guidance for poor visibility landing A72-12323
- BO-105 HELICOPTER**
Static and dynamic stability and controllability of rigid rotor BO-105 helicopter noting feedback effects N72-11008
- BODY-WING AND TAIL CONFIGURATIONS**
Aerodynamic forces and pressure distribution measurement on wing-body combination model, investigating boundary layer on wing upper surface A72-12228
Force and pressure distribution measurements on delta wing-body combination in compressible flow, investigating Reynolds number effect [DGLR PAPER 71-118] A72-12707
Unsteady pressure distribution on harmonically oscillating circular cylindrical fuselage body with conical nose and delta wing with straight, cubic or sinusoidal leading edges [DGLR PAPER 71-080] A72-12730
- BOEING 707 AIRCRAFT**
Design, fabrication, and ground tests of perforated stainless steel exhaust nozzle inserts for Boeing 707 aircraft noise reduction [NASA-CR-1853] N72-10043
- BOEING 747 AIRCRAFT**
Boeing 747B growth model FAA certification, discussing engine thrust, fuel capacity, taxi and flight weights and aircraft noise reduction [SAE PAPER 710753] A72-10251
Fail-operational automatic landing system for Boeing 747 aircraft, noting reduction in allowable minimum weather conditions in U.S. and UK A72-10961
- BOMBER AIRCRAFT**
B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation A72-12226
- BOUNDARY LAYER SEPARATION**
Hypersonic boundary layer separation of delta wing in shock tunnel using color and monochrome schlieren photography [NPL-AERO-NOTE-1097] N72-10022
- BOUNDARY LAYERS**
Aerodynamic forces and pressure distribution measurement on wing-body combination model, investigating boundary layer on wing upper surface A72-12228
Aerial expedition for studying conditions of atmospheric boundary layer over oasis and semiarid region [AD-727535] N72-10332
- BOUNDARY VALUE PROBLEMS**
Equilibrium configuration of cable towed in circular path, presenting multivalued boundary value problem mathematical analysis A72-11132
- BRAZING**
Application of brazing techniques for remanufacturing of jet engine components to reduce cost of commercial aircraft maintenance N72-11024

BREATHING VIBRATION

Paratroop type parachutes breathing oscillations and stability characteristics, using high speed cinematography and kinetheodolites to track during steady state descent

A72-10307

BRISTOL-SIDDELEY BS 53 ENGINE

Infrared spectrophotometer used for detection of trace contaminants from Pegasus and Olympus engines in aircraft cabin atmospheres

N72-10040

BUFFETING

Prediction of flight penetration of wing buffeting from wind tunnel model dynamic tests

N72-11044

C

C-130 AIRCRAFT

Multichannel multispectral scanner system for NASA C-130 earth resources aircraft, describing electronic equipment and calibration sources

A72-10946

CABIN ATMOSPHERES

Infrared spectrophotometer used for detection of trace contaminants from Pegasus and Olympus engines in aircraft cabin atmospheres

N72-10040

CABLES

Aerospace wire and cables testing methods standards for evaluating mechanical, electrical and chemical properties, coating thicknesses, continuity flaws, flammability, geometrical characteristics, etc

A72-10384

Equilibrium configuration of cable towed in circular path, presenting multivalued boundary value problem mathematical analysis

A72-11132

CALIBRATING

Flight test procedures for subsonic transport aircraft pitot static pressure system, recommending trailing cone calibration method

A72-10389

Calibration of pressure sensors used to measure aerodynamic noise

N72-11368

Calibration and performance of cosmic radiation detector for Concorde supersonic transport

N72-11370

CALIFORNIA

Aircraft activity effects on air pollution in San Francisco Bay area with engine emission and climatological data

N72-10361

Analysis of economic and feasibility factors pertaining to commuter oriented, short haul air transportation system in San Francisco, California area

N72-11845

CARBON FIBERS

Graphite fiber composite fan blade design for subsonic turbofan engines, discussing weight and fatigue sensitivity reductions and performance test results

A72-10265

Graphite filament reinforced plastics strength, performance properties, fabrication processes and tooling concepts

A72-10968

CARET WINGS

Thin shock layer theory of lifting properties of reentry caret and flat delta wings and waveriders at high incidence angles and Mach number

A72-12345

CARGO

Computerized design of civil aircraft using freight criteria in parametric analysis

N72-11061

CASCADE FLOW

One dimensional unsteady flow in turbine engines rotating and static vane cascades, discussing vibrations propagation

A72-11584

CASES (CONTAINERS)

Performance of axial flow compressor rotor with different casing treatment configuration

N72-10025

CASTINGS

Nondestructive radioactive gas penetrant tests for

porosity and fatigue damage in jet engine castings

A72-10813

CATALYTIC ACTIVITY

Possible catalytic reduction of stratospheric ozone by nitrogen oxides emitted from SST aircraft

N72-11334

CAUCHY PROBLEM

Velocity field of sonic flow about aircraft wing profile, solving mixed Cauchy problem

A72-11178

CENTRIFUGING STRESS

Aircraft gas turbine rotating disks thermal and mechanical stresses under variable thermal conditions, describing test assembly

A72-11637

CERTIFICATION

Boeing 747B growth model FAA certification, discussing engine thrust, fuel capacity, taxi and flight weights and aircraft noise reduction

A72-10251

Concorde airworthiness certification, discussing ground and flight test programs for performance, flying qualities and structures fatigue properties evaluation

A72-10253

Development and functions of organization for multinational certification of supersonic aircraft

N72-11029

CHEMICAL COMPOSITION

Jet fuel specifications for military and civil aircraft

N72-11669

CHEMICAL PROPERTIES

Lime, cement, fly ash and sand combination airport pavement design and testing, discussing material structural and chemical properties, compressive strength, costs, etc

A72-12023

CIRCULATION

Recirculation mechanism in jet powered V/STOL aircraft

N72-10828

CIVIL AVIATION

General and commercial aircraft service needs in air transportation, considering FAA and CAB roles and policies

A72-11716

Civil aviation air transportation contributing factors to American economy, considering disposable income, airline fares and time-trend variable

A72-11721

Soviet book on civil aircraft high altitude equipment covering air conditioning systems, oxygen equipment and cabin pressurization

A72-12295

Soviet book on course-indicating systems and automatic navigation aids for civil aviation aircraft covering design, operation principles, error analysis and reliability

A72-12298

Reports of accidents involving missing aircraft of US general aviation for 1968

N72-10041

Proceedings of conference on aviation maintenance in 1970 time period conducted at Oklahoma City, Oklahoma, December 8-10, 1970

N72-11019

Predictions of aircraft maintenance procedures to be employed during 1970 to 1980 time period

N72-11033

Computerized design of civil aircraft using freight criteria in parametric analysis

N72-11061

Analysis of economic and feasibility factors pertaining to commuter oriented, short haul air transportation system in San Francisco, California area

N72-11845

CLIMATOLOGY

Aircraft activity effects on air pollution in San Francisco Bay area with engine emission and climatological data

N72-10361

CLIMBING FLIGHT

Noise reduction for climbing takeoff and V/STOL aircraft affecting stability

N72-11040

SUBJECT INDEX

COMPUTER PROGRAMS

- Supersonic transport aircraft and BAC 221 aircraft piloted flight simulation near zero rate climb velocity for determining aircraft maneuver controllability at low speed
[ARC-CP-1165] N72-11048
- COAGULATION**
Jet fuels hydrocarbon composition effect on thermal stability, considering nonaromatic components influence on aromatic hydrocarbons oxidation products coagulation
A72-12800
- COCKPITS**
Elevator lift and cockpit position effects on flight altitude control during aircraft landing approach
[ARC-R/M-3662] N72-11049
- COHERENT ACOUSTIC RADIATION**
Mathematical models for studying incoherent and coherent structures of aerodynamically generated noise
[ONERA-TP-983] N72-11036
- COLLISION AVOIDANCE**
Mathematical analysis of separation standards and aircraft navigational collision risk for parallel tracks in radar monitored systems
A72-10178
Statistical analysis of track keeping Strumble VOR data for lateral navigation separation standards and collision risk in continental environment
A72-10179
Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques
A72-10180
Pilot collision warning indicator performance in terminal area traffic, using computer fast-time simulation for traffic model
A72-11134
FAA activity in collision avoidance system and pilot warning instrument areas
A72-12379
Development and operating principles of collision warning system for aircraft accident prevention
[NASA-CASE-HQM-10703] N72-11527
- COLOR PHOTOGRAPHY**
Hypersonic boundary layer separation of delta wing in shock tunnel using color and monochrome schlieren photography
[NPL-AERO-NOTE-1097] N72-10022
- COMBUSTION CHAMBERS**
Small scale combustion chamber rigs for combustion characteristics determination of aviation fuel
N72-11674
- COMBUSTION PRODUCTS**
Jet fuels hydrocarbon composition effect on thermal stability, considering nonaromatic components influence on aromatic hydrocarbons oxidation products coagulation
A72-12800
- COMET 4 AIRCRAFT**
Unpredicted structural vibration in Comet and Electra aircraft, Graf Zeppelin dirigible, missile antennas, etc
A72-12002
- COMFORT**
Aircraft ride comfort problem in turbulent air, comparing free and fixed wing aircraft responses
A72-11720
- COMMERCIAL AIRCRAFT**
Commercial transport market and technology forecasting, considering all-cargo, STOL, SST and CTOL aircraft
[SAE PAPER 710750] A72-10249
Propulsion system optimization for commercial transport aircraft design under Advanced Transport Technology study, considering impact on aircraft gross weight
[SAE PAPER 710760] A72-10257
Jet noise reduction technology, hardware and tests for NASA Quiet Engine Program to develop low noise subsonic civil transport aircraft propulsion system
[SAE PAPER 710774] A72-10266
General and commercial aircraft service needs in air transportation, considering FAA and CAB roles and policies
A72-11716
Reports of accidents involving missing aircraft of US general aviation for 1968
[NTSB-AMM-71-4] N72-10041
- Proceedings of conference on aviation maintenance in 1970 time period conducted at Oklahoma City, Oklahoma, December 8-10, 1970
N72-11019
Predictions of aircraft maintenance procedures to be employed during 1970 to 1980 time period
N72-11033
Computerized design of civil aircraft using freight criteria in parametric analysis
[AD-727231] N72-11061
Analysis of economic and feasibility factors pertaining to commuter oriented, short haul air transportation system in San Francisco, California area
[NASA-CR-114347] N72-11845
- COMPOSITE MATERIALS**
Design and development of numerically controlled machine for laying composite tape used in building aircraft structured from filament reinforced resin matrix composite materials
[AD-725765] N72-10425
- COMPOSITE STRUCTURES**
Graphite fiber composite fan blade design for subsonic turbofan engines, discussing weight and fatigue sensitivity reductions and performance test results
[SAE PAPER 710771] A72-10265
- COMPRESSIBLE FLOW**
Force and pressure distribution measurements on delta wing-body combination in compressible flow, investigating Reynolds number effect
[DGLR PAPER 71-118] A72-12707
Design programs for swept wings in subcritical, compressible, viscous flow
[NPL-AERO-NOTE-1100] N72-10018
- COMPRESSION TESTS**
Compression tests of short skin-stiffener specimens of conventional titanium alloys airframe structure with attached unidirectional brazed boron-aluminum composite
[NASA-TN-D-6548] N72-11428
- COMPRESSIVE STRENGTH**
Lime, cement, fly ash and sand combination airport pavement design and testing, discussing material structural and chemical properties, compressive strength, costs, etc
A72-12023
- COMPRESSOR BLADES**
Metallographic and fractographic analyses of cracking in T53-L13 gas turbine engine compressor disks
A72-10816
Forged Inconel alloy 718 metal powder preforms for dense aircraft engine compressor rotor blades
A72-11441
Tip clearance effect on compressor blade aerodynamic characteristics, applying Bolland analysis to low aspect ratio rectangular wing
A72-12825
- COMPRESSOR ROTORS**
Performance of axial flow compressor rotor with different casing treatment configuration
[NASA-TN-D-6538] N72-10025
- COMPUTER DESIGN**
Stellar attitude reference and navigation associative processor with high computational speed for radar approach control in ATC
A72-12033
- COMPUTER GRAPHICS**
Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities
A72-12420
Aircraft design interactive computer graphics technique, using human decision input response to computer output information
[DGLR PAPER 71-107] A72-12733
- COMPUTER PROGRAMS**
FAA air traffic control automation program, discussing en route stage, computer program, data processing and storage and terminal area navigation and display techniques
A72-12380
Technical programmers manual for automated procedure of optimizing practical aerospace structures - Vol. 2
[AD-725744] N72-10047
Customer utilization and program listing for computer program on two dimensional multicomponent

COMPUTER STORAGE DEVICES

SUBJECT INDEX

airfoils in viscous flow
[NASA-CR-1843] N72-11010
Application of computer techniques to improvement of
aircraft maintenance operations N72-11020
Application of computers for improved maintenance of
avionics equipment, fault isolation, and
verification of fault correction N72-11022
Development of computer programs for processing
flight test data and standardizing in-flight
performance of aircraft N72-11054
[AD-725741]
Airport/aircraft system computer listing for
Burroughs 5500 and IBM 7094 from study on
transportation noise N72-11058
[PB-201432]
COMPUTER STORAGE DEVICES
Digital computer memory system for real time
processing of air and naval traffic data,
discussing logic design, time comparisons and
optimum use A72-12647
COMPUTERIZED DESIGN
Aircraft design interactive computer graphics
technique, using human decision input response to
computer output information A72-12733
[DGLR PAPER 71-107]
Computerized design of civil aircraft using freight
criteria in parametric analysis N72-11061
[AD-727231]
COMPUTERIZED SIMULATION
Handling qualities simulation program for augmentor
wing jet STOL research aircraft considering
control devices design A72-11654
Mathematical models of rate gyros, servo
accelerometers, pressure transducers, and
telemetry systems and analog computer simulation
programs N72-10401
[NASA-CR-1768]
Cost analysis and operational procedures of
effective short range, high density computer
transportation system for Metropolitan Detroit
[NASA-CR-114340] N72-10984
CONCORDE AIRCRAFT
Concorde airworthiness certification, discussing
ground and flight test programs for performance,
flying qualities and structures fatigue properties
evaluation A72-10253
[SAE PAPER 710756]
Concorde engine performance, reviewing control,
reheat and exhaust systems A72-10267
[SAE PAPER 710775]
CONFERENCES
Parachutes and related technologies - Conference,
London, September 1971 A72-10301
Electronics and aerospace systems - IEEE Conference,
Washington, D.C., October 1971 A72-12376
Radio aids to maritime and aerial navigation -
Conference, Trieste, June 1971 A72-12640
Conference papers on jet and slipstream influence on
aerodynamic coefficients using aircraft models N72-10004
[DLR-MITT-70-28]
Rotor and propeller wake calculation, recovery
rotors, and rotor feedback control N72-11001
[DLR-MITT-71-12]
Proceedings of conference on aviation maintenance in
1970 time period conducted at Oklahoma City,
Oklahoma, December 8-10, 1970 N72-11019
Aircraft fuels, lubricants, and fire safety -
conferences N72-11668
[AGARD-CP-84-71]
CONICAL BODIES
Area rule for change in lift/drag ratio of
hypersonic delta wing due to conical body addition
on compression side A72-12270
CONTROL SIMULATION
Augmentor wing jet STOL research aircraft
development progress report covering design,
engine tests, performance prediction, control
simulation and stability augmentation A72-10254
[SAE PAPER 710757]

CONTROL SURFACES
Impinging inclined jet effect on aerodynamic
characteristics of control surface in VTOL
longitudinal stability N72-10011
CONTROL THEORY
Aircraft pitching and yawing cross couplings
compensation at high speed A72-10506
CONTROLLABILITY
Handling qualities simulation program for augmentor
wing jet STOL research aircraft considering
control devices design A72-11654
Static and dynamic stability and controllability of
rigid rotor BO-105 helicopter noting feedback
effects N72-11008
Supersonic transport aircraft and BAC 221 aircraft
piloted flight simulation near zero rate climb
velocity for determining aircraft maneuver
controllability at low speed N72-11048
[ARC-CP-1165]
CORDAGE
Axial cords effects on parachute drag and stability
characteristics and opening time, discussing wind
tunnel and balloon drop tests results A72-10306
Parachute canopy fabrics and rigging lines cordage
properties requirements, considering nylon,
polypropylene, silk, cotton and nonwoven
scrim-reinforced fabrics A72-10314
CORROSION
Effect of sulfur in JP-5 fuel on hot corrosion of
turbine blade materials operating in marine
environment N72-11706
[AD-725619]
COSMIC RAYS
In-flight warning meter for solar and cosmic
radiation dose equivalent measurements for
radiological protection in SST aircraft A72-12078
COST ANALYSIS
Variable speed constant frequency power generation
equipment influence weapon system effectiveness,
considering weight and cost A72-11067
Cost analysis and operational procedures of
effective short range, high density computer
transportation system for Metropolitan Detroit
[NASA-CR-114340] N72-10984
Graphs and tables of service cost for intraurban
transportation system N72-10985
[NASA-CR-114341]
Cost analysis and economic models for European
aerospace development compared to US experience
[AD-725478] N72-10992
COST REDUCTION
Helicopter elastomeric bearing rotors, discussing
downtime and cost reduction, maintenance,
endurance and inspection A72-10150
Aircraft design producibility to reduce production
cost and enhance product profitability, using
joint engineering and manufacturing team A72-10247
[SAE PAPER 710748]
Application of brazing techniques for
remanufacturing of jet engine components to reduce
cost of commercial aircraft maintenance N72-11024
COUNTERS
Electronic strain-level counter for in-flight
aircraft N72-11803
[NASA-CASE-LAR-10756-1]
CRACK INITIATION
Metallographic and fractographic analyses of
cracking in T53-L13 gas turbine engine compressor
disks A72-10816
CRACK PROPAGATION
Theoretical and analytical aspects of metal fatigue
failure and relationships to fracture mechanics
[AD-725028] N72-10957
CRACKING (FRACTURING)
Portable self contained ultrasonic field inspection
equipment for nondestructive crack detection in
T53 gas turbine compressor disks A72-10814

CRACKS

Residual buckling strength of Al alloy elastic column with fatigue crack
[SESA PAPER 1914A] A72-11511

CRASH LANDING

Simulated crash tests to assess fire resistance of aircraft fuels containing polymeric additives
N72-11692

CROSS COUPLING

Aircraft pitching and yawing cross couplings compensation at high speed
A72-10506

CROSS FLOW

Laminar three dimensional boundary layer nonequilibrium effects at hypersonic wing swept leading edge with intensively cooled surface, considering sweep induced crossflow effect
[VPI-E-71-23] A72-12422

Flight tests of BAC 221 aircraft crosswind landing and sidestep maneuvers
[ARC-CP-1168] N72-11045

CYLINDRICAL BODIES

Calculation of pressure distribution on cylindrical fuselage with perpendicular lifting jet using singularity method
N72-10014

D

DAMAGE

Metal fatigue damage nondestructive detection, discussing inspection methods, equipment, advantages, limitations and test results
A72-12498

DATA ACQUISITION

Radar data automatic extraction, discussing azimuth quantization methods, moving window detection, coordinate measurement and ATCAS extractor
A72-12650

Wind tunnels measuring equipment and procedures and data acquisition and processing systems electronics, describing computerized real time data processing system
A72-12898

Development of computer programs for processing flight test data and standardizing in-flight performance of aircraft
[AD-725741] N72-11054

DATA PROCESSING

Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities
A72-12420

Digital computer memory system for real time processing of air and naval traffic data, discussing logic design, time comparisons and optimum use
A72-12647

Radar data automatic extraction, discussing azimuth quantization methods, moving window detection, coordinate measurement and ATCAS extractor
A72-12650

Wind tunnels measuring equipment and procedures and data acquisition and processing systems electronics, describing computerized real time data processing system
A72-12898

DATA PROCESSING EQUIPMENT

Application of computer techniques to improvement of aircraft maintenance operations
N72-11020

Development of computer programs for processing flight test data and standardizing in-flight performance of aircraft
[AD-725741] N72-11054

DATA STORAGE

FAA air traffic control automation program, discussing en route stage, computer program, data processing and storage and terminal area navigation and display techniques
A72-12380

DATA SYSTEMS

Army data analysis system for fixed and rotary wing aircraft flight testing, including airborne and computer controlled ground stations equipment
A72-12408

Application of computer techniques to improvement of aircraft maintenance operations
N72-11020

DC 10 AIRCRAFT

Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness
[SAE PAPER 710778] A72-10270

DC-10 nondestructive testing manual, detailing section/subject format, methods, planned area accessibility and aircraft maintenance
A72-11109

DC 9 AIRCRAFT

Report of aircraft accident involving DC-9 aircraft at Gulfport, Mississippi on February 17, 1971
[NTSB-AAR-71-14] N72-10049

DECAY RATES

Flutter equation approximate true damping or rate-of-decay solution by determinant iteration
A72-11133

DECISION MAKING

Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques
A72-10180

ATC system decision making problem and future technological and administrative improvements
A72-11718

DELTA WINGS

Supersonic and hypersonic flows with attached shock waves over delta wing at angle of attack, deriving unified theory for flow field
A72-12030

Area rule for change in lift/drag ratio of hypersonic delta wing due to conical body addition on compression side
A72-12270

Thin shock layer theory of lifting properties of reentry caret and flat delta wings and waveriders at high incidence angles and Mach number
A72-12345

Unsteady pressure distribution on harmonically oscillating circular cylindrical fuselage body with conical nose and delta wing with straight, cubic or sinusoidal leading edges
[DGLR PAPER 71-080] A72-12730

Hypersonic boundary layer separation of delta wing in shock tunnel using color and monochrome schlieren photography
[NPL-AERO-NOTE-1097] N72-10022

Linear functional law for alleviating gusts on delta wing aircraft
[ONERA-TP-925] N72-10999

Three component shock tunnel strain gage balance for measuring aerodynamic forces on thin delta wings
[ARC-R/M-3664] N72-11375

DESCENT TRAJECTORIES

Terrain clearance during descent and approach of aircraft under radar control, discussing optimum profile, ATC, nav aids and rules
A72-10183

DESERTS

Aerial expedition for studying conditions of atmospheric boundary layer over oasis and semiarid region
[AD-727535] N72-10332

DETERIORATION

Analytical methods for early-stage detection of oil deterioration in aircraft engines
N72-11698

DETERMINANTS

Flutter equation approximate true damping or rate-of-decay solution by determinant iteration
A72-11133

DIFFERENTIAL EQUATIONS

Aerodynamic behavior of thin jet-flapped airfoil, investigating integrodifferential equation solution
A72-11669

DIGITAL COMPUTERS

Digital computer memory system for real time processing of air and naval traffic data, discussing logic design, time comparisons and optimum use
A72-12647

On-line digital computer for wind tunnel, operating systems, and real time operation
[NPL-AERO-1326] N72-10184

DIRECT CURRENT

Aircraft hybrid electrical power systems, describing variable frequency generation and high voltage dc distribution

- DIRECTIONAL CONTROL** A72-11068
Flight simulator used to determine lateral and directional aerodynamic characteristics of STOL transport aircraft [FAA-RD-71-81] N72-11037
- DISPLAY DEVICES**
Automated radar terminal system /ARTS/ for monitoring and tracking all aircraft within radar range, displaying identification, altitude and ground speed information to air traffic controller A72-10960
Electronic displays for attack aircraft, discussing subsystems, simulation technique and pilot role [DFVLR-SOWDDR-140] A72-11756
Airborne pictorial navigation systems for visual indication of aircraft position in addition to digital readout A72-12106
FAA air traffic control automation program, discussing en route stage, computer program, data processing and storage and terminal area navigation and display techniques A72-12380
Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities A72-12420
Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar A72-12421
- DISTANCE MEASURING EQUIPMENT**
VOR, Direct Measuring Equipment and TACAN polar coordinate radio navigation systems history, improvements and future development A72-12646
- DISTRICT OF COLUMBIA**
Short term airport access improvements in Baltimore-Washington area with service brochure implementation [PB-200686] N72-10232
- DOCUMENTATION**
Documentation of data used in intraurban transportation analysis appendix [NASA-CR-114343] N72-10987
- DOPPLER RADAR**
Doppler system with navigation radar device, computer unit and data transmitter for continuous recording of aircraft position and speed A72-12749
- DOSIMETERS**
In-flight warning meter for solar and cosmic radiation dose equivalent measurements for radiological protection in SST aircraft A72-12078
- DOWNTIME**
Helicopter elastomeric bearing rotors, discussing downtime and cost reduction, maintenance, endurance and inspection A72-10150
- DOWNWASH**
European airbus wind tunnel model aerodynamic force and downwash measurements noting jet interference reduction N72-10012
Rotor downwash variation by changing vortice diameter, flapping, rotor speed, and radius and placing infinite span wing in flow field N72-11003
Numerical evaluation of downwash integral for lifting rectangular wings noting wing loading [NPL-AERO-NOTE-1095] N72-11012
- DRAG**
Area rule for change in lift/drag ratio of hypersonic delta wing due to conical body addition on compression side A72-12270
Jet aircraft brake parachute loads under engine wake, evaluating velocity and drag coefficient influences A72-12504
- DRAG CHUTES**
Jet aircraft brake parachute loads under engine wake, evaluating velocity and drag coefficient influences A72-12504
- DRAG MEASUREMENT**
Drag and lift experimental determination for low aspect ratio rectangular wings with blunt trailing edges at Mach numbers 0.5-2.2 [DGLR PAPER 71-114] A72-12712
- DROP TESTS**
Ribbon parachutes drop tests at Mach 0.57-1.70, measuring opening shock loads and functioning time sequence A72-10312
- DUCTILITY**
Superalloys ductility and workability improvements without sacrificing elevated temperature strength for aircraft engine applications A72-12561
- DUST**
Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic performance [AD-725593] N72-11713
- DYNAMIC MODELS**
Aeroelastic models construction for flutter analysis of aircraft design, noting error risk reduction [DGLR PAPER 71-082] A72-12722
- DYNAMIC STABILITY**
Static and dynamic stability and controllability of rigid rotor BO-105 helicopter noting feedback effects N72-11008
- DYNAMIC TESTS**
Prediction of flight penetration of wing buffeting from wind tunnel model dynamic tests [ARC-CP-1171] N72-11044
- E**
- EARTH ATMOSPHERE**
Air law concept as totality of legal regulations related to atmosphere use by flying devices, discussing relation to international environmental protection A72-11107
- EARTH RESOURCES SURVEY AIRCRAFT**
Multichannel multispectral scanner system for NASA C-130 earth resources aircraft, describing electronic equipment and calibration sources A72-10946
- ECCENTRICS**
Formulae for components of perturbation velocity in linearized subsonic theory for symmetrical cranked wing panels at zero angle of attack [NPL-AERO-NOTE-1090] N72-10021
- ECONOMIC ANALYSIS**
Cost analysis and economic models for European aerospace development compared to US experience [AD-725478] N72-10992
- ECONOMIC FACTORS**
Evaluation of airway operations systems in Indonesia, Laos, Malaysia, and Thailand with proposed courses of action, equipment requirements, and economic factors in aeronautical telecommunications N72-10171
- ECONOMICS**
Civil aviation air transportation contributing factors to American economy, considering disposable income, airline fares and time-trend variable A72-11721
- EDUCATION**
Application of Apollo Project data and training concepts to maintenance of large commercial aircraft N72-11026
- EJECTORS**
Vertical takeoff aircraft wind tunnel model with high pressure ejectors to determine jet interference on aerodynamic coefficients N72-10007
- ELASTIC BUCKLING**
Residual buckling strength of Al alloy elastic column with fatigue crack [SESA PAPER 1914A] A72-11511
- ELASTIC WAVES**
Finite element method for determining transient response of box-type structure to traveling sonic pressure wave A72-10219

ELASTOMERS

Helicopter elastomeric bearing rotors, discussing downtime and cost reduction, maintenance, endurance and inspection

A72-10150

ELECTRA AIRCRAFT

Unpredicted structural vibration in Comet and Electra aircraft, Graf Zeppelin dirigible, missile antennas, etc

A72-12002

ELECTRIC CONNECTORS

Solvent removal by immersion of EC-2273 potting compound from F-4 aircraft electrical components [AD-725493]

N72-11473

ELECTRIC DISCHARGES

Electrodischarge and electrochemical machining applications in continuous repetitive production of aircraft jet engine components

A72-11150

ELECTRIC GENERATORS

Aircraft hybrid electrical power systems, describing variable frequency generation and high voltage dc distribution

A72-11068

German Research and Test Institute for Aero- and Astronautics 1970 report covering flow mechanics, power conversion, aerospace medicine, atmospheric physics, etc

A72-11151

ELECTRIC POWER

Variable speed constant frequency power generation equipment influence weapon system effectiveness, considering weight and cost

A72-11067

ELECTROCHEMICAL MACHINING

Electrodischarge and electrochemical machining applications in continuous repetitive production of aircraft jet engine components

A72-11150

ELECTROMAGNETIC RADIATION

Analysis of target signal requirements for aircraft navigation systems using millimeter wave radiometry from terrain radiation or ground-based beacons

N72-10539

ELECTROMECHANICAL DEVICES

Electromechanical nose wheel steering system for general aviation aircraft ground maneuverability improvement, describing design

A72-10963

ELECTRONIC EQUIPMENT

Multichannel multispectral scanner system for NASA C-130 earth resources aircraft, describing electronic equipment and calibration sources

A72-10946

Electronic strain-level counter for in-flight aircraft

N72-11803

ELECTRONICS

Electronics and aerospace systems - IEEE Conference, Washington, D.C., October 1971

A72-12376

ELECTROSTATIC CHARGE

Electrostatic charging in handling of aviation fuels, resulting in incendiary sparking in fuel tank

N72-11686

ELEVATORS (CONTROL SURFACES)

Elevator lift and cockpit position effects on flight altitude control during aircraft landing approach [ARC-R/M-3662]

N72-11049

EMULSIONS

Various gelled or emulsified fuels for reducing aircraft crash-fire hazard

N72-11689

ENDOTHERMIC REACTIONS

Cooling advanced engines by endothermic reactions of hydrocarbon fuels by absorbing sensible and latent heat

N72-11672

ENGINE CONTROL

Concorde engine performance, reviewing control, reheat and exhaust systems [SAE PAPER 710775]

A72-10267

ENGINE COOLANTS

Cooling advanced engines by endothermic reactions of hydrocarbon fuels by absorbing sensible and latent heat

N72-11672

ENGINE DESIGN

Propulsion system optimization for commercial transport aircraft design under Advanced Transport Technology study, considering impact on aircraft gross weight

[SAE PAPER 710760] A72-10257

Advanced technology air transports propulsion system requirements, considering design, engine performance and reliability, maintenance, airline problems, noise and pollution control

[SAE PAPER 710761] A72-10258

Graphite fiber composite fan blade design for subsonic turbofan engines, discussing weight and fatigue sensitivity reductions and performance test results

[SAE PAPER 710771] A72-10265

Small three spool, reverse and mixed flow turbofan engine for business jets, discussing fuel consumption reduction, thermodynamic performance, efficiency and maintainability

[SAE PAPER 710776] A72-10268

Aircraft power plant design and installation influence on operational effectiveness, discussing manufacturers and operators cooperation for reliability and maintainability enhancement

[SAE PAPER 710777] A72-10269

Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness

[SAE PAPER 710778] A72-10270

CP6 high bypass ratio turbofan engine design improvements for fuel consumption, thrust/weight ratio, starting, noise level, smoke emission, maintenance, monitoring and accessory replacement

[SAE PAPER 710779] A72-10271

PT6 and JT15D gas turbine aircraft engines development and service experience

A72-11699

Q/STOL jet aircraft engines design for low noise levels, describing takeoff thrust, bypass ratio and turbine stages

A72-12501

Disk shaped lift engine providing additional thrust during takeoff and transition phases of V/STOL aircraft, returning to ground by jet after task accomplishment

A72-12900

Development and application of modular design concept to improve jet aircraft engine maintenance

N72-11030

Cascade calculations and tests of blunt trailing edge blades used in advanced axial compressor concepts

[AD-725789] N72-11308

ENGINE FAILURE

STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure

A72-11700

ENGINE INLETS

Analysis of interaction of oblique shock with bow shock of blunt leading edge and application to design of hypersonic ramjet inlets

[AD-726111] N72-11312

ENGINE NOISE

Jet aircraft turbofan engine fan compressor noise reduction by acoustic linings, giving R and D results

[BAS PAPER 71 SA6] A72-10223

Aircraft engine noise effects in airport vicinities, discussing measurement scales, turbofan sources, noise reduction and future air traffic

A72-12022

Noise generation by rotating blades of axial flow fan in infinite annulus

[AD-726126] N72-11714

ENGINE PARTS

Electrodischarge and electrochemical machining applications in continuous repetitive production of aircraft jet engine components

A72-11150

Jet engine component overhaul procedures for fatigue damage repair, detailing distressed metal removal, replacement and welding techniques

A72-12499

ENGINE TESTS

Augmentor wing jet STOL research aircraft development progress report covering design, engine tests, performance prediction, control simulation and stability augmentation

ENVIRONMENT POLLUTION

SUBJECT INDEX

- [SAE PAPER 710757] A72-10254
Graphite fiber composite fan blade design for
subsonic turbofan engines, discussing weight and
fatigue sensitivity reductions and performance
test results
[SAE PAPER 710771] A72-10265
Thermal shock fatigue tests on aircraft gas turbine
engine inlet nozzles, showing cracks as function
of material A72-11373
- ENVIRONMENT POLLUTION**
Air law concept as totality of legal regulations
related to atmosphere use by flying devices,
discussing relation to international environmental
protection A72-11107
- ENVIRONMENT SIMULATION**
Suitability evaluation of fog simulator for weather
conditions during flight approach
[FAA-NA-71-44] N72-10233
- ENVIRONMENTAL ENGINEERING**
Acoustic echo sounder as real time monitor of
airport environmental meteorological parameters
A72-11137
- ENVIRONMENTAL TESTS**
Evaluation of simulated pilot/system performance in
manually controlled IFR formation flight task for
UH-1 helicopter under various environmental and
operational conditions
[AD-725209] N72-10044
- EPOXY RESINS**
Lightning protective coatings for boron/epoxy
composite materials, discussing high current
damage mechanisms, simulation facility and test
results on aluminum foils, meshes, etc A72-10783
- ERROR ANALYSIS**
Terminal aerodrome forecasts usefulness and accuracy
assessment A72-10864
Optimal stochastic /Kalman/ filters application to
integrated air and submarine navigation systems,
discussing measurement errors modeling as bias and
colored noise A72-12050
- ESCAPE SYSTEMS**
Parachute designs and applications to escape
systems, paratrooping, supply dropping, aircraft
braking, weapons systems stabilization, flight
testing aids and sport A72-10302
- ESTERS**
Synthesis and properties of aliphatic ester for
turbine lubrication in jet aircraft N72-11696
Synthetic high temperature lubricants thickened by
complex esters for supersonic aircraft N72-11701
- EUROPE**
European jet fuel lubricity evaluation N72-11679
- EUROPEAN AIRBUS**
European A300B airbus flying control hydraulic
system and landing gear design for safety and
reliability, fatigue life, weight and maintenance
A72-10724
European A300B airbus flap and slat systems and
tailplane actuator for longitudinal pitch trim
control A72-10725
European airbus wind tunnel model aerodynamic force
and downwash measurements noting jet interference
reduction N72-10012
- EUROPEAN SPACE PROGRAMS**
Cost analysis and economic models for European
aerospace development compared to US experience
[AD-725478] N72-10992
- EXHAUST FLOW SIMULATION**
Jet engine simulation with low speed wind tunnel
models for interference drag measurement N72-10005
- EXHAUST GASES**
Aircraft activity effects on air pollution in San
Francisco Bay area with engine emission and
climatological data N72-10361
Propulsion systems for low emission urban vehicles
and analysis of exhaust emissions from fossil-fueled heat engines
[PB-200144] N72-10830
- EXHAUST NOZZLES**
Nozzle shape, temperature, and velocity effects on
free hypersonic jet exhaust properties N72-10013
Design, fabrication, and ground tests of perforated
stainless steel exhaust nozzle inserts for Boeing
707 aircraft noise reduction
[NASA-CR-1853] N72-10043
- EXHAUST SYSTEMS**
Concorde engine performance, reviewing control,
reheat and exhaust systems
[SAE PAPER 710775] A72-10267
Reduction of harmful emissions of turbine engine
exhaust system N72-11675
- EXHAUST VELOCITY**
Nozzle shape, temperature, and velocity effects on
free hypersonic jet exhaust properties N72-10013
- EXPLOSIONS**
Analysis of fire and explosion hazards in aircraft
fuel tanks and methods for predicting fuel/air
concentrations in tanks N72-11056
Fire and explosion protection fuel tank ullages,
including oxygen reduction, vapor or mist
inerting, and plastic foam fillers N72-11690

F

- F-4 AIRCRAFT**
Solvent removal by immersion of EC-2273 potting
compound from F-4 aircraft electrical components
[AD-725493] N72-11473
- FABRICATION**
Graphite filament reinforced plastics strength,
performance properties, fabrication processes and
tooling concepts
[SME PAPER EM 71-205] A72-10968
- FAIL-SAFE SYSTEMS**
Fail-operational automatic landing system for Boeing
747 aircraft, noting reduction in allowable
minimum weather conditions in U.S. and UK
A72-10961
- FAILURE ANALYSIS**
Theoretical and analytical aspects of metal fatigue
failure and relationships to fracture mechanics
[AD-725028] N72-10957
- FATIGUE LIFE**
European A300B airbus flying control hydraulic
system and landing gear design for safety and
reliability, fatigue life, weight and maintenance
A72-10724
- FATIGUE TESTS**
Nondestructive radioactive gas penetrant tests for
porosity and fatigue damage in jet engine castings
A72-10813
Metal fatigue damage nondestructive detection,
discussing inspection methods, equipment,
advantages, limitations and test results
A72-12498
- FEEDBACK CONTROL**
Rotor and propeller wake calculation, recovery
rotors, and rotor feedback control
[DLR-MITT-71-12] N72-11001
Static and dynamic stability and controllability of
rigid rotor BO-105 helicopter noting feedback
effects N72-11008
- FILTERS**
Dual purpose filter-separators for dirt and water
removal from fuel N72-11676
- FINITE ELEMENT METHOD**
Airport apron surface pavement strain measurements
under field loading conditions, considering static
and dynamic loads with finite element method
A72-10192
Finite element method for determining transient
response of box-type structure to traveling sonic
pressure wave A72-10219
Technical programmers manual for automated procedure
of optimizing practical aerospace structures -
Vol. 2
[AD-725744] N72-10047

PINNED BODIES

Static and dynamic stability characteristics of
finned bodies with cruciform, slotted fin
configuration
[AD-728016] N72-10003

FIRE EXTINGUISHERS

Extinguishing flames and fires on aircraft
N72-11680
Fire extinguishing system in aircraft, using exhaust
gases of solid propellant gas generator to
pressurize extinguisher bottle N72-11685
Procedure for measuring performance of aircraft fire
extinguishing powders N72-11691
Use of fluorocarbon surfactants to extinguish
aircraft fuel fires N72-11693

FIRE PREVENTION

Basic requirements for airborne infrared forest fire
detection system
[AD-726953] N72-10396
Simulated crash tests to assess fire resistance of
aircraft fuels containing polymeric additives
N72-11692

FIRES

Analysis of fire and explosion hazards in aircraft
fuel tanks and methods for predicting fuel/air
concentrations in tanks
[AD-725027] N72-11056
Aircraft fuels, lubricants, and fire safety -
conferences
[AGARD-CP-84-71] N72-11668
Flammability properties of jet fuels and techniques
for fire and explosion suppression under simulated
hostile operating environment conditions
N72-11681
Various gelled or emulsified fuels for reducing
aircraft crash-fire hazard N72-11689
Fire and explosion protection fuel tank ullages,
including oxygen reduction, vapor or mist
inerting, and plastic foam fillers N72-11690

FIXED WINGS

Wing-fuselage combination aerodynamic coefficients,
comparing experimental data with subsonic linear
and nonlinear theoretical results
[DGLR PAPER 71-115] A72-12723

FLAPPING HINGES

Constant phase shift between flapping and action on
center of gravity for spring hinged rotor with
variable flapping stiffness N72-11007

FLAPS (CONTROL SURFACES)

European A300B airbus flap and slat systems and
tailplane actuator for longitudinal pitch trim
control A72-10725
Externally blown flaps for STOL characteristics in
medium and heavy jet transport aircraft,
demonstrating aerodynamic and flight mechanical
feasibility A72-12502
Effects of Reynolds number and frequency parameters
on buzz characteristics at subsonic speeds using
free oscillation method
[NPL-AERO-1312] N72-11291

FLIGHT

Radar observation of weather conditions for aircraft
flight
[ONM-264-TP-148] N72-11147

FLIGHT ALTITUDE

Elevator lift and cockpit position effects on flight
altitude control during aircraft landing approach
[ARC-R/M-3662] N72-11049

FLIGHT CHARACTERISTICS

Externally blown flaps for STOL characteristics in
medium and heavy jet transport aircraft,
demonstrating aerodynamic and flight mechanical
feasibility A72-12502
Soviet book on in-flight studies of aircraft
stability and controllability covering dynamic
characteristics, measurements, balancing curves,
aerodynamic forces and limiting and special flight
regimes A72-12542

FLIGHT CONTROL

Elevator lift and cockpit position effects on flight
altitude control during aircraft landing approach
[ARC-R/M-3662] N72-11049
Analysis of flight control system requirements for
helicopters and design of pilot assisted control
system
[AD-725590] N72-11057

FLIGHT CREWS

Effects of environmental stresses on attack
helicopter crew task performance in NATO theater
[AD-726949] N72-10122

FLIGHT PATHS

Soviet book on course-indicating systems and
automatic navigation aids for civil aviation
aircraft covering design, operation principles,
error analysis and reliability A72-12298

Suitability evaluation of fog simulator for weather
conditions during flight approach
[FAA-NA-71-44] N72-10233

FLIGHT RULES

German Federal Republic territorial air traffic
regulations covering general, VFR and IFR rules,
equipment and personnel examination and
certification, safety, takeoff and landing,
accidents, etc A72-12621

FLIGHT SIMULATION

Evaluation of simulated pilot/system performance in
manually controlled IFR formation flight task for
UH-1 helicopter under various environmental and
operational conditions
[AD-725209] N72-10044
Supersonic transport aircraft and BAC 221 aircraft
piloted flight simulation near zero rate climb
velocity for determining aircraft maneuver
controllability at low speed
[ARC-CP-1165] N72-11048

FLIGHT SIMULATORS

Flight simulator used to determine lateral and
directional aerodynamic characteristics of STOL
transport aircraft
[FAA-RD-71-81] N72-11037
Flight simulator exercise for investigation of pilot
performance in low visibility conditions during
approach and landing
[RAE-TR-71044] N72-11042

FLIGHT TESTS

TriStar commercial jet transport aircraft
development, discussing design and flight tests
for operating efficiency, reliability and safety
[SAE PAPER 710755] A72-10252
Concorde airworthiness certification, discussing
ground and flight test programs for performance,
flying qualities and structures fatigue properties
evaluation
[SAE PAPER 710756] A72-10253
Flight test procedures for subsonic transport
aircraft pitot static pressure system,
recommending trailing cone calibration method
[SAE-ARP-921] A72-10389
Army data analysis system for fixed and rotary wing
aircraft flight testing, including airborne and
computer controlled ground stations equipment
A72-12408
Flight vibration testing methods for ascertaining
flutter stability of high speed aircraft
[DGLR PAPER 71-083] A72-12725
Crew compartment vibration environment in B-52
aircraft during low altitude, high speed flight
[AD-727023] N72-10127
Ground and air tests of flight inspection marker
beacon receiving system
[FAA-NA-71-29] N72-10173
Flight tests of BAC 221 aircraft crosswind landing
and sidestep maneuvers
[ARC-CP-1168] N72-11045
Development of computer programs for processing
flight test data and standardizing in-flight
performance of aircraft
[AD-725741] N72-11054
FLIGHT TRAINING
Maneuver acceleration measured for estimating loads
during civil aircraft training and test flying
[ARC-CP-1176] N72-11043
FLIGHT VEHICLES
Air law concept as totality of legal regulations
related to atmosphere use by flying devices,

FLOW CHARACTERISTICS

SUBJECT INDEX

discussing relation to international environmental protection
A72-11107

FLOW CHARACTERISTICS
Parachutes flow characteristics in low speed free descent, discussing glide angle effect on total drag and water channel flow pattern studies
A72-10309

FLOW DEFLECTION
Velocity field of sonic flow about aircraft wing profile, solving mixed Cauchy problem
A72-11178

FLOW DISTRIBUTION
Supersonic and hypersonic flows with attached shock waves over delta wing at angle of attack, deriving unified theory for flow field
A72-12030
Lifting rotor flow noting wake models
N72-11002
Analysis of helicopter tail rotor flow patterns in and out of ground effect
[AD-725591]
N72-11060

FLOW MEASUREMENT
Gas turbine nozzles aerodynamic throat area air flow measurement, describing accuracy, standards, reference nozzles and mounting flanges
[SAE-ARP-1195]
A72-10390

FLOW THEORY
Subsonic linearized theory for symmetrical cranked wings at zero incidence, presenting corrected formulas for streamwise and spanwise perturbation velocity components due to wing thickness
A72-11154
High speed jet noise source physical properties interpretation by theory and scale-model experiments for supersonic transport aircraft noise suppression problem
A72-11973
Supersonic and hypersonic flows with attached shock waves over delta wing at angle of attack, deriving unified theory for flow field
A72-12030

FLOW VELOCITY
Velocity field of sonic flow about aircraft wing profile, solving mixed Cauchy problem
A72-11178

FLUID MECHANICS
German Research and Test Institute for Aero- and Astronautics 1970 report covering flow mechanics, power conversion, aerospace medicine, atmospheric physics, etc
A72-11151

FLUTTER ANALYSIS
Flutter equation approximate true damping or rate-of-decay solution by determinant iteration
A72-11133
Aeroelastic models construction for flutter analysis of aircraft design, noting error risk reduction
[DGLR PAPER 71-082]
A72-12722
Flight vibration testing methods for ascertaining flutter stability of high speed aircraft
[DGLR PAPER 71-083]
A72-12725

FOAMS
Liquid-base foam sound absorbing properties for jet aircraft noise reduction
A72-10160

FOG
Suitability evaluation of fog simulator for weather conditions during flight approach
[PAA-NA-71-44]
N72-10233

FORCE DISTRIBUTION
Force and pressure distribution measurements on delta wing-body combination in compressible flow, investigating Reynolds number effect
[DGLR PAPER 71-118]
A72-12707

FORESTS
Basic requirements for airborne infrared forest fire detection system
[AD-726953]
N72-10396

FORGING
Forged Inconel alloy 718 metal powder preforms for dense aircraft engine compressor rotor blades
A72-11441

FORMULAS (MATHEMATICS)
Formulae for components of perturbation velocity in linearized subsonic theory for symmetrical cranked wing panels at zero angle of attack
[NPL-AERO-NOTE-1090]
N72-10021

FRACTOGRAPHY
Metallographic and fractographic analyses of cracking in T53-L13 gas turbine engine compressor disks
A72-10816

FRACTURE MECHANICS
Theoretical and analytical aspects of metal fatigue failure and relationships to fracture mechanics
[AD-725028]
N72-10957

FREE FLIGHT TEST APPARATUS
Free flight simulation tests for V/STOL aircraft nonlinear attitude control system adaptation to helicopter pitch and roll control
[DGLR PAPER 71-060]
A72-12714

FREE JETS
Nozzle shape, temperature, and velocity effects on free hypersonic jet exhaust properties
N72-10013

FREE VIBRATION
Effects of Reynolds number and frequency parameters on buzz characteristics at subsonic speeds using free oscillation method
[NPL-AERO-1312]
N72-11291

FREQUENCIES
Effects of Reynolds number and frequency parameters on buzz characteristics at subsonic speeds using free oscillation method
[NPL-AERO-1312]
N72-11291

FRICTION MEASUREMENT
Skin friction measurement in nonisobaric subsonic flow with pressure gradient over airfoil section by surface impact probes
A72-12275

FUEL CONSUMPTION
Small three spool, reverse and mixed flow turbofan engine for business jets, discussing fuel consumption reduction, thermodynamic performance, efficiency and maintainability
[SAE PAPER 710776]
A72-10268

FUEL CONTROL
Variable-orifice gas turbine system for fuel rate control in aircraft
[NASA-CASE-LEW-11187-1]
N72-10824

FUEL SYSTEMS
Aviation fueling facilities and fueling operation
N72-11678

FUEL TANKS
Analysis of fire and explosion hazards in aircraft fuel tanks and methods for predicting fuel/air concentrations in tanks
[AD-725027]
N72-11056
Electrostatic charging in handling of aviation fuels, resulting in incendiary sparking in fuel tank
N72-11686
Fire and explosion protection fuel tank ullages, including oxygen reduction, vapor or mist inerting, and plastic foam fillers
N72-11690

FUEL TESTS
Viscosity and additive effects on jet engine fuel antiwear properties improvement
A72-11968
Properties evaluation of lubricants and fuels for use in advanced aircraft gas turbine
[NASA-CR-122842]
N72-11694

FUNCTIONAL INTEGRATION
Aircraft and spacecraft integrated avionics systems design with emphasis on telemetry, discussing space shuttle subsystems integration
A72-12403

FUNCTIONS (MATHEMATICS)
Linear functional law for alleviating gusts on delta wing aircraft
[ONERA-TP-925]
N72-10999

FUSELAGES
Acoustic power radiated by jet aircraft fuselage structure exposed to turbulent boundary layer pressure field, evaluating noise reduction treatments
A72-10216
Wing-fuselage combination aerodynamic coefficients, comparing experimental data with subsonic linear and nonlinear theoretical results
[DGLR PAPER 71-115]
A72-12723
Calculation of pressure distribution on cylindrical fuselage with perpendicular lifting jet using singularity method
N72-10014

GAS DYNAMICS

Development mechanisms of turbulent jet flows
[VKI-LS-36] N72-10245

GAS TURBINE ENGINES

Gas turbine nozzles aerodynamic throat area air flow measurement, describing accuracy, standards, reference nozzles and mounting flanges
[SAE-ARP-1195] A72-10390

Thermal shock fatigue tests on aircraft gas turbine engine inlet nozzles, showing cracks as function of material A72-11373

Aircraft gas turbine rotating disks thermal and mechanical stresses under variable thermal conditions, describing test assembly A72-11637

PT6 and JT15D gas turbine aircraft engines development and service experience A72-11699

Variable-orifice gas turbine system for fuel rate control in aircraft
[NASA-CASE-LEW-11187-1] N72-10824

Analysis of lubricant system used in civil supersonic gas turbine engine N72-11697

GAS TURBINES

Properties evaluation of lubricants and fuels for use in advanced aircraft gas turbine
[NASA-CR-122842] N72-11694

Assessment of high temperature stability of synthetic lubricants for aircraft gas turbines N72-11695

GAS VALVES

Aircraft high pressure oxygen cylinder system filler valve optimum standards, discussing automatic fill rate and pressure sensitive closing control, design, construction and performance
[SAE-AS-1225] A72-10385

GASEOUS DIFFUSION

Nondestructive radioactive gas penetrant tests for porosity and fatigue damage in jet engine castings A72-10813

GELLED PROPELLANTS

Crash safe turbine fuel program, using gelled fuels N72-11687

Various gelled or emulsified fuels for reducing aircraft crash-fire hazard N72-11689

GENERAL AVIATION AIRCRAFT

Electromechanical nose wheel steering system for general aviation aircraft ground maneuverability improvement, describing design A72-10963

General and commercial aircraft service needs in air transportation, considering FAA and CAB roles and policies A72-11716

Briefs of US general aviation accidents involving corporate/executive aircraft in 1968
[PB-201439] N72-11052

GERMANY

German Federal Republic territorial air traffic regulations covering general, VFR and IFR rules, equipment and personnel examination and certification, safety, takeoff and landing, accidents, etc A72-12621

German book on air traffic law covering norms relative to vehicles and air space, international air law, organizations, etc A72-12622

GLIDE PATHS

Parachutes flow characteristics in low speed free descent, discussing glide angle effect on total drag and water channel flow pattern studies A72-10309

GOVERNMENT/INDUSTRY RELATIONS

FAA activity in collision avoidance system and pilot warning instrument areas A72-12379

GRAPHIC ARTS

Development of technique for graphic presentation of fault isolation and problem correction for maintenance of large commercial aircraft N72-11028

GRAPHS (CHARTS)

Graphs and tables of service cost for intraurban transportation system
[NASA-CR-114341] N72-10985

Documentation of data used in intraurban transportation analysis appendix
[NASA-CR-114343] N72-10987

GREAT BRITAIN

Sonic boom waveforms measured during exercise summer sky in southern Great Britain
[ARC-R/M-3659] N72-11015

GROUND STATIONS

Array data analysis system for fixed and rotary wing aircraft flight testing, including airborne and computer controlled ground stations equipment A72-12408

GROUND SUPPORT EQUIPMENT

Analysis of facilities, equipment, and tools to maintain large commercial aircraft N72-11023

Development and characteristics of coordinated, in-flight and on-ground fault isolation system for maintenance of large commercial aircraft N72-11027

GROUND TESTS

Concorde airworthiness certification, discussing ground and flight test programs for performance, flying qualities and structures fatigue properties evaluation
[SAE PAPER 710756] A72-10253

Ground and air tests of flight inspection marker beacon receiving system
[FAA-NA-71-29] N72-10173

GUST ALLEVIATORS

Linear functional law for alleviating gusts on delta wing aircraft
[ONERA-TP-925] N72-10999

GUST LOADS

Analysis and comparison of gust load models based on either discrete gust concept or continuous gust concept
[NLR-TR-71025U] N72-10998

Aerodynamic lift characteristics of oscillating two dimensional airfoil subjected to sinusoidal gust
[AD-726132] N72-11017

GYROSCOPES

Passenger aircraft onboard automated inertial navigation devices, emphasizing accelerometer and gyroscope design and construction A72-10070

Mathematical models of rate gyros, servo accelerometers, pressure transducers, and telemetry systems and analog computer simulation programs
[NASA-CR-1768] N72-10401

H**HANDBOOKS**

Development of procedures for improving readability of maintenance manuals and evaluation of reading difficulty level N72-11021

HANGARS

Full scale measurement of flow in turbulent wake of hangars
[ABC-CP-1166] N72-11047

HARMONIC OSCILLATION

Low subsonic region unsteady interference effects on harmonically oscillating wing-tailplane model with variable sweep wing
[DGLR PAPER 71-081] A72-12709

Unsteady pressure distribution on harmonically oscillating circular cylindrical fuselage body with conical nose and delta wing with straight, cubic or sinusoidal leading edges
[DGLR PAPER 71-080] A72-12730

HEAT RESISTANT ALLOYS

Superalloys ductility and workability improvements without sacrificing elevated temperature strength for aircraft engine applications A72-12561

HEAVY NUCLEI

Thin-down intensities for heavy primaries at SST flight levels, using plastic stacks measurements A72-12077

HELICOPTER CONTROL

Free flight simulation tests for V/STOL aircraft nonlinear attitude control system adaptation to

HELICOPTER DESIGN

SUBJECT INDEX

- helicopter pitch and roll control
[DGLR PAPER 71-060] A72-12714
- Analysis of flight control system requirements for
helicopters and design of pilot assisted control
system
[AD-725590] N72-11057
- HELICOPTER DESIGN**
- Matrix method calculation for aerodynamic loads,
transverse forces, bending moments, torques and
twist of hinged main rotor blades in helicopter
during forward flight A72-12440
- Analysis of military helicopter reliability
requirements based on performance and reliability
test programs
[AD-725595] N72-11059
- HELICOPTER PERFORMANCE**
- Aerodynamic characteristics of helicopters and
principles of helicopter flight
[AD-726841] N72-10046
- HELICOPTER WAKES**
- Turbulent and laminar jet flow in rotating
environments noting application to jet mixing flow
in tip driven rotor wakes N72-10008
- Lifting rotor flow noting wake models N72-11002
- Variable geometry rotor system for direct control
over wake vortex
[NASA-CASE-LAR-10557] N72-11018
- HELICOPTERS**
- Helicopter antenna placement, using scale models for
three dimensional radiation pattern semiautomatic
recording under free space conditions A72-10149
- Helicopter elastomeric bearing rotors, discussing
downtime and cost reduction, maintenance,
endurance and inspection A72-10150
- Helicopter rotor tip drag relief estimate based on
two dimensional drag divergence with Mach number,
airfoil parameters and flight conditions A72-12882
- Aerodynamic characteristics of helicopters and
principles of helicopter flight
[AD-726841] N72-10046
- Helicopter lift margin system to aid in determining
power requirements for takeoff and landing
[AD-725207] N72-11053
- Analysis of helicopter tail rotor flow patterns in
and out of ground effect
[AD-725591] N72-11060
- Post-crash fire safety of helicopter turbine engine
fuels N72-11688
- HIGH ALTITUDE**
- Soviet book on civil aircraft high altitude
equipment covering air conditioning systems,
oxygen equipment and cabin pressurization A72-12295
- HIGH ASPECT RATIO**
- Theoretical performance of jet flap rotor at advance
ratios greater than 1.0
[AD-726706] N72-10037
- HIGH ENERGY PROPELLANTS**
- Possible high energy fuels for supersonic aircraft
N72-11670
- HIGH PRESSURE OXYGEN**
- Aircraft high pressure oxygen cylinder system filler
valve optimum standards, discussing automatic fill
rate and pressure sensitive closing control,
design, construction and performance
[SAE-AS-1225] A72-10385
- HIGH TEMPERATURE GASES**
- Recirculation mechanism in jet powered V/STOL
aircraft
[BMVG-FBWT-71-12] N72-10828
- HIGH TEMPERATURE LUBRICANTS**
- Assessment of high temperature stability of
synthetic lubricants for aircraft gas turbines
N72-11695
- Analysis of lubricant system used in civil
supersonic gas turbine engine N72-11697
- Synthetic high temperature lubricants thickened by
complex esters for supersonic aircraft N72-11701
- HORIZONTAL TAIL SURFACES**
- European A300B airbus flap and slat systems and
tailplane actuator for longitudinal pitch trim
control A72-10725
- Low subsonic region unsteady interference effects on
harmonically oscillating wing-tailplane model with
variable sweep wing
[DGLR PAPER 71-081] A72-12709
- HOSSES**
- Lightweight low pressure plastic hose assemblies in
aircraft and missile petroleum base fuel and
synthetic lubricating oil systems at 395-710 R and
up to 200 psi
[SAE-ARP-1180] A72-10388
- HUMAN FACTORS ENGINEERING**
- Aircraft ride comfort problem in turbulent air,
comparing free and fixed wing aircraft responses
A72-11720
- Analysis of flight control system requirements for
helicopters and design of pilot assisted control
system
[AD-725590] N72-11057
- HUMAN PERFORMANCE**
- Application of linear mathematical model to
represent human operator performance in
controlling attacking fighter aircraft
[AD-725069] N72-10042
- Effects of environmental stresses on attack
helicopter crew task performance in NATO theater
[AD-726949] N72-10122
- HYBRID PROPULSION**
- Mach 0.80 quiet intercity STOL transport design
comparison for turbofan, prop-fan and turboprop
systems
[SAE PAPER 710759] A72-10256
- HYDROCARBON FUELS**
- Jet fuels hydrocarbon composition effect on thermal
stability, considering nonaromatic components
influence on aromatic hydrocarbons oxidation
products coagulation A72-12800
- Propulsion systems for low emission urban vehicles
and analysis of exhaust emissions from
fossil-fueled heat engines
[PB-200144] N72-10830
- Possible high energy fuels for supersonic aircraft
N72-11670
- Cooling advanced engines by endothermic reactions of
hydrocarbon fuels by absorbing sensible and latent
heat N72-11672
- HYPERSONIC AIRCRAFT**
- Aerodynamic characteristics of wind tunnel model of
hypersonic aircraft
[NASA-TN-D-6577] N72-10045
- Kerosene-type fuel for supersonic and hypersonic
aircraft N72-11671
- HYPERSONIC BOUNDARY LAYER**
- Laminar three dimensional boundary layer
nonequilibrium effects at hypersonic wing swept
leading edge with intensively cooled surface,
considering sweep induced crossflow effect
[VPI-E-71-23] A72-12422
- HYPERSONIC FLOW**
- Supersonic and hypersonic flows with attached shock
waves over delta wing at angle of attack, deriving
unified theory for flow field A72-12030
- Hypersonic boundary layer separation of delta wing
in shock tunnel using color and monochrome
schlieren photography
[NPL-AERO-NOTE-1097] N72-10022
- HYPERSONIC VEHICLES**
- Area rule for change in lift/drag ratio of
hypersonic delta wing due to conical body addition
on compression side A72-12270
- IGNITION**
- Theoretical analysis of fuel ignition by hot
projectile and ignition delay time as function of
temperature and width of hot gas region
N72-11683
- Crash safe turbine fuel program, using gelled fuels
N72-11687
- IMPACT LOADS**
- Parachute opening shock and filling time calculation

SUBJECT INDEX

INTERNATIONAL LAW

- based on aerodynamic drag, air mass and effective porosity time functions, using momentum and continuity equations
A72-10310
- IMPACT TESTS**
Crash safe turbine fuel program, using gelled fuels
N72-11687
- IN-FLIGHT MONITORING**
In-flight warning meter for solar and cosmic radiation dose equivalent measurements for radiological protection in SST aircraft
A72-12078
Soviet book on in-flight studies of aircraft stability and controllability covering dynamic characteristics, measurements, balancing curves, aerodynamic forces and limiting and special flight regimes
A72-12542
- INCONEL (TRADEMARK)**
Forged Inconel alloy 718 metal powder preforms for dense aircraft engine compressor rotor blades
A72-11441
- INDICATING INSTRUMENTS**
Airfield Vehicle Obstacle Indication Device short range high-definition radar system for aircraft navigation aid
A72-12042
Soviet book on course-indicating systems and automatic navigation aids for civil aviation aircraft covering design, operation principles, error analysis and reliability
A72-12298
- INERTIAL NAVIGATION**
Passenger aircraft onboard automated inertial navigation devices, emphasizing accelerometer and gyroscope design and construction
A72-10070
Inertial navigation role in automatic ATC systems, discussing path control accuracies, environmental conditions, noise and air pollution, etc
A72-11118
- INFINITE SPAN WINGS**
Rotor downwash variation by changing vortice diameter, flapping, rotor speed, and radius and placing infinite span wing in flow field
N72-11003
- INFLATING**
Parachute opening shock and filling time calculation based on aerodynamic drag, air mass and effective porosity time functions, using momentum and continuity equations
A72-10310
Parachute inflation loads and times, presenting calculation method based on unsteady pressure distribution on decelerating inflating parabolic shell of revolution with unsteady starting vortex
A72-10311
- INFRARED DETECTORS**
Basic requirements for airborne infrared forest fire detection system
[AD-726953]
N72-10396
- INFRARED SPECTROPHOTOMETERS**
Infrared spectrophotometer used for detection of trace contaminants from Pegasus and Olympus engines in aircraft cabin atmospheres
[QAD-MATS-174]
N72-10040
- INFRASONIC FREQUENCIES**
Portable detector-recorder for automobile, blast furnace, railroad car, engine room and helicopter infrasonic noise measurements, discussing peak frequencies and subjective effects
A72-10157
- INGESTION (ENGINES)**
Recirculation mechanism in jet powered V/STOL aircraft
[BMVG-PBWT-71-12]
N72-10828
- INLET NOZZLES**
Thermal shock fatigue tests on aircraft gas turbine engine inlet nozzles, showing cracks as function of material
A72-11373
In-flight investigation of installation effects and aerodynamic characteristics of local flow field on auxiliary inlet ejector nozzle on underwing engine nacelle
[NASA-TM-X-2396]
N72-11711
- INPUT/OUTPUT ROUTINES**
Development of structural optimization algorithm for obtaining near optimum distributions of material for structural idealizations
[AD-726112]
N72-11820
- INSPECTION**
Metal fatigue damage nondestructive detection, discussing inspection methods, equipment, advantages, limitations and test results
A72-12498
Ground and air tests of flight inspection marker beacon receiving system
[FAA-WA-71-29]
N72-10173
Development of technique for graphic presentation of fault isolation and problem correction for maintenance of large commercial aircraft
N72-11028
- INSTRUMENT ERRORS**
Optimal stochastic /Kalman/ filters application to integrated air and submarine navigation systems, discussing measurement errors modeling as bias and colored noise
A72-12050
Performance tests on aerodynamically compensated pressure heads for BAC 221 aircraft noting pressure sensing errors
[ARC-CP-1167]
N72-11046
- INSTRUMENT LANDING SYSTEMS**
Aircraft ILS, covering history, adverse weather operations and replacement systems
A72-12645
- INTAKE SYSTEMS**
In-flight investigation of installation effects and aerodynamic characteristics of local flow field on auxiliary inlet ejector nozzle on underwing engine nacelle
[NASA-TM-X-2396]
N72-11711
- INTEGRAL EQUATIONS**
Aerodynamic behavior of thin jet-flapped airfoil, investigating integrodifferential equation solution
A72-11669
- INTERFERENCE DRAG**
Jet engine simulation with low speed wind tunnel models for interference drag measurement
N72-10005
Jet interference effects on yaw stability for SAAB 37 and 105 wind tunnel models
N72-10006
Vertical takeoff aircraft wind tunnel model with high pressure ejectors to determine jet interference on aerodynamic coefficients
N72-10007
Jet interference and lift drag ratio of swept wing aircraft with turbofan above wing
[RAE-TM-AERO-1271]
N72-10009
Influence of jet interference on aerodynamic coefficients of rectangular and swept wings mounted above the engine
N72-10010
Impinging inclined jet effect on aerodynamic characteristics of control surface in VTOL longitudinal stability
N72-10011
European airbus wind tunnel model aerodynamic force and downwash measurements noting jet interference reduction
N72-10012
Multipropeller slipstream and wing interference, noting lift, drag, pitching moment, normal force distribution, and wakes
N72-10015
- INTERFERENCE LIFT**
Low subsonic region unsteady interference effects on harmonically oscillating wing-tailplane model with variable sweep wing
[DGLR PAPER 71-081]
A72-12709
Multipropeller slipstream and wing interference, noting lift, drag, pitching moment, normal force distribution, and wakes
N72-10015
Aerodynamic lift characteristics of oscillating two dimensional airfoil subjected to sinusoidal gust
[AD-726132]
N72-11017
- INTERNATIONAL COOPERATION**
Uhf aeronautical satellite system, presenting ATC trends, international aspects, available flight levels, weather conditions and long haul conflicts
A72-12383
- INTERNATIONAL LAW**
Air law concept as totality of legal regulations related to atmosphere use by flying devices,

ITERATIVE SOLUTION

SUBJECT INDEX

discussing relation to international environmental protection

A72-11107

ITERATIVE SOLUTION

Flutter equation approximate true damping or rate-of-decay solution by determinant iteration

A72-11133

J

JET AIRCRAFT

Augmentor wing jet STOL research aircraft development progress report covering design, engine tests, performance prediction, control simulation and stability augmentation [SAE PAPER 710757]

A72-10254

Handling qualities simulation program for augmentor wing jet STOL research aircraft considering control devices design

A72-11654

Carrier system for controlled approach of Naval aircraft to provide pilot window to deck for tactical jet guidance for poor visibility landing

A72-12323

Externally blown flaps for STOL characteristics in medium and heavy jet transport aircraft, demonstrating aerodynamic and flight mechanical feasibility

A72-12502

Jet aircraft brake parachute loads under engine wake, evaluating velocity and drag coefficient influences

A72-12504

Full scale wind tunnel tests of small unpowered jet aircraft with T tail [NASA-TN-D-6573]

N72-10031

Description of maintenance procedures used on Beechcraft Hawker 125 commercial jet aircraft

N72-11032

Synthesis and properties of aliphatic ester for turbine lubrication in jet aircraft

N72-11696

JET AIRCRAFT NOISE

Liquid-base foam sound absorbing properties for jet aircraft noise reduction

A72-10160

Acoustic power radiated by jet aircraft fuselage structure exposed to turbulent boundary layer pressure field, evaluating noise reduction treatments

A72-10216

Jet aircraft turbofan engine fan compressor noise reduction by acoustic linings, giving R and D results

A72-10223

Jet noise reduction technology, hardware and tests for NASA Quiet Engine Program to develop low noise subsonic civil transport aircraft propulsion system

A72-10266

High speed jet noise source physical properties interpretation by theory and scale-model experiments for supersonic transport aircraft noise suppression problem

A72-11973

Q/STOL jet aircraft engines design for low noise levels, describing takeoff thrust, bypass ratio and turbine stages

A72-12501

Aladin 2 noiseless STOL jet aircraft project, describing exhaust nozzle configuration, design and economics

A72-12503

Annotated bibliography on aircraft noise pollution - Vol. 1 [AD-724850]

N72-10036

Sound generation and scale model experiments to suppress noise in turbulent jet flow eddies of supersonic transport aircraft

N72-10254

Noise generation by rotating blades of axial flow fan in infinite annulus [AD-726126]

N72-11714

JET ENGINE FUELS

Viscosity and additive effects on jet engine fuel antiwear properties improvement

A72-11968

Jet fuels hydrocarbon composition effect on thermal stability, considering nonaromatic components

influence on aromatic hydrocarbons oxidation products coagulation

A72-12800

Jet fuel specifications for military and civil aircraft

N72-11669

European jet fuel lubricity evaluation

N72-11679

Flammability properties of jet fuels and techniques for fire and explosion suppression under simulated hostile operating environment conditions

N72-11681

Effect of Sulfur in JP-5 fuel on hot corrosion of turbine blade materials operating in marine environment [AD-725619]

N72-11706

JET ENGINES

Electrodischarge and electrochemical machining applications in continuous repetitive production of aircraft jet engine components

A72-11150

Jet engine component overhaul procedures for fatigue damage repair, detailing distressed metal removal, replacement and welding techniques

A72-12499

Jet engine simulation with low speed wind tunnel models for interference drag measurement

N72-10005

Influence of jet interference on aerodynamic coefficients of rectangular and swept wings mounted above the engine

N72-10010

European airbus wind tunnel model aerodynamic force and downwash measurements noting jet interference reduction

N72-10012

JET EXHAUST

Nozzle shape, temperature, and velocity effects on free hypersonic jet exhaust properties

N72-10013

JET FLAPS

STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure

A72-11700

Theoretical performance of jet flap rotor at advance ratios greater than 1.0 [AD-726706]

N72-10037

JET FLOW

Conference papers on jet and slipstream influence on aerodynamic coefficients using aircraft models [DLR-HITT-70-28]

N72-10004

Impinging inclined jet effect on aerodynamic characteristics of control surface in VTOL longitudinal stability

N72-10011

Flow model for jet pipe sound transmission through nozzle flow [JEFW/69]

N72-10252

Sound generation in very low and very high turbulent jet flows from exhaust nozzle

N72-10253

JET LIFT

Calculation of pressure distribution on cylindrical fuselage with perpendicular lifting jet using singularity method

N72-10014

JOINING

Webbing joints stitching strain, considering nylon and flax yarns stretching properties and various stitching patterns strengths

A72-10315

K

KEROSENE

Kerosene-type fuel for supersonic and hypersonic aircraft

N72-11671

L

L-1011 AIRCRAFT

TriStar commercial jet transport aircraft development, discussing design and flight tests for operating efficiency, reliability and safety [SAE PAPER 710755]

A72-10252

LAMINAR FLOW

Turbulent and laminar jet flow in rotating environments noting application to jet mixing flow

- in tip driven rotor wakes
N72-10008
- LAND USE**
STOL aircraft for solving noise reduction and land use problems in future transportation systems, discussing airport location and layout for growing air traffic
A72-11153
[PB-201195] N72-10050
- LANDING AIDS**
Carrier system for controlled approach of Naval aircraft to provide pilot window to deck for tactical jet guidance for poor visibility landing
A72-12323
Microwave aircraft landing system development, discussing contract definition, feasibility, prototype development, management planning and program costs
A72-12377
Suitability evaluation of fog simulator for weather conditions during flight approach
[FAA-NA-71-44] N72-10233
- LANDING GEAR**
European A300B airbus flying control hydraulic system and landing gear design for safety and reliability, fatigue life, weight and maintenance
A72-10724
B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation
A72-12226
- LANDING SITES**
Measurement of three track runway and taxiway profiles at two international airports
[NASA-TN-D-6567] N72-11038
- LASERS**
Air traffic control radar beacon systems and laser warning systems
[AD-725743] N72-10543
- LATERAL CONTROL**
Three dimensional roll-controlled missile trajectory model for simple time-sharing digital or analog simulation, using wind-to-inertial axis transformation
A72-10964
STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure
A72-11700
- LAW (JURISPRUDENCE)**
Air law concept as totality of legal regulations related to atmosphere use by flying devices, discussing relation to international environmental protection
A72-11107
German book on air traffic law covering norms relative to vehicles and air space, international air law, organizations, etc
A72-12622
- LEADING EDGE SLATS**
European A300B airbus flap and slat systems and tailplane actuator for longitudinal pitch trim control
A72-10725
- LIFT**
Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts
A72-10220
Area rule for change in lift/drag ratio of hypersonic delta wing due to conical body addition on compression side
A72-12270
Drag and lift experimental determination for low aspect ratio rectangular wings with blunt trailing edges at Mach numbers 0.5-2.2
[DGLR PAPER 71-114] A72-12712
Turbofans under wings to provide lift and thrust for STOL aircraft
[NASA-CASE-LEW-11224-1] N72-10033
Helicopter lift margin system to aid in determining power requirements for takeoff and landing
[AD-725207] N72-11053
Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions
[NASA-TN-D-6530] N72-11289
- LIFT AUGMENTATION**
Disk shaped lift engine providing additional thrust during takeoff and transition phases of V/STOL aircraft, returning to ground by jet after task accomplishment
A72-12900
- LIFT DRAG RATIO**
Jet interference and lift drag ratio of swept wing aircraft with turbofan above wing
[RAE-TN-AERO-1271] N72-10009
- LIFTING BODIES**
Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions
[NASA-TN-D-6530] N72-11289
- LIFTING REENTRY VEHICLES**
Thin shock layer theory of lifting properties of reentry caret and flat delta wings and waveriders at high incidence angles and Mach number
A72-12345
- LIFTING ROTORS**
Helicopter rotor tip drag relief estimate based on two dimensional drag divergence with Mach number, airfoil parameters and flight conditions
A72-12882
Rotor and propeller wake calculation, recovery rotors, and rotor feedback control
[DLR-MTT-71-12] N72-11001
Lifting rotor flow noting wake models
N72-11002
Rotor downwash variation by changing vortice diameter, flapping, rotor speed, and radius and placing infinite span wing in flow field
N72-11003
Constant phase shift between flapping and action on center of gravity for spring hinged rotor with variable flapping stiffness
N72-11007
- LIGHTNING**
Lightning protective coatings for boron/epoxy composite materials, discussing high current damage mechanisms, simulation facility and test results on aluminum foils, meshes, etc
A72-10783
- LINEAR FILTERS**
Optimal stochastic /Kalman/ filters application to integrated air and submarine navigation systems, discussing measurement errors modeling as bias and colored noise
A72-12050
- LINEAR SYSTEMS**
Linear aerodynamic rotor theories showing effect of applied vortex model on exactitude of numerical analysis
N72-11005
- LININGS**
Design of flexible steel liners for adjustable transonic wind tunnel nozzle
[NPL-AERO-NOTE-1098] N72-10023
- LOAD DISTRIBUTION (FORCES)**
Airport apron surface pavement strain measurements under field loading conditions, considering static and dynamic loads with finite element method
A72-10192
Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core
A72-10723
- LOADS (FORCES)**
Maneuver acceleration measured for estimating loads during civil aircraft training and test flying
[ARC-CP-1176] N72-11043
- LOCKS (FASTENERS)**
Development of sprayable urethane sealant for protection of heated areas on aircraft structures
[AD-727592] N72-10489
- LOGIC CIRCUITS**
Improvements in aircraft maintenance procedures based on solid state electrical power management and solid state contactless switching circuits
N72-11034
- LOGIC DESIGN**
Digital computer memory system for real time processing of air and naval traffic data, discussing logic design, time comparisons and optimum use
A72-12647
- LOW ALTITUDE**
Crew compartment vibration environment in B-52 aircraft during low altitude, high speed flight

LOW ASPECT RATIO WINGS

SUBJECT INDEX

[AD-727023] N72-10127

LOW ASPECT RATIO WINGS

Force and pressure distribution measurements on delta wing-body combination in compressible flow, investigating Reynolds number effect [DGLR PAPER 71-118] A72-12707

Drag and lift experimental determination for low aspect ratio rectangular wings with blunt trailing edges at Mach numbers 0.5-2.2 [DGLR PAPER 71-114] A72-12712

Tip clearance effect on compressor blade aerodynamic characteristics, applying Bolland analysis to low aspect ratio rectangular wing A72-12825

LOW SPEED

Supersonic transport aircraft and BAC 221 aircraft piloted flight simulation near zero rate climb velocity for determining aircraft maneuver controllability at low speed [ARC-CP-1165] N72-11048

LOW SPEED WIND TUNNELS

Jet engine simulation with low speed wind tunnel models for interference drag measurement N72-10005

LOW VISIBILITY

Flight simulator exercise for investigation of pilot performance in low visibility conditions during approach and landing [RAE-TR-71044] N72-11042

LUBRICANT TESTS

Properties evaluation of lubricants and fuels for use in advanced aircraft gas turbine [NASA-CR-122842] N72-11694

LUBRICANTS

Aircraft fuels, lubricants, and fire safety - conferences [AGARD-CP-84-71] N72-11668

European jet fuel lubricity evaluation N72-11679

LUBRICATING OILS

Analytical methods for early-stage detection of oil deterioration in aircraft engines N72-11698

Thermal stability of trimethyl propane ester based lubricating oil for aircraft engines N72-11699

LUBRICATION

Synthesis and properties of aliphatic ester for turbine lubrication in jet aircraft N72-11696

LUBRICATION SYSTEMS

Lightweight low pressure plastic hose assemblies in aircraft and missile petroleum base fuel and synthetic lubricating oil systems at 395-710 R and up to 200 psi [SAE-ARP-1180] A72-10388

M

MACHINING

Warpage control of large Al alloy forgings machining of jumbo jet components, using packing and storage methods [SAE PAPER 710801] A72-10280

MAINTENANCE

Jet engine component overhaul procedures for fatigue damage repair, detailing distressed metal removal, replacement and welding techniques A72-12499

MAN MACHINE SYSTEMS

Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities A72-12420

Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar A72-12421

Aircraft design interactive computer graphics technique, using human decision input response to computer output information [DGLR PAPER 71-107] A72-12733

Application of linear mathematical model to represent human operator performance in controlling attacking fighter aircraft [AD-725069] N72-10042

MANAGEMENT PLANNING

Aircraft producibility considerations in preliminary

design and production planning phases [SAE PAPER 710746] A72-10245

ATC system decision making problem and future technological and administrative improvements A72-11718

MANEUVERS

Maneuver acceleration measured for estimating loads during civil aircraft training and test flying [ARC-CP-1176] N72-11043

MANUALS

DC-10 nondestructive testing manual, detailing section/subject format, methods, planned area accessibility and aircraft maintenance A72-11109

Development of procedures for improving readability of maintenance manuals and evaluation of reading difficulty level N72-11021

MANUFACTURING

Aircraft design producibility to reduce production cost and enhance product profitability, using joint engineering and manufacturing team [SAE PAPER 710748] A72-10247

Design and development of numerically controlled machine for laying composite tape used in building aircraft structured from filament reinforced resin matrix composite materials [AD-725765] N72-10425

MARAGING STEELS

Constant high tensile stress and rapid aerodynamic heating effect on maraging steels and Ti and Al alloys, evaluating test and simulation procedures for design data development A72-10749

MARKET RESEARCH

Commercial transport market and technology forecasting, considering all-cargo, STOL, SST and CTOL aircraft [SAE PAPER 710750] A72-10249

MARYLAND

Short term airport access improvements in Baltimore-Washington area with service brochure implementation [PB-200686] N72-10232

MATERIALS TESTS

Aerospace wire and cables testing methods standards for evaluating mechanical, electrical and chemical properties, coating thicknesses, continuity flaws, flammability, geometrical characteristics, etc [SAE-AS-1198] A72-10384

Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core A72-10723

MATHEMATICAL MODELS

Three dimensional roll-controlled missile trajectory model for simple time-sharing digital or analog simulation, using wind-to-inertial axis transformation A72-10964

Lifting rotor flow noting wake models N72-11002

Linear aerodynamic rotor theories showing effect of applied vortex model on exactitude of numerical analysis N72-11005

Mathematical models for studying incoherent and coherent structures of aerodynamically generated noise [ONERA-TP-983] N72-11036

MATRIX METHODS

Matrix method calculation for aerodynamic loads, transverse forces, bending moments, torques and twist of hinged main rotor blades in helicopter during forward flight A72-12440

MECHANICAL PROPERTIES

Parachute canopy fabrics and rigging lines cordage properties requirements, considering nylon, polypropylene, silk, cotton and nonwoven scrim-reinforced fabrics A72-10314

Graphite filament reinforced plastics strength, performance properties, fabrication processes and tooling concepts [SME PAPER EM 71-205] A72-10968

MERCATOR PROJECTION

Polar navigation with transverse mercator technique

- for aircraft using secant geared ground position indicators
A72-10181
- METAL FATIGUE**
Residual buckling strength of Al alloy elastic column with fatigue crack
[SESA PAPER 1914A] A72-11511
Metal fatigue damage nondestructive detection, discussing inspection methods, equipment, advantages, limitations and test results
A72-12498
Jet engine component overhaul procedures for fatigue damage repair, detailing distressed metal removal, replacement and welding techniques
A72-12499
Theoretical and analytical aspects of metal fatigue failure and relationships to fracture mechanics
[AD-725028] N72-10957
- METAL WORKING**
Integrity control procedures for machining, drilling and grinding of steel and Ti alloy aircraft parts, discussing nondestructive inspection method
[SME PAPER IQ 71-238] A72-10969
Superalloys ductility and workability improvements without sacrificing elevated temperature strength for aircraft engine applications
A72-12561
- METALLOGRAPHY**
Metallographic and fract ographic analyses of cracking in T53-L13 gas turbine engine compressor disks
A72-10816
- METEOROLOGICAL PARAMETERS**
Acoustic echo sounder as real time monitor of airport environmental meteorological parameters
A72-11137
- METEOROLOGICAL RADAR**
Radar observation of weather conditions for aircraft flight
[ONM-264-TP-148] N72-11147
- MICHIGAN**
Cost analysis and operational procedures of effective short range, high density computer transportation system for Metropolitan Detroit
[NASA-CR-114340] N72-10984
- MICROWAVE EQUIPMENT**
Microwave aircraft landing system development, discussing contract definition, feasibility, prototype development, management planning and program costs
A72-12377
- MILITARY AIRCRAFT**
Industry assisted state of art assessment of high lift turbofan configurations for USAF STOL tactical transport technology program
[SAE PAPER 710758] A72-10255
Military specification adoption for flight characteristics of piloted V/STOL aircraft
[AD-725746] N72-10048
- MILITARY HELICOPTERS**
Effects of environmental stresses on attack helicopter crew task performance in NATO theater
[AD-726949] N72-10122
Analysis of military helicopter reliability requirements based on performance and reliability test programs
[AD-725595] N72-11059
- MILITARY TECHNOLOGY**
Parachute designs and applications to escape systems, paratrooping, supply dropping, aircraft braking, weapons systems stabilization, flight testing aids and sport
A72-10302
Paratroop type parachutes breathing oscillations and stability characteristics, using high speed cinematography and kinetheodolites to track during steady state descent
A72-10307
- MILLIMETER WAVES**
Analysis of target signal requirements for aircraft navigation systems using millimeter wave radiometry from terrain radiation or ground-based beacons
[NASA-TM-X-62082] N72-10539
- MISSILE ANTENNAS**
Unpredicted structural vibration in Comet and Electra aircraft, Graf Zeppelin dirigible, missile antennas, etc
A72-12002
- MISSILE CONTROL**
Three dimensional roll-controlled missile trajectory model for simple time-sharing digital or analog simulation, using wind-to-inertial axis transformation
A72-10964
- MISSILE STRUCTURES**
Lightweight low pressure plastic hose assemblies in aircraft and missile petroleum base fuel and synthetic lubricating oil systems at 395-710 R and up to 200 psi
[SAE-ARP-1180] A72-10388
- MONITORS**
Acoustic echo sounder as real time monitor of airport environmental meteorological parameters
A72-11137
- MULTISPECTRAL BAND SCANNERS**
Multichannel multispectral scanner system for NASA C-130 earth resources aircraft, describing electronic equipment and calibration sources
A72-10946
- N**
- NACELLES**
Propulsion system optimization in transonic transport aircraft design, considering nacelle integration, engine choice, noise attenuation and technology utilization
[SAE PAPER 710762] A72-10259
- NASA PROGRAMS**
Jet noise reduction technology, hardware and tests for NASA Quiet Engine Program to develop low noise subsonic civil transport aircraft propulsion system
[SAE PAPER 710774] A72-10266
- NAVIGATION AIDS**
Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention
A72-11117
Inertial navigation role in automatic ATC systems, discussing path control accuracies, environmental conditions, noise and air pollution, etc
A72-11118
Airfield Vehicle Obstacle Indication Device short range high-definition radar system for aircraft navigation aid
A72-12042
Optimal stochastic /Kalman/ filters application to integrated air and submarine navigation systems, discussing measurement errors modeling as bias and colored noise
A72-12050
Airborne pictorial navigation systems for visual indication of aircraft position in addition to digital readout
A72-12106
Soviet book on course-indicating systems and automatic navigation aids for civil aviation aircraft covering design, operation principles, error analysis and reliability
A72-12298
Radio aids to maritime and aerial navigation - Conference, Trieste, June 1971
A72-12640
L band in satellite system for aerial navigation aid, discussing position accuracy, data transmission and voice communication and modulation methods
A72-12642
Radio aids for air navigation and traffic control in Italy, discussing facilities development
A72-12748
- NAVIGATION SATELLITES**
Uhf aeronautical satellite system, presenting ATC trends, international aspects, available flight levels, weather conditions and long haul conflicts
A72-12383
- NEW YORK**
Metropolitan aircraft noise abatement policy study, John F. Kennedy International Airport, New York, New York
[PB-200164] N72-11051
- NITROGEN OXIDES**
Possible catalytic reduction of stratospheric ozone by nitrogen oxides emitted from SST aircraft
[UCRL-20568] N72-11334

NOISE (SOUND)

SUBJECT INDEX

NOISE (SOUND)

Annotated bibliography on acoustics
[NPL-AERO-AC-47] A72-10589

NOISE INTENSITY

Aircraft engine noise effects in airport vicinities,
discussing measurement scales, turbofan sources,
noise reduction and future air traffic A72-12022

NOISE POLLUTION

Portable detector-recorder for automobile, blast
furnace, railroad car, engine room and helicopter
infrasound noise measurements, discussing peak
frequencies and subjective effects A72-10157

Aircraft noise effects on land use around airports
[PB-201195] A72-10050

NOISE REDUCTION

Liquid-base foam sound absorbing properties for jet
aircraft noise reduction A72-10160

Acoustic power radiated by jet aircraft fuselage
structure exposed to turbulent boundary layer
pressure field, evaluating noise reduction
treatments A72-10216

Jet aircraft turbofan engine fan compressor noise
reduction by acoustic linings, giving R and D
results [BAS PAPER 71 SA6] A72-10223

Jet noise reduction technology, hardware and tests
for NASA Quiet Engine Program to develop low noise
subsonic civil transport aircraft propulsion
system [SAE PAPER 710774] A72-10266

STOL aircraft for solving noise reduction and land
use problems in future transportation systems,
discussing airport location and layout for growing
air traffic A72-11153

High speed jet noise source physical properties
interpretation by theory and scale-model
experiments for supersonic transport aircraft
noise suppression problem A72-11973

Aircraft engine noise effects in airport vicinities,
discussing measurement scales, turbofan sources,
noise reduction and future air traffic A72-12022

Design, fabrication, and ground tests of perforated
stainless steel exhaust nozzle inserts for Boeing
707 aircraft noise reduction [NASA-CR-1853] A72-10043

Sound generation and scale model experiments to
suppress noise in turbulent jet flow eddies of
supersonic transport aircraft [ARC-32723] A72-10254

Noise reduction for climbing takeoff and V/STOL
aircraft affecting stability [DLR-FB-71-10] A72-11040

NOISE TOLERANCE

Incremental value of noise pollution level as basis
for aircraft noise rating [NPL-AERO-AC-49] A72-10035

NONDESTRUCTIVE TESTS

Nondestructive radioactive gas penetrant tests for
porosity and fatigue damage in jet engine castings
A72-10813

Portable self contained ultrasonic field inspection
equipment for nondestructive crack detection in
T53 gas turbine compressor disks A72-10814

Integrity control procedures for machining, drilling
and grinding of steel and Ti alloy aircraft parts,
discussing nondestructive inspection method
[SME PAPER IQ 71-238] A72-10969

Automatic ultrasonic testing equipment for NDT tests
of helicopter rotor blades A72-11021

DC-10 nondestructive testing manual, detailing
section/subject format, methods, planned area
accessibility and aircraft maintenance A72-11109

Metal fatigue damage nondestructive detection,
discussing inspection methods, equipment,
advantages, limitations and test results A72-12498

Application of nondestructive testing procedures to
maintenance of large commercial aircraft A72-11025

NONEQUILIBRIUM FLOW

Laminar three dimensional boundary layer
nonequilibrium effects at hypersonic wing swept
leading edge with intensively cooled surface,
considering sweep induced crossflow effect
[VPI-E-71-23] A72-12422

NONLINEAR SYSTEMS

Free flight simulation tests for V/STOL aircraft
nonlinear attitude control system adaptation to
helicopter pitch and roll control [DGLR PAPER 71-060] A72-12714

NOSE WHEELS

Electromechanical nose wheel steering system for
general aviation aircraft ground maneuverability
improvement, describing design A72-10963

NOZZLE DESIGN

Aladin 2 noiseless STOL jet aircraft project,
describing exhaust nozzle configuration, design
and economics A72-12503

Design of flexible steel liners for adjustable
transonic wind tunnel nozzle [NPL-AERO-NOTE-1098] A72-10023

NOZZLE FLOW

Gas turbine nozzles aerodynamic throat area air flow
measurement, describing accuracy, standards,
reference nozzles and mounting flanges [SAE-ARP-1195] A72-10390

Flow model for jet pipe sound transmission through
nozzle flow [JEPFV/69] A72-10252

Sound generation in very low and very high turbulent
jet flows from exhaust nozzle A72-10253

NOZZLE GEOMETRY

Gas turbine nozzles aerodynamic throat area air flow
measurement, describing accuracy, standards,
reference nozzles and mounting flanges [SAE-ARP-1195] A72-10390

NOZZLE INSERTS

Design, fabrication, and ground tests of perforated
stainless steel exhaust nozzle inserts for Boeing
707 aircraft noise reduction [NASA-CR-1853] A72-10043

NUMERICAL ANALYSIS

Mathematical analysis of separation standards and
aircraft navigational collision risk for parallel
tracks in radar monitored systems A72-10178

NUMERICAL INTEGRATION

Aircraft stability coefficient determination by
numerical integration fitting to differential
equations of motion A72-11136

Numerical evaluation of downwash integral for
lifting rectangular wings noting wing loading
[NPL-AERO-NOTE-1095] A72-11012

NYLON (TRADEMARK)

Parachute canopy fabrics and rigging lines cordage
properties requirements, considering nylon,
polypropylene, silk, cotton and nonwoven
scrim-reinforced fabrics A72-10314

Webbing joints stitching strain, considering nylon
and flax yarns stretching properties and various
stitching patterns strengths A72-10315

ON-LINE PROGRAMMING

On-line digital computer for wind tunnel, operating
systems, and real time operation [NPL-AERO-1326] A72-10184

ONE DIMENSIONAL FLOW

One dimensional unsteady flow in turbine engines
rotating and static vane cascades, discussing
vibrations propagation A72-11584

OPERATING SYSTEMS (COMPUTERS)

On-line digital computer for wind tunnel, operating
systems, and real time operation [NPL-AERO-1326] A72-10184

OPERATIONS RESEARCH

Roles of time and money cost in demand for air
travel [AD-725480] A72-11850

OPTIMIZATION

- Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness
[SAE PAPER 710778] A72-10270
- Technical programmers manual for automated procedure of optimizing practical aerospace structures - Vol. 2
[AD-725744] N72-10047
- Development of structural optimization algorithm for obtaining near optimum distributions of material for structural idealizations
[AD-726112] N72-11820
- ORIFICES**
Variable-orifice gas turbine system for fuel rate control in aircraft
[NASA-CASE-LEW-11187-1] N72-10824
- OXYGEN SUPPLY EQUIPMENT**
Soviet book on civil aircraft high altitude equipment covering air conditioning systems, oxygen equipment and cabin pressurization
A72-12295

OZONE

- Possible catalytic reduction of stratospheric ozone by nitrogen oxides emitted from SST aircraft
[UCRL-20568] N72-11334

P**PARACHUTE DESCENT**

- Paratroop type parachutes breathing oscillations and stability characteristics, using high speed cinematography and kinetheodolites to track during steady state descent
A72-10307
- Parachutes flow characteristics in low speed free descent, discussing glide angle effect on total drag and water channel flow pattern studies
A72-10309
- Parachute opening shock and filling time calculation based on aerodynamic drag, air mass and effective porosity time functions, using momentum and continuity equations
A72-10310
- Parachute inflation loads and times, presenting calculation method based on unsteady pressure distribution on decelerating inflating parabolic shell of revolution with unsteady starting vortex
A72-10311

PARACHUTE FABRICS

- Parachute canopy fabrics and rigging lines cordage properties requirements, considering nylon, polypropylene, silk, cotton and nonwoven scrim-reinforced fabrics
A72-10314

PARACHUTES

- Parachutes and related technologies - Conference, London, September 1971
A72-10301
- Parachute designs and applications to escape systems, paratrooping, supply dropping, aircraft braking, weapons systems stabilization, flight testing aids and sport
A72-10302
- Nonporous rigid parachute models three component measurements, using low speed wind tunnel for testing skirt length effects on aerodynamic characteristics
A72-10303
- Industrial parachute R and D in UK, discussing management, technical staff requirements and government/industry liaison
A72-10304
- Axial cords effects on parachute drag and stability characteristics and opening time, discussing wind tunnel and balloon drop tests results
A72-10306

PASSENGER AIRCRAFT

- Passenger aircraft onboard automated inertial navigation devices, emphasizing accelerometer and gyroscope design and construction
A72-10070

PAVEMENTS

- Airport apron surface pavement strain measurements under field loading conditions, considering static and dynamic loads with finite element method
A72-10192
- Line, cement, fly ash and sand combination airport pavement design and testing, discussing material

structural and chemical properties, compressive strength, costs, etc

A72-12023

PENETRANTS

- Nondestructive radioactive gas penetrant tests for porosity and fatigue damage in jet engine castings
A72-10813

PENETRATION

- Prediction of flight penetration of wing buffeting from wind tunnel model dynamic tests
[ARC-CP-1171] N72-11044

PERFORATED PLATES

- Design, fabrication, and ground tests of perforated stainless steel exhaust nozzle inserts for Boeing 707 aircraft noise reduction
[NASA-CR-1853] N72-10043

PERFORMANCE

- Evaluation of simulated pilot/system performance in manually controlled IFR formation flight task for UH-1 helicopter under various environmental and operational conditions
[AD-725209] N72-10044

PERFORMANCE PREDICTION

- Procedure for measuring performance of aircraft fire extinguishing powders
N72-11691

PERFORMANCE TESTS

- Supersonic ribbon parachute testing by transonic wind tunnel, rocket sled and water channel simulator
A72-10305
- Performance of axial flow compressor rotor with different casing treatment configuration
[NASA-TN-D-6538] N72-10025
- Basic requirements for airborne infrared forest fire detection system
[AD-726953] N72-10396
- Performance tests on aerodynamically compensated pressure heads for BAC 221 aircraft noting pressure sensing errors
[ARC-CP-1167] N72-11046
- Analysis of military helicopter reliability requirements based on performance and reliability test programs
[AD-725595] N72-11059
- Calibration and performance of cosmic radiation detector for Concorde supersonic transport
[FAA-AM-71-26] N72-11370
- Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic performance
[AD-725593] N72-11713
- PHASE SHIFT**
Constant phase shift between flapping and action on center of gravity for spring hinged rotor with variable flapping stiffness
N72-11007

PHASED ARRAYS

- Phased scanning array for ATC radar beacon systems, airport or air route surveillance radars and ground landing systems
A72-10962

PHYSICAL PROPERTIES

- High speed jet noise source physical properties interpretation by theory and scale-model experiments for supersonic transport aircraft noise suppression problem
A72-11973

PILOT PERFORMANCE

- Evaluation of simulated pilot/system performance in manually controlled IFR formation flight task for UH-1 helicopter under various environmental and operational conditions
[AD-725209] N72-10044
- Flight simulator exercise for investigation of pilot performance in low visibility conditions during approach and landing
[RAE-TR-71044] N72-11042

PILOTS (PERSONNEL)

- Crew compartment vibration environment in B-52 aircraft during low altitude, high speed flight
[AD-727023] N72-10127

PIPE FLOW

- Pitot stem blockage corrections in uniform and nonuniform pipe flow determined by wind tunnel measurements
[ARC-CP-1175] N72-11295

PITCH (INCLINATION)

- Aircraft pitching and yawing cross couplings

PITCHING MOMENTS

SUBJECT INDEX

compensation at high speed
A72-10506

PITCHING MOMENTS
Multipropeller slipstream and wing interference,
noting lift, drag, pitching moment, normal force
distribution, and wakes
N72-10015

PITOT TUBES
Flight test procedures for subsonic transport
aircraft pitot static pressure system,
recommending trailing cone calibration method
[SAE-ARP-921]
A72-10389

PLASTIC AIRCRAFT STRUCTURES
Lightweight low pressure plastic hose assemblies in
aircraft and missile petroleum base fuel and
synthetic lubricating oil systems at 395-710 R and
up to 200 psi
[SAE-ARP-1180]
A72-10388

PLASTIC COATINGS
Development of sprayable urethane sealant for
protection of heated areas on aircraft structures
[AD-727592]
N72-10489

PNEUMATIC EQUIPMENT
Aircraft high pressure oxygen cylinder system filler
valve optimum standards, discussing automatic fill
rate and pressure sensitive closing control,
design, construction and performance
[SAE-AS-1225]
A72-10385

POLAR COORDINATES
VOR, Direct Measuring Equipment and TACAN polar
coordinate radio navigation systems history,
improvements and future development
A72-12646

POLAR NAVIGATION
Polar navigation with transverse mercator technique
for aircraft using secant geared ground position
indicators
A72-10181

POLYPROPYLENE
Parachute canopy fabrics and rigging lines cordage
properties requirements, considering nylon,
polypropylene, silk, cotton and nonwoven
scrim-reinforced fabrics
A72-10314

PORTABLE EQUIPMENT
Portable detector-recorder for automobile, blast
furnace, railroad car, engine room and helicopter
infrasonic noise measurements, discussing peak
frequencies and subjective effects
A72-10157

Portable self contained ultrasonic field inspection
equipment for nondestructive crack detection in
T53 gas turbine compressor disks
A72-10814

POSITION ERRORS
ATC separation minima and navigational errors on
airways in general and long range oceanic
environments
A72-10177

POSITION INDICATORS
Polar navigation with transverse mercator technique
for aircraft using secant geared ground position
indicators
A72-10181

Airborne pictorial navigation systems for visual
indication of aircraft position in addition to
digital readout
A72-12106

Doppler system with navigation radar device,
computer unit and data transmitter for continuous
recording of aircraft position and speed
A72-12749

POWDER (PARTICLES)
Procedure for measuring performance of aircraft fire
extinguishing powders
N72-11691

POWDER METALLURGY
Forged Inconel alloy 718 metal powder preforms for
dense aircraft engine compressor rotor blades
A72-11441

POWER
Helicopter lift margin system to aid in determining
power requirements for takeoff and landing
[AD-725207]
N72-11053

POWER SUPPLIES
Aircraft hybrid electrical power systems, describing
variable frequency generation and high voltage dc
distribution
A72-11068

PREFORMS
Forged Inconel alloy 718 metal powder preforms for
dense aircraft engine compressor rotor blades
A72-11441

PRESSURE DISTRIBUTION
Parachute inflation loads and times, presenting
calculation method based on unsteady pressure
distribution on decelerating inflating parabolic
shell of revolution with unsteady starting vortex
A72-10311

Sonic boom pressure signatures during P-104
overflights at Mach 1.3 and 30,000 ft, explaining
variations by atmospheric turbulence
A72-11158

Aerodynamic forces and pressure distribution
measurement on wing-body combination model,
investigating boundary layer on wing upper surface
A72-12228

Force and pressure distribution measurements on
delta wing-body combination in compressible flow,
investigating Reynolds number effect
[DGLR PAPER 71-118]
A72-12707

Unsteady pressure distribution on harmonically
oscillating circular cylindrical fuselage body
with conical nose and delta wing with straight,
cubic or sinusoidal leading edges
[DGLR PAPER 71-080]
A72-12730

Calculation of pressure distribution on cylindrical
fuselage with perpendicular lifting jet using
singularity method
N72-10014

In-flight investigation of installation effects and
aerodynamic characteristics of local flow field on
auxiliary inlet ejector nozzle on underwing engine
nacelle
[NASA-TM-X-2396]
N72-11711

PRESSURE EFFECTS
Acoustic power radiated by jet aircraft fuselage
structure exposed to turbulent boundary layer
pressure field, evaluating noise reduction
treatments
A72-10216

PRESSURE GRADIENTS
Skin friction measurement in nonisobaric subsonic
flow with pressure gradient over airfoil section
by surface impact probes
A72-12275

PRESSURE HEADS
Performance tests on aerodynamically compensated
pressure heads for BAC 221 aircraft noting
pressure sensing errors
[ARC-CP-1167]
N72-11046

PRESSURE MEASUREMENTS
Unsteady flow about two dimensional airfoils,
determining surface pressure fluctuations induced
by turbulent boundary layers
A72-10217

Pressure altimeter system minimum safe performance
standards for subsonic aircraft operation,
describing test procedures
[SAE-AS-942]
A72-10386

Pitot stem blockage corrections in uniform and
nonuniform pipe flow determined by wind tunnel
measurements
[ARC-CP-1175]
N72-11295

PRESSURE SENSORS
Aircraft high pressure oxygen cylinder system filler
valve optimum standards, discussing automatic fill
rate and pressure sensitive closing control,
design, construction and performance
[SAE-AS-1225]
A72-10385

Mathematical models of rate gyros, servo
accelerometers, pressure transducers, and
telemetry systems and analog computer simulation
programs
[NASA-CR-1768]
N72-10401

Calibration of pressure sensors used to measure
aerodynamic noise
[ONERA-TP-982]
N72-11368

PRIMARY COSMIC RAYS
Thin-down intensities for heavy primaries at SST
flight levels, using plastic stacks measurements
A72-12077

PRODUCT DEVELOPMENT
Aircraft producibility considerations in preliminary
design and production planning phases
[SAE PAPER 710746]
A72-10245

PRODUCTION ENGINEERING
Aircraft producibility considerations in preliminary

design and production planning phases
[SAE PAPER 710746] A72-10245

Aircraft design producibility to reduce production cost and enhance product profitability, using joint engineering and manufacturing team
[SAE PAPER 710748] A72-10247

Electrodischarge and electrochemical machining applications in continuous repetitive production of aircraft jet engine components A72-11150

PROJECT PLANNING
Transportation planning for national and local levels
[PB-200076] N72-11849

PROPELLER DRIVE
Slipstream vortex street geometry influence on velocity and load distribution of VTOL propellers N72-11004

PROPELLER SLIPSTREAMS
Conference papers on jet and slipstream influence on aerodynamic coefficients using aircraft models
[DLR-MITT-70-28] N72-10004

Multipropeller slipstream and wing interference, noting lift, drag, pitching moment, normal force distribution, and wakes N72-10015

Rotor and propeller wake calculation, recovery rotors, and rotor feedback control
[DLR-MITT-71-12] N72-11001

Slipstream vortex street geometry influence on velocity and load distribution of VTOL propellers N72-11004

PROPULSION
Propulsion systems for low emission urban vehicles and analysis of exhaust emissions from fossil-fueled heat engines
[PB-200144] N72-10830

PROPULSION SYSTEM CONFIGURATIONS
Propulsion system optimization for commercial transport aircraft design under Advanced Transport Technology study, considering impact on aircraft gross weight
[SAE PAPER 710760] A72-10257

Propulsion system optimization in transonic transport aircraft design, considering nacelle integration, engine choice, noise attenuation and technology utilization
[SAE PAPER 710762] A72-10259

PROPULSION SYSTEM PERFORMANCE
Advanced technology air transports propulsion system requirements, considering design, engine performance and reliability, maintenance, airline problems, noise and pollution control
[SAE PAPER 710761] A72-10258

Jet noise reduction technology, hardware and tests for NASA Quiet Engine Program to develop low noise subsonic civil transport aircraft propulsion system
[SAE PAPER 710774] A72-10266

Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness
[SAE PAPER 710778] A72-10270

Fuel related problems in aircraft fuel systems, emphasizing hydrogen treated fuel N72-11677

Feasibility analysis of solid lubricated ball bearings for aircraft propulsion systems application N72-11700

PROPULSIVE EFFICIENCY
Small three spool, reverse and mixed flow turbofan engine for business jets, discussing fuel consumption reduction, thermodynamic performance, efficiency and maintainability
[SAE PAPER 710776] A72-10268

PROTECTIVE COATINGS
Lightning protective coatings for boron/epoxy composite materials, discussing high current damage mechanisms, simulation facility and test results on aluminum foils, meshes, etc A72-10783

QUALITY CONTROL
Integrity control procedures for machining, drilling and grinding of steel and Ti alloy aircraft parts, discussing nondestructive inspection method

Q

[SME PAPER IQ 71-238] A72-10969

R

RADAR APPROACH CONTROL
Terrain clearance during descent and approach of aircraft under radar control, discussing optimum profile, ATC, nav aids and rules A72-10183

Airfield Vehicle Obstacle Indication Device short range high-definition radar system for aircraft navigation aid A72-12042

Limited scan antenna system for precision approach radar, detailing design for reflector, aperture gain and phased array A72-12393

Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar A72-12421

RADAR BEACONS
Phased scanning array for ATC radar beacon systems, airport or air route surveillance radars and ground landing systems A72-10962

Discrete address ATC radar beacon system operation and design A72-12378

Air traffic control radar beacon systems and laser warning systems [AD-725743] N72-10543

RADAR DATA
Radar data automatic extraction, discussing azimuth quantization methods, moving window detection, coordinate measurement and ATCAS extractor A72-12650

RADAR NAVIGATION
Mathematical analysis of separation standards and aircraft navigational collision risk for parallel tracks in radar monitored systems A72-10178

Stellar attitude reference and navigation associative processor with high computational speed for radar approach control in ATC A72-12033

RADAR RANGE
Automated radar terminal system /ARTS/ for monitoring and tracking all aircraft within radar range, displaying identification, altitude and ground speed information to air traffic controller A72-10960

Airfield Vehicle Obstacle Indication Device short range high-definition radar system for aircraft navigation aid A72-12042

RADAR SCANNING
Phased scanning array for ATC radar beacon systems, airport or air route surveillance radars and ground landing systems A72-10962

Limited scan antenna system for precision approach radar, detailing design for reflector, aperture gain and phased array A72-12393

RADAR TRACKING
Automated radar terminal system /ARTS/ for monitoring and tracking all aircraft within radar range, displaying identification, altitude and ground speed information to air traffic controller A72-10960

RADIATION DETECTORS
Calibration and performance of cosmic radiation detector for Concorde supersonic transport [PAA-AM-71-26] N72-11370

RADIATION MEASUREMENT
Thin-down intensities for heavy primaries at SST flight levels, using plastic stacks measurements A72-12077

RADIATION PROTECTION
In-flight warning meter for solar and cosmic radiation dose equivalent measurements for radiological protection in SST aircraft A72-12078

RADIO BEACONS
Radio aids for air navigation and traffic control in Italy, discussing facilities development A72-12748

- Ground and air tests of flight inspection marker beacon receiving system
[FAA-NA-71-29] N72-10173
- RADIO NAVIGATION**
Radio aids to maritime and aerial navigation - Conference, Trieste, June 1971 A72-12640
- L band in satellite system for aerial navigation aid, discussing position accuracy, data transmission and voice communication and modulation methods A72-12642
- VOR, Direct Measuring Equipment and TACAN polar coordinate radio navigation systems history, improvements and future development A72-12646
- RADIOACTIVE ISOTOPES**
Nondestructive radioactive gas penetrant tests for porosity and fatigue damage in jet engine castings A72-10813
- RAMJET ENGINES**
Analysis of interaction of oblique shock with bow shock of blunt leading edge and application to design of hypersonic ramjet inlets
[AD-726111] N72-11312
- REAL GASES**
Real gas effects in atmosphere to make sonic bang shock wave full dispersion and thickness wide variations A72-11972
- REAL TIME OPERATION**
Acoustic echo sounder as real time monitor of airport environmental meteorological parameters A72-11137
- Digital computer memory system for real time processing of air and naval traffic data, discussing logic design, time comparisons and optimum use A72-12647
- Wind tunnels measuring equipment and procedures and data acquisition and processing systems electronics, describing computerized real time data processing system A72-12898
- On-line digital computer for wind tunnel, operating systems, and real time operation
[NPL-AERO-1326] N72-10184
- RECEIVERS**
Ground and air tests of flight inspection marker beacon receiving system
[FAA-NA-71-29] N72-10173
- RECORDING INSTRUMENTS**
Doppler system with navigation radar device, computer unit and data transmitter for continuous recording of aircraft position and speed A72-12749
- RECTANGULAR WINGS**
Drag and lift experimental determination for low aspect ratio rectangular wings with blunt trailing edges at Mach numbers 0.5-2.2
[DGLR PAPER 71-114] A72-12712
- Influence of jet interference on aerodynamic coefficients of rectangular and swept wings mounted above the engine N72-10010
- Numerical evaluation of downwash integral for lifting rectangular wings noting wing loading
[NPL-AERO-NOTE-1095] N72-11012
- REFUELING**
Aviation fueling facilities and fueling operation N72-11678
- REGULATIONS**
German Federal Republic territorial air traffic regulations covering general, VFR and IFR rules, equipment and personnel examination and certification, safety, takeoff and landing, accidents, etc A72-12621
- REINFORCED PLASTICS**
Lightning protective coatings for boron/epoxy composite materials, discussing high current damage mechanisms, simulation facility and test results on aluminum foils, meshes, etc A72-10783
- Graphite filament reinforced plastics strength, performance properties, fabrication processes and tooling concepts
[SME PAPER 28 71-205] A72-10968
- Design and development of numerically controlled machine for laying composite tape used in building aircraft structured from filament reinforced resin matrix composite materials
[AD-725765] N72-10425
- REINFORCEMENT (STRUCTURES)**
Compression tests of short skin-stiffener specimens of conventional titanium alloys airframe structure with attached unidirectional brazed boron-aluminum composite
[NASA-TN-D-6548] N72-11428
- RELIABILITY ENGINEERING**
Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention A72-11117
- Description of aircraft accessory reliability program to provide improved safety of operation for commercial aircraft N72-11035
- Analysis of military helicopter reliability requirements based on performance and reliability test programs
[AD-725595] N72-11059
- RESEARCH AIRCRAFT**
Augmentor wing jet STOL research aircraft development progress report covering design, engine tests, performance prediction, control simulation and stability augmentation
[SAE PAPER 710757] A72-10254
- Handling qualities simulation program for augmentor wing jet STOL research aircraft considering control devices design A72-11654
- RESEARCH AND DEVELOPMENT**
Industrial parachute R and D in UK, discussing management, technical staff requirements and government/industry liaison A72-10304
- German Research and Test Institute for Aero- and Astronautics 1970 report covering flow mechanics, power conversion, aerospace medicine, atmospheric physics, etc A72-11151
- Cost analysis and economic models for European aerospace development compared to US experience
[AD-725478] N72-10992
- RESEARCH MANAGEMENT**
Industrial parachute R and D in UK, discussing management, technical staff requirements and government/industry liaison A72-10304
- RESIDUAL STRESS**
Residual buckling strength of Al alloy elastic column with fatigue crack
[SESA PAPER 1914A] A72-11511
- RETRACTABLE EQUIPMENT**
European A300B airbus flying control hydraulic system and landing gear design for safety and reliability, fatigue life, weight and maintenance A72-10724
- REYNOLDS NUMBER**
Force and pressure distribution measurements on delta wing-body combination in compressible flow, investigating Reynolds number effect
[DGLR PAPER 71-118] A72-12707
- Effects of Reynolds number and frequency parameters on buzz characteristics at subsonic speeds using free oscillation method
[NPL-AERO-1312] N72-11291
- RIBBON PARACHUTES**
Supersonic ribbon parachute testing by transonic wind tunnel, rocket sled and water channel simulator A72-10305
- Ribbon parachutes drop tests at Mach 0.57-1.70, measuring opening shock loads and functioning time sequence A72-10312
- RIGGING**
Parachute canopy fabrics and rigging lines cordage properties requirements, considering nylon, polypropylene, silk, cotton and nonwoven scrim-reinforced fabrics A72-10314
- RIGID ROTORS**
Static and dynamic stability and controllability of rigid rotor BO-105 helicopter noting feedback

- effects
N72-11008
- RIGID STRUCTURES**
Nonporous rigid parachute models three component measurements, using low speed wind tunnel for testing skirt length effects on aerodynamic characteristics
A72-10303
- ROCKET PROPELLED SLEDS**
Wind tunnel and rocket sled results with ribbon parachutes for supersonic release, discussing aerodynamic, structural flutter and inflation time characteristics.
A72-10308
- ROLLING**
Rolling vertical takeoff and landing procedure for VTOL aircraft using thrust argumentation by afterburning
[BNVG-FBWT-71-13]
N72-10034
- ROLLING MOMENTS**
STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure
A72-11700
- ROTARY WINGS**
Automatic ultrasonic testing equipment for NDT tests of helicopter rotor blades
A72-11021
- Matrix method calculation for aerodynamic loads, transverse forces, bending moments, torques and twist of hinged main rotor blades in helicopter during forward flight
A72-12440
- Helicopter rotor tip drag relief estimate based on two dimensional drag divergence with Mach number, airfoil parameters and flight conditions
A72-12882
- Theoretical performance of jet flap rotor at advance ratios greater than 1.0
[AD-726706]
N72-10037
- Variable geometry rotor system for direct control over wake vortex
[NASA-CASE-LAR-10557]
N72-11018
- Aerodynamic and aeroelastic characteristics of rigid two-bladed rotor system with full-scale rotor operating at very high advance ratios and during start/stop operation
[AD-727653]
N72-11050
- Analysis of helicopter tail rotor flow patterns in and out of ground effect
[AD-725591]
N72-11060
- ROTATING DISKS**
Thermal radial stresses in axial compressor disk-to-drum transition areas of operating AM-3 aircraft engine
A72-11374
- Aircraft gas turbine rotating disks thermal and mechanical stresses under variable thermal conditions, describing test assembly
A72-11637
- ROTATING ENVIRONMENTS**
Turbulent and laminar jet flow in rotating environments noting application to jet mixing flow in tip driven rotor wakes
N72-10008
- ROTOR AERODYNAMICS**
Rotor and propeller wake calculation, recovery rotors, and rotor feedback control
[DLR-MITT-71-12]
N72-11001
- Linear aerodynamic rotor theories showing effect of applied vortex model on exactitude of numerical analysis
N72-11005
- ROTOR BLADES**
Automatic ultrasonic testing equipment for NDT tests of helicopter rotor blades
A72-11021
- ROTOR BLADES (TURBOMACHINERY)**
Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts
A72-10220
- Forged Inconel alloy 718 metal powder preforms for dense aircraft engine compressor rotor blades
A72-11441
- ROTOR SPEED**
Rotor downwash variation by changing vortice diameter, flapping, rotor speed, and radius and placing infinite span wing in flow field
N72-11003
- RUN TIME (COMPUTERS)**
Stellar attitude reference and navigation associative processor with high computational speed for radar approach control in ATC
A72-12033
- RUNWAYS**
Airport apron surface pavement strain measurements under field loading conditions, considering static and dynamic loads with finite element method
A72-10192
- Atmospheric temperature and pressure altitude effects on runway lengths and aircraft takeoff weights
[ASCE PREPRINT 1242]
A72-10193
- Lime, cement, fly ash and sand combination airport pavement design and testing, discussing material structural and chemical properties, compressive strength, costs, etc
A72-12023
- Measurement of three track runway and taxiway profiles at two international airports
[NASA-TN-D-6567]
N72-11038
- S**
- SAAB 105 AIRCRAFT**
Jet interference effects on yaw stability for SAAB 37 and 105 wind tunnel models
N72-10006
- SAAB 37 AIRCRAFT**
Jet interference effects on yaw stability for SAAB 37 and 105 wind tunnel models
N72-10006
- SAFETY FACTORS**
Pressure altimeter system minimum safe performance standards for subsonic aircraft operation, describing test procedures
[SAE-AS-942]
A72-10386
- SANDS**
Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic performance
[AD-725593]
N72-11713
- SANDWICH STRUCTURES**
Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core
A72-10723
- SATELLITE TRANSMISSION**
L band in satellite system for aerial navigation aid, discussing position accuracy, data transmission and voice communication and modulation methods
A72-12642
- SCALE MODELS**
High speed jet noise source physical properties interpretation by theory and scale-model experiments for supersonic transport aircraft noise suppression problem
A72-11973
- Full scale wind tunnel tests of small unpowered jet aircraft with T tail
[NASA-TN-D-6573]
N72-10031
- SCHLIEREN PHOTOGRAPHY**
Hypersonic boundary layer separation of delta wing in shock tunnel using color and monochrome schlieren photography
[NPL-AERO-NOTE-1097]
N72-10022
- SELF INDUCED VIBRATION**
One dimensional unsteady flow in turbine engines rotating and static vane cascades, discussing vibrations propagation
A72-11584
- SEPARATION**
Sand and dust particle filter tests for evaluation of separation efficiency and aerodynamic performance
[AD-725593]
N72-11713
- SEPARATORS**
Dual purpose filter-separators for dirt and water removal from fuel
N72-11676
- SERVOMECHANISMS**
Analysis of flight control system requirements for helicopters and design of pilot assisted control system
[AD-725590]
N72-11057

SHEAR STRAIN

Webbing joints stitching strain, considering nylon and flax yarns stretching properties and various stitching patterns strengths

A72-10315

SHOCK LAYERS

Thin shock layer theory of lifting properties of reentry caret and flat delta wings and waveriders at high incidence angles and Mach number

A72-12345

SHOCK LOADS

Ribbon parachutes drop tests at Mach 0.57-1.70, measuring opening shock loads and functioning time sequence

A72-10312

SHOCK TUNNELS

Hypersonic boundary layer separation of delta wing in shock tunnel using color and monochrome schlieren photography
[NPL-AERO-NOTE-1097]

N72-10022

SHOCK WAVES

Real gas effects in atmosphere to make sonic bang shock wave full dispersion and thickness wide variations

A72-11972

Supersonic and hypersonic flows with attached shock waves over delta wing at angle of attack, deriving unified theory for flow field

A72-12030

Analysis of interaction of oblique shock with bow shock of blunt leading edge and application to design of hypersonic ramjet inlets
[AD-726111]

N72-11312

SHORT HAUL AIRCRAFT

Future aircraft design trends for transcontinental and short haul operation, considering traffic forecasts, current transport aircraft and potential derivatives and technology
[SAE PAPER 710749]

A72-10248

Short haul air transport system need for future short takeoff and landing aircraft, considering airports, airways, economics and navigation and landing aids

A72-11719

SHORT TAKEOFF AIRCRAFT

STOL transport aircraft technology assessment, analyzing airports growth problems
[SAE PAPER 710751]

A72-10250

Augmentor wing jet STOL research aircraft development progress report covering design, engine tests, performance prediction, control simulation and stability augmentation
[SAE PAPER 710757]

A72-10254

Industry assisted state of art assessment of high lift turbofan configurations for USAF STOL tactical transport technology program
[SAE PAPER 710758]

A72-10255

Mach 0.80 quiet intercity STOL transport design comparison for turbofan, prop-fan and turboprop systems
[SAE PAPER 710759]

A72-10256

STOL aircraft for solving noise reduction and land use problems in future transportation systems, discussing airport location and layout for growing air traffic

A72-11153

STOL and VTOL aircraft performance and efficiency, discussing landing and takeoff distances reduction

A72-11258

Handling qualities simulation program for augmentor wing jet STOL research aircraft considering control devices design

A72-11654

STOL aircraft roll moment control possibility for externally-blown jet flap due to engine failure

A72-11700

Short haul air transport system need for future short takeoff and landing aircraft, considering airports, airways, economics and navigation and landing aids

A72-11719

Q/STOL jet aircraft engines design for low noise levels, describing takeoff thrust, bypass ratio and turbine stages

A72-12501

Externally blown flaps for STOL characteristics in medium and heavy jet transport aircraft, demonstrating aerodynamic and flight mechanical feasibility

Aladin 2 noiseless STOL jet aircraft project, describing exhaust nozzle configuration, design and economics

A72-12502

STOL aircraft integrated landing approach flight control system with elevator and thrust control coupling to angle of attack, altitude and other state variables
[DGLR PAPER 71-063]

A72-12503

Turbofans under wings to provide lift and thrust for STOL aircraft
[NASA-CASE-LEW-11224-1]

A72-12705

Cost analysis and operational procedures of effective short range, high density computer transportation system for Metropolitan Detroit
[NASA-CR-114340]

N72-10033

Flight simulator used to determine lateral and directional aerodynamic characteristics of STOL transport aircraft
[PAA-RD-71-81]

N72-10984

SIGNATURE ANALYSIS

Sonic boom pressure signatures during F-104 overflights at Mach 1.3 and 30,000 ft, explaining variations by atmospheric turbulence

N72-11037

A72-11158

SIMULATION

Simulated crash tests to assess fire resistance of aircraft fuels containing polymeric additives

N72-11692

SINGULARITY (MATHEMATICS)

Calculation of pressure distribution on cylindrical fuselage with perpendicular lifting jet using singularity method

N72-10014

SKIN FRICTION

Increasing lift and Reynolds number effects on displacement and skin friction of three dimensional turbulent boundary layer on infinite swept wing

A72-11395

Skin friction measurement in nonisobaric subsonic flow with pressure gradient over airfoil section by surface impact probes

A72-12275

SMALL PERTURBATION FLOW

Subsonic linearized theory for symmetrical cranked wings at zero incidence, presenting corrected formulas for streamwise and spanwise perturbation velocity components due to wing thickness

A72-11154

SOLAR COSMIC RAYS

Calibration and performance of cosmic radiation detector for Concorde supersonic transport
[PAA-AM-71-26]

N72-11370

SOLID LUBRICANTS

Feasibility analysis of solid lubricated ball bearings for aircraft propulsion systems application

N72-11700

SOLID STATE DEVICES

Improvements in aircraft maintenance procedures based on solid state electrical power management and solid state contactless switching circuits

N72-11034

SOLVENT EXTRACTION

Solvent removal by immersion of EC-2273 potting compound from F-4 aircraft electrical components
[AD-725493]

N72-11473

SONIC BOOMS

Finite element method for determining transient response of box-type structure to traveling sonic pressure wave

A72-10219

Sonic boom pressure signatures during F-104 overflights at Mach 1.3 and 30,000 ft, explaining variations by atmospheric turbulence

A72-11158

Real gas effects in atmosphere to make sonic bang shock wave full dispersion and thickness wide variations

A72-11972

Sonic boom waveforms measured during exercise summer sky in southern Great Britain
[ARC-R/M-3659]

N72-11015

SOUND GENERATORS

Sound generation in very low and very high turbulent jet flows from exhaust nozzle

N72-10253

SUBJECT INDEX

SUBCRITICAL FLOW

Noise generation by rotating blades of axial flow fan in infinite annulus
[AD-726126] N72-11714

SOUND TRANSMISSION
Flow model for jet pipe sound transmission through nozzle flow
[JEPW/69] N72-10252

SOUND WAVES
Acoustic power radiated by jet aircraft fuselage structure exposed to turbulent boundary layer pressure field, evaluating noise reduction treatments
A72-10216

Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts
A72-10220

SOUTHEAST ASIA
Evaluation of airway operations systems in Indonesia, Laos, Malaysia, and Thailand with proposed courses of action, equipment requirements, and economic factors in aeronautical telecommunications
N72-10171

SPACE SHUTTLES
Aircraft and spacecraft integrated avionics systems design with emphasis on telemetry, discussing space shuttle subsystems integration
A72-12403

SPACECRAFT RECOVERY
Rotor and propeller wake calculation, recovery rotors, and rotor feedback control
[DLR-MITT-71-12] N72-11001

SPECTRUM ANALYSIS
Spectral analysis of transient data applied to auto-pilot parameter studies of coupler transfer function
[AD-725068] N72-10501

SPEED INDICATORS
Doppler system with navigation radar device, computer unit and data transmitter for continuous recording of aircraft position and speed
A72-12749

SPIN DYNAMICS
Aircraft spin characteristics due to superstall, comparing three stall types with respect to recovery, yaw damping and rate of rotation
[DGLR PAPER 71-057] A72-12718

STABILITY TESTS
Static and dynamic stability characteristics of finned bodies with cruciform, slotted fin configuration
[AD-728016] N72-10003

STABILIZERS (FLUID DYNAMICS)
Parachute designs and applications to escape systems, paratrooping, supply dropping, aircraft braking, weapons systems stabilization, flight testing aids and sport
A72-10302

STAINLESS STEELS
Design, fabrication, and ground tests of perforated stainless steel exhaust nozzle inserts for Boeing 707 aircraft noise reduction
[NASA-CR-1853] N72-10043

STANDARDIZATION
Aircraft high pressure oxygen cylinder system filler valve optimum standards, discussing automatic fill rate and pressure sensitive closing control, design, construction and performance
[SAE-AS-1225] A72-10385

STANDARDS
Aerospace wire and cables testing methods standards for evaluating mechanical, electrical and chemical properties, coating thicknesses, continuity flaws, flammability, geometrical characteristics, etc
[SAE-AS-1198] A72-10384

Pressure altimeter system minimum safe performance standards for subsonic aircraft operation, describing test procedures
[SAE-AS-942] A72-10386

STATIC PRESSURE
Flight test procedures for subsonic transport aircraft pitot static pressure system, recommending trailing cone calibration method
[SAE-ARP-921] A72-10389

Pitot stem blockage corrections in uniform and nonuniform pipe flow determined by wind tunnel measurements
[ARC-CP-1175] N72-11295

STATIC STABILITY
Jet interference effects on yaw stability for SAAB 37 and 105 wind tunnel models
N72-10006

STATISTICAL ANALYSIS
Statistical analysis of track keeping Strumble VOR data for lateral navigation separation standards and collision risk in continental environment
A72-10179

Statistical analysis of home built aircraft accidents
[PB-201438] N72-10038

Statistical analysis of weather effects in aircraft accidents
[PB-201437] N72-10039

Briefs of US general aviation accidents involving corporate/executive aircraft in 1968
[PB-201439] N72-11052

STEERING
Electromechanical nose wheel steering system for general aviation aircraft ground maneuverability improvement, describing design
A72-10963

STIFFNESS
Constant phase shift between flapping and action on center of gravity for spring hinged rotor with variable flapping stiffness
N72-11007

STRAIN GAGE BALANCES
Three component shock tunnel strain gage balance for measuring aerodynamic forces on thin delta wings
[ARC-R/N-3664] N72-11375

STRAIN GAGES
Electronic strain-level counter for in-flight aircraft
[NASA-CASE-LAR-10756-1] N72-11803

STRATOSPHERE
Possible catalytic reduction of stratospheric ozone by nitrogen oxides emitted from SST aircraft
[UCL-20568] N72-11334

STREAMS
Axial and tangential velocity distributions within trailing line vortex to large distance downstream of generating wing extended from available data
A72-11135

STRESS (PHYSIOLOGY)
Effects of environmental stresses on attack helicopter crew task performance in NATO theater
[AD-726949] N72-10122

Crew compartment vibration environment in B-52 aircraft during low altitude, high speed flight
[AD-727023] N72-10127

STRESS ANALYSIS
Structural sandwich panel design, establishing simple stress and deflection formulas under transverse loading based on tests evaluating balsa as laminate core
A72-10723

STRESS MEASUREMENT
Airport apron surface pavement strain measurements under field loading conditions, considering static and dynamic loads with finite element method
A72-10192

STRUCTURAL ANALYSIS
Development of structural optimization algorithm for obtaining near optimum distributions of material for structural idealizations
[AD-726112] N72-11820

STRUCTURAL DESIGN
Aircraft design interactive computer graphics technique, using human decision input response to computer output information
[DGLR PAPER 71-107] A72-12733

STRUCTURAL VIBRATION
Finite element method for determining transient response of box-type structure to traveling sonic pressure wave
A72-10219

Unpredicted structural vibration in Comet and Electra aircraft, Graf Zeppelin dirigible, missile antennas, etc
A72-12002

STRUCTURAL WEIGHT
Atmospheric temperature and pressure altitude effects on runway lengths and aircraft takeoff weights
[ASCE PREPRINT 1242] A72-10193

SUBCRITICAL FLOW
Design programs for swept wings in subcritical,

- compressible, viscous flow
[NPL-AERO-NOTE-1100] N72-10018
- SUBMARINES**
Optimal stochastic /Kalman/ filters application to integrated air and submarine navigation systems, discussing measurement errors modeling as bias and colored noise
A72-12050
- SUBSONIC AIRCRAFT**
Flight test procedures for subsonic transport aircraft pitot static pressure system, recommending trailing cone calibration method [SAE-ARP-921] A72-10389
Unsolved aerodynamic problems in sub- and transonic civil and military aircraft design, considering flow problems during transonic flight, takeoff and landing
[DGLR PAPER 71-105] A72-12745
- SUBSONIC FLOW**
Subsonic linearized theory for symmetrical cranked wings at zero incidence, presenting corrected formulas for streamwise and spanwise perturbation velocity components due to wing thickness
A72-11154
Skin friction measurement in nonisobaric subsonic flow with pressure gradient over airfoil section by surface impact probes
A72-12275
Low subsonic region unsteady interference effects on harmonically oscillating wing-tailplane model with variable sweep wing
[DGLR PAPER 71-081] A72-12709
Formulae for components of perturbation velocity in linearized subsonic theory for symmetrical cranked wing panels at zero angle of attack
[NPL-AERO-NOTE-1090] N72-10021
- SUBSONIC SPEED**
Full scale wind tunnel tests of small unpowered jet aircraft with T tail
[NASA-TN-D-6573] N72-10031
Effects of Reynolds number and frequency parameters on buzz characteristics at subsonic speeds using free oscillation method
[NPL-AERO-1312] N72-11291
- SUITABILITY**
Suitability evaluation of fog simulator for weather conditions during flight approach
[FAA-NA-71-44] N72-10233
- SULFUR**
Effect of sulfur in JP-5 fuel on hot corrosion of turbine blade materials operating in marine environment
[AD-725619] N72-11706
- SUMMER**
Sonic boom waveforms measured during exercise summer sky in southern Great Britain
[ARC-R/M-3659] N72-11015
- SUPERSONIC AIRCRAFT**
B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation
A72-12226
Unsolved aerodynamic problems in sub- and transonic civil and military aircraft design, considering flow problems during transonic flight, takeoff and landing
[DGLR PAPER 71-105] A72-12745
Development and functions of organization for multinational certification of supersonic aircraft
N72-11029
Possible high energy fuels for supersonic aircraft
N72-11670
Kerosene-type fuel for supersonic and hypersonic aircraft
N72-11671
Synthetic high temperature lubricants thickened by complex esters for supersonic aircraft
N72-11701
- SUPERSONIC FLOW**
Supersonic and hypersonic flows with attached shock waves over delta wing at angle of attack, deriving unified theory for flow field
A72-12030
- SUPERSONIC JET FLOW**
High speed jet noise source physical properties interpretation by theory and scale-model experiments for supersonic transport aircraft noise suppression problem
A72-11973
- SUPERSONIC SPEEDS**
Supersonic ribbon parachute testing by transonic wind tunnel, rocket sled and water channel simulator
A72-10305
- SUPERSONIC TRANSPORTS**
Thin-down intensities for heavy primaries at SST flight levels, using plastic stacks measurements
A72-12077
In-flight warning meter for solar and cosmic radiation dose equivalent measurements for radiological protection in SST aircraft
A72-12078
Sound generation and scale model experiments to suppress noise in turbulent jet flow eddies of supersonic transport aircraft
[ARC-32723] N72-10254
Possible catalytic reduction of stratospheric ozone by nitrogen oxides emitted from SST aircraft
[UCRL-20568] N72-11334
- SUPERSONIC TURBINES**
Analysis of lubricant system used in civil supersonic gas turbine engine
N72-11697
- SURFACE PROPERTIES**
Unsteady flow about two dimensional airfoils, determining surface pressure fluctuations induced by turbulent boundary layers
A72-10217
- SURFACES**
Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions
[NASA-TN-D-6530] N72-11289
- SURFACTANTS**
Use of fluorocarbon surfactants to extinguish aircraft fuel fires
N72-11693
- SURVEILLANCE**
Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention
A72-11117
- SURVEILLANCE RADAR**
Avionics contribution to airspace decision making problems, considering navigation, surveillance radar, collision avoidance and ATC techniques
A72-10180
Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar
A72-12421
- SWEPT EFFECT**
Laminar three dimensional boundary layer nonequilibrium effects at hypersonic wing swept leading edge with intensively cooled surface, considering sweep induced crossflow effect
[VPI-E-71-23] A72-12422
- SWEPT WINGS**
Subsonic linearized theory for symmetrical cranked wings at zero incidence, presenting corrected formulas for streamwise and spanwise perturbation velocity components due to wing thickness
A72-11154
Increasing lift and Reynolds number effects on displacement and skin friction of three dimensional turbulent boundary layer on infinite swept wing
A72-11395
Laminar three dimensional boundary layer nonequilibrium effects at hypersonic wing swept leading edge with intensively cooled surface, considering sweep induced crossflow effect
[VPI-E-71-23] A72-12422
Jet interference and lift drag ratio of swept wing aircraft with turbofan above wing
[RAE-TN-AERO-1271] N72-10009
Influence of jet interference on aerodynamic coefficients of rectangular and swept wings mounted above the engine
N72-10010
Design programs for swept wings in subcritical, compressible, viscous flow
[NPL-AERO-NOTE-1100] N72-10018
Vortex drag factor of untapered swept wing with part-span flap, noting spanwise loading
[NPL-AERO-1324] N72-11011

SYNTHESIS

Synthesis and properties of aliphatic ester for turbine lubrication in jet aircraft
N72-11696

SYSTEMS ANALYSIS

Evaluation of airway operations systems in Indonesia, Laos, Malaysia, and Thailand with proposed courses of action, equipment requirements, and economic factors in aeronautical telecommunications
N72-10171

SYSTEMS ENGINEERING

Airline Propulsion Team approach to DC-10 aircraft power plant design for maximum operational effectiveness
[SAE PAPER 710778]
A72-10270

Air transportation system design for safety and efficiency, discussing navigation facilities and surveillance systems employment for blunder prevention
A72-11117

Inertial navigation role in automatic ATC systems, discussing path control accuracies, environmental conditions, noise and air pollution, etc
A72-11118

ATC system decision making problem and future technological and administrative improvements
A72-11718

Microwave aircraft landing system development, discussing contract definition, feasibility, prototype development, management planning and program costs
A72-12377

Discrete address ATC radar beacon system operation and design
A72-12378

Aircraft and spacecraft integrated avionics systems design with emphasis on telemetry, discussing space shuttle subsystems integration
A72-12403

Computer-aided interactive graphic displays for ATC, discussing subsystems, data processing flow and operational capabilities
A72-12420

Analytical methods for early-stage detection of oil deterioration in aircraft engines
N72-11698

T

T TAIL SURFACES

Full scale wind tunnel tests of small unpowered jet aircraft with T tail
[NASA-TN-D-6573]
N72-10031

T-53 ENGINE

Portable self contained ultrasonic field inspection equipment for nondestructive crack detection in T53 gas turbine compressor disks
A72-10814

Metallographic and fract ographic analyses of cracking in T53-L13 gas turbine engine compressor disks
A72-10816

TABLES (DATA)

Graphs and tables of service cost for intraurban transportation system
[NASA-CR-114341]
N72-10985

Documentation of data used in intraurban transportation analysis appendix
[NASA-CR-114343]
N72-10987

TACAN

Tactical ATC display system for airport surveillance, precision approach and landing and operator/aircraft/machine operations by using terminal Area Surveillance Radar
A72-12421

VOR, Direct Measuring Equipment and TACAN polar coordinate radio navigation systems history, improvements and future development
A72-12646

TAKEOFF

Noise reduction for climbing takeoff and V/STOL aircraft affecting stability
[DLR-FB-71-10]
N72-11040

Helicopter lift margin system to aid in determining power requirements for takeoff and landing
[AD-725207]
N72-11053

TAKEOFF RUNS

Atmospheric temperature and pressure altitude

effects on runway lengths and aircraft takeoff weights
[ASCE PREPRINT 1242]
A72-10193

TAXIING

Measurement of three track runway and taxiway profiles at two international airports
[NASA-TN-D-6567]
N72-11038

TECHNOLOGICAL FORECASTING

Commercial transport market and technology forecasting, considering all-cargo, STOL, SST and CTOL aircraft
[SAE PAPER 710750]
A72-10249

TECHNOLOGY ASSESSMENT

STOL transport aircraft technology assessment, analyzing airports growth problems
[SAE PAPER 710751]
A72-10250

Industry assisted state of art assessment of high lift turbopfan configurations for USAF STOL tactical transport technology program
[SAE PAPER 710758]
A72-10255

TELECOMMUNICATION

Evaluation of airway operations systems in Indonesia, Laos, Malaysia, and Thailand with proposed courses of action, equipment requirements, and economic factors in aeronautical telecommunications
N72-10171

TELEMETRY

Aircraft and spacecraft integrated avionics systems design with emphasis on telemetry, discussing space shuttle subsystems integration
A72-12403

Mathematical models of rate gyros, servo accelerometers, pressure transducers, and telemetry systems and analog computer simulation programs
[NASA-CR-1768]
N72-10401

TEMPERATURE MEASUREMENT

Nozzle shape, temperature, and velocity effects on free hypersonic jet exhaust properties
N72-10013

TENSILE TESTS

Constant high tensile stress and rapid aerodynamic heating effect on maraging steels and Ti and Al alloys, evaluating test and simulation procedures for design data development
A72-10749

TERMINAL BALLISTICS

Theoretical analysis of fuel ignition by hot projectile and ignition delay time as function of temperature and width of hot gas region
N72-11683

TERMINAL FACILITIES

Airport efficiency improvement measures, considering boarding gates, parking space, baggage handling, fire protection, monitoring and central control
A72-11717

TERMINAL GUIDANCE

Terrain clearance during descent and approach of aircraft under radar control, discussing optimum profile, ATC, nav aids and rules
A72-10183

TERRAIN

Terrain clearance during descent and approach of aircraft under radar control, discussing optimum profile, ATC, nav aids and rules
A72-10183

TEST EQUIPMENT

Metal fatigue damage nondestructive detection, discussing inspection methods, equipment, advantages, limitations and test results
A72-12498

Analysis of facilities, equipment, and tools to maintain large commercial aircraft
N72-11023

THERMAL FATIGUE

Thermal shock fatigue tests on aircraft gas turbine engine inlet nozzles, showing cracks as function of material
A72-11373

THERMAL INSULATION

Development of sprayable urethane sealant for protection of heated areas on aircraft structures
[AD-727592]
N72-10489

THERMAL SHOCK

Thermal shock fatigue tests on aircraft gas turbine engine inlet nozzles, showing cracks as function of material
A72-11373

THERMAL STABILITY

Jet fuels hydrocarbon composition effect on thermal stability, considering nonaromatic components influence on aromatic hydrocarbons oxidation products coagulation

A72-12800

Assessment of high temperature stability of synthetic lubricants for aircraft gas turbines

N72-11695

Thermal stability of trimethyl propane ester based lubricating oil for aircraft engines

N72-11699

THERMAL STRESSES

Thermal radial stresses in axial compressor disk-to-drum transition areas of operating AM-3 aircraft engine

A72-11374

Aircraft gas turbine rotating disks thermal and mechanical stresses under variable thermal conditions, describing test assembly

A72-11637

THIN WINGS

Three component shock tunnel strain gage balance for measuring aerodynamic forces on thin delta wings [ARC-R/M-3664]

N72-11375

THREE DIMENSIONAL BOUNDARY LAYER

Increasing lift and Reynolds number effects on displacement and skin friction of three dimensional turbulent boundary layer on infinite swept wing

A72-11395

Laminar three dimensional boundary layer nonequilibrium effects at hypersonic wing swept leading edge with intensively cooled surface, considering sweep induced crossflow effect [VPI-E-71-23]

A72-12422

THREE DIMENSIONAL MOTION

Three dimensional roll-controlled missile trajectory model for simple time-sharing digital or analog simulation, using wind-to-inertial axis transformation

A72-10964

THRUST

Turbofans under wings to provide lift and thrust for STOL aircraft [NASA-CASE-LEW-11224-1]

N72-10033

THRUST AUGMENTATION

Rolling vertical takeoff and landing procedure for VTOL aircraft using thrust augmentation by afterburning [BMVG-FBWT-71-13]

N72-10034

THRUST CONTROL

STOL aircraft integrated landing approach flight control system with elevator and thrust control coupling to angle of attack, altitude and other state variables [DGLR PAPER 71-063]

A72-12705

TIME FUNCTIONS

Parachute opening shock and filling time calculation based on aerodynamic drag, air mass and effective porosity time functions, using momentum and continuity equations

A72-10310

TIME RESPONSE

Parachute inflation loads and times, presenting calculation method based on unsteady pressure distribution on decelerating inflating parabolic shell of revolution with unsteady starting vortex

A72-10311

Ribbon parachutes drop tests at Mach 0.57-1.70, measuring opening shock loads and functioning time sequence

A72-10312

TIP DRIVEN ROTORS

Turbulent and laminar jet flow in rotating environments noting application to jet mixing flow in tip driven rotor wakes

N72-10008

TITANIUM ALLOYS

Constant high tensile stress and rapid aerodynamic heating effect on maraging steels and Ti and Al alloys, evaluating test and simulation procedures for design data development

A72-10749

Compression tests of short skin-stiffener specimens of conventional titanium alloys airframe structure with attached unidirectional brazed boron-aluminum composite [NASA-TN-D-6548]

N72-11428

TOOLING

Graphite filament reinforced plastics strength, performance properties, fabrication processes and tooling concepts

[SME PAPER EM 71-205]

A72-10968

TOOLS

Analysis of facilities, equipment, and tools to maintain large commercial aircraft

N72-11023

TOWED BODIES

Equilibrium configuration of cable towed in circular path, presenting multivalued boundary value problem mathematical analysis

A72-11132

TRACE CONTAMINANTS

Infrared spectrophotometer used for detection of trace contaminants from Pegasus and Olympus engines in aircraft cabin atmospheres [QAD-MATS-174]

N72-10040

TRAILING EDGES

Axial and tangential velocity distributions within trailing line vortex to large distance downstreams of generating wing extended from available data

A72-11135

Drag and lift experimental determination for low aspect ratio rectangular wings with blunt trailing edges at Mach numbers 0.5-2.2 [DGLR PAPER 71-114]

A72-12712

TRAINING DEVICES

Application of Apollo Project data and training concepts to maintenance of large commercial aircraft

N72-11026

TRAJECTORY ANALYSIS

Three dimensional roll-controlled missile trajectory model for simple time-sharing digital or analog simulation, using wind-to-inertial axis transformation

A72-10964

TRANSFER FUNCTIONS

Spectral analysis of transient data applied to auto-pilot parameter studies of coupler transfer function [AD-725068]

N72-10501

TRANSIENT RESPONSE

Finite element method for determining transient response of box-type structure to traveling sonic pressure wave

A72-10219

TRANSONIC FLIGHT

Unsolved aerodynamic problems in sub- and transonic civil and military aircraft design, considering flow problems during transonic flight, takeoff and landing [DGLR PAPER 71-105]

A72-12745

TRANSONIC FLOW

Velocity field of sonic flow about aircraft wing profile, solving mixed Cauchy problem

A72-11178

TRANSONIC SPEED

Numerical analysis of transonic flow about thin lifting wings and analytic expressions for far field conditions [NASA-TN-D-6530]

N72-11289

TRANSONIC WIND TUNNELS

Design of flexible steel liners for adjustable transonic wind tunnel nozzle [NPL-AERO-NOTE-1098]

N72-10023

TRANSPORT AIRCRAFT

Future aircraft design trends for transcontinental and short haul operation, considering traffic forecasts, current transport aircraft and potential derivatives and technology [SAE PAPER 710749]

A72-10248

Commercial transport market and technology forecasting, considering all-cargo, STOL, SST and CTOL aircraft

[SAE PAPER 710750]

A72-10249

STOL transport aircraft technology assessment, analyzing airports growth problems [SAE PAPER 710751]

A72-10250

Industry assisted state of art assessment of high lift turbofan configurations for USAF STOL tactical transport technology program [SAE PAPER 710758]

A72-10255

Mach 0.80 quiet intercity STOL transport design comparison for turbofan, prop-fan and turboprop systems [SAE PAPER 710759]

A72-10256

- Propulsion system optimization for commercial transport aircraft design under Advanced Transport Technology study, considering impact on aircraft gross weight
[SAE PAPER 710760] A72-10257
- Advanced technology air transports propulsion system requirements, considering design, engine performance and reliability, maintenance, airline problems, noise and pollution control
[SAE PAPER 710761] A72-10258
- Propulsion system optimization in transonic transport aircraft design, considering nacelle integration, engine choice, noise attenuation and technology utilization
[SAE PAPER 710762] A72-10259
- Flight test procedures for subsonic transport aircraft pitot static pressure system, recommending trailing cone calibration method
[SAE-ARP-921] A72-10389
- Externally blown flaps for STOL characteristics in medium and heavy jet transport aircraft, demonstrating aerodynamic and flight mechanical feasibility
A72-12502
- Full scale wind tunnel tests of small unpowered jet aircraft with T tail
[NASA-TN-D-6573] N72-10031
- Description of maintenance procedures used on Beechcraft Hawker 125 commercial jet aircraft
N72-11032
- Predictions of aircraft maintenance procedures to be employed during 1970 to 1980 time period
N72-11033
- Flight simulator used to determine lateral and directional aerodynamic characteristics of STOL transport aircraft
[FAA-RD-71-81] N72-11037
- TRANSPORTATION**
Transportation planning for national and local levels
[PB-200076] N72-11849
- TRAVELING WAVES**
Finite element method for determining transient response of box-type structure to traveling sonic pressure wave
A72-10219
- TURBINE BLADES**
Graphite fiber composite fan blade design for subsonic turbofan engines, discussing weight and fatigue sensitivity reductions and performance test results
[SAE PAPER 710771] A72-10265
- One dimensional unsteady flow in turbine engines rotating and static vane cascades, discussing vibrations propagation
A72-11584
- Effect of sulfur in JP-5 fuel on hot corrosion of turbine blade materials operating in marine environment
[AD-725619] N72-11706
- TURBINE ENGINES**
Reduction of harmful emissions of turbine engine exhaust system
N72-11675
- Post-crash fire safety of helicopter turbine engine fuels
N72-11688
- TURBINE EXHAUST NOZZLES**
Aladin 2 noiseless STOL jet aircraft project, describing exhaust nozzle configuration, design and economics
A72-12503
- TURBINES**
Synthesis and properties of aliphatic ester for turbine lubrication in jet aircraft
N72-11696
- TURBOCOMPRESSORS**
Jet aircraft turbofan engine fan compressor noise reduction by acoustic linings, giving R and D results
[BAS PAPER 71 SA6] A72-10223
- Thermal radial stresses in axial compressor disk-to-drum transition areas of operating AM-3 aircraft engine
A72-11374
- Performance of axial flow compressor rotor with different casing treatment configuration
[NASA-TN-D-6538] N72-10025
- Cascade calculations and tests of blunt trailing edge blades used in advanced axial compressor concepts
[AD-725789] N72-11308
- TURBOFAN AIRCRAFT**
Industry assisted state of art assessment of high lift turbofan configurations for USAF STOL tactical transport technology program
[SAE PAPER 710758] A72-10255
- Mach 0.80 quiet intercity STOL transport design comparison for turbofan, prop-fan and turboprop systems
[SAE PAPER 710759] A72-10256
- TURBOFAN ENGINES**
Jet aircraft turbofan engine fan compressor noise reduction by acoustic linings, giving R and D results
[BAS PAPER 71 SA6] A72-10223
- Graphite fiber composite fan blade design for subsonic turbofan engines, discussing weight and fatigue sensitivity reductions and performance test results
[SAE PAPER 710771] A72-10265
- Small three spool, reverse and mixed flow turbofan engine for business jets, discussing fuel consumption reduction, thermodynamic performance, efficiency and maintainability
[SAE PAPER 710776] A72-10268
- CF6 high bypass ratio turbofan engine design improvements for fuel consumption, thrust/weight ratio, starting, noise level, smoke emission, maintenance, monitoring and accessory replacement
[SAE PAPER 710779] A72-10271
- Jet interference and lift drag ratio of swept wing aircraft with turbofan above wing
[RAE-TM-AERO-1271] N72-10009
- TURBOFANS**
Turbofans under wings to provide lift and thrust for STOL aircraft
[NASA-CASE-LEW-11224-1] N72-10033
- TURBOJET ENGINES**
Development and application of modular design concept to improve jet aircraft engine maintenance
N72-11030
- TURBOPROP AIRCRAFT**
Mach 0.80 quiet intercity STOL transport design comparison for turbofan, prop-fan and turboprop systems
[SAE PAPER 710759] A72-10256
- TURBULENCE EFFECTS**
Sonic boom pressure signatures during F-104 overflights at Mach 1.3 and 30,000 ft, explaining variations by atmospheric turbulence
A72-11158
- Aircraft ride comfort problem in turbulent air, comparing free and fixed wing aircraft responses
A72-11720
- TURBULENT BOUNDARY LAYER**
Acoustic power radiated by jet aircraft fuselage structure exposed to turbulent boundary layer pressure field, evaluating noise reduction treatments
A72-10216
- Unsteady flow about two dimensional airfoils, determining surface pressure fluctuations induced by turbulent boundary layers
A72-10217
- Increasing lift and Reynolds number effects on displacement and skin friction of three dimensional turbulent boundary layer on infinite swept wing
A72-11395
- TURBULENT DIFFUSION**
Sound generation and scale model experiments to suppress noise in turbulent jet flow eddies of supersonic transport aircraft
[ARC-32723] N72-10254
- TURBULENT FLOW**
Sound radiation from axial flow fans running in turbulent flow, evaluating fluctuating lift on rotor blades due to incident gusts
A72-10220
- Development mechanisms of turbulent jet flows
[VKI-LS-36] N72-10245
- Techniques for forecasting turbulent weather conditions below 10,000 feet for light aircraft operating in Hawaiian Islands
[AD-726107] N72-11525

TURBULENT JETS

SUBJECT INDEX

TURBULENT JETS

- Turbulent and laminar jet flow in rotating environments noting application to jet mixing flow in tip driven rotor wakes N72-10008
- Development mechanisms of turbulent jet flows [VKI-LS-36] N72-10245
- Flow model for jet pipe sound transmission through nozzle flow [JEPW/69] N72-10252
- Sound generation in very low and very high turbulent jet flows from exhaust nozzle N72-10253
- Sound generation and scale model experiments to suppress noise in turbulent jet flow eddies of supersonic transport aircraft [ABC-32723] N72-10254
- TURBULENT WAKES**
- Full scale measurement of flow in turbulent wake of hangars [ABC-CP-1166] N72-11047
- TWISTING**
- Matrix method calculation for aerodynamic loads, transverse forces, bending moments, torques and twist of hinged main rotor blades in helicopter during forward flight A72-12440
- TWO DIMENSIONAL FLOW**
- Customer utilization and program listing for computer program on two dimensional multicomponent airfoils in viscous flow [NASA-CR-1843] N72-11010

U

- UH-1 HELICOPTER**
- Evaluation of simulated pilot/system performance in manually controlled IPR formation flight task for UH-1 helicopter under various environmental and operational conditions [AD-725209] N72-10044
- ULTRAHIGH FREQUENCIES**
- Uhf aeronautical satellite system, presenting ATC trends, international aspects, available flight levels, weather conditions and long haul conflicts A72-12383
- L band in satellite system for aerial navigation aid, discussing position accuracy, data transmission and voice communication and modulation methods A72-12642
- ULTRASONIC TESTS**
- Portable self contained ultrasonic field inspection equipment for nondestructive crack detection in T53 gas turbine compressor disks A72-10814
- Automatic ultrasonic testing equipment for NDT tests of helicopter rotor blades A72-11021
- Application of nondestructive testing procedures to maintenance of large commercial aircraft N72-11025
- UNITED STATES OF AMERICA**
- Cost analysis and economic models for European aerospace development compared to US experience [AD-725478] N72-10992
- UNSTEADY FLOW**
- Unsteady flow about two dimensional airfoils, determining surface pressure fluctuations induced by turbulent boundary layers A72-10217
- One dimensional unsteady flow in turbine engines rotating and static vane cascades, discussing vibrations propagation A72-11584
- URBAN TRANSPORTATION**
- Mach 0.80 quiet intercity STOL transport design comparison for turbofan, prop-fan and turboprop systems [SAE PAPER 710759] A72-10256
- Propulsion systems for low emission urban vehicles and analysis of exhaust emissions from fossil-fueled heat engines [PB-200144] N72-10830
- Graphs and tables of service cost for intraurban transportation system [NASA-CR-114341] N72-10985
- Aircraft design concepts for intraurban transportation system

- [NASA-CR-114342] N72-10986
- Documentation of data used in intraurban transportation analysis appendix [NASA-CR-114343] N72-10987

V

- V/STOL AIRCRAFT**
- Free flight simulation tests for V/STOL aircraft nonlinear attitude control system adaptation to helicopter pitch and roll control [DGLR PAPER 71-060] A72-12714
- Disk shaped lift engine providing additional thrust during takeoff and transition phases of V/STOL aircraft, returning to ground by jet after task accomplishment A72-12900
- Military specification adoption for flight characteristics of piloted V/STOL aircraft [AD-725746] N72-10048
- Recirculation mechanism in jet powered V/STOL aircraft [BMVG-PBWT-71-12] N72-10828
- Noise reduction for climbing takeoff and V/STOL aircraft affecting stability [DLR-PB-71-10] N72-11040
- Full scale measurement of flow in turbulent wake of hangars [ABC-CP-1166] N72-11047
- VARIABLE SWEEP WINGS**
- B-1 strategic supersonic bomber design, emphasizing variable sweep wing, landing gear, control and instrumentation A72-12226
- Low subsonic region unsteady interference effects on harmonically oscillating wing-tailplane model with variable sweep wing [DGLR PAPER 71-081] A72-12709
- VELOCITY DISTRIBUTION**
- Arial and tangential velocity distributions within trailing line vortex to large distance downstream of generating wing extended from available data A72-11135
- Subsonic linearized theory for symmetrical cranked wings at zero incidence, presenting corrected formulas for streamwise and spanwise perturbation velocity components due to wing thickness A72-11154
- Velocity field of sonic flow about aircraft wing profile, solving mixed Cauchy problem A72-11178
- VERTICAL LANDING**
- Rolling vertical takeoff and landing procedure for VTOL aircraft using thrust argumentation by afterburning [BMVG-PBWT-71-13] N72-10034
- VERTICAL TAKEOFF AIRCRAFT**
- STOL and VTOL aircraft performance and efficiency, discussing landing and takeoff distances reduction A72-11258
- Vertical takeoff aircraft wind tunnel model with high pressure ejectors to determine jet interference on aerodynamic coefficients N72-10007
- Rolling vertical takeoff and landing procedure for VTOL aircraft using thrust argumentation by afterburning [BMVG-PBWT-71-13] N72-10034
- Slipstream vortex street geometry influence on velocity and load distribution of VTOL propellers N72-11004
- VHF OMNIRANGE NAVIGATION**
- Statistical analysis of track keeping Strumble VOR data for lateral navigation separation standards and collision risk in continental environment A72-10179
- VOR, Direct Measuring Equipment and TACAN polar coordinate radio navigation systems history, improvements and future development A72-12646
- VIBRATION DAMPING**
- Flutter equation approximate true damping or rate-of-decay solution by determinant iteration A72-11133
- VIBRATION MEASUREMENT**
- Crew compartment vibration environment in B-52 aircraft during low altitude, high speed flight [AD-727023] N72-10127

VIBRATION MODE
Unpredicted structural vibration in Comet and Electra aircraft, Graf Zeppelin dirigible, missile antennas, etc

A72-12002

VIBRATION TESTS
Flight vibration testing methods for ascertaining flutter stability of high speed aircraft
[DGLR PAPER 71-083]

A72-12725

VISCOSITY
Viscosity and additive effects on jet engine fuel antiwear properties improvement

A72-11968

VISCOUS FLOW
Design programs for swept wings in subcritical, compressible, viscous flow
[NPL-AERO-NOTE-1100]
Customer utilization and program listing for computer program on two dimensional multicomponent airfoils in viscous flow
[NASA-CR-1843]

N72-10018

N72-11010

VISIBILITY
Suitability evaluation of fog simulator for weather conditions during flight approach
[FAA-NA-71-44]

N72-10233

VORTEX STREETS
Slipstream vortex street geometry influence on velocity and load distribution of VTOL propellers

N72-11004

VORTICES
Axial and tangential velocity distributions within trailing line vortex to large distance downstreams of generating wing extended from available data

A72-11135

Rotor downwash variation by changing vortice diameter, flapping, rotor speed, and radius and placing infinite span wing in flow field

N72-11003

Linear aerodynamic rotor theories showing effect of applied vortex model on exactitude of numerical analysis

N72-11005

Vortex drag factor of untapered swept wing with part-span flap, noting spanwise loading
[NPL-AERO-1324]

N72-11011

W

WARNING SYSTEMS
Pilot collision warning indicator performance in terminal area traffic, using computer fast-time simulation for traffic model

A72-11134

FAA activity in collision avoidance system and pilot warning instrument areas

A72-12379

Development and operating principles of collision warning system for aircraft accident prevention
[NASA-CASE-HQN-10703]

N72-11527

WARPAGE
Warpage control of large Al alloy forgings machining of jumbo jet components, using packing and storage methods
[SAE PAPER 710801]

A72-10280

WAVE DISPERSION
Real gas effects in atmosphere to make sonic bang shock wave full dispersion and thickness wide variations

A72-11972

WAVEFORMS
Sonic boom waveforms measured during exercise summer sky in southern Great Britain
[ARC-R/M-3659]

N72-11015

WEAPON SYSTEMS
Variable speed constant frequency power generation equipment influence weapon system effectiveness, considering weight and cost

A72-11067

WEAR TESTS
Viscosity and additive effects on jet engine fuel antiwear properties improvement

A72-11968

WEATHER
Statistical analysis of weather effects in aircraft accidents
[PB-201437]
Suitability evaluation of fog simulator for weather conditions during flight approach
[FAA-NA-71-44]

N72-10039

N72-10233

Radar observation of weather conditions for aircraft flight
[OMM-264-TP-148]

N72-11147

WEATHER FORECASTING
Terminal aerodrome forecasts usefulness and accuracy assessment

A72-10864

Techniques for forecasting turbulent weather conditions below 10,000 feet for light aircraft operating in Hawaiian Islands
[AD-726107]

N72-11525

WEBS
Webbing joints stitching strain, considering nylon and flax yarns stretching properties and various stitching patterns strengths

A72-10315

WEIGHT ANALYSIS
Variable speed constant frequency power generation equipment influence weapon system effectiveness, considering weight and cost

A72-11067

WELDING
Jet engine component overhaul procedures for fatigue damage repair, detailing distressed metal removal, replacement and welding techniques

A72-12499

WIND PRESSURE
Analysis and comparison of gust load models based on either discrete gust concept or continuous gust concept
[NLR-TR-710250]

N72-10998

WIND TUNNEL APPARATUS
Wind tunnels measuring equipment and procedures and data acquisition and processing systems electronics, describing computerized real time data processing system

A72-12898

WIND TUNNEL CALIBRATION
Three component shock tunnel strain gage balance for measuring aerodynamic forces on thin delta wings
[ARC-R/M-3664]

N72-11375

WIND TUNNEL MODELS
Nonporous rigid parachute models three component measurements, using low speed wind tunnel for testing skirt length effects on aerodynamic characteristics

A72-10303

Wind tunnel and rocket sled results with ribbon parachutes for supersonic release, discussing aerodynamic, structural flutter and inflation time characteristics.

A72-10308

Wing-fuselage combination aerodynamic coefficients, comparing experimental data with subsonic linear and nonlinear theoretical results
[DGLR PAPER 71-115]

A72-12723

Conference papers on jet and slipstream influence on aerodynamic coefficients using aircraft models
[DLR-MIT-70-28]

N72-10004

Jet engine simulation with low speed wind tunnel models for interference drag measurement

N72-10005

Vertical takeoff aircraft wind tunnel model with high pressure ejectors to determine jet interference on aerodynamic coefficients

N72-10007

Aerodynamic characteristics of wind tunnel model of hypersonic aircraft
[NASA-TN-D-6577]

N72-10045

Prediction of flight penetration of wing buffeting from wind tunnel model dynamic tests
[ARC-CP-1171]

N72-11044

WIND TUNNEL NOZZLES
Design of flexible steel liners for adjustable transonic wind tunnel nozzle
[NPL-AERO-NOTE-1098]

N72-10023

WIND TUNNEL STABILITY TESTS
Full scale wind tunnel tests of small unpowered jet aircraft with T tail
[NASA-TN-D-6573]

N72-10031

WIND TUNNELS
On-line digital computer for wind tunnel, operating systems, and real time operation
[NPL-AERO-1326]

N72-10184

Pitot stem blockage corrections in uniform and nonuniform pipe flow determined by wind tunnel measurements
[ARC-CP-1175]

N72-11295

WING FLOW METHOD TESTS

Aerodynamic forces and pressure distribution
measurement on wing-body combination model,
investigating boundary layer on wing upper surface
A72-12228

WING LOADING

Increasing lift and Reynolds number effects on
displacement and skin friction of three
dimensional turbulent boundary layer on infinite
swept wing
A72-11395

Thin shock layer theory of lifting properties of
reentry caret and flat delta wings and waveriders
at high incidence angles and Mach number
A72-12345

Analysis and comparison of gust load models based on
either discrete gust concept or continuous gust
concept
[NLR-TR-71025U] N72-10998

Vortex drag factor of untapered swept wing with
part-span flap, noting spanwise loading
[NPL-AERO-1324] N72-11011

Numerical evaluation of downwash integral for
lifting rectangular wings noting wing loading
[NPL-AERO-NOTE-1095] N72-11012

WING OSCILLATIONS

Aerodynamic lift characteristics of oscillating two
dimensional airfoil subjected to sinusoidal gust
[AD-726132] N72-11017

WING PANELS

Formulae for components of perturbation velocity in
linearized subsonic theory for symmetrical cranked
wing panels at zero angle of attack
[NPL-AERO-NOTE-1090] N72-10021

WING PROFILES

Velocity field of sonic flow about aircraft wing
profile, solving mixed Cauchy problem
A72-11178

WING SPAN

Vortex drag factor of untapered swept wing with
part-span flap, noting spanwise loading
[NPL-AERO-1324] N72-11011

WING TIPS

Tip clearance effect on compressor blade aerodynamic
characteristics, applying Bolland analysis to low
aspect ratio rectangular wing
A72-12825

WINGS

Multipropeller slipstream and wing interference,
noting lift, drag, pitching moment, normal force
distribution, and wakes
N72-10015

WIRE

Aerospace wire and cables testing methods standards
for evaluating mechanical, electrical and chemical
properties, coating thicknesses, continuity flaws,
flammability, geometrical characteristics, etc
[SAE-AS-1198] A72-10384

X

X RAY INSPECTION

Application of nondestructive testing procedures to
maintenance of large commercial aircraft
N72-11025

Y

YARNS

Webbing joints stitching strain, considering nylon
and flax yarns stretching properties and various
stitching patterns strengths
A72-10315

YAW

Aircraft pitching and yawing cross couplings
compensation at high speed
A72-10506


Jet interference effects on yaw stability for SAAB
37 and 105 wind tunnel models
N72-10006

PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 15)

FEBRUARY 1972

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the title, e.g., N72-10044. Under any one author's name the accession numbers are arranged in sequence with the IAA accession numbers appearing first.

A

- ACKERMAN, G. H.**
Cooling of advanced engines by endothermic reactions of hydrocarbon fuels
N72-11672
- ADAMS, H. W.**
Maintenance fault isolation in the seventies
N72-11027
- ADAMSON, G. P.**
Modular design concept improves jet engine maintainability
N72-11030
- AIKEN, T. H.**
Full-scale wind-tunnel tests of a small unpowered jet aircraft with a T-tail
[NASA-TN-D-6573]
N72-10031
- ALLKOFER, O. C.**
Preliminary results of measurements of heavy primaries in the region of supersonic transport using plastic stacks.
A72-12077
- ANDERSON, P. A.**
Investigation of display requirements for helicopter IFR manual formation flight under various operational and environmental conditions
[AD-725209]
N72-10044
- ARGYRIS, J. H.**
Application of interactive computer graphics in wing unit designs
[DGLR PAPER 71-107]
A72-12733
- ARON, I.**
Problems of the use of inertial navigation systems in aviation
A72-10070
- ARZT, P.**
Integrity control procedures for machining 300 M steel and titanium aircraft components.
[SME PAPER IQ 71-238]
A72-10969
- AUGL, J. H.**
Solvent removal of EC-2273 potting compound from F-4 aircraft electrical components
[AD-725493]
N72-11473
- AULELIA, F.**
Basic investigations of recirculation with configurations consisting of 1 to 6 jets
[BMVG-FBWT-71-12]
N72-10828
- BAGLEY, J. A.**
Some experiments on an engine installation above the wing of a swept-winged aircraft
[RAE-TN-AERO-1271]
N72-10009
- BAHBERGER, E. H.**
Lubricant and fuel interactions in advanced aircraft gas turbines
[NASA-CR-122842]
N72-11694
- BARCHE, J.**
Unsolved problems of airplane aerodynamics
[DGLR PAPER 71-105]
A72-12745
- BARNES, C. S.**
Flight and wind-tunnel tests on an aerodynamically compensated pitot-static head for the BAC 221 aircraft
[ARC-CP-1167]
N72-11046
- BARTKOWIAK, A.**
Fire hazard evaluation of thickened aircraft fuels
N72-11689
- BARTON, J. R.**
Fatigue damage detection.
A72-12498
- BATILL, S. H.**
Determining aircraft stability coefficients from dynamic motions.
A72-11136
- BAUMERT, W.**
Influence of a jet on the aerodynamic properties of wings positioned above the jet nozzle
N72-10010
- BAYER, H.**
Maintenance fault isolation in the seventies
N72-11027
- BAZOV, D. I.**
Helicopter aerodynamics
[AD-726841]
N72-10046
- BEAUREGARD, J. P.**
The development of small gas turbine engines at OACL /Lecture/.
A72-11699
- BECKER, J.**
Investigation of unsteady interference effects on a harmonically oscillating wing-tailplane model with a variable sweep wing in the low subsonic region
[DGLR PAPER 71-081]
A72-12709
- BECKETT, R. G.**
Fuel related problems in aircraft fuel systems
N72-11677
- BECKWITH, W. B.**
Utilization of meteorological radar for aeronautics
[OHM-264-TP-148]
N72-11147
- BEDAGUE, P.**
Synthesis and properties of esters of tetramethyl-2,2-7,7 octane diol-1,8
N72-11696
- BELIKH, V. S.**
Course-indicating systems and automatic navigation aids for civil aviation aircraft
A72-12298
- BENNETT, C. L.**
Control of warpage during machining.
[SAE PAPER 710801]
A72-10280
- BENWICH, G.**
Interference effects from jets on aircraft static stability. Wind tunnel methods used in Sweden
N72-10006
- BERAN, D. W.**
Acoustics - A new approach for monitoring the environment near airports.
A72-11137
- BERG, H. A.**
A flight simulator study of STOL transport directional control characteristics
[FAA-RD-71-81]
N72-11037

- BERKOVITS, A.
Buckling of an elastic column containing a fatigue crack.
[SESA PAPER 1914A] A72-11511
- BERNITT, C. L.
Theoretical performance of a pure jet flap rotor at high advance ratios
[AD-726706] N72-10037
- BESPOLOV, I. E.
Ways of improving the antiwear properties of fuels for jet engines A72-11968
Influence of the hydrocarbon composition of jet fuels on their thermal stability A72-12800
- BEST, D. L.
Forecasting low level turbulence for light aircraft in Hawaii
[AD-726107] N72-11525
- BEYER, H.
Electronic displays for attack aircraft
[DPVLR-SONDDR-140] A72-11756
- BHAT, W. V.
Interior noise radiated by an airplane fuselage subjected to turbulent boundary layer excitation and evaluation of noise reduction treatments.
A72-10216
- BIGLER, S. G.
Utilization of meteorological radar for aeronautics
[ONM-264-TP-148] N72-11147
- BIRCH, S. A.
Materials for use in parachutes.
A72-10314
- BISHOP, D. J.
The infra-red analysis of aircraft cabin-gas atmospheres
[QAD-MATS-174] N72-10040
- BISHOP, K. A.
On the noise sources of the unsuppressed high-speed jet.
A72-11973
On the noise sources of the unsuppressed high speed jet
[ARC-32723] N72-10254
- BLACK, R. E.
The crystal ball focuses on the next generation of transport aircraft.
[SAE PAPER 710750] A72-10249
- BLADE, R. J.
Effect of casing treatment on overall and blade element performance of a compressor rotor
[NASA-TN-D-6538] N72-10025
- BLAKE, B. H. L.
Pictorial navigation systems.
A72-12106
- BOGDANCHENKO, N. M.
Course-indicating systems and automatic navigation aids for civil aviation aircraft
A72-12298
- BOTTERI, B. P.
Flammability properties of jet fuels and techniques for fire and explosion suppression
N72-11681
- BRADEN, J. A.
Mathematical model for two-dimensional multi-component airfoils in viscous flow
[NASA-CR-1843] N72-11010
- BRADLEY, R. G.
Skin-friction measurement in flow with pressure gradient.
A72-12275
- BRAVERMAN, W.
Aviation system design for safety and efficiency.
A72-11117
- BRENNAN, J. L.
FAA CAS/PWI program - Past, present, future.
A72-12379
- BREUGELMANS, F. A. E.
Research on advanced axial compressor concepts
[AD-725789] N72-11308
- BRINES, G. L.
Propulsion system optimization for the ATT.
[SAE PAPER 710760] A72-10257
- BRITLAND, C. M.
A preliminary analysis of navigational performance observed at Strumble 1969-70.
A72-10179
- BROWN, A. D.
Category 2: A simulation study of low visibility approaches and landings at night
[BAE-TR-71044] N72-11042
- BROWN, J. H., JR.
Smoother travel in rough air.
A72-11720
- BURGE, H. L.
Jet-noise reduction through liquid-base foam injection.
A72-10160
- BURGHARD, H. C., JR.
A metallurgical analysis of cracking in compressor discs of the T53-L13 gas turbine engine.
A72-10816
- BURKE, J. P.
Computer application strategy for control of airline maintenance in the seventies
N72-11020
- BURLEY, R. R.
Flight investigation of airframe installation effects on an auxiliary inlet ejector nozzle on an underwing engine nacelle
[NASA-TN-X-2396] N72-11711
- BUSHUEVA, E. M.
Influence of the hydrocarbon composition of jet fuels on their thermal stability
A72-12800
- BYERS, R. H.
Improving the efficiency of airports.
A72-11717

C

- CALDER, P. H.
Olympus 593 powerplant in Concorde.
[SAE PAPER 710775] A72-10267
- CALUDA, M.
Optimization studies of aircraft control variables
[AD-725069] N72-10042
- CAMP, J.
Aircraft power steering.
A72-10963
- CAMPBELL, M. J.
Aircraft power steering.
A72-10963
- CARR-HILL, G. A.
A programme of research into viscous aspects of flow on swept wings
[NPL-AERO-NOTE-1100] N72-10018
- CARRI, R. L.
Compressive behavior of titanium alloy skin-stiffener specimens selectively reinforced with boron-aluminum composite
[NASA-TN-D-6548] N72-11428
- CASE, R. F.
Separation measurements on a delta wing in a shock tunnel at M=8.6 using monochrome and colour-schlieren photography
[NPL-AERO-NOTE-1097] N72-10022
- CATLEY, A. M.
Separation measurements on a delta wing in a shock tunnel at M=8.6 using monochrome and colour-schlieren photography
[NPL-AERO-NOTE-1097] N72-10022
- CHADWICK, J. ., W.
For a better, short-haul flight.
A72-11719
- CHANDRASHEKHARA, N.
Tone radiation from axial flow fans running in turbulent flow.
A72-10220
- CHAO, K.
Calculation of the unsteady pressure distribution on harmonically oscillating slender wing-fuselage configurations
[DGLB PAPER 71-080] A72-12730
- CHASMAN, M. R.
Solid lubrication for aero propulsion systems
N72-11700
- CHAUVIN, J.
Research on advanced axial compressor concepts
[AD-725789] N72-11308
- CHIKULAYEV, M. S.
Systems of aircraft automatic control
[JPRS-54332] N72-11039
- CHIN, C. Y.
A hybrid electrical power system for aircraft application.
A72-11068

- CHOO, Y.
The configuration of a cable towed in a circular path.
A72-11132
- CLARE, T. A.
Effect of fin slots on the static and dynamic stability characteristics of finned bodies
[AD-728016] N72-10003
- CLEVELAND, W. B.
The handling qualities simulation program for the augmentor wing jet STOL research aircraft.
A72-11654
- CLIFFORD, D. W.
Experimental evaluation of lightning protective coatings for boron/epoxy composites.
A72-10783
- COLNER, M. J.
Some full-scale measurements of the flow in the wake of a hangar
[ARC-CP-1166] N72-11047
- COOK, R. F.
Harnessing the digital computer for aircraft maintenance
N72-11022
- CORBETT, J. K.
The infra-red analysis of aircraft cabin-gas atmospheres
[QAD-MATS-174] N72-10040
- CORNISH, J. J., III
Advanced technology for STOL transports.
[SAE PAPER 710751] A72-10250
- COUPRY, G.
Some results on gust alleviation
[ONERA-TP-925] N72-10999
- CRAIG, R. L.
Air transportation in the American economy.
A72-11721
- CRAIG, R. R.
Experimental study of shock impingement on a blunt leading edge with application to hypersonic inlet design
[AD-726111] N72-11312
- CRAIG, S. J.
A flight simulator study of STOL transport directional control characteristics
[FAA-RD-71-81] N72-11037
- CURRY, R. E.
Display research collision warning system
[NASA-CASE-HQN-10703] N72-11527
- D**
- DANIELS, P.
Effect of fin slots on the static and dynamic stability characteristics of finned bodies
[AD-728016] N72-10003
- DAVENROY, T. B.
Density altitude variations and runway lengths.
[ASCE PREPRINT 1242] A72-10193
- DAVIS, S. O.
An application of fracture concepts to the prediction of critical length of fatigue cracks. Part 2: A review of pertinent aspects of fracture (theoretical and analytical aspects of fatigue of metals)
[AD-725028] N72-10957
- DAY, B.
Radiological protection in SST aircraft.
A72-12078
- DE STASIO, G.
Investigation of an associative memory for use in digital computers employed as aids to air and naval traffic
A72-12647
- DEBELLEVAL, J.
Studying the coherent and incoherent structures of aerodynamically generated noise
[ONERA-TP-983] N72-11036
- DEE, W. F.
Brief flight tests of crosswind landings and sidestep manoeuvres on the BAC 221 aircraft
[ARC-CP-1168] N72-11045
- DEGAUDENARIS, G.
Synthesis and properties of esters of tetramethyl-2,2-7,7 octane diol-1,8
N72-11696
- DEJONGE, J. B.
Comparison between discrete and continuous models for vertical gusts
- [NLR-TR-71025U] N72-10998
- DEN HARTOG, J. P.
Vibration - A review of interesting cases.
A72-12002
- DESALVO, J. S.
Proceedings of a conference on regional transportation planning
[PB-200076] N72-11849
- DEVANY, A. S.
The value of time in air travel: Theory and evidence
[AD-725480] N72-11850
- DIBELLA, J. P.
Computer application strategy for control of airline maintenance in the seventies
N72-11020
- DINWIDDIE, B. A., III
Study and development of acoustic treatment for jet engine tailpipes
[NASA-CR-1853] N72-10043
- DOHERT, K.
Three component measurements for rigid parachute models.
A72-10303
- DOHERTY, E. W.
Lubricant experience and duties in a civil supersonic gas turbine engine
N72-11697
- DORN, H.
Synthetic lubricants for supersonic aircraft
N72-11701
- DOYLE, H.
Facilities, equipment and tools to support wind bodied airplane maintenance in the seventies
N72-11023
- DREBBING, W. H.
Development of composite tape laying process for advanced fibrous reinforced composite structures
[AD-725765] N72-10425
- DUNLAP, E. W.
Theory of the measurement and standarization of in-flight performance of aircraft
[AD-725741] N72-11054
- DUNN, R. G.
Ductility improvements in superalloys.
A72-12561
- DVORSKY, L. A.
Investigation of airborne marker beacon
[FAA-NA-71-29] N72-10173
- DWYER, W. J.
An automated procedure for the optimization of practical aerospace structures. Volume 2: Technical programmer's manual
[AD-725744] N72-10047
- An automated procedure for the optimization of practical aerospace structures. Volume 1: Theoretical development and user's information
[AD-726112] N72-11820
- DYER, G. C.
Polar navigation - A new Transverse Mercator technique.
A72-10181
- E**
- EATON, H. L.
Development of composite tape laying process for advanced fibrous reinforced composite structures
[AD-725765] N72-10425
- EDDY, W. C., JR.
Radioactive gas penetrant system - A report on initial product application.
A72-10813
- EDER, W.
Basic investigations of recirculation with configurations consisting of 1 to 6 jets
[BNVG-PBWT-71-12] N72-10828
- EDGERTON, B. W.
Helicopter lift-margin system, volume 2
[AD-725207] N72-11053
- EDWARDS, J. W.
The microwave landing system development program.
A72-12377
- ELLIS, D. E.
Telemetry and the integrated avionics approach.
A72-12403
- EMERTON, R. K.
An automated procedure for the optimization of practical aerospace structures. Volume 2:

- Technical programmer's manual
[AD-725744] N72-10047
- An automated procedure for the optimization of
practical aerospace structures. Volume 1:
Theoretical development and user's information
[AD-726112] N72-11820
- ENGE, W.**
Preliminary results of measurements of heavy
primaries in the region of supersonic transport
using plastic stacks. A72-12077
- ERDEMAN, V. J.**
Field practices in the repair of fatigue damaged jet
engine components. A72-12499
- ERICKSON, J. D.**
Automated air traffic control. A72-10960
- ERICKSON, P. W.**
Solvent removal of EC-2273 potting compound from F-4
aircraft electrical components
[AD-725493] N72-11473
- EUVRARD, D.**
Numerical calculation of a sonic flow about an
aircraft wing profile, by an inverse method
A72-11178
- EYDNOV, N. M.**
Systems of aircraft automatic control
[JPRS-54332] N72-11039
- F**
- PAGAN, C. H.**
Elastomeric bearings for rotor system applications.
A72-10150
- FAITH, L. E.**
Cooling of advanced engines by endothermic reactions
of hydrocarbon fuels N72-11672
- FECHER, P. J.**
Manufacturing experiences with graphite filament
reinforced composites.
[SME PAPER EM 71-205] A72-10968
- FERRARO, A.**
Two examples of application of Kalman filters to
integrated navigation systems A72-12050
- FFOWCSWILLIAMS, J. E.**
On the noise sources of the unsuppressed high-speed
jet. A72-11973
- Transmission of low frequency jet pipe sound through
a nozzle flow N72-10252
- [JEPW/69] N72-10253
- Jet noise at very low and very high speed
On the noise sources of the unsuppressed high speed
jet N72-10254
- [ARC-32723] N72-10254
- FIALA, R.**
Contribution to the selection of fire extinguishing
systems and agents for aircraft fires N72-11685
- Investigation of fire extinguishing powders by means
of a new measuring procedure N72-11691
- FLEMING, C. M.**
Integrity control procedures for machining 300 M
steel and titanium aircraft components.
[SME PAPER IQ 71-238] A72-10969
- FORGHAN, S. L.**
Fuel related problems in aircraft fuel systems
N72-11677
- FORNICHEV, V. I.**
Experimental investigation of the strength of
rotating disks in aircraft gas turbines operating
under variable thermal conditions A72-11637
- FRAIZE, W. E.**
A survey of propulsion systems for low emission
urban vehicles
[PB-200144] N72-10830
- FRICHTEL, J. S.**
Influence of electric power quality on avionic
design and weapon system effectiveness. A72-11067
- FRIEDBERG, W.**
Calibration of the Concorde radiation detection
instrument and measurements at SST altitude
[FAA-AM-71-26] N72-11370
- FRISTROM, R. M.**
Flame inhibition chemistry N72-11680
- FROST, W. O.**
Telemetry and the integrated avionics approach.
A72-12403
- FUETTERER, H.**
Measuring, data-acquisition, and data-processing
systems for the large wind tunnels of the
Aerodynamische Versuchsanstalt Goettingen
A72-12898
- FUHR, J. W.**
Influence of different parameters (like jet
contraction, vortex core diameter) upon rotor
downwash calculation. Application to the case of
an auxiliary wing N72-11003
- FULLER, E. W.**
Radiological protection in SST aircraft. A72-12078
- FULLER, K. L.**
AVOID - A short-range high-definition radar.
A72-12042
- FURNO, A. L.**
Fire hazard evaluation of thickened aircraft fuels
N72-11689
- G**
- GARDNER, L.**
Jet fuel specifications N72-11669
- Fuel cleanliness N72-11676
- GARNER, H. C.**
The vortex drag of a swept wing with part-span flaps
[NPL-AERO-1324] N72-11011
- Convergence of current routines for evaluating
downwash at a lifting surface
[NPL-AERO-NOTE-1095] N72-11012
- GEHR, K.**
Linear aerodynamic rotor theory N72-11005
- GEISSLER, W.**
Force and downwash measurements with jet simulation
on models of the European airbus in a low speed
wind tunnel N72-10012
- GEMPERLEIN, H.**
The possibilities of actually testing the combustion
characteristics of aviation fuels with appropriate
equipment N72-11674
- GERSTEIN, H.**
Analysis of aircraft fuel tank fire and explosion
hazards
[AD-725027] N72-11056
- GLADSTONE, D.**
Parachute R & D in industry. A72-10304
- GLAGG, J.**
Doppler - A modern aid for air navigation
A72-12749
- GLOVER, I.**
Ultrasonic inspection of helicopter rotor blades.
A72-11021
- GOLD, H. C.**
Gas turbine engine fuel control
[NASA-CASE-LEW-11187-1] N72-10824
- GOLOD, A.**
Buckling of an elastic column containing a fatigue
crack.
[SESA PAPER 1914A] A72-11511
- GOODHANSON, L. T.**
Installation and integration of transonic transport
propulsion systems.
[SAE PAPER 710762] A72-10259
- GORADIA, S. H.**
Mathematical model for two-dimensional
multi-component airfoils in viscous flow
[NASA-CR-1843] N72-11010
- GOULD, R. W. F.**
Pitot-stem blockage corrections in uniform and
non-uniform flow
[ARC-CP-1175] N72-11295
- GRABNER, E.**
Air traffic regulations A72-12621

Air traffic law A72-12622

GRADL, W.
Linear aerodynamic rotor theory N72-11005

GRASSO, G.
Techniques for the extraction of radar data A72-12650

GRAZIANI, D.
ILS system for landing aircraft and its future developments A72-12645

Aircraft radio navigation systems by means of polar coordinates and their development A72-12646

GREEN, S. J.
The general aviation maintenance outlook for the seventies N72-11033

GRIEGER, I.
Application of interactive computer graphics in wing unit designs [DGLR PAPER 71-107] A72-12733

GRIGOR'EV, P. F.
Thermal strength testing methods for aircraft gas turbine engine nozzle apparatuses A72-11373

GRISHANOV, N. G.
High-altitude equipment of civil aircraft A72-12295

H

HAAS, J.
An application of modern maintenance concepts and safety analysis to the multinational certification of a supersonic aircraft N72-11029

HAASE, R. J.
Data analysis system for Army flight testing. A72-12408

HAGENHAUER, D. J.
Development of the DC-10 Nondestructive Testing Manual. A72-11109

HAIDL, G.
Methods of flight vibration testing of modern high-performance aircraft [DGLR PAPER 71-083] A72-12725

HALL, A. W.
Three-track runway and taxiway profiles measured at International Airports E and F [NASA-TN-D-6567] N72-11038

HALL, O. J., JR.
Study and development of acoustic treatment for jet engine tailpipes [NASA-CR-1853] N72-10043

HANEL, P.
Noise-abatement flight profiles for CTOL and V/STOL aircraft [DLR-FB-71-10] N72-11040

HAREL, P.
Studying the coherent and incoherent structures of aerodynamically generated noise [ONERA-TP-983] N72-11036

HARMS, L.
Influence of a jet on the aerodynamic properties of wings positioned above the jet nozzle N72-10010

HARPUR, N.
The airworthiness certification of Concorde. [SAE PAPER 710756] A72-10253

HARTMANN, K.
Force and pressure distribution measurements on a wing-body combination with wing of low aspect ratio in compressible flow [DGLR PAPER 71-118] A72-12707

HASSIG, H. J.
An approximate true damping solution of the flutter equation by determinant iteration. A72-11133

HATFIELD, J. R.
Display research collision warning system [NASA-CASE-HQN-10703] N72-11527

HAUSER, D.
Tensile behavior of high-strength alloys during rapid heating. A72-10749

HAWKES, J. E.
Development status of the L-1011 TriStar. [SAE PAPER 710755] A72-10252

HECHTMAN, H.
C-SCAN - Pilot's window to the deck. A72-12323

HEIDRICH, H.
Preliminary tests and performance of rolling vertical takeoff and landing of the VJ 101 C-X2 with ignited afterburners [BMVG-FBWT-71-13] N72-10034

HEINRICH, H. G.
Theory and experiment on parachute opening shock and filling time. A72-10310

HEINRICH, W.
Preliminary results of measurements of heavy primaries in the region of supersonic transport using plastic stacks. A72-12077

HEINZLERING, W.
Technique of propulsion system simulation with high pressure ejectors for subsonic wind tunnel measurements on a fighter aircraft model with vertical takeoff characteristics N72-10007

HENDERSON, H. T.
Cooling of advanced engines by endothermic reactions of hydrocarbon fuels N72-11672

HENTON, G. B.
A simple three-dimensional missile trajectory model. A72-10964

HERPFER, E.
Experimental studies of aerodynamic coefficients of a wing-fuselage combination and comparison with the results of linear and nonlinear theories at subsonic speeds [DGLR PAPER 71-115] A72-12723

HERRING, R. W.
Compressive behavior of titanium alloy skin-stiffener specimens selectively reinforced with boron-aluminum composite [NASA-TN-D-6548] N72-11428

HESTER, D. B.
Lubricant and fuel interactions in advanced aircraft gas turbines [NASA-CR-122842] N72-11694

HEVENER, R. W.
The CF6 engine - Designed to improve operational effectiveness. [SAE PAPER 710779] A72-10271

Accessibility: The key to good powerplant maintainability N72-11031

HEYNATZ, J. T.
Experimental studies of aerodynamic coefficients of a wing-fuselage combination and comparison with the results of linear and nonlinear theories at subsonic speeds [DGLR PAPER 71-115] A72-12723

Turbulent and laminar jet propagation in rotating systems and its application to jet mixing in the wake of reaction driven rotors N72-10008

HILL, J. D.
Air traffic control - A problem in decision-making. A72-11718

HIRSCH, S. N.
Airborne infrared forest fire detection system [AD-726953] N72-10396

HITT, E. F.
For a better, short-haul flight. A72-11719

HODGSON, J. P.
Real-gas effects in very weak shock waves in the atmosphere and the structure of sonic bangs. A72-11972

HOEFS, K. W.
Future trends in aircraft design. [SAE PAPER 710749] A72-10248

HOENLINGER, H.
Methods of construction of aeroelastic models for a rational flutter analysis of modern aircraft designs [DGLR PAPER 71-082] A72-12722

HOPMANN, H.
Air traffic regulations A72-12621

- Air traffic law
A72-12622
- HOLLINGSWORTH, S. R.
Investigation of display requirements for helicopter
IPR manual formation flight under various
operational and environmental conditions
[AD-725209] N72-10044
- HOOD, B. A.
Field measurement of infrasonic noise.
A72-10157
- HOUBOLT, J. C.
On the aerodynamic forces of oscillating two
dimensional lifting surfaces
[AD-726132] N72-11017
- HUBER, H.
The stability- and control behavior of the hingeless
Boelkow rotor system
N72-11008
- HUBERT, J.
Numerical calculation of a sonic flow about an
aircraft wing profile, by an inverse method
A72-11178
- HUI, W. H.
Supersonic and hypersonic flow with attached shock
waves over delta wings.
A72-12030
- HUME, R. G.
Observations on breathing and related phenomena in
some paratroop type parachutes when freely
descending.
A72-10307
- HUMPELT, G. L.
Automated air traffic control.
A72-10960
- HUNT, P. L.
Sonic bang measurements during exercise summer sky
[ARC-E/M-3659] N72-11015
- HURSH, J. W.
The role of inertial navigation in future air
traffic control systems.
A72-11118
- I
INGER, G. R.
Nonequilibrium boundary layer flow on highly-swept
hypersonic wings.
[VPI-E-71-23] A72-12422
- INGRAM, C. W.
Determining aircraft stability coefficients from
dynamic motions.
A72-11136
- IRANI, K. K.
Experimental manufacture of Inconel Alloy 718
compressor rotor blades from metal powder
preforms.
A72-11441
- J
JABLONSKI, W.
Improving the readability of maintenance manuals
N72-11021
- JAMES, K.
The influence of axial cords on parachute
performance.
A72-10306
- JANOUR, Z.
Boundary-layer development on a wing-body
combination.
A72-12228
- JANTZEN, E.
Early stage detection of oil changes in aircraft
engines
N72-11698
- JOHANNESEN, W. H.
Real-gas effects in very weak shock waves in the
atmosphere and the structure of sonic bangs.
A72-11972
- JOHNSON, D. W.
Supersonic and transonic deployment of ribbon
parachutes at low altitudes.
A72-10312
- JOHNSTON, H.
Catalytic reduction of stratospheric ozone by
nitrogen oxides
[UCRL-20568] N72-11334
- JULIENNE, A.
Study and calibration of pressure sensors in
particular environments
[ONERA-TP-982] N72-11368
- K
KAMALI, G.
Time dependence of variances of sonic boom waveform.
A72-11158
- KEITH, I. P.
Maintaining the B8 125 in the seventies
N72-11032
- KELLEY, A. L.
Data analysis system for Army flight testing.
A72-12408
- KESLING, P. H.
Study of aircraft in intraurban transportation
systems, volume 1
[NASA-CR-114340] N72-10984
- Study of aircraft in intraurban transportation
systems, volume 2
[NASA-CR-114341] N72-10985
- Study of aircraft in intraurban transportation
systems, volume 3
[NASA-CR-114342] N72-10986
- Study of aircraft in intraurban transportation
systems. Volume 4: Appendix
[NASA-CR-114343] N72-10987
- KEY, D. L.
The generation of a military specification for
flying qualities of Piloted V/STOL Aircraft
MIL-P-83300
[AD-725746] N72-10048
- KHAIKIN, M. D.
Ways of improving the antiwear properties of fuels
for jet engines
A72-11968
- KHOKHLACHEVA, M. V.
Ways of improving the antiwear properties of fuels
for jet engines
A72-11968
- KIDA, T.
A note of the configuration of jet sheet on a thin,
jet-flapped airfoil.
A72-11669
- KING, G. E.
Civil Aircraft Airworthiness Data Recording
Programme. Manoeuvre loads during training and
test flying
[ABC-CP-1176] N72-11043
- KINTLEY, J. G.
Fuels for supersonic and hypersonic aircraft
N72-11671
- KLUNKER, E. B.
Contribution to methods for calculating the flow
about thin lifting wings at transonic speeds:
Analytic expressions for the far field
[NASA-TN-D-6530] N72-11289
- KNAPP, S. C.
Environmental effects on attack helicopter crew task
performance in the NATO theater
[AD-726949] N72-10122
- KOFF, B. L.
Graphite fan blade development.
[SAE PAPER 710771] A72-10265
- KOROBOW, B. F.
Ways of improving the antiwear properties of fuels
for jet engines
A72-11968
- KOSTAREV, V. V.
Utilization of meteorological radar for aeronautics
[OMH-264-TP-148] N72-11147
- KOSVIC, T. C.
Analysis of aircraft fuel tank fire and explosion
hazards
[AD-725027] N72-11056
- KOVALEV, A. A.
Determination of radial stresses in ring-to-drum
transition areas of disks
A72-11374
- KOVICH, G.
Effect of casing treatment on overall and blade
element performance of a compressor rotor
[NASA-TN-D-6538] N72-10025
- KOZLOV, I. A.
Experimental investigation of the strength of
rotating disks in aircraft gas turbines operating
under variable thermal conditions
A72-11637

- KRAMER, J. J.
The NASA Quiet Engine.
[SAE PAPER 710774] A72-10266
- KUCHTA, J. B.
Fire hazard evaluation of thickened aircraft fuels N72-11689
- KUEHL, P.
Externally blown flaps, aerodynamic feasibility study of a STOL-transporter. A72-12502
- KUGLER, W.
Theoretical considerations of a spring, hinged rotor of variable flapping stiffness and constant phase shift N72-11007
- KURTSEVA, I. I.
Determination of radial stresses in ring-to-drum transition areas of disks A72-11374
- KUSENBERGER, F. W.
Fatigue damage detection. A72-12498
- KUSSMANN, A.
Survey of different models for computing the flow of a lifting rotor N72-11002
- L
- LA ROVERE, P.
Automation of air traffic - The ATCAS system A72-12649
- LALIBERTE, W. G.
Automated air traffic control. A72-10960
- LAMBOURION, J.
Studying the coherent and incoherent structures of aerodynamically generated noise [ONERA-TP-983] N72-11036
- LANGE, W. R.
Analysis of pilot warning indicator performance in terminal area traffic. A72-11134
- LANGLEY, M.
Strength and stiffness of sandwich panels under transverse loading. A72-10723
- LAY, R. K.
A survey of propulsion systems for low emission urban vehicles [PB-200144] N72-10830
- LEE, C. H.
A hybrid electrical power system for aircraft application. A72-11068
- LEHMAN, A. F.
Model studies of helicopter tail rotor flow patterns in and out of ground effect [AD-725591] N72-11060
- LEHRMAN, D. E.
Convergence of current routines for evaluating downwash at a lifting surface [NPL-AERO-NOTE-1095] N72-11012
- LEMOAL, G. A.
Rigid pavement stresses under aircraft loading. A72-10192
- LEONARD, B. E.
Development of ultrasonic field inspection equipment for T53 gas turbine compressor discs. A72-10814
- LESHCHENKO, V. M.
Experimental investigation of the strength of rotating disks in aircraft gas turbines operating under variable thermal conditions A72-11637
- LEVENTHALL, H. G.
Field measurement of infrasonic noise. A72-10157
- LEVINE, G. B.
Tactical displays. A72-12421
- LEWIS, A.
Fuels for supersonic and hypersonic aircraft N72-11671
Electrostatic charging in the handling of aviation fuels N72-11686
- LINSCHIED, L. L.
Study and development of acoustic treatment for jet engine tailpipes [NASA-CR-1853] N72-10043
- LLOYD, D. E.
Mathematical studies on separation standards. A72-10178
- LOCK, R. C.
A note on subsonic linearised theory for symmetrical cranked wings at zero incidence. A72-11154
A note on subsonic linearised theory for symmetrical cranked wings at zero-incidence [NPL-AERO-NOTE-1090] N72-10021
- LOEBERT, G.
Aerodynamic calculations for the interference of several propeller-jets with an aerofoil N72-10015
- LOGAN, A. H.
Vortex velocity distributions at large downstream distances. A72-11135
- LOOMIS, J. P.
Air transportation in our changing society. A72-11716
- LORDI, J. A.
A study of noise generation by a rotating blade row in an infinite annulus [AD-726126] N72-11714
- LOSENSKY, J. B.
Airborne infrared forest fire detection system [AD-726953] N72-10396
- LOWRY, R. B.
Air Force STOL tactical transport technology program. A72-10255
[SAE PAPER 710758]
- LUCIFREDI, A.
Two examples of application of Kalman filters to integrated navigation systems A72-12050
- LUIDENS, R. W.
Multiple fan integrated propulsion wing system [NASA-CASE-LEW-11224-1] N72-10033
- LUNDQUIST, G. E.
FAA plans for AEROSAT. A72-12383
- M
- MABEY, D. G.
An hypothesis for the prediction of flight penetration of wing buffeting from dynamic tests on wind tunnel models [ARC-CP-1171] N72-11044
- MACDONALD, J. A.
Fire and explosion protection of fuel tank ullage N72-11690
- MACKINNON, D.
The role of inertial navigation in future air traffic control systems. A72-11118
- MADDEN, P. H.
Airborne infrared forest fire detection system [AD-726953] N72-10396
- MAGGI, C.
Investigation of an associative memory for use in digital computers employed as aids to air and naval traffic A72-12647
- MAHMUTH, N.
A new area rule for hypersonic wing-bodies. A72-12270
- MANGIAROTTY, R. A.
The reduction of aircraft engine fan-compressor noise using acoustic linings. A72-10223
[BAS PAPER 71 SA6]
- MAHN, A. R.
Skin-friction measurement in flow with pressure gradient. A72-12275
- HANSON, L.
Jet-noise reduction through liquid-base foam injection. A72-10160
- MARCUS, N. G.
The mechanical design of an adjustable nozzle for the NPL 25 in by 20 in (635 mm by 508 mm) transonic wind tunnel [NPL-AERO-NOTE-1098] N72-10023
- MARSHALL, E. E.
STOL aircraft in future transport systems.

- MATTESON, D. E. A72-11153
Study of aircraft in intraurban transportation systems, volume 3 [NASA-CR-114342] N72-10986
- MATTESON, H. C. A72-11584
Study of aircraft in intraurban transportation systems, volume 1 [NASA-CR-114340] N72-10984
Study of aircraft in intraurban transportation systems, volume 2 [NASA-CR-114341] N72-10985
Study of aircraft in intraurban transportation systems. Volume 4: Appendix [NASA-CR-114343] N72-10987
- MAYDEW, R. C. A72-10312
Supersonic and transonic deployment of ribbon parachutes at low altitudes.
- MAYER, A. A72-10539
Target contrast considerations in millimeter wave radiometry for airborne navigation [NASA-TM-X-62082]
- MAYES, E. C. N72-11025
Nondestructive inspection: An aircraft maintenance tool of the seventies
- MCANALLY, W. J., III N72-11713
Investigation of feasibility of integral gas turbine engine solid particle inlet separators. Phase 2: Feasibility demonstration [AD-725593]
- MCFARLAND, S. R. A72-10814
Development of ultrasonic field inspection equipment for T53 gas turbine compressor discs.
- MCPAUL, H. J. A72-11109
Development of the DC-10 Nondestructive Testing Manual.
- MCINTOSH, S. N72-10992
Cost growth and productivity in European aerospace development programs [AD-725478]
- MCPHATE, A. J. N72-10042
Optimization studies of aircraft control variables [AD-725069]
Spectral analysis of transient data with application to auto-pilot parameter studies [AD-725068] N72-10501
- MECHETNYI, V. S. A72-10506
Compensation of cross-couplings in aircraft motion
- MEHNEL, D. A72-12898
Measuring, data-acquisition, and data-processing systems for the large wind tunnels of the Aerodynamische Versuchsanstalt Goettingen
- MELANCON, L. A72-12393
A limited scan antenna.
- MELZER, E. N72-10005
Possibilities for jet simulation in the 3m-wind tunnel of the DPVLR-AVA Goettingen
- MESCHERIAKOV, M. P. A72-11373
Thermal strength testing methods for aircraft gas turbine engine nozzle apparatuses
- MIKHAEV, I. A. N72-11039
Systems of aircraft automatic control [JPRS-54332]
- MILLER, R. E. N72-11692
Simulated crash tests as a means of rating aircraft safety fuels
- MILLER, T. S. A72-10309
Projected maintainability advantages of solid state electrical power management and solid state contactless switching systems
- MITCHELL, J. R. A72-10315
The performance of parachutes at low speeds.
The strain of stitched joins.
- NITROKHIN, V. T. A72-10047
One-dimensional unsteady flow in a rotating vane cascade
- MIYAI, Y. A72-11584
A note of the configuration of jet sheet on a thin, jet-flapped airfoil.
- MOORE, R. D. A72-11669
Effect of casing treatment on overall and blade element performance of a compressor rotor [NASA-TN-D-6538] N72-10025
- MUGRIDGE, B. D. A72-10217
Turbulent boundary layers and surface pressure fluctuations on two-dimensional aerofoils.
- MURPHY, D. G. A72-10249
The crystal ball focuses on the next generation of transport aircraft. [SAE PAPER 710750]
- MURPHY, J. N. A72-11689
Fire hazard evaluation of thickened aircraft fuels
- N
- NAKAMURA, Y. N72-11291
Effects of Reynolds number and frequency parameter on control-surface buzz at high subsonic speeds [NPL-AERO-1312]
- NANTOIS, R. N72-11368
Study and calibration of pressure sensors in particular environments [ONERA-TP-982]
- NARDI, G. N72-11675
Low emission fuels and devices for aviation engines
- NARR, T. C., JR. A72-10254
A progress report on the development of an augmentor wing jet STOL research aircraft. [SAE PAPER 710757]
- NASH, J. P. A72-11395
The three-dimensional turbulent boundary layer on an infinite yawed wing.
- NELMS, W. P., JR. N72-10045
Aerodynamic characteristics of an all-body hypersonic aircraft configuration at Mach numbers from 0.65 to 10.6 [NASA-TN-D-6577]
- NELSON, J. C. A72-10960
Automated air traffic control.
- NELSON, J. M. N72-11370
Calibration of the Concorde radiation detection instrument and measurements at SST altitude [FAA-AH-71-26]
- NELSON, M. D. N72-10043
Study and development of acoustic treatment for jet engine tailpipes [NASA-CR-1853]
- NEPPERT, H. A72-12718
Spin control by means of the 'superstall' characteristic [DGLR PAPER 71-057]
- NICHOLAS, O. P. N72-11045
Brief flight tests of crosswind landings and sidestep manoeuvres on the BAC 221 aircraft [ARC-CP-1168]
Flight and wind-tunnel tests on an aerodynamically compensated pitot-static head for the BAC 221 aircraft [ARC-CP-1167] N72-11046
- NORTHEY, D. A72-10308
High speed parachute research in the U.K.
- O
- O'KEEFE, J. V. A72-10254
A progress report on the development of an augmentor wing jet STOL research aircraft. [SAE PAPER 710757]
- OATES, G. S., JR. A72-10255
Air Force STOL tactical transport technology program. [SAE PAPER 710758]
- OJALVO, I. U. A72-10047
An automated procedure for the optimization of practical aerospace structures. Volume 2: Technical programmer's manual [AD-725744]

- An automated procedure for the optimization of practical aerospace structures. Volume 1: Theoretical development and user's information [AD-726112] N72-11820
- OKOYERHOV, B. W.
Systems of aircraft automatic control [JPRS-54332] N72-11039
- OLSON, R. L.
Future trends in aircraft design. [SAE PAPER 710749] A72-10248
- OLSON, R.
Design comparison of quiet $M = 0.80$ STOL transports. [SAE PAPER 710759] A72-10256
- OPATOWSKI, T.
A three component gun tunnel balance designed for testing thin delta wings [ARC-R/M-3664] N72-11375
- ORTWERTH, P. J.
Experimental study of shock impingement on a blunt leading edge with application to hypersonic inlet design [AD-726111] N72-11312
- OTANI, K.
Utilization of meteorological radar for aeronautics [OMM-264-TP-148] N72-11147

P

- PALLANT, R. J.
Sonic bang measurements during exercise summer sky [ARC-R/M-3659] N72-11015
- PARKER, G. R.
Aircraft fuelling operations and quality control N72-11678
- PAVLINA, I. G.
Systems of aircraft automatic control [JPRS-54332] N72-11039
- PEASLEE, R. L.
Remanufacturing of jet engine components employing brazing techniques N72-11024
- PEPE, A.
Current situation of radio aids for aerial navigation in Italy and prospects for the near future A72-12748
- PERULLI, M.
Studying the coherent and incoherent structures of aerodynamically generated noise [ONERA-TP-983] N72-11036
- PETRONIO, G.
Producibility in design. [SAE PAPER 710748] A72-10247
- PETROV, Y. V.
The KFA (Department of the Atmospheric Physics) aerial expeditions 1 and 2 for study of the peculiarities of conditions of the boundary layer of the atmosphere over an oasis and a semiarid region [AD-727535] N72-10332
- PPAPHAH, E.
FAA certification and the growth model 747B airplane. [SAE PAPER 710753] A72-10251
- PIEKARZ, R.
Cost growth and productivity in European aerospace development programs [AD-725478] N72-10992
- PIERCE, A. D.
Time dependence of variances of sonic boom waveform. A72-11158
- PINSKEE, W. J. G.
A theoretical study of height control in flight close to the ground as affected by elevator lift and cockpit position [ARC-R/M-3662] N72-11049
- PITTS, P. L.
Electronic strain level counter [NASA-CASE-LAR-10756-1] N72-11803
- POPIK, M. J.
Automated landing system. A72-10961
- POPP, H. G.
Field practices in the repair of fatigue damaged jet engine components. A72-12499
- POPPELWELL, B.
The vibration of a box-type structure. II - Response

to a travelling pressure wave.

A72-10219

- PORTER, H. B.
Theory of the measurement and standardization of in-flight performance of aircraft [AD-725741] N72-11054
- PORTER, R. F.
For a better, short-haul flight. A72-11719
- POWELL, B. J.
A programme of research into viscous aspects of flow on swept wings [NPL-AERO-NOTE-1100] N72-10018
- POZESKY, M. T.
A discrete address ATC beacon system. A72-12378
- PROCTOR, J. D.
Terrain clearance during descent and approach. A72-10183
- PROUTY, R.
The rostrum. A72-12882
- PUDDU, G.
Doppler - A modern aid for air navigation A72-12749

Q

- QUAGLIONE, G.
Problems and technical aspects connected with the use of the L band in an aerial navigation aid system via satellite A72-12642
- QUIGG, H. T.
Effect of very low sulfur in JP-5 fuel on hot corrosion [AD-725619] N72-11706
- QUIGLEY, H. C.
A progress report on the development of an augmentor wing jet STOL research aircraft. [SAE PAPER 710757] A72-10254

R

- RABB, J. W.
The FAA air traffic control automation program. A72-12380
- RATCLIFFE, S.
The potential of existing avionics technology. A72-10180
- REID, J. A. I.
The testing of parachutes at supersonic speeds. A72-10305
- REYNAUD, F.
Thermal stability of a tri-methyl-propane ester based lubricating oil N72-11699
- REYNOLDS, L. J.
Smoother travel in rough air. A72-11720
- RICHARZ, O.
Preliminary tests and performance of rolling vertical takeoff and landing of the VJ 101 C-X2 with ignited afterburners [BMVG-PBWT-71-13] N72-10034
- RIEGELS, F. W.
Measuring, data-acquisition, and data-processing systems for the large wind tunnels of the Aerodynamische Versuchsanstalt Goettingen A72-12898
- RIGAUT, P.
Numerical calculation of a sonic flow about an aircraft wing profile, by an inverse method A72-11178
- RIST, D.
Conception and flight behavior of a jet-powered recoverable lift engine A72-12900
- RITTER, M.
Test and evaluation of a daytime cockpit fog simulator [FAA-NA-71-44] N72-10233
- ROBERTS, B.
Research on advanced axial compressor concepts [AD-725789] N72-11308
- ROBERTS, B. W.
The aerodynamic inflation of shell type structures with particular reference to parachutes. A72-10311

- ROBINSON, A. C.
Air traffic control - A problem in decision-making.
A72-11718
- ROBINSON, D. W.
A new basis for aircraft noise rating
[NPL-AERO-AC-49] N72-10035
Index of NPL acoustics publications, 1960 - 1970
[NPL-AERO-AC-47] N72-10589
- ROBSON, R.
Stability of synthetic aviation gas turbine
lubricants at high temperatures
N72-11695
- ROHRS, H.
Preliminary results of measurements of heavy
primaries in the region of supersonic transport
using plastic stacks.
A72-12077
- ROLFE, R. J.
Automated air traffic control.
A72-10960
- ROPELEWSKI, R. R.
B-1 design keyed to future growth.
A72-12226
- ROSE, J. F., JR.
Crew compartment vibration environment in the B-52
aircraft during low-altitude, high-speed flight
[AD-727023] N72-10127
- ROSE, R.
Brief flight tests of crosswind landings and
sidestep manoeuvres on the BAC 221 aircraft
[ARC-CP-1168] N72-11045
- ROSS, G. A.
Rigid pavement stresses under aircraft loading.
A72-10192
- ROTHNDI, G.
From the propeller to the jet engine
A72-11258
- ROTTIERS, H.
Research on advanced axial compressor concepts
[AD-725789] N72-11308
- RUDOLPH, F. J.
Methods of flight vibration testing of modern
high-performance aircraft
[DGLR PAPER 71-083] A72-12725
- RUETENIK, J. R.
Analysis of pilot warning indicator performance in
terminal area traffic.
A72-11134
- RUMMEL, K. G.
Helicopter development reliability test
requirements. Volume 1
[AD-725595] N72-11059
- RUSSEL, R. A., JR.
Crash safe turbine fuel development by the Federal
Aviation Administration, 1964 - 1970
N72-11687
- S**
- SABEL, J. B.
Computer application strategy for control of airline
maintenance in the seventies
N72-11020
- SALVAGE, J.
Research on advanced axial compressor concepts
[AD-725789] N72-11308
- SANDSTROM, R.
The load on the brake parachute of a jet aeroplane
under the influence of the engine wake.
A72-12504
- SARGIOUS, M.
Rigid pavement stresses under aircraft loading.
A72-10192
- SASHEVSKII, V. V.
Ways of improving the antiwear properties of fuels
for jet engines
A72-11968
- SATER, J. C.
Automated air traffic control.
A72-10960
- SAWYER, R. P.
Flame inhibition chemistry
N72-11680
- SCHAEKEL, F. W.
Emulsified fuels and aircraft safety
N72-11688
- SCHAEENZER, G.
Angle of attack and thrust control for steeply
approaching aircraft
A72-12705
- [DGLR PAPER 71-063] A72-12705
- SCHERRER, R.
Design comparison of quiet M = 0.80 STOL transports.
[SAE PAPER 710759] A72-10256
- SCHILLING, R. T.
Investigation of feasibility of integral gas turbine
engine solid particle inlet separators. Phase 2:
Feasibility demonstration
[AD-725593] N72-11713
- SCHIRMER, R. M.
Effect of very low sulfur in JP-5 fuel on hot
corrosion
[AD-725619] N72-11706
- SCHIRWITZ, D.
Three component measurements for rigid parachute
models.
A72-10303
- SCHMIDT, R.
Turbulent and laminar jet propagation in rotating
systems and its application to jet mixing in the
wake of reaction driven rotors
N72-10008
- SCHMIDTLEIN, H.
Adaptation of the nonlinear characteristic of an
attitude control system developed for a V/STOL
aircraft to a helicopter
[DGLR PAPER 71-060] A72-12714
- SCHNEIDER, W.
Force and pressure distribution measurements on a
wing-body combination with wing of low aspect
ratio in compressible flow
[DGLR PAPER 71-118] A72-12707
- SCHULTE, R. H.
Experimental evaluation of lightning protective
coatings for boron/epoxy composites.
A72-10783
- SCHULTHEISS, G.
Influence of the wake geometry on the velocity and
load distribution of VTOL propellers
N72-11004
- SCHULTZ, W. H.
Installation and integration of transonic transport
propulsion systems.
[SAE PAPER 710762] A72-10259
- SCHULE, G.
Calculation of the pressure distribution on an
aircraft fuselage with emerging lifting jets using
singularities
N72-10014
- SCHWANTES, E.
Investigations of exhaust jets of TL-engine models
N72-10013
- SCHWARTZ, M. B.
Propulsion system requirements for advanced
technology air transports.
[SAE PAPER 710761] A72-10258
- SCHWARZ, R.
Utilization of meteorological radar for aeronautics
[OMN-264-TP-148] N72-11147
- SCHWENK, W.
On the concept of air law
A72-11107
- SEIDEL, M.
The influence of an inclined jet on the aerodynamic
characteristics of a control surface
N72-10011
- SEKISTOV, V. A.
Experimental investigation of the strength of
rotating disks in aircraft gas turbines operating
under variable thermal conditions
A72-11637
- SHARMA, O. P.
Ignition of fuels by a hot projectile
N72-11683
- SHAYESON, M. W.
Lubricant and fuel interactions in advanced aircraft
gas turbines
[NASA-CR-122842] N72-11694
- SHERWOOD, D. E.
Study of aircraft in intraurban transportation
systems, volume 1
[NASA-CR-114340] N72-10984
Study of aircraft in intraurban transportation
systems, volume 2
[NASA-CR-114341] N72-10985
Study of aircraft in intraurban transportation
systems, volume 3
[NASA-CR-114342] N72-10986

- Study of aircraft in intraurban transportation systems. Volume 4: Appendix
[NASA-CR-114343] N72-10987
- SHIELDS, C. B.
Improving the efficiency of airports. A72-11717
- SHIRLEY, W. A.
A flight simulator study of STOL transport directional control characteristics
[PAA-RD-71-81] N72-11037
- SILLION, B.
Synthesis and properties of esters of tetramethyl-2,2-7,7 octane diol-1,8 N72-11696
- SIMAKOV, A. A.
Determination of radial stresses in ring-to-drum transition areas of disks A72-11374
- SIMONS, W., JR.
Air transportation in the American economy. A72-11721
- SINCLAIR, S. R. H.
A progress report on the development of an augmentor wing jet STOL research aircraft. A72-10254
[SAE PAPER 710757]
- SIRIGNANO, W. A.
Ignition of fuels by a hot projectile N72-11683
- SKOP, R. A.
The configuration of a cable towed in a circular path. A72-11132
- SMITH, T. B., III
Display research collision warning system
[NASA-CASE-HQN-10703] N72-11527
- SMITH, W.
On the noise sources of the unsuppressed high-speed jet. A72-11973
On the noise sources of the unsuppressed high speed jet
[ARC-32723] N72-10254
- SNESHKO, I. I.
In-flight studies of aircraft stability and controllability A72-12542
- SNYDER, D.
Pacific Airmotive Corporation accessory reliability program (PACAR) N72-11035
- SODERMAN, P. T.
Full-scale wind-tunnel tests of a small unpowered jet aircraft with a T-tail
[NASA-TN-D-6573] N72-10031
- SPEARMAN, J. D.
Crew compartment vibration environment in the B-52 aircraft during low-altitude, high-speed flight
[AD-727023] N72-10127
- SPEEG, R.
Spectral analysis of transient data with application to auto-pilot parameter studies
[AD-725068] N72-10501
- SPENCER, J. L.
Electronic strain level counter
[NASA-CASE-LAR-10756-1] N72-11803
- SPONSELLER, D. I.
Ductility improvements in superalloys. A72-12561
- SQUIRE, L. C.
A comparison of the lift of flat delta wings and waveriders at high angles of incidence and high Mach number. A72-12345
- STAHL, W.
Force and pressure distribution measurements on a wing-body combination with wing of low aspect ratio in compressible flow
[DGLR PAPER 71-118] A72-12707
- STANDER, A.
Development of a stress crack resistant urethane sealant for heated areas of aircraft surfaces
[AD-727592] N72-10489
- STANGEL, J. J.
Electronic scanning array for ATC. A72-10962
- STEHN, J. A.
The crystal ball focuses on the next generation of transport aircraft.
[SAE PAPER 710750] A72-10249
- STEVENS, G. W. H.
A review of parachute applications and some associated current research problems. A72-10302
- Observations on breathing and related phenomena in some paratroop type parachutes when freely descending. A72-10307
- STEVENS, W. A.
Mathematical model for two-dimensional multi-component airfoils in viscous flow
[NASA-CR-1843] N72-11010
- STOUT, E. G.
Study of aircraft in intraurban transportation systems, volume 1
[NASA-CR-114340] N72-10984
- Study of aircraft in intraurban transportation systems, volume 2
[NASA-CR-114341] N72-10985
- Study of aircraft in intraurban transportation systems, volume 3
[NASA-CR-114342] N72-10986
- Study of aircraft in intraurban transportation systems. Volume 4: Appendix
[NASA-CR-114343] N72-10987
- STRAWSON, H.
Fuels for supersonic and hypersonic aircraft N72-11671
- Electrostatic charging in the handling of aviation fuels N72-11686
- SUGIYAMA, Y.
On the characteristics of wing with tip clearance. III - The force acting on a rectangular wing of low aspect ratio. A72-12825
- SUNAPRANK, W. O.
Development of composite tape laying process for advanced fibrous reinforced composite structures
[AD-725765] N72-10425
- T
- TANWER, M.
Experimental investigation of the drag and lift of wings with a blunt trailing edge in compressible flow
[DGLR PAPER 71-114] A72-12712
- TANSLEY, B.
High speed parachute research in the U.K. A72-10308
- TEPER, G. L.
A flight simulator study of STOL transport directional control characteristics
[PAA-RD-71-81] N72-11037
- THOMAS, C. L.
Aerodynamic characteristics of an all-body hypersonic aircraft configuration at Mach numbers from 0.65 to 10.6
[NASA-TN-D-6577] N72-10045
- THOMPSON, B. G.
A programme of research into viscous aspects of flow on swept wings
[NPL-AERO-NOTE-1100] N72-10018
- THOMPSON, J. H.
Analysis of pilot warning indicator performance in terminal area traffic. A72-11134
- THOMPSON, R. E.
Improving the efficiency of airports. A72-11717
- THORP, J. H.
Development of ultrasonic field inspection equipment for T53 gas turbine compressor discs. A72-10814
- TIMMS, R. J.
Electronic scanning array for ATC. A72-10962
- TOIVANEN, H. L.
Investigation of display requirements for helicopter IFR manual formation flight under various operational and environmental conditions
[AD-725209] N72-10044
- TORGET, S. J.
Producibility considerations in production planning for new aircraft.
[SAE PAPER 710746] A72-10245
- TOURNEHINE, G.
Numerical calculation of a sonic flow about an

- aircraft wing profile, by an inverse method
A72-11178
- TRENKA, A. R.
The aerodynamic and aeroelastic characteristics of a full scale rotor operating at very high advance ratios and during start/stop operation
[AD-727653] N72-11050
- TREUSSART, H.
Utilization of meteorological radar for aeronautics
[OMM-264-TP-148] N72-11147
- TRIEBSTEIN, H.
Investigation of unsteady interference effects on a harmonically oscillating wing-tailplane model with a variable sweep wing in the low subsonic region
[DGLR PAPER 71-081] A72-12709
- TRIPPLEMAN, B.
Experimental manufacture of Inconel Alloy 718 compressor rotor blades from metal powder preforms.
A72-11441
- TSENG, R. B.
The three-dimensional turbulent boundary layer on an infinite yawed wing.
A72-11395
- TUCK, W. R., JR.
Study of aircraft in intraurban transportation systems, volume 1
[NASA-CR-114340] N72-10984
Study of aircraft in intraurban transportation systems, volume 2
[NASA-CR-114341] N72-10985
Study of aircraft in intraurban transportation systems, volume 3
[NASA-CR-114342] N72-10986
Study of aircraft in intraurban transportation systems. Volume 4: Appendix
[NASA-CR-114343] N72-10987
- TURLEY, A. R.
The testing of parachutes at supersonic speeds.
A72-10305
- TUVE, R. L.
Surface active considerations in fuel fires
N72-11693
- V**
- VAN NIMWEGEN, R. R.
Design features of the Garrett ATF3 turbofan engine.
[SAE PAPER 710776] A72-10268
- VAUGHN, L. A.
Study of aircraft in intraurban transportation systems, volume 1
[NASA-CR-114340] N72-10984
Study of aircraft in intraurban transportation systems, volume 2
[NASA-CR-114341] N72-10985
Study of aircraft in intraurban transportation systems, volume 3
[NASA-CR-114342] N72-10986
Study of aircraft in intraurban transportation systems. Volume 4: Appendix
[NASA-CR-114343] N72-10987
- VENDITTI, A.
Automation of air traffic - The ATCAS system
A72-12649
- VERDIE, G.
Aeronautical significance of polycyclic saturated hydrocarbons
N72-11670
- VERE, R. A.
Aviation fuel lubricity
N72-11679
- VITALI, E.
Problems and technical aspects connected with the use of the L band in an aerial navigation aid system via satellite
A72-12642
- VOLOSHIN, G. I.
Course-indicating systems and automatic navigation aids for civil aviation aircraft
A72-12298
- W**
- WACHSMAN, H.
Conflict detection at Knoxville.
A72-12033
- WAGGONER, J. T.
Operating logic: New data and training concept
N72-11692
- developments of the Apollo program
N72-11026
- WAGNER, P. C.
Experimental manufacture of Inconel Alloy 718 compressor rotor blades from metal powder preforms.
A72-11441
- WAGNER, S.
Linear aerodynamic rotor theory
N72-11005
- WARD, J. P.
Variable geometry rotor system
[NASA-CASE-LAR-10557] N72-11018
- WARREN, E. L.
Analysis and design study of a pilot assist system for helicopters
[AD-725590] N72-11057
- WATKINS, W. W.
Streamlined L-1011 fault isolation techniques
N72-11028
- WEATHERFORD, W. D., JR.
Emulsified fuels and aircraft safety
N72-11688
- WEBB, D. R. B.
Sonic bang measurements during exercise summer sky
[ARC-R/M-3659] N72-11015
- WEBSTER, R. C.
Compressive behavior of titanium alloy skin-stiffener specimens selectively reinforced with boron-aluminum composite
[NASA-TN-D-6548] N72-11428
- WEINBERGER, M. R.
Flight instrument and telemetry response and its inversion
[NASA-CR-1768] N72-10401
- WEISS, H. G.
Air traffic control
[AD-725743] N72-10543
- WELCH, A. J.
Analysis and design study of a pilot assist system for helicopters
[AD-725590] N72-11057
- WELTE, D.
Externally blown flaps, aerodynamic feasibility study of a STOL-transporter.
A72-12502
- WETHERSPEE, J. K.
Air transportation in our changing society.
A72-11716
- WHITE, A.
Air traffic control separation minima and navigational capability.
A72-10177
- WHITEHOUSE, G. D.
Optimization studies of aircraft control variables
[AD-725069] N72-10042
Spectral analysis of transient data with application to auto-pilot parameter studies
[AD-725068] N72-10501
- WHYTE, R. B.
Jet fuel specifications
N72-11669
- WICKENS, R. H.
On the possibility of roll control for the externally-blown jet flap.
A72-11700
- WILBERS, L. G.
Field practices in the repair of fatigue damaged jet engine components.
A72-12499
- WILBY, J. P.
Interior noise radiated by an airplane fuselage subjected to turbulent boundary layer excitation and evaluation of noise reduction treatments.
A72-10216
- WILCOCK, T.
Piloted simulator investigations of flight near zero rate of climb speed
[ARC-CP-1165] N72-11048
- WILCOX, J. B.
Influence of powerplant design on airplane operational effectiveness - The operator's point of view.
[SAE PAPER 710777] A72-10269
- WILFORD, S. P.
Simulated crash tests as a means of rating aircraft safety fuels
N72-11692

PERSONAL AUTHOR INDEX

ZUNG, L. B.

- WILLIAMS, R. M.
Theoretical performance of a pure jet flap rotor at
high advance ratios
[AD-726706] N72-10037
- WILLIAMS, S. B.
Helicopter lift-margin system, volume 2
[AD-725207] N72-11053
- WILSON, R. A.
Airborne infrared forest fire detection system
[AD-726953] N72-10396
- WINTERFELD, G.
Investigation of fire extinguishing powders by means
of a new measuring procedure
N72-11691
- WRIGHT, J. W., JR.
Tensile behavior of high-strength alloys during
rapid heating.
A72-10749
- WRIGHT, L. A.
Team approach to power plant design for maximum
operational effectiveness.
[SAE PAPER 710778] A72-10270
- WRIGHT, P. B.
An assessment scheme for aerodrome forecasts.
A72-10864
- WULF, R.
Possibilities for jet simulation in the 3m-wind
tunnel of the DFVLR-AVA Goettingen
N72-10005
- WYETH, H. W. G.
Fire and explosion protection of fuel tank ullage
N72-11690

Y

- YANG, N. C.
New paving concept for New York airports.
A72-12023
- YATES, J. E.
On the aerodynamic forces of oscillating two
dimensional lifting surfaces
[AD-726132] N72-11017
- YOUNG, L. R.
Display research collision warning system
[NASA-CASE-HQN-10703] N72-11527
- YOUNG, R. J.
Possible developments of a wind tunnel computer
system
[NPL-AERO-1326] N72-10184
- YUN, G. H.
Selecting the basic parameters of civil aircraft for
specified ranges and commercial load
[AD-727231] N72-11061

Z


- ZAITZEFF, E. M.
MSDS - An experimental 24-channel multispectral
scanner system.
A72-10946
- ZEIDLER, V.
Preliminary tests and performance of rolling
vertical takeoff and landing of the VJ 101 C-X2
with ignited afterburners
[BMVG-FBWT-71-13] N72-10034
Basic investigations of recirculation with
configurations consisting of 1 to 6 jets
[BMVG-FBWT-71-12] N72-10828
- ZERREK, L.
Matrix method of calculating the strength of hinged
main-rotor blades for a helicopter in steady
forward flight
A72-12440
- ZILLER, M. A.
Recording antenna radiation patterns by
semi-automation.
A72-10149
- ZIMMERMANN, G.
Future aircraft noise in the vicinity of airports.
A72-12022
- ZUNG, L. B.
Analysis of aircraft fuel tank fire and explosion
hazards
[AD-725027] N72-11056

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 15)

FEBRUARY 1972

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number, the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF PROJ. 649L	N72-10543	F19628-68-C-0365	N72-10830
AF PROJ. 682 (R)	N72-10332	F19628-70-C-0230	N72-10543
AF PROJ. 698DC	N72-10048	F33615-67-C-1271	N72-10425
AF PROJ. 872-7	N72-10425	F33615-69-C-1278	N72-10047
AF PROJ. 3012	N72-11312	F33615-69-C-1895	N72-11820
AF PROJ. 3048	N72-11056	F33615-70-C-1322	N72-11056
AF PROJ. 5710	N72-11820	F44620-68-C-0021	N72-10048
AF PROJ. 7065	N72-11308	F44620-68-C-0021	N72-10042
AF PROJ. 7231	N72-10127	F44620-69-C-0130	N72-10501
AF PROJ. 7351	N72-10957	F44620-71-C-0021	N72-11714
AF PROJ. 7921	N72-10042	F61052-69-C-0025	A72-12270
	N72-10501		N72-11308
AF PROJ. 9781	N72-11714	NAS1-8541	N72-10401
AF PROJ. 9782-01	N72-11017	NAS1-9143	N72-11010
AF 33(615)-3736	N72-10048	NAS1-9425	A72-10160
AF 49(638)-1640	N72-11017	NAS1-9622	N72-10043
ARPA ORDER 636	N72-10396	NAS1-10703	A72-10259
DA PROJ. 1-F-1-62204-A-14231	N72-11060	NAS2-5969	N72-11845
DA PROJ. 1-G-162207-AA-71	N72-11713	NAS2-5989	N72-10984
DA PROJ. 1F1-62204-A-139	N72-11050		N72-10985
DA PROJ. 1F1-62204-A-14232	N72-11060		N72-10986
DA-31-124-ARO(D)-149	A72-11135		N72-10987
DAAD05-70-C-0250	N72-11688	NAS12-659	A72-11068
DAAJ-01-68-C-1981(31)	A72-10814	NAS12-698	A72-11134
DAAJ02-68-C-0017	N72-11050	NGR-22-009-444	N72-11527
DAAJ02-68-C-0069	N72-11060		NGR-52-025-003
DAAJ02-68-C-0103	N72-11060		A72-10219
DAAJ02-69-C-0030	N72-11688	NOL PROJ. 341/AIR-520C01	N72-11473
DAAJ02-70-C-0003	N72-11713	NR PROJ. 213-054	N72-10044
DAAJ02-70-C-0019	N72-11057	NR PROJ. 213-067	N72-11053
DAAJ02-70-C-0039	N72-11059	NSF GI-12	N72-11680
DAHC15-67-C-0011	N72-10992	N00014-66-C-0362	N72-10044
DOT-FA-70-WA-2395	N72-11037	N00014-68-A-0091	N72-11850
DOT-OS-00074	N72-11849	N00014-68-C-0300	N72-11053
		N60921-68-C-0220	A72-10749
		OCD-OS-72-174	N72-10396
		PROJ. THEMIS	N72-10042
			N72-10501
		PROJ. T702301-2301	N72-10046
		PROJ. WF32.421.202	N72-10037
		PROJ. 073-323-04X	N72-10233
		PROJ. 341-004-03X	N72-10173

W-7405-ENG-48
 N72-11334
 WP51.543.202 N72-10489
 126-13-01-43-21
 N72-10031
 133-61-12-02 N72-11038
 134-03-23-01 N72-11428
 136-13-05-01 N72-11289
 720-03 N72-10025
 N72-11711
 722-01-10-02-21
 N72-10045

1. Report No. NASA SP-7037 (15)	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle AERONAUTICAL ENGINEERING A Special Bibliography (Supplement 15)		5. Report Date February 1972	
		6. Performing Organization Code	
7. Author(s)		8. Performing Organization Report No.	
		10. Work Unit No.	
9. Performing Organization Name and Address National Aeronautics and Space Administration Washington, D. C. 20546		11. Contract or Grant No.	
		13. Type of Report and Period Covered	
12. Sponsoring Agency Name and Address		14. Sponsoring Agency Code	
15. Supplementary Notes			
16. Abstract <p>This special bibliography lists 363 reports, articles, and other documents introduced into the NASA scientific and technical information system in January 1972. Emphasis is placed on engineering and theoretical aspects for design, construction, evaluation, testing, operation and performance of aircraft (including aircraft engines) and associated components, equipment and systems. Also included are entries on research and development in aeronautics and aerodynamics and research and ground support for aeronautical vehicles.</p>			
17. Key Words (Suggested by Author(s)) Aerodynamics Aeronautical Engineering Aeronautics Bibliographies		18. Distribution Statement Unclassified - Unlimited	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 115	22. Price* \$3.00 HC

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA deposits its technical documents and bibliographic tools in eleven Federal Regional Technical Report Centers located in the organizations listed below. Each center is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

PENNSYLVANIA

Carnegie Library of Pittsburgh

TEXAS

Southern Methodist University, Dallas

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

DELAWARE

Wilmington Institute Free Library, Wilmington

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library

James Jerome Hill Reference Library, St. Paul

MISSOURI

Kansas City Public Library

St. Louis Public Library

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati Public Library

Cleveland Public Library

Dayton Public Library

Toledo Public Library

OKLAHOMA

Oklahoma County Libraries, Oklahoma City

TENNESSEE

Cossitt-Goodwin Libraries, Memphis

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 750 Third Avenue, New York, New York, 10017.

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the National Lending Library for Science and Technology, Boston Spa, Yorkshire, England. By virtue of arrangements other than with NASA, the National Lending Library also has available many of the non-NASA publications cited in *STAR*. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "#" and "*", from: ESRO/ELDO Space Documentation Service, European Space Research Organization, 114, av de Neuilly, 92-Neuilly-sur-Seine, France.



POSTMASTER: If Undeliverable (Section 15
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

— NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Washington, D.C. 20546